

DRILL HOLE LOG

DIP TESTS

Property CANYON Gold C.C.

Hole Number

CGGC-11

At _____ Ft. _____

At _____

Dip..... - 45°

At _____ Ft. _____

Claim No.

Length 233'

At _____ Ft. _____

Working Place_____

Bearing 225° Az.

At _____ Ft. _____

Baseline Footage 11+300E

Elev. Collar.

At _____ Ft. _____

Baseline Offset 9+637.5 N

Horiz. Trace.

At _____ Ft. _____

Date Started.....

Vert. Trace.

Date Completed.....2003

Date Logged

FROM	TO	DESCRIPTION	SAMPLE NUMBER	ASSAY	
				Fe	Si
0'	14'	OVERMINE			
14'	233'	<u>RHYOLITE QUARTZ FELDSPAR PORPHYRY</u>			
		Coarse quartz, feldspar and clay colored feldspar phenocrysts are set in a gray-green groundmass. Superficial oxidation continues to 45' - the upper portion being hematite rich 121' - c. 3" pyrite + clay fracture zone @ 60° ENE angle. 122' - light brecciation, silicification along fracture @ 80° CA. 122 1/2' - clay + pyrite along fracture 60° CA. 053802 120'-123' <5 0.01 128' - light brecciation + silicification along fracture @ 75° CA. 145' - 1 cm. fractured phas-clay - 60° CA 150' - thin amethyst lenslet @ 10° CA 193' - 3 cm. fracture-clay @ 45° CA 202'-207' - Highly fractured + white clay. E.O. 14 233'			

Logged by

Om Oshu