

CORE RECOVERY

59.00 m drilled = 100.00%
53.68 m recovered = 90.98%
5.32 m lost = 9.02%

ASSAY SAMPLES 04 KEL 4

SAMPLE #	INTERVAL
K 071	3.00 – 6.10 m
K 072	6.10 – 9.14
K 073	9.14 -12.19
K 074	12.19 -15.24
K 075	15.24 -18.29
K 076	18.29 -21.34
K 077	21.34 -24.38
K 078	24.38 -28.96
K 079	28.96 -32.00
K 080	32.00 -35.05
K 081	35.05 -38.10
K 082	38.10 -41.15
K 083	41.15 -44.20
K 084	44.20 -47.24
K 085	47.24 -50.29
K 086	50.29 -53.34
K 087	53.34 -56.39
K 088	56.39 -59.00
End of Hole	



SAMPLE#	Au** ppb	Sample kg
K067	4	4.61
K068	<2	4.90
K069	2	4.16
K070	7	2.31
K071	191	3.91
K072	10	2.26
K073	4	3.45
K074	4	3.81
K075	5	3.51
K076	4	4.10
K077	8	4.35
K078	17	4.30
K079	12	5.05
K080	8	6.69
RE K080	6	-
RRE K080	9	-
K081	65	4.02
K082	110	4.26
K083	21	3.44
K084	135	4.27
K085	41	3.15
K086	150	3.84
K087	169	3.56
K088	172	3.65
K089	5	5.44
K090	3	3.75
K091	8	4.76
K092	14	4.70
K093	16	5.39
K094	14	3.56
K095	96	3.50
K096	25	4.30
STANDARD AU-R2	589	-

Sample type: CORE R150 60C. Samples beginning 'RE' are Reruns and 'RRE' are Reject Reruns.