

MICHELLE PROJECT

PROPERTY: MICHELLE

Easting	Northing	Elev.	Depth (m)
372682	7208154	1599	89.00

HOLE: MCH-08-19

Contractor: ELITE
Drill: JKS Super

Core size:	BTW		
Casing depth:	2.13	(m)	out

Drilling dates: Aug 17,2008 - Aug 18,2008

Logged by: M.Nunez

Target: _____

SURVEY							
Depth (m)	Azimuth	Dip	Method	Depth (m)	Azimuth	Dip	Method
0	100	45	BRUNTON	89	96.3	49.7	
13.72	95.1	47.9					
28.96	96	48.3					
44.2	95.9	48.5					
59.44	95.8	48.9					
74.68	96	49.3					

[illegible]

SAMPLES	
Numbers:	NO SAMPLES TAKEN
Total:	
Date sent:	

COMMENTS	

PROPERTY				MCH-08-19				Zone:				GULLY				CLAIM:				MICHELLE 19				Page 1 of 1																																
MICHELLE CALAMINE				Northing: 7208154				Easting: 372682				Elevation: 1432 m				Depth: 0.00		28.96	44.20	74.68	89.00																																			
				Drilling Dates: Aug 17, 2008- Aug 18, 2008				Logged By: M.NUNEZ								Dip: 45.00		48.30	48.50	49.30	49.70																																			
				Length: 89.00				Core Diameter: BTW				Casing Depth: 2.13				Casing: OUT		Azimuth: 100.00		96.00	95.90	96.00	96.30																																	
From	To	Interval	UNIT	ALTERATION AND MINERALIZATION																GEOTECHNICAL						SAMPLES				ASSAYS																										
(m)	(m)	(m)		HYDROZINCITE				LIMONITE				CALCITE		DOLOMITE		FRACTURES				BEDDING		From	To	Rec.	Rec.	RQD	RQD	From	To	Interval	Sample	Zn	Pb	Ag	Ga																					
0.00	7.40	7.40	LST	0	W	M	S	MODE	TYPE	INT.	MODE	INT.	MODE	INT.	TYPE	DENS.	INT.	ANGLE	ANGLE	TYPE	ANGLE	(m)	(m)	(m)	%	(m)	%	(m)	(m)	(m)	Number	ppm	ppm	ppm	ppm																					
5.53	7.41	1.88	LSWT																			0.00	2.13	2.39	100	0.95	45																													
LT GY AND LT ORANGE FAIRLY LI STAINED AND FRACTURED LST																						2.13	5.18	1.15	38	1.14	37	4.18	5.18	1.00	G005919	70	20	<1	<50																					
5.53-7.41 SANDY LI LSWT; WEAK REACTION TO ZINC ZAP ; Ca < OCCUR 52 TO C/A																						5.18	8.23	1.39	46	0.95	31	5.18	7.24	2.06	G005920	510	170	<1	<50																					
																						8.23	11.28	2.92	96	1.93	63	BLANK				G005921	50	>20	<1	<50																				
7.40	14.33	6.93	LST																			11.28	14.33	2.82	92	2.38	78	7.24	7.95	0.71	G005922	90	>20	<1	<50																					
																						14.33	17.37	2.12	70	0.62	20	13.71	15.56	1.85	G005923	140	60	<1	<50																					
LTGY + LT ORANGE WEAKLY STAINED AND FR'D LST; FR'S OCCUR 65 TO C/A																						17.37	20.42	2.17	71	0.36	12	15.56	17.37	1.81	G005924	120	40	<1	<50																					
																						20.42	23.47	2.34	77	0.85	28	24.00	25.52	1.52	G005925	80	40	<1	<50																					
14.33	24.07	9.74	LST																			23.47	26.52	1.52	50	0.14	5	25.52	26.52	1.00	G005926	80	60	<1	<50																					
																						26.52	29.57	1.29	42	0.00	0	26.52	29.52	3.00	G005927	110	80	<1	<50																					
																						29.57	32.61	1.62	53	0.14	5	29.52	31.00	1.48	G005928	90	60	<1	<50																					
LT GY AND LT ORANGE FAIRLY STAINED AND FRACTURED LST WITH SPECKS OF OXIDIZED PY ON FRACTURE SURFACES; Ca VEINING OCCUR																						32.61	35.66	2.87	94	0.46	15	31.00	32.38	1.38	G005929	330	250	<1	<50																					
30 TO C/A; FRACTURES OCCURING 40 TO C/A																						35.66	38.71	2.73	90	0.46	15	32.38	34.06	1.68	G005930	100	60	<1	<50																					
																						38.71	41.76	2.87	94	0.36	12	34.06	35.66	1.60	G005931	100	>20	<1	<50																					
24.07	34.06	9.99	LSWT																			41.76	44.81	2.82	92	1.19	39	35.66	37.02	1.36	G005932	120	>20	<1	<50																					
																						44.81	47.85	2.51	83	0.16	5	37.02	38.71	1.69	G005933	90	>20	<1	<50																					
WEATHERED SANDY LST WITH WEAK TO MODERATE LI STAING ON LST FRAGMENTS; SANDY CONTACT OCCURS 41 TO C/A																						47.85	50.90	2.95	97	1.85	61	END OF SAMPLING																												
31.01-32.30 UNIT IS COMPLETEY WEATHERED TO ORANGE GREY SAND																						50.90	53.95	2.96	97	1.65	54																													
																						53.95	57.00	2.34	77	1.04	34																													
34.06	89.00	54.94	LST																			57.00	60.05	2.84	93	1.79	59																													
																						60.05	63.09	2.95	97	1.86	61																													
LT GY BEDDED AND OCCASIONALLY STYOLITIC LST WITH TRACE TO WEAK INTERSTITIAL LI; La 50 TO C/A; LI RESULT OF OXIDIZED PY ON FRA																						63.09	66.14	2.96	97	2.55	84																													
SURFACES																						66.14	69.19	3.12	100	2.57	84																													
																						69.19	72.24	2.79	91	2.50	82																													
																						72.24	75.29	2.98	98	2.56	84																													
																						75.29	78.33	2.99	98	2.85	94																													
																						78.33	81.38	2.94	96	2.38	78																													
EOH 89.00																						81.38	84.43	2.88	94	2.61	86																													
																						84.43	87.48	2.98	98	2.58	85																													
																						87.48	89.00	1.83	100	1.83	100																													