

**Table 1**  
**Significant Intervals - Diamond Drilling and Reverse Circulation Percussion Drilling - Nucleus Zone**

Drill Hole	From (m)	To (m)	Interval (m)	Sample No	Gold (g/t)	Copper (ppm)
DN84-01	4.57	6.10	1.52	N 31152	0.97	88
	6.10	7.62	1.52	N 31153	0.05	110
			3.05		0.51	99
DN84-01	15.70	17.68	1.98	N 31159	0.18	147
	17.68	19.81	2.13	N 31160	0.83	378
			4.11		0.52	267
DN84-01	25.60	27.43	1.83	N 31164	0.59	132
	27.43	28.96	1.52	N 31165	0.69	502
			3.35		0.64	300
DN84-01	46.18	47.40	1.22	N 31176	1.23	488
	47.40	48.77	1.37	N 31177	1.68	770
			2.59		1.47	637
DN84-01	52.12	54.56	2.44	N 31180	0.52	250
	54.56	57.00	2.44	N 31181	0.50	340
			4.88		0.51	295
DN84-01	79.25	80.77	1.52	N 31194	1.04	2430
	80.77	82.30	1.52	N 31195	0.23	4700
	82.30	83.82	1.52	N 31196	0.61	3150
			4.57		0.63	3427
DN84-02	7.32	8.84	1.52	N 31199	0.41	58
	8.84	10.36	1.52	N 31200	0.63	80
			3.04		0.52	69
DN84-02	23.47	24.99	1.52	N 31208	2.32	50
	24.99	26.52	1.53	N 31209	0.36	27
	26.52	28.04	1.52	N 31210	0.71	48
	28.04	29.57	1.53	N 31211	0.68	42
	29.57	31.09	1.52	N 31212	7.33	240
	31.09	32.61	1.52	N 31213	1.55	94
	32.61	33.83	1.22	N 31214	0.40	52
	33.83	35.36	1.53	N 31215	1.09	58
	35.36	37.34	1.98	N 31216	0.18	38
	37.34	38.25	0.91	N 31217	1.48	1250
	38.25	39.93	1.68	N 31218	0.49	310
	39.93	41.45	1.52	N 31219	0.24	33
	41.45	43.28	1.83	N 31220	2.74	58
	43.28	45.26	1.98	N 31221	2.02	148
	45.26	46.63	1.37	N 31222	2.08	1630
			23.16		1.58	230
DN84-02	29.57	31.09	1.52	N 31212	7.33	240
	31.09	32.61	1.52	N 31213	1.55	94
	32.61	33.83	1.22	N 31214	0.40	52
	33.83	35.36	1.53	N 31215	1.09	58
DN84-02			5.79		2.70	
	41.45	43.28	1.83	N 31220	2.74	114
	43.28	45.26	1.98	N 31221	2.02	58
	45.26	46.63	1.37	N 31222	2.08	148
DN84-02			5.18		2.29	508
	56.39	58.52	2.13	31228	3.82	220
	58.52	60.96	2.44	31229	1.31	240
DN84-02			4.57		2.48	231
	73.15	74.68	1.53	31238	1.00	114
	74.68	76.20	1.52	31239	1.48	45
	76.20	78.43	2.23	31240	0.33	59
	78.43	79.55	1.12	31241	1.02	217
	79.55	81.08	1.53	31242	0.76	419
	81.08	82.60	1.52	31243	2.02	336
DN84-02			9.45		1.05	187
	70.10	71.63	1.53	31236	0.98	86
	71.63	73.15	1.52	31237	0.65	40
	73.15	74.68	1.53	31238	1.00	114
	74.68	76.20	1.52	31239	1.48	45
DN84-02	76.20	78.43	2.23	31240	0.33	59