

**Table 1**  
**Significant Intervals - Diamond Drilling and Reverse Circulation Percussion Drilling - Nucleus Zone**

Drill Hole	From (m)	To (m)	Interval (m)	Sample No	Gold (g/t)	Copper (ppm)
DN84-01	4.57	6.10	1.52	N 31152	0.97	88
	6.10	7.62	1.52	N 31153	0.05	110
			3.05		0.51	99
DN84-01	15.70	17.68	1.98	N 31159	0.18	147
	17.68	19.81	2.13	N 31160	0.83	378
			4.11		0.52	267
DN84-01	25.60	27.43	1.83	N 31164	0.59	132
	27.43	28.96	1.52	N 31165	0.69	502
			3.35		0.64	300
DN84-01	46.18	47.40	1.22	N 31176	1.23	488
	47.40	48.77	1.37	N 31177	1.68	770
			2.59		1.47	637
DN84-01	52.12	54.56	2.44	N 31180	0.52	250
	54.56	57.00	2.44	N 31181	0.50	340
			4.88		0.51	295
DN84-01	79.25	80.77	1.52	N 31194	1.04	2430
	80.77	82.30	1.52	N 31195	0.23	4700
	82.30	83.82	1.52	N 31196	0.61	3150
			4.57		0.63	3427
DN84-02	7.32	8.84	1.52	N 31199	0.41	58
	8.84	10.36	1.52	N 31200	0.63	80
			3.04		0.52	69
DN84-02	23.47	24.99	1.52	N 31208	2.32	50
	24.99	26.52	1.53	N 31209	0.36	27
	26.52	28.04	1.52	N 31210	0.71	48
	28.04	29.57	1.53	N 31211	0.68	42
	29.57	31.09	1.52	N 31212	7.33	240
	31.09	32.61	1.52	N 31213	1.55	94
	32.61	33.83	1.22	N 31214	0.40	52
	33.83	35.36	1.53	N 31215	1.09	58
	35.36	37.34	1.98	N 31216	0.18	38
	37.34	38.25	0.91	N 31217	1.48	1250
	38.25	39.93	1.68	N 31218	0.49	310
	39.93	41.45	1.52	N 31219	0.24	33
	41.45	43.28	1.83	N 31220	2.74	58
	43.28	45.26	1.98	N 31221	2.02	148
	45.26	46.63	1.37	N 31222	2.08	1630
			23.16		1.58	230
DN84-02	29.57	31.09	1.52	N 31212	7.33	240
	31.09	32.61	1.52	N 31213	1.55	94
	32.61	33.83	1.22	N 31214	0.40	52
	33.83	35.36	1.53	N 31215	1.09	58
DN84-02			5.79		2.70	
	41.45	43.28	1.83	N 31220	2.74	114
	43.28	45.26	1.98	N 31221	2.02	58
	45.26	46.63	1.37	N 31222	2.08	148
DN84-02			5.18		2.29	508
	56.39	58.52	2.13	31228	3.82	220
	58.52	60.96	2.44	31229	1.31	240
DN84-02			4.57		2.48	231
	73.15	74.68	1.53	31238	1.00	114
	74.68	76.20	1.52	31239	1.48	45
	76.20	78.43	2.23	31240	0.33	59
	78.43	79.55	1.12	31241	1.02	217
	79.55	81.08	1.53	31242	0.76	419
	81.08	82.60	1.52	31243	2.02	336
			9.45		1.05	187
DN84-02	70.10	71.63	1.53	31236	0.98	86
	71.63	73.15	1.52	31237	0.65	40
	73.15	74.68	1.53	31238	1.00	114
	74.68	76.20	1.52	31239	1.48	45
	76.20	78.43	2.23	31240	0.33	59

Drill Hole	From (m)	To (m)	Interval (m)	Sample No	Gold (g/t)	Copper (ppm)
	78.43	79.55	1.12	31241	1.02	217
	79.55	81.08	1.53	31242	0.76	419
	81.08	82.60	1.52	31243	2.02	336
			12.50		0.99	157
DN84-02	90.22	91.74	1.52	31249	4.89	540
	91.74	93.27	1.53	31250	0.47	290
	93.27	94.79	1.52	31251	1.52	377
	94.79	96.32	1.53	31252	0.87	400
	96.32	97.84	1.52	3690	0.08	290
	97.84	99.36	1.52	3691	0.80	960
	99.36	100.89	1.53	3692	3.04	336
	100.89	102.41	1.52	3693	0.91	520
	102.41	104.39	1.98	3694	0.28	720
	104.39	105.92	1.53	3695	1.02	360
	105.92	107.90	1.98	3696	1.49	166
	107.90	109.42	1.52	3697	0.52	122
	109.42	110.95	1.53	3698	0.28	67
	110.95	112.47	1.52	3699	0.58	53
	112.47	114.00	1.53	3700	2.30	110
	114.00	115.98	1.98	31501	0.69	600
	115.98	117.50	1.52	31502	2.42	650
	117.50	119.18	1.68	31503	1.16	1300
			28.96		1.27	444
DN84-02	90.22	91.74	1.52	31249	4.89	540
	91.74	93.27	1.53	31250	0.47	290
	93.27	94.79	1.52	31251	1.52	377
			4.57		2.29	402
DN84-03	21.34	22.86	1.52	31482	1.00	272
	22.86	24.38	1.52	31483	1.48	211
	24.38	25.91	1.53	31484	0.33	134
	25.91	27.43	1.52	31485	1.02	230
	27.43	28.96	1.53	31486	0.76	180
	28.96	30.48	1.52	31487	2.02	170
			9.14		1.10	199
DN84-03	18.29	19.81	1.52	31380	0.98	188
	19.81	21.34	1.53	31481	0.65	200
	21.34	22.86	1.52	31482	1.00	272
	22.86	24.38	1.52	31483	1.48	211
	24.38	25.91	1.53	31484	0.33	134
	25.91	27.43	1.52	31485	1.02	230
	27.43	28.96	1.53	31486	0.76	180
	28.96	30.48	1.52	31487	2.02	170
			12.19		1.03	198
DN84-03	38.10	39.62	1.52	31493	0.44	400
	39.62	41.15	1.53	31494	0.83	495
			3.05		0.64	448
DN84-03	42.67	43.89	1.22	31496	0.17	550
	43.89	45.72	1.83	31497	0.80	136
			3.05		0.55	302
DN84-03	50.75	52.27	1.52	31364	3.4	455
	52.27	53.80	1.53	31365	0.47	710
	53.80	55.78	1.98	31366	2.95	470
	55.78	57.09	1.31	31367	0.04	60
	57.09	58.61	1.52	31368	0.08	52
	58.61	60.14	1.53	31369	0.8	160
	60.14	61.87	1.73	31370	3.04	327
	61.87	63.40	1.53	31371	0.91	423
	63.40	64.92	1.52	31372	0.28	412
	64.92	66.45	1.53	31373	1.02	440
	66.45	67.97	1.52	31374	1.49	1750
	67.97	69.49	1.52	31375	0.51	980
	69.49	71.02	1.53	31376	0.68	750
	71.02	72.85	1.83	31377	1.69	295
	72.85	74.68	1.83	31378	2.72	160
	74.68	76.20	1.52	31379	3.82	170
	76.20	77.72	1.52	31380	1.31	188
	77.72	79.25	1.53	3681	1.49	146