

GEOTECHNICAL LOG

HOLE: ROSY-10-01

From (m)	To (m)	Interval (m)	Recovery (m)	Recovery (%)	RQD (m)	RQD (%)	Hardness	Weathering		Comments
0.00	2.46	2.46	0.00	0	1	47				Casing
2.46	3.96	1.50	1.50	100	1.15	77	VS	FR		
3.96	5.49	1.53	1.53	100	1.43	93	VS	FR		
5.49	7.01	1.52	1.42	93	1.20	79	VS	FR		
7.01	8.53	1.52	1.55	102	1.50	99	VS	FR		
8.53	10.06	1.53	1.50	98	1.33	87	VS	FR		
10.06	11.58	1.52	1.50	99	1.15	76	VS	FR		
11.58	13.11	1.53	1.50	98	0.22	14	VS	FR		
13.11	14.63	1.52	1.54	101	0.36	24	VS	FR		
14.63	16.15	1.52	1.53	101	1.53	101	W	FR		
16.15	17.68	1.53	1.50	98	1.47	96	W	FR		
17.68	19.20	1.52	1.50	99	1.49	98	VS	FR		
19.20	20.73	1.53	1.50	98	1.34	88	VS	FR		
20.73	22.25	1.52	1.54	101	1.25	82	VS	FR		
22.25	23.77	1.52	1.53	101	1.53	101	VS	FR		
23.77	25.30	1.53	1.54	101	1.49	97	VS	FR		
25.30	26.82	1.52	1.42	93	1.39	91	VS	FR		
26.82	28.35	1.53	1.53	100	1.43	93	VS	FR		
28.35	29.87	1.52	1.55	102	1.55	102	VS	FR		
29.87	31.39	1.52	1.51	99	1.39	91	VS	FR		
31.39	31.98	0.59	0.59	100	0.59	100	VS	FR		End of HQ core
31.98	34.44	2.46	1.50	61	0.88	36	VS	FR		
34.44	37.49	3.05	3.00	98	2.90	95	VS	FR		
37.49	39.01	1.52	1.50	99	1.37	90	VS	FR		
39.01	42.06	3.05	1.98	65	1.27	42	VS	FR		Crumbled core
42.06	45.11	3.05	3.02	99	2.72	89	VS	FR		
45.11	48.16	3.05	3.05	100	3.05	100	VS	FR		
48.16	51.21	3.05	3.05	100	2.17	71	VS	FR		
51.21	54.25	3.04	3.04	100	2.49	82	VS	FR		
54.25	57.30	3.05	3.05	100	2.93	96	VS	FR		
57.30	60.35	3.05	3.05	100	3.05	100	VS	FR		
60.35	63.40	3.05	3.05	100	3.05	100	VS	FR		
63.40	64.92	1.52	1.50	99	1.50	99	VS	FR		
64.92	67.97	3.05	3.05	100	2.74	90	VS	FR		End of hole