

GEOTECHNICAL LOG

HOLE: ROSY-10-02

From (m)	To (m)	Interval (m)	Recovery (m)	Recovery (%)	RQD (m)	RQD (%)	Hardness	Weathering		Comments
0.00	2.44	2.44		0		0				
2.44	3.96	1.52	1.53	101	1.35	89	VS	FR		
3.96	5.49	1.53	1.54	101	1.29	84	VS	FR		
5.49	7.01	1.52	1.54	101	1.17	77	VS	FR		
7.01	8.53	1.52	1.51	99	1.36	89	VS	FR		
8.53	10.06	1.53	1.54	101	1.53	100	VS	FR		
10.06	11.58	1.52	1.50	99	1.50	99	VS	FR		
11.58	13.11	1.53	1.56	102	1.56	102	VS	FR		
13.11	14.63	1.52	1.42	93	1.04	68	VS	FR		
14.63	16.15	1.52	1.52	100	1.29	85	VS	FR		
16.15	17.68	1.53	1.51	99	1.51	99	VS	FR		
17.68	19.20	1.52	1.50	99	1.50	99	VS	FR		
19.20	20.73	1.53	1.53	100	1.29	84	VS	FR		
20.73	22.25	1.52	1.51	99	1.51	99	VS	FR		
22.25	23.77	1.52	1.48	97	1.48	97	VS	FR		
23.77	25.30	1.53	1.55	101	1.50	98	VS	FR		
25.30	26.82	1.52	1.56	103	1.53	101	VS	FR		
26.82	28.35	1.53	1.52	99	1.35	88	VS	FR		
28.35	29.87	1.52	1.51	99	1.45	95	VS	FR		
29.87	31.39	1.52	1.53	101	1.53	101	VS	FR		
31.39	32.92	1.53	1.51	99	1.51	99	VS	FR		
32.92	34.44	1.52	1.55	102	1.55	102	VS	FR		
34.44	35.97	1.53	1.48	97	1.33	87	VS	FR		
35.97	37.49	1.52	1.60	105	1.55	102	VS	FR		
37.49	39.01	1.52	1.55	102	0.65	43	VS	FR		
39.01	40.54	1.53	1.50	98	1.50	98	VS	FR		
40.54	42.06	1.52	1.49	98	1.29	85	VS	FR		
42.06	43.59	1.53	1.53	100	1.46	95	VS	FR		
43.59	45.11	1.52	1.47	97	1.17	77	VS	FR		
45.11	46.63	1.52	1.55	102	1.49	98	VS	FR		
46.63	48.16	1.53	1.53	100	1.40	92	VS	FR		
48.16	49.68	1.52	1.55	102	1.18	78	VS	FR		
49.68	51.21	1.53	1.48	97	1.48	97	VS	FR		
51.21	52.73	1.52	1.51	99	1.51	99	VS	FR		
52.73	54.25	1.52	1.48	97	1.48	97	VS	FR		
54.25	55.78	1.53	1.42	93	1.42	93	VS	FR		
55.78	57.30	1.52	1.53	101	1.39	91	W	FR		
57.30	58.83	1.53	1.52	99	1.14	75	VS	FR		
58.83	60.35	1.52	1.54	101	1.48	97	VS	FR		
60.35	61.87	1.52	1.52	100	1.27	84	VS	FR		
61.87	63.40	1.53	1.56	102	1.56	102	VS	FR		
63.40	64.92	1.52	1.52	100	1.52	100	VS	FR		
64.92	66.45	1.53	1.50	98	1.50	98	VS	FR		
66.45	67.97	1.52	1.52	100	1.52	100	VS	FR		
67.97	69.49	1.52	1.52	100	1.47	97	VS	FR		
69.49	71.02	1.53	1.51	99	1.51	99	VS	FR		
71.02	72.54	1.52	1.54	101	1.45	95	VS	FR		
72.54	74.07	1.53	1.54	101	1.54	101	VS	FR		
74.07	75.59	1.52	1.53	101	1.53	101	VS	FR		
75.59	77.11	1.52	1.51	99	1.48	97	VS	FR		
77.11	78.64	1.53	1.54	101	1.32	86	VS	FR		

GEOTECHNICAL LOG

From (m)	To (m)	Interval (m)	Recovery (m)	Recovery (%)	RQD (m)	RQD (%)	Hardness	Weathering		Comments
78.64	80.16	1.52	1.48	97	1.48	97	VS	FR		
80.16	81.69	1.53	1.46	95	1.46	95	VS	FR		
81.69	83.21	1.52	1.51	99	1.48	97	VS	FR		
83.21	84.73	1.52	1.51	99	1.51	99	S	FR		
84.73	86.26	1.53	1.48	97	0.84	55	S	FR		
86.26	87.78	1.52	1.54	101	0.80	53	S	FR		
87.78	89.31	1.53	1.50	98	1.50	98	VS	FR		
89.31	90.83	1.52	1.54	101	1.54	101	VS	FR		
90.83	92.35	1.52	1.50	99	1.50	99	VS	FR		
92.35	93.88	1.53	1.51	99	1.51	99	VS	FR		
93.88	95.40	1.52	1.40	92	0.85	56	VS	FR		End of the hole