RECORD OF BOREHOLE: BH95G-30

PROJECT: 952-1523I

SHEET 1 OF 1

LOCATION: 6816765N, 415439E, NE WASTE DUMP

DRILLING DATE: Aug. 19-21, 1995

DATUM: NAD 83

INCLINATION: -90 AZIMUTH:

DRILL RIG: Boyles Brothers - Rotary

DRILLING CONTRACTOR: D.J. Drilling

FR-FRACTURE, CL-CLEAVAGE, SH-SHEAR, VN-VEIN, F-FAULT, J-JOINT, P-POLISHED, S-SLICKENSIDED, SM-SMOOTH, R-ROUGH, ST-STEPPED, PL-PLANAR, FL-FLEXURED, UE-UNEVEN, W-WAVY, C-CURVED

DEPTH SCALE METRES	DRILLING RECORD	DESCRIPTION	SYMBOLIC LOG	ELEV. / DEPTH (m)	RUN No.	PENETRATION RATE (m/min.)	FLUSH / COLOUR % RETURN	RECOVERY: TOTAL CORE %	RECOVERY: SOLID CORE %	R.Q.D. %	FRACT. INDEX PER 0.3m	DISCONTINUITY DATA: DIP w.r.t. CORE AXIS	DISCONTINUITY DATA: TYPE AND SURFACE DESCRIPTION	ROCK STR. (MPa)	WEATHERING INDEX (w)	NOTES / TEST RESULTS
0		Ground Surface		1387.12												
		Compact to dense, moist to wet, brown SAND, some gravel to SAND and GRAVEL, trace to some silt, cobbles and boulders.		0.00	1											
2					2											Aug. 26 1995
3																
4					3											
5																Bentonite Seal
6					4											
7					5											
8																
9					6											
10					7											
11																
12					8											
				1374.32												
13		Bedrock - ARGILLITE MUDSTONE with carbonate bands.		12.80	9								F			
				1372.22												
15		Sericite-quartz SCHIST. Abundant disseminated to 1 + 5mm sulphide.		14.90	10											Sand Pack
17					11											32mm dia. PVC Screen
18					12											
				1367.92												
19		End of Borehole		19.20												
20																

DATA FORM: ROCKMV8

DEPTH SCALE: 1 to 100

CLIENT: Cominco

Golder Associates

LOGGED: L.P.

DATE: Aug. 19-21, 1995

CHECKED: C.J.C.