



GEOLOGIC LOG OF DRILL HOLE NO.: MW05-3B

CLIENT: Yukon Zinc Corporation	PROJECT NO.: M09234A02
PROJECT: Wolverine Feasibility Design and Environmental Assessment	DATE HOLE STARTED: 5/25/2005 FINISHED: 5/26/2005
LOCATION:	DATUM: NAD27
DIRECTION AZIMUTH: DIP (from horiz): -90	TOP OF PIPE ELEVATION: m
CO-ORDINATES: E 439946.6m N 6810580m	GROUND ELEVATION: 1338 m
MANUFACTURER'S DRILL DESIGNATION: BBS 25A	TOTAL DEPTH OF HOLE: 5 m
DRILLING CONTRACTOR: Advanced Drilling Ltd.	DRILLING METHOD SOIL: HW Casing ROCK: 100mm dia. Tricone
LOGGED BY: EA/RB	DRILLING FLUID: Water
CHECKED BY:	HOLE DIA.:

DEPTH (m)	SYMBOL	SAMPLE No.	LITHOLOGY	PIEZOMETER DETAILS	HYDRAULIC CONDUCTIVITY CM/SEC			DISCONTINUITY DATA	ROCK STRENGTH BASED ON POINT LOAD TEST (MPa) <small>(a)=axial; (d)=diametrical</small>	TEMPERATURE	FIELD/LAB DATA								
					10-6	10-4	10-2				SEE BOTTOM OF FORM FOR CODES	CORE RECOVERY %	SPT/LPT N			WATER CONTENT %			
					Dip Angle														
1			Gravel, mainly angular, clayey, dark grey. Sand in drill cuttings.																
2																			
3																			
4																			
5			5.0 1,333.0 End of Hole at: 5.0 m																
6																			
7																			
8																			
9																			
10																			
11																			
12																			
13																			
14																			
15																			
16																			
17																			
18																			
19																			
20																			
21																			
22																			
23																			
24																			
25																			
26																			
27																			
28																			
29																			
30																			

KC-ROCK-SI@4 WOLVERINE TEST HOLES - NOV 17, 05 PJ ROCK-LOG.GDT 23/06

DISCONTINUITY CODES: B: BEDDING D: DRILL BRK F: FAULT G: GNEISS'TY J: JOINT M: SCHIST'TY S: SHEAR T: TENSION CRK
 CORE LOSS FRACTURED/BROKEN CORE DIP ANGLES MEASURED WITH RESPECT TO