



PROVINCE YUKON TERRITORY
 FIELD WILDCAT
 LOCATION 60° 10' N 124° 0' W
 WELL PAN AM HOME SIGNAL CSP
 A-1 KOTANEELIEE Y. T.
 COMPANY PAN AMERICAN PETROLEUM CORPORATION
 WELL PAN AM HOME SIGNAL
 FIELD WILDCAT
 LOCATION UNIT J SECTION 50
 60° 10' N 124° 0' W
 PROVINCE YUKON TERRITORY
 Elevation: D.F. K.B. 1490
 or G.L. 1475.25
 FILING No.

Date	25 JUNE 62
Run No.	ONE
First Reading	5427
Last Reading	419
Feet Measured	414
Csg. Schlum.	417
Csg. Driller	
Depth Reached	3430
Bottom Driller	5545
Depth Datum	K. B.
Mud Nat.	GEL-CHEM
Density	99
Viscosity	200
Mox. Temp. °F	192
Bit Size	12 1/2"
Depth intervals between shots	50'
Computed By	McKINNON
Mag. Decl.	33° E
P.C. No.	COMPUTED FROM ODM
Qpr. Rig Time	6 HRS.
Truck No.	DSU-A-#7
Recorded By	FRATHER
Witnessed by	HOOKS & ANTONENKO

REMARKS ANY DIRECTIONAL COMPUTATIONS MADE FROM THE DIPMETER LOG MUST BE REGARDED AS APPROXIMATE ONLY. THIS IS BECAUSE THE DIPMETER LOG INDICATES THE ORIENTATION OF THE INSTRUMENT ITSELF, RATHER THAN THE DIRECTION AND AMOUNT OF THE WALL DRIFT. THEREFORE, WE DO NOT AND CANNOT GUARANTEE THE ACCURACY OF SUCH DIRECTIONAL COMPUTATIONS, AND WE SHALL NOT BE LIABLE OR RESPONSIBLE FOR ANY LOSS, COSTS, DAMAGES OR EXPENSES INCURRED OR SUSTAINED THAT MAY RESULT FROM ANY SUCH COMPUTATIONS.

Depth	Drift Angle	DEFLECTION			LATITUDE		DEPARTURE		COORDINATES				
		True Bearing	Horizontal Footage	Vertical Footage	N	S	E	W	N	S	E	W	
417	CSG.Shoe			417.00									
450	1-00	N 63 W	0.58	449.99	0.26			0.51	0.26				0.51
500	1-00	N 72 W	0.88	499.98	0.27			0.83	0.53				1.34
550	1-15	N 72 W	1.09	549.97	0.34			1.04	0.87				2.38
600	1-30	N 76 W	1.31	599.96	0.32			1.27	1.19				3.65
650	1-45	N 78 W	1.53	649.94	0.32			1.50	1.51				5.15
700	1-45	S 88 W	1.53	699.92		0.06		1.52	1.45				6.67
750	2-00	N 87 W	1.75	749.89	0.09			1.75	1.54				8.42
800	2-00	S 88 W	1.75	799.86		0.06		1.75	1.48				10.17
850	1-45	S 83 W	1.53	849.84		0.19		1.52	1.29				11.69
900	1-15	N 71 W	1.09	899.83	0.36			1.03	1.65				12.72
950	0-30	N 67 W	0.44	949.83	0.17			0.40	1.82				13.12
1000	0-45	N 57 W	0.66	999.83	0.36			0.55	2.18				13.67
1050	0-30	N 78 E	0.44	1049.83	0.09		0.43		2.27				13.24
1100	0-45	S 84 E	0.66	1099.83		0.07	0.65		2.20				12.59
1150	0-45	N 33 E	0.66	1149.83	0.55		0.36		2.75				12.23
1200	0-30	S 47 E	0.44	1199.83		0.30	0.32		2.45				11.91
1250	1-15	N 73 E	1.09	1249.82	0.32		1.05		2.77				10.86
1300	0-45	N 83 E	0.66	1299.82	0.08		0.65		2.85				10.21
1350	1-15	S 37 E	1.09	1349.81		0.87	0.66		1.98				9.55
1400	1-30	N 53 E	1.31	1399.80	0.79		1.05		2.77				8.50
1450	0-15	S 17 E	0.22	1449.80		0.21	0.07		2.56				8.43
1500	0-15	S 67 E	0.22	1499.80		0.09	0.20		2.47				8.23
1550	0-30	S 2 E	0.44	1549.80		0.44	0.02		2.03				8.21
1600	0-15	S 8 W	0.22	1599.80		0.22		0.03	1.81				8.24
1650	1-00	S 32 E	0.88	1649.79		0.74	0.47		1.07				7.77
1700	1-00	S 27 E	0.88	1699.78		0.78	0.40		0.29				7.37
1750	1-15	S 57 E	1.09	1749.77		0.60	0.92			0.31			6.45
1800	2-00	N 85 E	1.75	1799.74	0.15		1.74			0.16			4.71
1850	2-15	S 82 E	1.97	1849.70		0.28	1.95			0.44			2.76
1900	2-15	N 73 E	1.97	1899.66	0.58		1.88				0.14		0.88
1950	2-30	S 87 E	2.18	1949.61		0.12	2.18			0.02		1.30	
2000	2-45	S 62 E	2.40	1999.55		1.13	2.12				1.11	3.42	
2050	3-00	S 82 E	2.62	2049.48		0.37	2.59				1.48	6.01	
2100	4-00	S 82 E	2.49	2099.31		0.49	3.46				1.97	9.47	
2150	3-45	S 77 E	3.27	2149.21		0.74	3.19				2.71	12.66	
2200	3-30	S 72 E	3.05	2199.11		0.95	2.91				3.66	15.57	
2250	3-45	S 87 E	3.27	2249.01		0.17	3.27				3.83	18.84	
2300	3-30	N 87 E	3.05	2298.91	0.16		3.05				3.67	21.89	
2350	2-00	S 88 E	1.75	2348.88		0.06	1.75				3.73	23.64	
2400	1-45	N 88 E	1.53	2398.86	0.06		1.53				3.67	25.17	
2450	1-45	S 83 E	1.53	2448.84		0.19	1.02				3.86	26.19	
2500	2-00	S 47 E	1.75	2498.81		1.19	1.28				5.05	27.47	
2550	1-45	S 47 E	1.53	2548.79		1.04	1.12				6.09	28.59	
2600	1-45	S 52 E	1.53	2598.77		0.94	1.21				7.03	29.80	
2650	2-00	S 52 E	1.75	2648.74		1.08	1.38				8.11	31.18	
2700	2-45	S 79 E	2.40	2698.68		0.46	2.36				8.57	33.54	
2750	3-00	S 87 E	2.62	2748.61		0.14	2.62				8.71	36.16	
2800	2-15	S 59 E	1.97	2798.57		1.01	1.69				9.72	37.85	
2850	2-00	S 67 E	1.75	2848.54		0.68	1.61				10.40	39.46	
2900	2-00	S 32 E	1.75	2898.51		1.40	1.05				11.80	40.51	
2950	1-45	S 22 E	1.53	2948.49		1.42	0.57				13.22	41.08	
3000	1-45	S 52 E	1.53	2998.47		0.94	1.21				14.16	42.29	
3050	2-15	S 85 E	1.97	3048.43		0.17	1.96				14.33	44.25	
3100	2-45	S 77 E	2.40	3098.40		0.54	2.34				14.87	46.59	
3150	3-00	S 72 E	2.67	3148.33		0.81	2.49				15.68	49.08	
3200	3-30	S 69 E	3.05	3198.23		1.10	2.85				16.78	51.93	
3250	3-15	S 72 E	2.84	3248.15		0.88	2.70				17.66	54.63	
3300	2-00	S 83 E	1.75	3298.12		0.22	1.73				17.88	56.36	
3350	1-30	S 80 E	1.31	3348.10		0.23	1.29				18.11	57.65	
3400	1-45	S 77 E	1.53	3398.07		0.35	1.49				18.46	59.14	
3450	1-00	N 68 E	0.88	3448.06	0.33		0.81				18.31	59.95	
3500	1-45	S 8 W	1.53	3498.03		1.51		0.21			19.64	59.74	
3550	1-45	S 13 W	1.53	3548.00		1.49		0.35			21.13	59.39	
3600	2-00	S 17 E	1.75	3597.97		1.67	0.51				22.80	59.90	
3650	2-30	S 27 E	2.18	3647.92		1.95	0.99				24.75	60.89	
3700	2-30	S 57 E	2.18	3697.87		1.19	1.83				25.94	62.72	
3750	3-30	S 62 E	3.05	3747.77		1.44	2.69				27.38	65.41	
3800	4-00	S 79 E	3.49	3797.65		0.67	3.43				28.05	68.84	
3850	3-30	S 77 E	3.05	3847.55		0.69	2.98				28.74	71.82	
3900	3-45	S 69 E	3.27	3897.44		1.17	3.05				29.91	74.87	
3950	3-45	S 67 E	3.27	3947.33		1.28	3.01				31.19	77.88	
4000	3-30	S 62 E	3.05	3997.23		1.44	2.70				32.63	80.58	
4050	3-00	S 72 E	2.62	4047.16		0.81	2.49				33.44	83.07	
4100	3-15	S 62 E	2.84	4097.08		1.33	2.50				34.77	85.57	
4150	4-15	S 69 E	3.71	4146.94		1.33	3.46				36.10	89.03	
4200	5-00	S 85 E	4.36	4196.75		0.38	4.34				36.48	93.37	
4250	4-30	S 77 E	3.93	4246.59		0.88	3.83				37.36	97.20	
4300	5-00	S 79 E	4.36	4296.40		0.83	4.28				38.19	101.48	
4350	5-15	S 85 E	4.58	4346.19		0.40	4.56				38.59	106.04	
4400	4-30	S 67 E	3.93	4396.03		1.54	3.61				40.13	109.65	
4450	4-30	S 83 E	3.93	4445.87		0.48	3.89				40.61	113.54	
4500	4-45	S 82 E	4.14	4495.70		0.58	4.10				41.19	117.64	
4550	4-45	S 82 E	4.14	4545.53		0.58	4.10				41.77	121.74	
4600	4-30	S 86 E	3.93	4595.37		0.28	3.92				42.05	125.66	
4650	5-00	S 79 E	4.36	4645.18		0.83	4.28				42.88	129.94	
4700	4-00	S 77 E	3.49	4695.06		0.79	3.40				43.67	133.34	
4750	4-45	S 83 E	4.14	4744.89		0.51	4.11				44.18	137.45	
4800	5-30	S 82 E	4.79	4794.66		0.67	4.75				44.85	142.20	
4850	6-30	S 77 E	5.66	4844.34		1.28	5.52				46.13	147.72	
4900	6-45	S 77 E	5.88	4894.00		1.32	5.73				47.45	153.45	
4950	6-15	S 79 E	5.45	4943.69		1.04	5.35				48.49	158.80	
5000	7-00	S 77 E	6.10	4993.32		1.37	5.94				49.86	164.74	
5050	7-15	S 82 E	6.31	5042.92		0.88	6.25				50.74	170.99	
5100	7-00	S 80 E	6.10	5092.55		1.06	6.00				51.80	176.99	
5150	7-45	S 83 E	6.75	5142-10		0.82	6.70				52.62	183.69	
5200	7-30	S 85 E	6.53	5191.67		0.57	6.50				53.19	190.19	
5250	7-45	S 82 E	6.75	5241.22		0.94	6.68				54.13	196.87	
5300	7-30	S 77 E	6.53	5290.79		1.47	6.36				55.60	203.23	
5350	8-00	S 82 E	6.96	5340.33		0.97	6.69				56.57	209.92	
5430	7-30	S 83 E	10.44	5419.64		1.27	10.36						