

INEXCO OIL COMPANY

INEXCO ET AL MALLARD YI 018

AUG 16 / 72

DEPTH	DRIFT ANGLE	TRUE BEARING	HORIZ FOOTAGE	TRUE		DEPART URE	LATITUDE		COORDINATES	
				VERT DEPTH			E=+, W=-	N=+, S=-	E=+, W=-	N=+, S=-
CSG SHBE 954.										
954	.0	0	.00	954.00	.00	.00	.00	.00	.00	.00
1000	3.9	112	3.13	999.89	2.90	-1.17	2.90	-1.17		
1100	4.1	110	7.15	1099.64	6.72	-2.45	9.62	-3.62		
1200	3.9	120	6.80	1199.41	5.89	-3.40	15.51	-7.02		
1300	4.0	124	6.98	1299.16	5.78	-3.90	21.29	-10.92		
1400	4.0	128	6.98	1398.92	5.50	-4.29	26.79	-15.21		
1500	4.0	118	6.98	1498.68	6.16	-3.27	32.95	-18.49		
1600	3.9	122	6.80	1598.44	5.77	-3.60	38.72	-22.09		
1700	4.0	129	6.98	1698.20	5.42	-4.39	44.14	-26.48		
1800	4.1	130	7.15	1797.94	5.48	-4.60	49.61	-31.08		
1900	4.9	130	8.54	1897.58	6.54	-5.49	56.16	-36.57		
2000	5.2	132	9.06	1997.17	6.74	-6.06	62.89	-42.63		
2100	4.9	140	8.54	2096.80	5.49	-6.54	68.38	-49.18		
2200	5.4	138	9.41	2196.36	6.30	-6.99	74.68	-56.17		
2300	6.0	131	10.45	2295.81	7.89	-6.80	82.57	-63.03		
2400	5.9	129	10.28	2395.28	7.99	-6.47	90.56	-69.50		
2500	5.7	128	9.93	2494.79	7.83	-6.11	98.38	-75.61		
2600	5.5	125	9.58	2594.33	7.85	-5.50	106.24	-81.11		
2700	5.3	123	9.24	2693.90	7.75	-5.03	113.98	-86.14		
2800	5.2	121	9.06	2793.49	7.77	-4.67	121.75	-90.81		
2900	5.1	121	8.89	2893.09	7.62	-4.58	129.37	-95.39		
3000	4.6	125	8.02	2992.77	6.57	-4.60	135.94	-99.99		
3100	4.6	126	8.02	3092.45	6.49	-4.71	142.43	-104.70		
3200	4.6	120	8.02	3192.12	6.95	-4.01	149.37	-108.71		
3300	4.9	115	8.54	3291.76	7.74	-3.61	157.12	-112.32		
3400	5.4	107	9.41	3391.31	9.00	-2.75	166.12	-115.07		
3500	6.6	115	11.49	3490.65	10.42	-4.80	176.53	-119.93		
3600	10.0	122	17.36	3589.13	14.73	-9.20	191.20	-129.13		
3700	10.5	115	18.22	3687.46	16.52	-7.70	207.77	-136.83		
3800	10.4	110	18.05	3785.82	16.96	-6.17	224.74	-143.01		
3900	10.8	109	18.74	3884.04	17.72	-6.10	242.46	-149.11		
4000	11.2	110	19.42	3982.14	18.25	-6.64	260.71	-155.75		
4100	11.0	112	19.08	4080.30	17.69	-7.15	278.40	-162.90		
4200	11.2	117	19.42	4178.40	17.31	-8.82	295.71	-171.72		
4300	11.2	120	19.42	4276.49	16.82	-9.71	312.53	-181.43		
4400	10.8	122	18.74	4374.72	15.89	-9.93	328.42	-191.36		
4500	10.2	120	17.71	4473.14	15.34	-8.80	343.75	-200.21		
4600	10.0	124	17.36	4571.62	14.40	-9.71	358.15	-209.92		
4700	10.0	129	17.36	4670.10	13.49	-10.93	371.64	-220.85		

GEODIGIT

4800	10.2	133	17.71	4758.52	12.95	-12.08	384.60	-252.93
4900	9.5	139	16.50	4857.15	10.83	-12.46	395.42	-245.38
5000	10.4	137	18.05	4955.51	12.31	-13.20	407.74	-258.59
5100	11.5	133	19.94	5053.50	14.58	-13.60	422.32	-272.18
5200	13.2	134	22.84	5150.86	16.43	-15.86	438.74	-288.05
5300	14.2	135	24.53	5257.80	17.35	-17.35	456.09	-305.39
5400	13.7	134	23.68	5354.96	17.04	-16.45	473.12	-321.84
5500	12.7	127	21.98	5452.51	17.56	-13.25	490.68	-335.07
5600	12.3	126	21.30	5550.22	17.23	-12.52	507.92	-347.60
5713	12.0	120	23.49	5650.75	20.35	-11.75	528.26	-359.34
5800	13.8	122	20.75	5745.24	17.60	-11.00	545.86	-370.34
5900	15.6	117	26.89	5841.55	23.96	-12.21	569.82	-382.55
6000	17.4	104	29.90	5936.98	29.02	-7.25	598.84	-389.78
6100	18.8	102	32.23	6031.64	31.52	-6.70	630.36	-396.48
6200	16.2	99	27.90	6127.67	27.56	-4.36	657.92	-400.85
6300	15.3	95	26.39	6224.13	26.29	-2.30	684.20	-403.15
6400	17.5	91	30.07	6319.50	30.07	- .52	714.27	-403.67
6500	20.7	90	35.35	6413.04	35.35	- .00	749.62	-403.67
6600	22.6	87	38.43	6505.36	38.38	2.01	787.99	-401.66
6700	21.0	85	35.84	6598.72	35.70	3.12	823.69	-398.54
6800	20.7	74	35.35	6692.27	33.98	9.74	857.67	-388.80
6900	22.1	67	37.62	6784.92	34.63	14.70	892.30	-374.10
7000	20.8	70	35.51	6878.40	33.37	12.15	925.67	-361.95
7100	20.3	74	34.69	6972.19	33.35	9.55	959.02	-352.39
7200	19.6	73	33.55	7056.40	32.08	9.51	991.10	-342.58
7300	19.3	74	33.05	7150.78	31.77	9.11	1022.87	-333.47
7400	19.3	75	33.05	7255.16	31.93	8.55	1054.80	-324.91
7500	18.8	74	32.23	7349.82	30.98	8.88	1085.78	-316.03
7600	19.2	82	32.89	7444.26	32.57	4.58	1118.34	-311.46
7700	19.8	64	33.87	7538.35	30.45	14.85	1148.79	-296.61
7800	20.1	81	34.37	7632.26	33.94	5.38	1182.73	-291.23
7900	19.3	87	33.05	7726.64	33.01	1.75	1215.74	-289.50
8000	18.4	77	31.56	7821.52	30.76	7.10	1246.49	-282.40
8100	17.0	82	29.24	7917.15	28.95	4.07	1275.45	-278.33
8200	17.4	99	29.90	8012.58	29.54	-4.68	1304.98	-283.01
8300	17.9	114	30.74	8107.74	28.08	-12.50	1333.06	-295.51
8400	17.2	118	29.57	8203.27	26.11	-13.88	1359.17	-309.39
8500	16.8	117	28.90	8299.00	25.75	-13.12	1384.92	-322.51
8600	16.6	113	28.57	8394.83	26.30	-11.16	1411.22	-333.68
8700	16.9	108	29.07	8490.51	27.65	-8.98	1438.87	-342.66
8800	19.0	106	32.56	8585.06	31.30	-8.97	1470.16	-351.63
8900	20.1	108	34.37	8678.97	32.68	-10.62	1502.85	-362.25
9000	20.4	113	34.86	8772.70	32.09	-13.62	1534.93	-375.87
9100	19.8	100	33.87	8866.79	33.36	-5.88	1568.29	-381.76
9200	17.5	101	30.07	8952.16	29.52	-5.74	1597.81	-387.49
9300	16.2	96	27.90	9058.19	27.75	-2.92	1625.56	-390.41
9400	16.5	90	28.40	9154.07	28.40	- .00	1653.96	-390.41
9500	17.2	88	29.57	9249.60	29.55	1.03	1683.51	-389.38
9600	17.4	100	29.90	9345.02	29.45	-5.19	1712.96	-394.57
9700	17.3	102	29.74	9440.50	29.09	-6.18	1742.05	-400.75
9800	19.7	106	33.71	9534.65	32.40	-9.29	1774.45	-410.05
9900	20.1	100	34.37	9628.56	33.84	-5.97	1808.30	-416.01
10000	20.1	94	34.37	9722.47	34.28	-2.40	1842.58	-418.41
10100	19.2	97	32.89	9816.90	32.64	-4.01	1875.22	-422.42

10200	19.4	89	33.22	9911.23	33.21	.58	1908.43	-421.84
10300	19.8	84	33.87	10055.31	33.69	3.54	1942.12	-418.30
10400	19.6	75	33.55	10099.52	32.40	8.68	1974.52	-409.62
10498	19.3	83	32.39	10132.01	32.15	3.95	2006.67	-405.67

DRIFT DISTANCE = 2047.27 FEET  
AZM OF DRIFT = 101 DEGREES

SCALE = 300. FEET/IN.  
XMAX = 2006.00 XMIN = .00  
YMAX = .00 YMIN = -422.00