

NEXCO OIL COMPANY

WELL FILE

NEXCOHUSKY ET AL PORCUPINE YT G31

ARCH 29/72

SPARE COPY

DEPTH	DRIFT ANGLE	TRUE BEARING	HORIZ FOOTAGE	TRUE VERT DEPTH	DEPART URE	LATITUDE		COORDINATES	
						E=+, W=-	N=+, S=-	E=+, W=-	N=+, S=-
990	CSG	SHOE							
990	.0	0	.00	990.00	.00	.00	.00	.00	.00
1100	1.3	230	2.50	1099.97	-1.91	-1.60	-1.91	-1.60	
1200	1.6	214	2.79	1199.93	-1.56	-2.31	-3.47	-3.92	
1300	1.9	199	3.32	1299.88	-1.08	-3.13	-4.55	-7.05	
1400	2.4	189	4.19	1399.79	-.66	-4.14	-5.21	-11.19	
1500	3.0	178	5.23	1499.65	.18	-5.23	-5.02	-16.42	
1600	3.7	169	6.45	1599.44	1.23	-6.33	-3.79	-22.75	
1700	4.4	158	7.67	1699.15	2.87	-7.11	-.92	-29.87	
1800	5.1	149	8.89	1798.75	4.58	-7.62	3.66	-37.49	
1900	5.2	149	9.06	1898.34	4.67	-7.77	8.33	-45.26	
2000	5.0	139	8.72	1997.96	5.72	-6.58	14.04	-51.83	
2100	4.7	128	8.19	2097.63	6.46	-5.04	20.50	-56.88	
2200	4.3	115	7.50	2197.34	6.80	-3.17	27.30	-60.05	
2300	4.2	104	7.32	2297.08	7.11	-1.77	34.40	-61.82	
2400	4.3	99	7.50	2396.79	7.41	-1.17	41.81	-62.99	
2500	5.0	97	8.72	2496.41	8.65	-1.06	50.46	-64.05	
2600	5.8	99	10.11	2595.90	9.98	-1.58	60.44	-65.64	
2700	5.5	95	9.58	2695.44	9.55	-.64	69.99	-66.47	
2800	5.3	89	9.27	2795.01	9.27	.18	79.27	-66.71	
2900	5.4	90	9.41	2894.57	9.41	-.00	88.63	-66.31	
3000	6.4	90	11.15	2993.95	11.15	-.00	99.78	-66.31	
3100	8.2	88	14.26	3092.92	14.25	.50	114.04	-65.81	
3200	9.5	83	16.50	3191.55	16.38	2.01	130.42	-63.80	
3300	9.3	65	16.16	3290.24	14.65	6.83	145.06	-56.97	
3400	8.8	67	15.30	3389.06	14.08	5.98	159.15	-50.99	
3500	8.8	74	15.30	3487.88	14.71	4.22	173.85	-46.78	
3600	8.3	78	14.44	3586.84	14.12	3.00	187.97	-43.78	
3700	8.1	83	14.09	3685.84	13.99	1.72	201.96	-42.05	
3800	7.9	94	13.74	3784.89	13.71	-.96	215.67	-43.02	
3900	7.7	96	13.40	3883.99	13.33	-1.40	228.99	-44.42	
4000	7.6	90	13.23	3983.11	13.23	-.00	242.22	-44.42	
4100	7.6	75	13.23	4082.23	12.77	3.42	254.99	-40.99	
4200	7.6	66	13.23	4181.35	12.08	5.38	267.08	-35.61	
4300	7.4	69	12.88	4280.52	12.02	4.62	279.10	-31.00	
4400	7.0	66	12.19	4379.77	11.13	4.96	290.23	-26.04	
4500	6.7	65	11.67	4479.09	10.57	4.93	300.81	-21.11	
4600	6.3	65	10.97	4578.49	9.95	4.64	310.75	-16.47	
4700	6.3	64	10.97	4677.88	9.86	4.81	320.62	-11.66	
4800	6.5	68	11.32	4777.24	10.50	4.24	331.11	-7.42	

GEODIGIT

4890	6.3	69	9.88	4866.70	9.22	3.54	340.33	-3.88
5000	6.2	64	11.88	4976.05	10.68	5.21	351.01	1.32
5100	5.7	59	9.93	5075.56	8.51	5.12	359.52	6.44
5200	5.3	52	9.24	5175.13	7.28	5.69	366.80	12.13
5300	4.9	54	8.54	5274.77	6.91	5.02	373.71	17.15
5400	5.0	51	8.72	5374.39	6.77	5.48	380.49	22.63
5500	5.1	52	8.89	5473.99	7.00	5.47	387.49	28.10
5600	5.3	49	9.24	5573.56	6.97	6.06	394.46	34.16
5700	5.2	49	9.06	5673.15	6.84	5.95	401.30	40.11
5800	5.2	58	9.06	5772.74	7.69	4.80	408.99	44.91
5900	4.8	64	8.37	5872.39	7.52	3.67	416.51	48.58
6000	4.7	68	8.19	5972.05	7.60	3.07	424.11	51.65
6100	4.6	63	8.02	6071.73	7.15	3.64	431.25	55.29
6200	4.8	74	8.37	6171.38	8.04	2.31	439.30	57.60
6300	4.7	69	8.19	6271.04	7.65	2.94	446.95	60.54
6400	4.4	74	7.67	6370.75	7.37	2.11	454.32	62.65
6500	3.7	69	6.45	6470.54	6.02	2.31	460.35	64.96
6600	3.4	65	5.93	6570.36	5.37	2.51	465.72	67.47
6700	3.2	75	5.58	6670.21	5.39	1.41	471.11	68.91
6800	3.1	64	5.41	6770.06	4.86	2.37	475.97	71.28
6900	2.6	89	4.54	6869.96	4.54	.08	480.51	71.36
7000	2.7	89	4.71	6969.85	4.71	.08	485.22	71.45
7100	2.6	84	4.54	7069.75	4.51	.47	489.73	71.92
7200	2.5	76	4.36	7169.65	4.23	1.06	493.96	72.98
7300	2.9	69	5.06	7269.52	4.72	1.81	498.69	74.79
7400	3.3	74	5.76	7369.36	5.53	1.59	504.22	76.37
7500	2.5	104	4.36	7469.26	4.23	-1.06	508.45	75.32
7600	3.0	114	5.23	7569.12	4.78	-2.13	513.23	73.19
7700	3.8	129	6.63	7668.90	5.15	-4.17	518.38	69.02
7800	4.6	119	8.02	7768.58	7.01	-3.89	525.40	65.13
7900	6.0	106	10.45	7868.03	10.05	-2.88	535.44	62.25
8000	7.6	89	13.23	7967.16	13.22	.23	548.67	62.48
8100	8.5	106	14.78	8066.06	14.21	-4.07	562.88	58.41
8200	8.8	104	15.30	8164.88	14.84	-3.70	577.72	54.71
8300	8.7	89	15.13	8263.73	15.12	.26	592.84	54.97
8350	9.1	99	7.91	8313.10	7.81	-1.24	600.66	53.73
8400	10.9	99	9.45	8362.20	9.34	-1.48	609.99	52.25
8500	12.0	94	20.79	8460.01	20.74	-1.45	630.73	50.80
8550	13.4	80	11.59	8508.65	11.41	2.01	642.15	52.82
8600	14.6	84	12.60	8557.04	12.53	1.32	654.68	54.13
8650	15.7	76	13.53	8605.17	13.13	3.27	667.81	57.41
8720	17.5	75	21.05	8671.93	20.33	5.45	688.14	62.85

DRIFT DISTANCE= 691.00 FEET
AZM OF DRIFT = 84 DEGREES

SCALE= 90. FEET/IN.
XMAX= 688.00 XMIN= -5.00
YMAX= 76.00 YMIN= -66.00