

000961

DDH. N°	FOOTAGE	Pb+Zn	CORR S.G.	CUFT/Tonn.	CRUSHED S.G.	CUFT/Tonn.
66-1	132	2.4	3.94	8.14	3.98	8.06
66-2	183	16.1	4.58	7.01	4.52	7.10
66-4	242	.5	4.02	7.98	4.06	7.90
66-5	514	4.8	4.63	6.93	4.66	6.88
66-5	534	7.4	4.30	7.46	4.35	7.37
66-6	613	8.1	4.86	6.60	4.88	6.58
66-8	391	7.9	4.61	6.96	4.94	6.50
66-8	501	7.2	4.28	7.50	4.73	6.78
66-10	556	3.5	2.94	10.91	3.09	10.38
66-10	629	2.9	3.80	8.44	4.02	7.98
66-12	283	10.6	4.36	7.36	4.48	7.16
66-18	181	8.3	4.45	7.21	3.55	9.04
66-18	204	.5	3.20	10.03	3.30	9.73
66-18	209	12.7	3.16	10.15	3.33	9.63
66-19	143	18.1	4.25	7.55	4.44	7.23
66-22	219	.2	3.53	9.09	3.65	8.79
66-22	222	.1	4.22	7.60	4.40	7.29
		6.66A%	4.066	8.054 (7.892)	4.140	7.964 (7.751)