

001412

CURRAGH RESOURCES INC.
MONTH FORECAST DEVELOPMENT/PRODUCTION
file: MARSCHED

FOX GEOLOGICAL CONSULTANTS LTD.

*MAR SCHED
ROUGH*

| DEVELOPMENT | | | | | ASSAY GRADES | | | DILUTION | | | | NOTES | |
|------------------|---------------|---------------|----------------|-----------------|--------------|------|------|----------|------|----------------|----------------|-------------------|--|
| | HEADING | HEIGHT | WIDTH | ADVANCE | TONNES | Pb | Zn | Ag | ZHW | ZFW | IHW T's | | IFW T's |
| SA400 | 16 | 16 | 50 | 1408 | 4.99 | 7.09 | 77 | | | 0.0 | 0.0 | 1408.0 | 70' ADV SAK AREA |
| SK100 | 12.5 | 16 | 12 | 264 | | | | | | 0.0 | 0.0 | 264.0 | |
| SK100 RSE | 6 | 6 | 15 | 59 | | | | | | 0.0 | 0.0 | 59.4 | |
| SJK RAMP | 16 | 16 | 15 | 422 | | | | | | 0.0 | 0.0 | 422.4 | |
| SN1100 | 14 | 16 | 70 | 1725 | | | | | | 0.0 | 0.0 | 1724.8 | 210' ORE |
| SN1600 | 14 | 15 | 40 | 832 | | | | | | 0.0 | 0.0 | 831.6 | |
| SN1800 | 16 | 16 | 100 | 2816 | | | | | | 0.0 | 0.0 | 2816.0 | 80' WASTE 290' ADV SN AREA (ALMOST 1 ROUND/DAY) |
| SX RAMP | 14 | 15 | 60 | 832 | | | | | | 0.0 | 0.0 | 831.6 | |
| SK100 | 16 | 16 | 100 | 2816 | | | | | | 0.0 | 0.0 | 2816.0 | 380' ADV = 1 ROUND/DAY SX AREA |
| SK200 | 14 | 15 | 70 | 1455 | | | | | | 0.0 | 0.0 | 1455.3 | |
| SK300 | 16 | 16 | 30 | 845 | | | | | | 0.0 | 0.0 | 844.8 | |
| SK300 | 14 | 15 | 40 | 832 | | | | | | 0.0 | 0.0 | 831.6 | |
| SK400 | 16 | 16 | 100 | 2816 | | | | | | 0.0 | 0.0 | 2816.0 | |
| SUB TOTAL | 16 | 16 | 710 | 682 | 17122 | 0.00 | 0.00 | 0 | 0.0% | 0.0% | 0 | 0 | 17122 |

WASTE

| DEVELOPMENT | HEADING | HEIGHT | WIDTH | ADVANCE | WASTE TONNES |
|-------------|---------|--------|-------|---------|--------------|
| SN1400 | 14 | 15 | 50 | 1040 | |
| SN1600 | 14 | 15 | 30 | 624 | |
| SL300 BE | 6 | 16 | 35 | 370 | |
| | | | | 0 | |
| SUB TOTAL | | | 115 | 2033 | |

| PRODUCTION HEADING | HEIGHT | WIDTH | ADVANCE | TONNES | ASSAY GRADES | | | DILUTION | | | NOTES |
|-----------------------|--------|-------|---------|--------|--------------|------|----|----------|-----|--------|-------|
| | | | | | Pb | Zn | Ag | %HW | %FW | HW T's | |
| SA RMS | 16 | 20 | 40 | 1408 | 4.33 | 6.56 | 66 | 0.0 | 0.0 | 1408.0 | |
| SA BRST | 17 | 16 | 100 | 2992 | 4.33 | 6.56 | 66 | 0.0 | 0.0 | 2992.0 | |
| SB BRST | 8 | 16 | 100 | 1408 | | | | 0.0 | 0.0 | 1408.0 | |
| SC RMS | 16 | 20 | 25 | 880 | 4.83 | 7.15 | 75 | 0.0 | 0.0 | 880.0 | |
| SC BE | 15 | 16 | 200 | 5280 | 4.33 | 6.60 | 81 | 0.0 | 0.0 | 5280.0 | |
| SD RMS | 16 | 20 | 1039 | 1056 | 5.88 | 8.47 | 80 | 0.0 | 0.0 | 1056.0 | |
| SG151 BE | 16 | 30 | 45 | 2376 | 4.87 | 9.11 | 79 | 0.0 | 0.0 | 2376.0 | |
| SG100 BE | 10 | 16 | 40 | 704 | | | | 0.0 | 0.0 | 704.0 | |
| SGH100 RMS | 14 | 20 | 60 | 1848 | | | | 0.0 | 0.0 | 1848.0 | |
| SH BRST | 14 | 16 | 110 | 2710 | 4.11 | 7.12 | 67 | 0.0 | 0.0 | 2710.4 | |
| SH 002 | 16 | 20 | 10 | 352 | 4.11 | 7.12 | 67 | 0.0 | 0.0 | 352.0 | |
| SHB00 BE | 15 | 16 | 100 | 2640 | 5.02 | 7.73 | 66 | 0.0 | 0.0 | 2640.0 | |
| SH1000 RM | 16 | 20 | 10 | 352 | | | | 0.0 | 0.0 | 352.0 | |
| SH1000 BE | 14 | 16 | 100 | 2464 | 3.68 | 7.72 | 69 | 0.0 | 0.0 | 2464.0 | |
| SK100 BE | 9 | 16 | 83 | 1315 | | | | 0.0 | 0.0 | 1314.7 | |
| SL300 RMS | 16 | 20 | 60 | 2112 | 4.63 | 6.28 | 69 | 0.0 | 0.0 | 2112.0 | |
| SL400 BEN | 10 | 16 | 100 | 1760 | 4.69 | 6.28 | 69 | 0.0 | 0.0 | 1760.0 | |
| SN900 RMS | 16 | 20 | 90 | 3168 | 4.33 | 7.75 | 62 | 0.0 | 0.0 | 3168.0 | |
| SN940 RMS | 16 | 20 | 100 | 3520 | 4.33 | 7.75 | 62 | 0.0 | 0.0 | 3520.0 | |
| SN1000 RM | 16 | 20 | 30 | 1056 | 4.83 | 7.88 | 82 | 0.0 | 0.0 | 1056.0 | |
| SN1000 BE | 16 | 16 | 100 | 2816 | " | " | " | 0.0 | 0.0 | 2816.0 | |
| SN1200 RMS | 16 | 20 | 20 | 704 | 4.22 | 7.42 | 67 | 0.0 | 0.0 | 704.0 | |
| SN500 RMS | 16 | 20 | 25 | 0 | | | | 0.0 | 0.0 | 0.0 | |
| | | | | 0 | | | | 0.0 | 0.0 | 0.0 | |
| | | | | 0 | | | | 0.0 | 0.0 | 0.0 | |

7123T PROD
 2153T DEV
 9276 T
 SA/B AREA = 15%
 7920T FROM SCD AREA = 13%
 7286 T FROM SG/H AREA = 12%
 5456 T SH800 / SH1000 = 9%
 3892T ORE = 4242 T SL300/400 7%
 390T W
 SN900/940 DEV. SX AREA = 16284 T SN 900/940/SX
 6688 PROD + 9596T
 SN1000/1200 DEV. SN AREA = 11613 T SN/SN1000/SN1200
 4576 + 7037 = 11613 T
 SN: 11264T PROD 16633 T DEV 27897 T
 45% SN AREA
 27% = DEV.

SUB TOTAL 1553 42921 0.00 0.00 0 0.0% 0.0% 0 0 42921

GRAND TOTAL ORE 2235 60043 0.00 0.00 0 0.0% 0.0% 0 0 60043

GRAND TOTAL WASTE 115 2033
 GRAND TOTAL BREAK 2350 62075
 62002

TOTAL DAYS: 31

DEVELOPMENT ADVANCE: 797 PERCENT DEVELOPMENT: 33.9% 34.5%
 PRODUCTION ADVANCE: 1553 PERCENT PRODUCTION: 66.1% 65.5%
 TOTAL TONNAGE/DAY: 2002 2000T TOTAL ORE TONNAGE/DAY: 1937
 PERCENT Pb+Zn: 0 TOTAL PERCENT DILUTION: 0.0%

DATE: 29-Feb-92

NOTES: