

ANVIL MINING CORPORATION

JUN 30, 1975

ORE RESERVES ZONE

Available Ore with ramp on E. side (Alternate I)  
Following Same Test Hole Division.

3750 Bench

Page 1 of 1

Drill Hole	Area Units	Tons (A.U. x K*)	O R E			Remarks	Yards (A.U.xC*)	W A S T E		Total Yards
			Grade					Area Units	Yards (x7407.4)	
			Pb	Zn	Comb					
3750-K(2)		35,238	4.1	4.6						
TH-11	28	6,596	3.6	3.7						
TH-10	64	15,076	4.5	5.2						
TH-28	100	23,556	3.7	3.3						
TH-40	100	23,556	3.6	4.2						
TH-26	78	18,373	3.0	3.1						
TH-25	46	10,836	4.9	5.0						
K-34	18	4,240	3.3	4.6						
TH-30	80	18,844	4.3	4.3						
ZL-02	124	29,208	2.3	3.9						
66-33	48	11,307	4.2	7.2						
74-09	50	11,778	4.1	5.5						
74-05	104	942	4.6	3.8						
TH-34	-	471	3.1	4.3						
TH-17	-	5889	3.2	3.9						
TH-20	-	14,369	4.0	5.6						
K-12	-	5,654	2.0	3.2						
70-09	-	3,533	4.8	7.5						
TH-43	-	14,723	2.2	3.2						
TH-49	-	14,015	2.2	4.0						
K-361	-	17,902	6.4	8.2						
I-292	-	942	2.6	3.8						
TH-23	40	9422	9.3	10.9						
TH-22	100	23,556	7.1	8.9						
K-284	-	11,502	5.2	7.1						
TH-05	-	5,359	5.6	7.2						
I-170	-	589	4.8	5.8						
TH-53	60	14,133	2.9	4.6						
TH-54	-	21,554	3.9	6.5						
TH-56	-	12,249	2.3	4.2						
0-53	-	2,297	7.3	7.8						
0-85	-	2,944	3.4	4.8						
72-08	-	20,493	6.7	7.5						
78-03	-	2,356	4.2	6.1						
65-08	-	64,778	6.8	7.5						
72-03	-	1,624.2	5.4	7.2						
Total a*										
Total b*										
Total (a+b)										
Cum Totala										
Cum Totalb										
Total(a+b)		495,122	4.6	5.7						