

*** VANGORDA - Drill Hole Database ***

007175

| | | | | | |
|---------|------|------|-------|----------|---|
| B1VR-24 | .0 | 10.7 | # | | 0 |
| B1VR-24 | 10.7 | 21.3 | 4EG | | 0 |
| B1VR-24 | 21.3 | 25.9 | 4L/3G | | 0 |
| B1VR-24 | 25.9 | 30.5 | 5A | | 0 |
| B1VR-25 | .0 | 7.6 | # | | 0 |
| B1VR-25 | 7.6 | 13.7 | 4L/3G | | 0 |
| B1VR-25 | 13.7 | 19.8 | 4EG | | 0 |
| B1VR-25 | 19.8 | 22.9 | 4L/3G | | 0 |
| B1VR-25 | 22.9 | 24.4 | 4EG | | 0 |
| B1VR-25 | 24.4 | 25.9 | 4L/3G | | 0 |
| B1VR-25 | 25.9 | 30.5 | 5A | | 0 |
| B1VR-26 | .0 | 10.7 | # | CASING | 0 |
| B1VR-26 | 10.7 | 18.3 | 4EG | | 0 |
| B1VR-26 | 18.3 | 19.8 | 4L/3G | | 0 |
| B1VR-26 | 19.8 | 21.3 | 4EG | | 0 |
| B1VR-26 | 21.3 | 24.4 | 4L/3G | | 0 |
| B1VR-26 | 24.4 | 30.5 | 4A | | 0 |
| B1VR-26 | 30.5 | 42.7 | 4L/3G | | 0 |
| B1VR-26 | 42.7 | 45.7 | 4E | | 0 |
| B1VR-34 | .0 | 4.6 | # | | 0 |
| B1VR-34 | 4.6 | 9.1 | 4EG | | 0 |
| B1VR-34 | 9.1 | 12.2 | 4L/3G | | 0 |
| B1VR-34 | 12.2 | 13.7 | 4EG | | 0 |
| B1VR-34 | 13.7 | 25.9 | 4L/3G | | 0 |
| B1VR-34 | 25.9 | 29.0 | 4EG | | 0 |
| B1VR-34 | 29.0 | 30.5 | 4EC | | 0 |
| B1VR-21 | .0 | 6.1 | # | TRICONED | 0 |
| B1VR-21 | 6.1 | 12.2 | 4L/3G | | 0 |
| B1VR-21 | 12.2 | 22.9 | 4EG | | 0 |
| B1VR-21 | 22.9 | 30.5 | 4A/5A | | 0 |
| B1VR-20 | .0 | 6.1 | # | | 0 |
| B1VR-20 | 6.1 | 12.2 | 4A | | 0 |
| B1VR-20 | 12.2 | 16.8 | 4L/3G | | 0 |
| B1VR-20 | 16.8 | 19.8 | 4EG | | 0 |
| B1VR-20 | 19.8 | 22.9 | 4A | | 0 |
| B1VR-20 | 22.9 | 29.0 | 4L/3G | | 0 |
| B1VR-22 | .0 | 4.6 | # | | 0 |
| B1VR-22 | 4.6 | 9.1 | # | | 0 |
| B1VR-22 | 9.1 | 16.8 | 4L/3G | | 0 |
| B1VR-22 | 16.8 | 18.3 | 5A | | 0 |
| B1VR-22 | 18.3 | 22.9 | 4EG | | 0 |
| B1VR-22 | 22.9 | 27.4 | 4EC | | 0 |
| B1VR-22 | 27.4 | 30.5 | 4CO | | 0 |
| B1VR-23 | .0 | 7.6 | # | | 0 |
| B1VR-23 | 7.6 | 12.2 | 4EG | | 0 |
| B1VR-23 | 12.2 | 19.8 | 4EC | | 0 |
| B1VR-23 | 19.8 | 21.3 | 4EG | | 0 |
| B1VR-23 | 21.3 | 22.9 | 4EC | | 0 |
| B1VR-23 | 22.9 | 25.9 | 4CO | | 0 |
| B1VR-23 | 25.9 | 30.5 | 4L/3G | | 0 |
| B1VR-18 | .0 | 4.6 | # | | 0 |
| B1VR-18 | 4.6 | 10.7 | # | | 0 |
| B1VR-18 | 10.7 | 19.8 | 4EG | | 0 |
| B1VR-18 | 19.8 | 22.9 | 4EC | | 0 |

*** VANGORDA - Drill Hole Database ***

| | | | | | |
|---------|------|------|-------|-----------------------|-----|
| B1VR-18 | 22.9 | 27.4 | 4CO | | 0 |
| B1VR-18 | 27.4 | 30.5 | 4L/3G | | 0 |
| B1VR-13 | .0 | 6.1 | # | | 0 |
| B1VR-13 | 6.1 | 7.6 | 4EG | | 0 |
| B1VR-13 | 7.6 | 25.9 | 4L/3G | | 0 |
| B1VR-15 | .0 | 7.6 | # | | 0 |
| B1VR-15 | 7.6 | 12.2 | 4EG | | 0 |
| B1VR-15 | 12.2 | 19.8 | 4EC | | 0 |
| B1VR-15 | 19.8 | 25.9 | 4L/3G | | 0 |
| B1VR-12 | .0 | 10.7 | # | CASING | 0 |
| B1VR-12 | 10.7 | 25.9 | 4EG | | 0 |
| B1VR-12 | 25.9 | 29.0 | 4EC | | 0 |
| B1VR-12 | 29.0 | 30.5 | 4L/3G | | 0 |
| B1VR-07 | .0 | 7.6 | # | CASING | 0 |
| B1VR-07 | 7.6 | 13.7 | 4L/3G | | 0 |
| B1VR-07 | 13.7 | 24.4 | 4EG | | 0 |
| B1VR-07 | 24.4 | 29.0 | 4EC | | 0 |
| B1VR-07 | 29.0 | 33.5 | 4EG | | 0 |
| B1VR-07 | 33.5 | 38.1 | 4EC | | 0 |
| B1VR-07 | 38.1 | 44.2 | 4CO | | 0 |
| B1VR-07 | 44.2 | 56.4 | 4L/3G | | 0 |
| B1VR-09 | .0 | 12.2 | # | CASING | 0 |
| B1VR-09 | 12.2 | 13.7 | # | TILL | 0 |
| B1VR-09 | 13.7 | 15.2 | 4L/3G | | 0 |
| B1VR-09 | 15.2 | 25.9 | 4EG | | 0 |
| B1VR-09 | 25.9 | 27.4 | 4EC | | 0 |
| B1VR-09 | 27.4 | 47.2 | 4CO | | 0 |
| B1VR-09 | 47.2 | 56.4 | 4L/3G | | 0 |
| B1VR-10 | .0 | 16.8 | # | CASING | 0 |
| B1VR-10 | 16.8 | 18.3 | 4EG | | 0 |
| B1VR-10 | 18.3 | 27.4 | 4EC | | 0 |
| 90V-17 | .0 | 2.0 | 0 | CASING, NO RECOVERY | 0 |
| 90V-17 | 2.0 | 5.2 | OB | OB | 300 |
| 90V-17 | 5.2 | 11.3 | 4L0 | WEATHERED | 120 |
| 90V-17 | 11.3 | 15.4 | 4G4 | +/-8, BROKEN & RUBBLY | 60 |
| 90V-17 | 15.4 | 15.9 | 4L0 | +/-4, WEATHERED | 120 |
| 90V-17 | 15.9 | 16.5 | 4E0 | +/-7 | 50 |
| 90V-17 | 16.5 | 17.4 | 4L24 | +/-1 | 120 |
| 90V-17 | 17.4 | 19.1 | 4G4 | +/-1 (4L0) 80/20% | 60 |
| 90V-17 | 19.1 | 21.4 | 4G44 | +/-8 | 60 |
| 90V-17 | 21.4 | 23.1 | 4L2 | +/-4.5 | 120 |
| 90V-17 | 23.1 | 25.7 | 4A0 | | 20 |
| 90V-17 | 25.7 | 33.2 | 3E0 | | 110 |
| 90V-17 | 33.2 | 33.5 | 4E0 | | 50 |