

HF 6-134

SHEET 1

1. 1250
Yukon Survey
LVA Series 1 6612

CONTOUR INTERVAL 20 GAMMA
 MEAN FLIGHT LINE SPACING 1000 FEET
 MEAN TERRAIN CLEARANCE (BIRD) 100 FEET
 500 GAMMA CONTOUR
 100 GAMMA CONTOUR
 20 GAMMA CONTOUR
 MAGNETIC LOW
 FIDUCIAL POINTS
 FLIGHT LINES

MEAN FLIGHT LINE SPACING 1000 FEET
 MEAN TERRAIN CLEARANCE (BIRD) 100 FEET
 ELECTROMAGNETIC CONTOURS 5, 10, 15 etc
 FIDUCIAL POINTS
 FLIGHT LINES
 The contours represent amplitude of in phase response of the resultant field expressed in parts per million of the primary in phase component
 The figures (5) represent amplitude quadrature component
 The frequency of the primary current is 4000 cycles per second.

TAY RIVER AREA
 YUKON TERRITORY

SCALE - 1 inch to 1320 Feet

Drawn and Compiled for
 DYNASTY EXPLORATION LIMITED
 by
 LOCKWOOD SURVEY CORPORATION LIMITED
 TORONTO, CANADA
 1965

010329