



CONTOUR INTERVAL..... 20 GAMMA
 MEAN FLIGHT LINE SPACING..... 1000 FEET
 MEAN TERRAIN CLEARANCE (BIRD)..... 100 FEET
 500 GAMMA CONTOUR.....
 100 GAMMA CONTOUR.....
 20 GAMMA CONTOUR.....
 MAGNETIC LOW.....
 FIDUCIAL POINTS.....
 FLIGHT LINES.....

MEAN FLIGHT LINE SPACING..... 1000 FEET
 MEAN TERRAIN CLEARANCE (BIRD)..... 100 FEET
 ELECTROMAGNETIC CONTOURS 5, 10, 15 etc.
 1, 2, 3, 4, etc.....
 FIDUCIAL POINTS.....
 FLIGHT LINES.....

The contours represent amplitude of in phase response of the resultant field expressed in parts per million of the primary.
 The figures represent amplitude in phase component.
 The frequency of the primary current is 4000 cycles per second.

TAY RIVER AREA
YUKON TERRITORY

010334

Flown and Compiled
for
DYNASTY EXPLORATION LIMITED
by
LOCKWOOD SURVEY CORPORATION LIMITED
TORONTO, CANADA
1965

SCALE - 1 inch to 1320 Feet

