

015499

Mark this file
Diamond Drilling
Bonnefance

of 7/5/c

July 6th, 1965

- W.S.R.
- K.C.G.
- J.H.S.
- E.F.
- R.D.S.
- B.C.B.
- P.M.K. ✓
- G.W.M.
- R.O.M.
- C.K.W.
- J.B.S.
- G.P.R.
- K.F.L.
- ~~A.B.~~
- E.C.J.

Taken from W. M. Sirola's Monthly Report for June, 1965.

SWIM LAKES 'A' GROUP

The diamond drill reached the 'A' group on June 3rd. Drill hole A-2 was collared at a location marked 65W. 900S. The bearing of the hole is S.32W. with a dip of 60°S.W. Drilling commenced on June 6th after considerable difficulty, and the hole was terminated on June 14th. On this date the drill rods were dropped in the hole and could not be recovered. In consequence, the hole was abandoned.

From 191 - 240 ft. the hole was in massive sulphides containing low values in lead, zinc, copper and silver.

Drill hole A-3 was collared 200 ft. westerly (at right angles to line 65W.) of 10 + 12 S. This was a vertical hole which encountered bedrock at 14 ft. and penetrated graphitic and sericitic schist to 88 ft. From 88 - 113 ft. no core was recovered and the hole was abandoned at 113 ft. At this stage we do not know why the second hole could not be reamed and cased through the non-coring section.

We then advised McRae to collar A-4 at line 9 S. 66 W. At last report on June 29th, the casing at A-4 was in overburden at 25 ft.

The copious water supply encountered at 183 ft. in hole A-2 apparently ceased to flow. Hose is being laid from A-1 to A-4, a distance of some 3,600 ft.