

ANVIL MINING CORPORATION LIMITED

Whitehorse, Yukon

PROPERTY NAME FRRO ZONE N° 2LOCATION ROSE CREEK, YUKONDATE DRILLED MAY 6, 1966 to MAY 16/66SCALE OF LOG 1" = 40' LOGGED BY D.M. DATE MAY 17/66
(1" = 10' in ore zone) no ore zone D.M.HOLE NO. 44-63A DEPTH 350'COLLAR ELEVATION 3937.5 CORE SIZE AXBEARING — (MAG OR TRUE DIP -90°)CO-ORDINATES 5701.1 N. 16.782.0 E.SURFACE ☒ OR UNDERGROUND —TOTAL RECOVERY 163.2 = 55.33%

SHEET 1 OF 2

6,913,824.10 N

585,308.15 E

ROCK TYPES AND ALTERATION	MINERALIZATION AND STRUCTURES	FOOTAGE BLOCKS	% RECOVERY	SAMPLE NO.	INTERVAL							
					FROM	TO						
0.0' - 30.0' OVERBURDEN												
30-57. Rock bitted												
57.0' - 75.0' - QUARTZ FELDSPAR porphyry (minor pyrite) - m. grained, feldspars slightly altered	Foliation - 450' - 800' - 45°	57.5 60 61.4 63.5 67 71 71.5 80	10 0.8 0 2.5 1.4 1.0 2.2									
75 80												
75.0' - 139.0' - QUARTZITIC METAPHYLITE biotitic; sericitic; light medium grey in color; quartz veining - v. minor.	Foliation - 80.0' - 120.0' - 40° 75.0' - 139.0' - Crenulated	80 90 93 96 102 108 110 116 118 120	1.4 1.6 1.2 0.8 1.8 4.4 1.8 5.8 1.6 4.2									
120												
139												
139.0' - 148.0' - QUARTZ DIORITE; moderately altered; v. light grey in color; m. grained	Foliation - 120.0' - 139.0' - 30°	120 124 126 128 130	2.3 1.0 1.1 1.3									
148.0' - 177.0' - QUARTZ DIORITE; sl. altered.	140' - 144' - FAULT ZONE - Broken core, gouged 177' - 181' - FAULT ZONE - Intense alteration, broken core, gouged.	140 144 146 150 154 156	4.5 1.7 0.8 1.2 0.7									
160												
177.0' - 282.0' - QUARTZ DIORITE; moderate alteration		161 167 171 176 181 183 185 187 190	0.7 0.8 1.8 2.3 1.5 1.8 0.8 1.9 4.2									
200												
		201 206 211 213 216	2.8 1.0 1.2 1.0 1.6									
		226 227 232	2.0 4.3 1.1									



PAGE OF

COMPANY NAME _____
PROPERTY NAME _____
DRILLING CONTRACTOR _____
ASSAYER _____
PURPOSE OF HOLE _____

HOLE NO. 66-63A

CLAIM NAME _____

COMMENCED _____

FINISHED _____

PROJECT NO. _____

[illegible]