015738

ANVIL MINING CORPORATION LIMITED
Whitehorse, Yukon

HOLE NO. 72R1 DEPTH 400'

SHEET 1 OF 2

PROPERTY NAME RAM CLAIMS

COLLAR ELEVATION ..... CORE SIZE BQ ..... INCLINATION TESTS

LOCATION ..... BEARING ..... (MAG OR TRUE DIP -90°

CO-ORDINATES 1600 N. 0 E.

DATE DRILLED 25 AUGUST - 6 SEPT 1972 SURFACE ✓ OR UNDERGROUND .....

SCALE OF LOG 1" = 40' LOGGED BY U. J. DATE ..... TOTAL RECOVERY 96.7

	ROCK TYPES AND ALTERATION		MINERALIZATION AND STRUCTURES	FOOTAGE BLOCKS	% RECOVERY	SAMPLE No.	INTERVAL FROM	INTERVAL TO
0			S_2					
10	OVERBURDEN							
	AMPHIBOLITE, Med Grain, Grey-Green		tr cpy, py all << 0.01%	0.9, 0.6, 1.6, 0.3, 5.0, 8.4				
30½	AMPHIBOLITE, Fine Grain, Dark Grey-Green			10.8				
	Chloritic sections 74-89, 86-86½, 91-95		S^2 35-40°	8.4, 10.4, 5.1, 8.5, 2.0, 3.6				
				0.3, 5.6, 1.5, 4.3, 2.6, 10.6, 6.3, 10.7				
				10.6, 10.4				
142	AMPHIBOLITE, Med.-Fine Grain, Gn-Gy chloritic		1" qtz stringer @ 148, 150	10.4				
152½	AMPHIBOLITE Med-Fine grain, Gy-Gn		tr cpy	10.0				
167	AMPHIBOLITE, Chloritic		tr cpy	10.2, 6.0				
185	AMPHIBOLITE, Med Grain, Gn-Gy			10.4				
194	AMPHIBOLITE, Fine Grain, Gn Gy		tr cpy ; to 2-3% cpy po for ½" @ 211½	7.5				
				10.1, 4.2				
215	AMPHIBOLITE, Med Grain Gn Gy		tr cpy	10.4, 9.0				
229	AMPHIBOLITE, Med-Fine gr		tr FeOx on fractures	10.3				

ANVIL MINING CORPORATION LIMITED Whitehorse, Yukon

PROPERTY NAME RAM HOLE NO. 72R1 SCALE OF LOG 1" = 40

SHEET 2 OF 2

	ROCK TYPES AND ALTERATION	S_2 R_2	MINERALIZATION AND STRUCTURES	FOOTAGE BLOCKS	% RECOVERY	SAMPLE No.	INTERVAL FROM	INTERVAL TO
243	AMPHIBOLITE, Med. Grain, Dk Gy		<1%, tr coarse gr Po & tr cpy	4.0 0.1 3.4				
253	AMPHIBOLITE, Banded, chloritic grades to white, fn fine gr tuff @ 258. Becomes dark gy towards contact.		No sulfides noted. Banded-foliated rock. Fo 25-30° @ 269, 30-50° @ 271. tr py	1.3 1.0 1.0 1.0