THE DECLINATION OF THE COMPASS NEEDLE, 1950



The declination of the compass needle at any place along a red line is the declination given on that red line. At other places the declination is between those given on the neighbouring red lines; thus at the place marked A, the declination is between 31.5° E and 32.5° E. The easterly declinations of the compass needle are decreasing 4.5 minutes annually.

Surveyed, compiled, drawn and printed by the ARMY SURVEY ESTABLISHMENT R.C.E., 1949-51
Aerial photography by the R.C.A.F. 1949.
Published 1951.

REFERENCE

	More than 2 Lanes	Partially Completed
Road, Hard Surface, All Weather	2 Lanes	Route No. 13 / Less than 2 Lanes
,, Hard Surface, All Weather	More than 2 Lanes	2 Lanes
,, Loose Surface, All Weather	All Weather	Dry Weather
,, Loose Surface, Less than 2 Lanes		
Railway, Multiple Track		
,, Single Track		
Boundary, International		
,, Province or State		
,, County or District		
,, Reservations, Indian, Military, Park, etc.		

Scale 1 : 250,000
Approximately 1 Inch to 4 Miles

Miles 5 0 5 10 15 20 Miles
Kilometres 5 0 5 10 15 20 25 30 Kilometres

Copies may be obtained from
The Map Distribution Office,
Dept. of Mines and Technical Surveys,
Ottawa, at 25 cents each.

inches 0 1 2
0 1 2 3 4 5 centimetres

YUKON GEOLOGICAL SURVEY

This reference scale bar has been added to the original image. It will scale at the same rate as the image, therefore it can be used as a reference for the original size.

Contour interval 500 Feet.
All Elevations in Feet above Mean Sea Level.
Universal Transverse Mercator Projection

REFERENCE

Triangulation Station	Spot Elevation, in feet 257
Contours, Elevation ..... 500 / 1000	Wooded Areas
,, Depression ..... 1000 / 500	Swamp or Marsh
,, Approximate	
Stream, Intermittent	W.L. 241
Dam	Ferry / Mud
Falls	Navigation Light / Sand
Aerodrome, on Land	Elevation in Feet 250 / on Water
Main Electric Power Line	



NOTE: On the above index the sheets published are shown tinted green

TAY RIVER
YUKON TERRITORY

016056

SHEET 105 K
FIRST EDITION