

018006

①

Swim Lakes "A" Group

May 26/64

Line	Sta	Readings		Line 14 is on chain line between #17	
14W	0	-24	+19	-5	8045
"	50 S	-23	+20	-3	8045
"	100 S	-25	+21	-4	9125
"	150 S	-28	+23	-5	
"	200 S	-29	+24	-5	8810
"	250 S	-27	+22	-5	
"	300 S	-24	+22	-2	9325
"	400 S	-18	+14	-4	9615
"	500 S	-16	+12	-4	9360
"	600 S	-15	+9	-6	9860
"	700 S	-13	+9	-4	9898
"	800 S	-10	+8	-2	9395
"	900 S	-5	+5	-0	9325
"	1000 S	-6	+3	-3	9430
"	1100 S	-8	+5	-3	9395
"	1200 S	-8	+7	-1	9430
"	1300 S	-6	+2	-4	9395
"	1350 S	-4	-1	-5	
"	1400 S	-6	-3	-9 N	9475
"	1450 S	-9	-3	-12 N	
"	1500 S	-12	0	-12	9580
"	1550 S	-20	-2	-22	
"	1600 S	-22	-3	-25 N	9650
"	1650 S	-20	-6	-26	

<u>Line</u>	<u>Sta</u>	<u>Readings</u>			
148N	1700 S	-23	-10	-33	9475
"	1750 S	-22	-14	-36	
"	1800 S	-22	-16	-38	9545
"	1850 S	-22	-12	-34	
"	1900 S	-17	-12	-29	
"	1950 S	-15	-12	-27	
"	2000 S	-16	-9	-25	8950?
"	2050 S	-15	-7	-22	
"	2100 S	-14	-9	-23	9395
"	2150 S	-18	-8	-26	
"	2200 S	-21	-10	-31	9395
"	2250 S	-19	-12	-31	
"	2300 S	-11	-8	-19	9580
"	2350 S	-13	-6	-19N	
"	2400 S	-17	-5	-22N	9545
"	2450 S	-18	-8	-26N	
"	2500 S	-17	-11	-28	9720
"	2550 S	-13	-13	-26	
"	2600 S	-11	-8	-19N	9545
"	2650 S	-5	-6	-11	
"	2700 S	-10	-9	-19	9545
"	2750 S	-15	-11	-26	

Chain Post 100' W of the Sta

"	2800 S	-19	-15	-34	9580
"	2850 S	-15	-20	-35	

<u>Line</u>	<u>Sta</u>	<u>Readings</u>			
14W	2900 S	-9	-20	-29	9475
"	2950 S	-8	-10	-18	
"	3000 S	-8	-7	-15	9395
"	3050 S	-9	-8	-17	
"	3100 S	-10	-10	-20	9280
"	3150 S	-11	-7	-18	
"	3200 S	-9	0	-9	9220
"	3250 S	-10	+2	-8	
"	3300 S	-8	+5	-3	9255
"	3350 S	-6	+5	-1	
"	3400 S	-1	0	-1	9255
	3500 S				9395

<u>Line</u>	<u>Sta</u>	<u>Readings</u>			
18W	3500 S	-4	+2	-2	
"	3400 S	-5	0	-5	9160
"	3300 S	-1	-1	-2	9160
"	3200 S	+5	-7	-2	9255
"	3100 S	+7	-9	-2	9020
"	3000 S	-4	-11	-15	9395
"	2900 S	-6	-12	-18	9360
	at 2015 around the claim line				
"	2800 S	-6	-18	-24	9430
"	2700 S	-19	-19	-38	9790
"	2600 S	-23	-12	-35	9650
"	2500 S	-17	-11	-28	9255

Line	Sta	Readings			
10W	2400 S	-18	-21	-39	9825
"	2300 S	-18	-10	-28	9755
"	2200 S	-15	-10	-25	9360
"	2100 S	-18	-14	-32	9510
"	2000 S	-20	-12	-32	9685
"	1900 S	-17	-15	-32	9430
"	1800 S	-15	-13	-28	9375
"	1700 S	-15	-14	-29	9430
"	1600 S	-19	-9	-28	8845
"	1520 S	-16	-7	-23 N	8845
"	1450 S	-23	-2	-25	9090
"	1300 S	-9	-3	-12	9580
"	1200 S	-4	-0	-4	9325
"	1100 S	-7	+6	-1	9290
"	1000 S	-12	+10	-2	9160
"	900 S	-11	+11	0	9050
"	800 S	-10	+10	0	9160
"	700 S	-10	+9	-1	9020
"	600 S	-10	+8	-2	9020
"	500 S	-11	+9	-2	9125
"	400 S	-12	+12	-0	9090
"	300 S	-14	+12	-2	9195
"	200 S	-14	+11	-3	9090
"	100 S	-14	+11	-3	8950
"	0	-19	+18	-1	8845
"	100 N	-26	+23	-3	8985
"	200 N	-28	+26	-2	8915

This is 1st picket on picket line

2nd picket on line (its line cutters 1500' picket)

This is base line

<u>kmc</u>	<u>Sta</u>	<u>Readings</u>			
26 W	0-BL	-17	+15	-2	8915
"	100 S	-20	+17	-3	8915
"	200 S	-20	+18	-2	9160
"	300 S	-17	+14	-3	8950
"	400 S	-16	+12	-4	9125
"	500 S	-15	+10	-5	9290
"	600 S	-11	+9	-2	9055
"	700 S	-10	+5	-5 N	9255
"	800 S	-9	+6	-3	9160
"	900 S	-13	+9	-4	9020
"	1000 S	-17	+10	-7	9125
"	1100 S	-18	+12	-6	9325
"	1200 S	-21	0	-21	9125
"	1300 S	-24	+6	-18	9220
"	1400 S	-21	-3	-24 (top edge of hill)	9160
"	1500 S	-20	-2	-22 N	9360
"	1600 S	-19	-14	-33	9125
"	1700 S	-20	-15	-30	9220
"	1800 S	-22	-16	-40	9255
"	1900 S	-19	-17	-36	9475
"	2000 S	-21	-13	-34	9580
"	2100 S	-14	-14	-28	9325
"	2200 S	-10	-14	-24	9580
"	2300 S	-7	-12	-19	9430
"	2400 S	+1	-15	-14	9685

Line	Sta	Readings			
26 W	2500 S	+4	-12	-8	9430
26 W	2600 S	+6	-8	-2	9220
"	2700 S	+6	-7	-1	9125
"	2800 S	+5	-8	-3	9090
"	2900 S	+5	-4	+1	8985
"	3000 S	+5	-6	-1	8950

Line	Sta	Readings			
34 W	3000 S	+2	0	+2	8775
"	2900 S	+1	0	-1	8915
"	2800 S	+1	-1	0	8915
"	2700 S	+2	-3	-1	8845
"	2600 S	+2	-2	0	8915
"	2500 S	+2	-5	-3	8985
"	2400 S	+1	-7	-6	9090
"	2300 S	-3	-10	-13	9055
"	2200 S	-7	-13	-20	9220
"	2100 S	-14	-14	-28	9720
"	2000 S	-20	-5	-25	9720
"	1900 S	-18	-12	-30	9615
"	1800 S	-20	-14	-34	9615
"	1700 S	-21	-16	-37	9510
"	1600 S	-20	-7	-27	9650

1st picket 50' E of this pt
 The picket was for 1700 S of line center line
 for 32 W.

Line	Sta	Readings			
32W	1500 S	-17	-9	-26	9720
"	1400 S	-20	-7	-27	9685
"	1300 S	-25	-2	-27	9220
"	1200 S	-24	+6	-18	9160
"	1100 S	-24	+0	-24	9220
"	1000 S	-15	+22	-3 N	8915
"	900 S	-13	+13	0	9020
"	800 S	-18	+10	+1	8810
"	700 S	-11	+12	+1	9020
"	600 S	-14	+15	+1	9020
"	500 S	-14	+15	+1	8845
"	400 S	-14	+16	+2	8775
"	300 S	-15	+14	-1	8775
"	200 S	-13	+13	0	8915
"	100 S	-17	+16	-1	8915
"	0	-22	+20	-2	9020
"	*100 N	-19	+18	-1	8845 B. Line