

31/08/77 KERR ADDISON MINES LTD. - GRUM PROJECT

D I A M O N D D R I L L L O G M A - UNDERGROUND

018840

HOLE NO: U-1 LATITUDE: 10778.51 ✓ ✓ AZIMUTH: 110.13 ✓
 HOLE LENGTH: 62.50 DEPARTURE: 7691.73 ✓ ✓ DIP: 3.00 ✓
 ELEVATION: 1154.57 ✓

INTERVAL		ASSAYS				
FROM	TO	PB	ZN	AG		
		%	%	GM/TON		Ag
0.00	2.00	3.98 ✓	5.89 ✓	55.53		0.2/TON
2.00	4.00	4.17 ✓	4.60 ✓	54.51		1.62
4.00	6.00	4.28 ✓	6.45 ✓	62.39		1.59
6.00	8.00	4.05 ✓	9.45 ✓	63.42		1.82
8.00	9.00	4.09 ✓	6.90 ✓	57.59		1.85
9.00	14.00	N/A	N/A	N/A		1.68
14.00	15.00	9.26 ✓	15.00 ✓	129.24		3.77
15.00	17.30	3.38 ✓	10.46 ✓	55.53		3.77
17.30	18.80	8.50 ✓	17.22 ✓	111.07		1.62
18.80	44.10	N/A	N/A	N/A		3.24
44.10	45.70	8.35 ✓	12.52 ✓	139.18		—
45.70	47.20	8.15 ✓	14.81 ✓	115.87		4.06
47.20	48.80	6.79 ✓	13.74 ✓	109.01		3.38
48.80	50.30	7.56 ✓	12.16 ✓	97.70		3.18
50.30	51.80	N/A	N/A	N/A		2.85
51.80	53.30	7.99 ✓	10.07 ✓	164.89		—
53.30	54.90	8.85 ✓	14.60 ✓	129.24		4.81
54.90	62.50	N/A	N/A	N/A		3.77

SPECIAL MOORE BUSINESS FORMS 4

HOLE NO: U-3 LATITUDE: 10717.12 AZIMUTH: 225.03 ✓
 HOLE LENGTH: 82.30 DEPARTURE: 7628.66 DIP: 35.00 ✓
 ELEVATION: 1155.32 ✓

INTERVAL		ASSAYS				
FROM	TO	PB	ZN	AG	AG	
		%	%	GM/TON	02/TON	
0.00	1.00	1.88✓	2.10✓	23.31	.68	
1.00	3.00	3.30✓	5.25✓	39.42	1.15	
3.00	5.00	3.68✓	5.00✓	36.34	1.06	
5.00	7.00	5.15✓	6.35✓	62.39	1.82	
7.00	7.80	3.98✓	4.00✓	54.51	1.59	
7.80	8.90	4.43✓	8.95✓	72.67	2.12	
8.90	11.90	1.65✓	1.30✓	35.31	1.03	
11.90	14.30	1.50✓	2.05✓	28.45	.83	
14.30	16.00	10.08✓	19.27✓	158.37	4.62	<i>J</i>
16.00	42.70	N/A	N/A	N/A	-	
42.70	43.50	7.95✓	6.82✓	102.84	3.00	
43.50	45.50	6.32✓	5.00✓	94.61	2.76	
45.50	47.50	6.71✓	5.00✓	90.84	2.65	
47.50	49.00	11.40✓	6.52✓	127.52	3.72	
49.00	51.80	1.73✓	1.55✓	20.23	.59	
51.80	52.80	1.95✓	1.82✓	25.37	.74	
52.80	64.00	N/A	N/A	N/A	-	
64.00	65.40	1.00	1.30	16.45	15.09	
65.40	66.70	7.04	5.65	97.36	88.80	
66.70	72.40	N/A	N/A	N/A	-	
72.40	74.10	3.68✓	2.90✓	49.36	1.44	
74.10	82.30	N/A	N/A	N/A	-	

SHEET 10 MOORE BUSINESS FORMS 4

HOLE NO: U-4 LATITUDE: 10720.19 AZIMUTH: 235.37✓
 HOLE LENGTH: 53.30 DEPARTURE: 7631.53 DIP: 75.00✓
 ELEVATION: 1155.62✓

INTERVAL		ASSAYS			AG
FROM	TO	PB	ZN	AG	
		%	%	GM/TON	OZ/TON
0.00	6.90	N/A	N/A	N/A	
6.90	10.60	2.98✓	4.95✓	44.22	40.46
10.60	14.20	2.68✓	4.63✓	42.16	38.40
14.20	14.90	1.13✓	2.10✓	20.91	19.20
14.90	15.50	2.40✓	3.80✓	43.19	39.43
15.50	17.50	10.31✓	17.51✓	153.23	4.47
17.50	19.00	9.81✓	17.25✓	144.32	4.21
19.00	45.70	N/A	N/A	N/A	
45.70	46.20	2.70✓	2.50✓	30.17	.88
46.20	47.80	9.70✓	6.72✓	126.15	3.68
47.80	48.70	2.25✓	1.49✓	27.42	.86
48.70	53.30	N/A	N/A	N/A	

☆

SPECIFIC TO MOORE BUSINESS FORMS 4

HOLE NO: U-5 LATITUDE: 10720.45 ✓
 HOLE LENGTH: 99.10 DEPARTURE: 7632.27 ✓
 ELEVATION: 1151.62 ✓
 ✓ AZIMUTH: 0.00 ✓
 ✓ DIP: -90.00 ✓

INTERVAL		ASSAYS				
FROM	TO	PB	ZN	AG		AG
		%	%	GM/TON		02/TON
0.00	27.40	N/A	N/A	N/A		
27.40	28.40	2.70 ✓	3.88 ✓	53.13	48.34	-
28.40	30.40	6.03 ✓	11.86 ✓	76.79		2.24
30.40	32.40	1.55 ✓	2.50 ✓	32.22		.94
32.40	34.00	4.80 ✓	10.85 ✓	81.59		2.38
34.00	34.90	N/A	N/A	N/A		-
34.90	37.70	3.53 ✓	6.72 ✓	57.59		1.68
37.70	40.50	N/A	N/A	N/A		-
40.50	43.80 ✓	2.95 ✓	5.93 ✓	51.76	47.31	-
43.80	44.60 ✓	3.40 ✓	4.80 ✓	143.63	130.97	-
44.60	46.40 ✓	2.30 ✓	4.10 ✓	37.71	34.29	-
46.40	48.80 ✓	1.43 ✓	3.53 ✓	26.74	24.34	-
48.80	50.20	2.80 ✓	5.93 ✓	46.28		1.35
50.20	52.20	4.55 ✓	10.04 ✓	69.59		2.03
52.20	54.20	3.90 ✓	8.50 ✓	64.45		1.88
54.20	56.20	5.10 ✓	9.47 ✓	88.79		2.59
56.20	58.20	4.05 ✓	6.56 ✓	75.76		2.21
58.20	60.20	3.53 ✓	4.15 ✓	53.48		1.56
60.20	62.20	1.93 ✓	3.20 ✓	31.19		.91
62.20	64.20	7.04 ✓	12.21 ✓	107.98		3.15
64.20	66.20	6.53 ✓	12.57 ✓	109.01		3.18
66.20	68.20	4.13 ✓	6.92 ✓	68.56		2.00
68.20	70.20	8.17 ✓	21.13 ✓	129.92		3.79
70.20	72.20	7.05 ✓	9.77 ✓	93.93		2.74
72.20	74.20	1.73 ✓	3.27 ✓	19.20		.56
74.20	99.10	N/A	N/A	N/A		-

HOLE NO: U-6 LATITUDE: 10719.91 AZIMUTH: 45.00 ✓
 HOLE LENGTH: 36.60 DEPARTURE: 7632.55 DIP: 80.00 ✓
 ELEVATION: 1155.60 ✓

INTERVAL		ASSAYS				
FROM	TO	PB	ZN	AG		AG
		%	%	GM/TON		OZ/TON
0.00	2.40	2.85 ✓	3.65 ✓	44.22	40.46	-
2.40	4.60	2.30 ✓	4.70 ✓	33.25		.97
4.60	6.00	1.95 ✓	3.75 ✓	27.42		.80
6.00	9.10	2.28 ✓	4.58 ✓	37.71	34.29	-
9.10	11.10	3.08 ✓	5.40 ✓	40.45		1.18
11.10	14.30	3.08 ✓	4.65 ✓	35.31		1.03
14.30	15.20	.95 ✓	2.70 ✓	15.43	14.06	-
15.20	18.50	1.93 ✓	3.65 ✓	37.71	34.29	-
18.50	19.50	1.78 ✓	3.50 ✓	38.74	35.31	-
19.50	21.20	3.78 ✓	6.85 ✓	69.59	63.43	-
21.20	21.80	4.83 ✓	7.50 ✓	90.50	82.63	-
21.80	23.80	13.55 ✓	26.10 ✓	211.85		6.18
23.80	25.90	11.34 ✓	22.17 ✓	176.54		5.15
25.90	28.00	2.93 ✓	5.85 ✓	50.39		1.47
28.00	30.00	9.32	17.82 ✓	161.46		4.71
30.00	32.00	8.42 ✓	14.00 ✓	128.21		3.24
32.00	33.20	8.60 ✓	15.52 ✓	135.06		3.94
33.20	36.60	N/A	N/A	N/A		

SPECIAL MOORE BUSINESS FORMS 4

HOLE NO: U-7 LATITUDE: 10746.70 AZIMUTH: 44.00 ✓
 HOLE LENGTH: 73.20 DEPARTURE: 7652.80 DIP: -60.00 ✓
 ELEVATION: 1151.80

INTERVAL		ASSAYS				
FROM	TO	PB	ZN	AG		Ag
		%	%	GM/TON		02/TON
0.00	10.70	N/A	N/A	N/A		
10.70	11.20	3.40 ✓	1.53 ✓	50.73	46.29	-
11.20	13.20	4.65 ✓	1.98 ✓	52.45		1.53
13.20	15.20	3.85 ✓	2.60 ✓	50.39		1.47
15.20	19.80	2.93 ✓	2.43 ✓	49.71	45.26	-
19.80	21.40	.39 ✓	.90 ✓	9.94	8.91	-
21.40	23.00	.68 ✓	1.00 ✓	12.00	10.97	-
23.00	24.80	2.70 ✓	3.65 ✓	40.45		1.18
24.80	32.00	N/A	N/A	N/A		-
32.00	35.00	1.65 ✓	2.45 ✓	31.19	28.46	-
35.00	35.70	3.38 ✓	5.09 ✓	62.05	56.57	-
35.70	53.80	N/A	N/A	N/A		-
53.80	54.70	7.39 ✓	12.72 ✓	128.21		3.74
54.70	56.10	3.00 ✓	4.00 ✓	44.22		1.29
56.10	73.20	N/A	N/A	N/A		-

HOLE NO: U-8
HOLE LENGTH: 50.30

LATITUDE: 10746.71 ✓
DEPARTURE: 7652.78 ✓
ELEVATION: 1155.87 ✓

✓ AZIMUTH: 218.26 ✓
DIP: ~~80.00~~ ✓
75.35

INTERVAL		ASSAYS				
FROM	TO	PB	ZN	AG	AG	
		%	%	GM/TON	OZ/TON	
0.00	30.50	N/A	N/A	N/A	-	
30.50	31.90	2.35 ✓	2.35 ✓	33.25	.97	
31.90	32.70	N/A	N/A	N/A	-	
32.70	34.20	3.60 ✓	3.90 ✓	45.25	1.32	
34.20	34.70	N/A	N/A	N/A	-	✓
34.70	36.20	3.45 ✓	6.30 ✓	43.54	1.27	
36.20	36.70	N/A	N/A	N/A	-	
36.70	38.70	1.65 ✓	3.50 ✓	29.14	.85	
38.70	40.90	1.50 ✓	2.60 ✓	24.34	.71	
40.90	42.90	8.37 ✓	16.26 ✓	105.93	3.09	
42.90	43.90	6.54 ✓	12.95 ✓	105.93	3.09	
43.90	50.30	N/A	N/A	N/A	-	

HOLE NO: U-9 LATITUDE: 10765.60 AZIMUTH: 44.00 ✓
 HOLE LENGTH: 64.00 DEPARTURE: 7671.80 DIP: -55.00 ✓
 ELEVATION: 1152.00

INTERVAL		ASSAYS				
FROM	TO	PB	ZN	AG	AG	
		%	%	GM/TON	02/TON	
0.00	4.50	N/A	N/A	N/A	-	
4.50	6.50	3.68✓	3.95✓	50.39	1.47	
6.50	8.50	2.28✓	3.20✓	33.25	.97	
8.50	10.50	6.31✓	3.25✓	63.42	1.85	
10.50	12.50	4.88✓	7.48✓	52.45	1.53	
12.50	14.50	4.05✓	5.60✓	49.36	1.44	
14.50	16.50	3.68✓	4.75✓	44.22	1.29	
16.50	18.00	3.38✓	6.92✓	46.28	1.35	
18.00	22.30	N/A	N/A	N/A	-	
22.30	24.30	1.83✓	4.40✓	29.14	.85	
24.30	26.00	6.11✓	12.11✓	89.81	2.62	
26.00	27.00	9.70✓	12.52✓	140.21	4.09	
27.00	29.00	N/A	N/A	N/A	-	
29.00	31.00	7.81✓	13.69✓	159.40	4.65	
31.00	32.00	2.10✓	2.00✓	38.74	35.31	
32.00	33.00	2.20✓	2.98✓	37.71	34.29	
33.00	38.10 ✓	N/A	N/A	N/A	-	
38.10	39.50	.33	1.10	4.46	-	
39.50	41.10	7.38✓	10.69✓	100.78	101.13	2.95
41.10	42.70	7.54✓	12.93✓	115.87	3.38	
42.70	44.20	9.75✓	14.05✓	168.31	4.91	
44.20	45.40	3.38✓	7.23✓	52.45	1.53	
45.40	47.20	4.80✓	7.53✓	72.67	2.12	
47.20	48.70	5.03✓	6.10✓	74.73	2.18	
48.70	50.30	6.50✓	7.84✓	79.53	2.32	
50.30	51.20	6.50✓	10.69✓	102.84	3.00	
51.20	53.30	2.25✓	4.50✓	36.34	1.06	
53.30	64.00	N/A	N/A	N/A	-	
33.00	* 35.10	N/A	N/A	N/A	N/A	
35.10	36.60	4.05	6.42	52.44	1.53	
36.60	39.50	.33	1.10	4.11	-	

535-9

HOLE NO: U-10
 HOLE LENGTH: 64.00

LATITUDE: 10765.58
 DEPARTURE: 7671.82
 ELEVATION: 1155.95

AZIMUTH: 233.47
 DIP: 80.00

INTERVAL		ASSAYS				
FROM	TO	PB	ZN	AG	AG	
		%	%	GM/TON	GM/TON	
0.00	2.70	4.43✓	9.63✓	82.61	2.41	
2.70	4.30	2.85✓	4.75✓	50.39	1.47	
4.30	6.10	3.38✓	7.12✓	50.39	1.47	
6.10	7.60	3.08✓	7.43✓	47.31	1.38	
7.60	9.10	3.08✓	5.80✓	46.28	1.35	
9.10	10.70	6.74✓	8.91✓	109.01	3.18	
10.70	12.20	2.25✓	6.32✓	36.34	1.06	
12.20	13.70	.37✓	.94✓	3.09	.09	
13.70	15.20	.98✓	3.00✓	12.00	.35	✓
15.20	40.40	N/A	N/A	N/A	-	
40.40	41.10	11.69✓	15.98✓	160.43	4.68	
41.10	44.50	1.63✓	3.95✓	25.37	.74	
44.50	50.40	N/A	N/A	N/A	-	
50.40	52.50	1.05✓	1.60✓	21.25	.62	
52.50	53.30	N/A	N/A	N/A	-	
53.30	54.90	2.50✓	4.10✓	43.54	1.27	
54.90	56.40	3.30✓	5.90✓	49.36	1.44	
56.40	57.20	9.17✓	16.09✓	141.23	4.12	
57.20	64.00	N/A	N/A	N/A	-	

HOLE NO: U-11
HOLE LENGTH: 24.40

LATITUDE: 10781.47 ✓
DEPARTURE: 7694.46 ✓
ELEVATION: 1153.72 ✓

✓ AZIMUTH: 26.10 ✓
DIP: ~~40.00~~ ✓
-41.23

INTERVAL		ASSAYS				
FROM	TO	PB	ZN	AG	AG	
		%	%	GM/TON		
0.00	5.30	.00	.00	.00	02/TON	
5.30	7.30	7.17 ✓	20.51 ✓	127.18	3.71	✓
7.30	9.30	3.60 ✓	12.04 ✓	62.39	1.82	
9.30	24.40	N/A	N/A	N/A	-	

HOLE NO: U-12 LATITUDE: 10685.91 AZIMUTH: 43.47 ✓
 HOLE LENGTH: 79.90 DEPARTURE: 7600.50 DIP: -70.00 ✓
 ELEVATION: 1152.91

INTERVAL		ASSAYS			
FROM	TO	PB	ZN	AG	AG
		%	%	GM/TON	02/TON
0.00	15.70	N/A	N/A	N/A	-
15.70	16.80	8.29✓	15.96✓	107.98	3.15
16.80	18.00	2.85✓	4.75✓	49.36	1.44
18.00	19.00	5.20✓	6.71✓	81.59	2.38
19.00	20.70	5.78✓	7.28✓	80.56	2.35
20.70	22.30	1.13✓	3.65✓	18.17	.53
22.30	23.70	5.48✓	7.50✓	109.01	3.18
23.70	24.90	5.98✓	10.57✓	90.84	2.65
24.90	26.10	6.20✓	10.12✓	82.61	2.41
26.10	27.40	3.55✓	4.93✓	36.34	1.06
27.40	28.70	3.85✓	5.50✓	57.59	1.68
28.70	55.10	N/A	N/A	N/A	-
55.10	56.40	6.94✓	6.35✓	121.01	3.53
56.40	57.90	7.06✓	11.03✓	100.78	2.94
57.90	59.40	5.78✓	8.95✓	75.76	2.21
59.40	61.00	3.00✓	4.65✓	45.25	1.32
61.00	62.50	1.70✓	.48✓	30.17	.88
62.50	64.00	.15✓	.28✓	9.94	.29
64.00	65.50	4.50✓	4.90✓	70.62	2.06
65.50	67.00	6.33✓	5.35✓	84.67	2.47
67.00	68.60	.20✓	1.18✓	9.94	.29
68.60	70.10	.05✓	.88✓	9.94	.29
70.10	71.60	.25✓	.90✓	12.00	.35
71.60	73.10	.25✓	2.00✓	10.97	.32
73.10	74.70	2.80✓	2.38✓	46.28	1.35
74.70	76.20	.45✓	6.51✓	9.94	.29
76.20	79.90	N/A	N/A	N/A	-

SPEEDY LO MOORE BUSINESS FORMS

DIAMOND DRILL LOG MA

STER FILE

HOLE NO: U-13

LATITUDE: 10685.48

AZIMUTH: 43.47 ✓

HOLE LENGTH: 182.90

DEPARTURE: 7600.08

DIP: -83.00 ✓

ELEVATION: 1152.91

DIP TESTS: DEPTH DIP AZIMUTH
 152.40 -81.00 42.00

INTERVAL		ASSAYS				AG
FROM	TO	PB	ZN	AG	AG	
		%	%	GM/TON	02/TON	
0.00	17.10	N/A	N/A	N/A	-	
17.10	18.30	5.20 ✓	6.86 ✓	71.65	2.09	
18.30	19.80	7.26 ✓	11.03 ✓	112.10	3.27	
19.80	21.30	6.84 ✓	7.96 ✓	100.78	2.94	
21.30	22.90	4.30 ✓	4.20 ✓	73.70	2.15	
22.90	24.40	4.40 ✓	5.62 ✓	63.08	1.84	
24.40	25.90	4.60 ✓	6.51 ✓	74.73	2.18	
25.90	27.90	10.03 ✓	14.69 ✓	130.95	3.82	
27.90	55.20	N/A	N/A	N/A	-	
55.20	56.40	6.61 ✓	8.98 ✓	96.67	2.82	
56.40	57.90	4.40 ✓	5.25 ✓	70.62	2.06	
57.90	59.50	6.94 ✓	8.55 ✓	98.73	2.88	
59.50	62.50	3.50 ✓	2.95 ✓	54.51	1.59	
62.50	64.00	.15 ✓	.53 ✓	8.91	.26	
64.00	65.50	2.85 ✓	.78 ✓	49.36	1.44	
65.50	67.10	.20 ✓	1.03 ✓	9.94	.29	
67.10	68.60	.35 ✓	1.70 ✓	10.97	.32	
68.60	70.10	4.60 ✓	2.03 ✓	74.73	2.18	
70.10	71.60	3.10 ✓	3.48 ✓	42.51	1.24	
71.60	77.40	N/A	N/A	N/A	-	
77.40	78.20	11.06 ✓	17.37 ✓	151.17	4.41	
78.20	157.20	N/A	N/A	N/A	-	
157.20	158.50	2.40 ✓	2.28 ✓	31.19	.91	
158.50	160.00	3.85 ✓	3.15 ✓	45.25	1.32	
160.00	161.50	5.25 ✓	3.75 ✓	58.62	1.71	
161.50	178.00	N/A	N/A	N/A	-	
178.00	179.80	2.00 ✓	.88 ✓	34.28	1.06	
179.80	182.90	N/A	N/A	N/A	-	

HOLE NO: U-14 LATITUDE: 10684.80 AZIMUTH: 233.06 ✓
 HOLE LENGTH: 51.80 DEPARTURE: 7602.59 DIP: 59.00 ✓
 ELEVATION: 1157.71

INTERVAL		ASSAYS				
FROM	TO	PB	ZN	AG	AG	
		%	%	GM/TON	OZ/TON	
0.00	19.50	N/A	N/A	N/A	-	
19.50	20.10	10.69 ✓	9.88 ✓	130.95	3.82	
20.10	21.70	3.85 ✓	2.15 ✓	49.36	1.44	
21.70	23.50	.48 ✓	.13 ✓	31.19	.91	
23.50	24.90	6.47 ✓	6.49 ✓	92.90	2.71	
24.90	26.40	.40 ✓	.15 ✓	20.23	.59	
26.40	27.40	7.00 ✓	6.47 ✓	84.67	2.47	6.74
27.40	29.10	6.90 ✓	7.20 ✓	94.61	2.76	
29.10	30.30	8.41 ✓	3.96 ✓	103.87	3.63	
30.30	32.30	1.35 ✓	1.20 ✓	14.05	.41	
32.30	36.20	N/A	N/A	N/A	-	
36.20	37.30	1.53 ✓	1.68 ✓	18.17	.53	
37.30	38.90	8.36 ✓	7.86 ✓	117.92	3.44	
38.90	40.30	6.75 ✓	7.52 ✓	100.78	2.94	
40.30	41.60	6.98 ✓	8.46 ✓	112.10	3.27	
41.60	43.20	6.90 ✓	8.82 ✓	109.01	3.18	✓
43.20	44.50	2.60 ✓	1.88 ✓	44.22	1.29	
44.50	45.10	8.38 ✓	8.77 ✓	104.90	3.06	
45.10	51.80	N/A	N/A	N/A	-	

HOLE NO: U-15
 HOLE LENGTH: 185.90

LATITUDE: 10704.13
 DEPARTURE: 7531.34
 ELEVATION: 1166.19

AZIMUTH: 44.00 ✓
 DIP: -60.00 ✓

DIP TESTS:	DEPTH	DIP	AZIMUTH
	91.40	-68.00	42.20
	182.90	-74.00	65.20

INTERVAL		ASSAYS				AG
FROM	TO	PB %	ZN %	AG GM/TON	AG OZ/TON	
0.00	19.80	N/A	N/A	N/A	-	
19.80	21.30	3.35✓	1.82✓	52.45	1.53	
21.30	22.90	2.55✓	.53✓	39.42	1.15	
22.90	24.40	5.35✓	3.00✓	76.79	2.24	
24.40	25.90	1.85✓	1.53✓	48.33	1.41	
25.90	27.40	6.07✓	5.53✓	82.61	2.41	
27.40	29.10	8.57✓	5.67✓	107.98	3.15	
29.10	30.50	3.40✓	3.25✓	45.25	1.32	
30.50	65.50	N/A	N/A	N/A	-	
65.50	67.00	1.15✓	1.20✓	20.91	19.20	-
67.00	68.60	4.13✓	5.30✓	69.59	2.63	
68.60	70.10	7.28✓	9.22✓	138.15	4.03	
70.10	71.30	7.59✓	11.81✓	130.95	3.82	
71.30	106.70	N/A	N/A	N/A	-	
106.70	108.20	.78✓	1.48✓	12.00	10.97	-
108.20	109.70	5.65✓	7.05✓	90.84	2.65	
109.70	111.30	7.50✓	8.21✓	125.12	3.65	
111.30	112.80	8.01✓	12.77✓	128.21	3.74	
112.80	113.90	.98✓	1.48✓	23.31	.68	
113.90	115.00	4.90✓	7.25✓	74.73	2.18	
115.00	116.10	3.23✓	3.60✓	49.36	1.44	
116.10	117.30	2.28✓	2.90✓	45.25	1.32	
117.30	118.50	.95✓	1.38✓	21.25	.62	
118.50	119.90	3.85✓	8.16✓	59.30	1.73	
119.90	121.30	4.10✓	4.10✓	65.47	1.91	
121.30	122.50	.45	.83✓	15.08	1.44	
122.50	124.80	2.25✓	1.56✓	34.28	1.00	
124.80	125.50	4.55✓	10.04✓	63.42	1.85	
125.50	126.60	1.73✓	2.88✓	32.22	.94	
126.60	127.60	1.48✓	4.80✓	25.37	.74	
127.60	171.80	N/A	N/A	N/A	-	
171.80	172.90	2.15✓	2.00✓	30.17	.88	
172.90	174.50	3.95✓	3.40✓	41.48	1.21	
174.50	175.70	4.30✓	4.00✓	42.51	1.24	
175.70	177.30	3.30✓	3.15✓	49.36	1.44	
177.30	178.60	2.40✓	2.25✓	33.25	.97	
178.60	179.50	2.95✓	3.43✓	36.34	1.06	
179.50	181.00	2.85✓	2.70✓	34.28	1.00	
181.00	182.40	3.60✓	2.78✓	42.51	1.24	
182.40	183.80	1.60✓	1.28✓	23.31	.68	
183.80	184.80	.50✓	.70✓	15.08	.44	
184.80	185.90	2.55✓	2.03✓	33.25	.97	



SHEDDEN MOORE BUSINESS FORMS 4

HOLE NO: U-16
 HOLE LENGTH: 106.70

LATITUDE: 10727.09 ✓
 DEPARTURE: 7639.76 ✓
 ELEVATION: 1151.80 ✓

AZIMUTH: 45.58 ✓
 DIP: ~~36.00~~

-35.14 ✓

INTERVAL		ASSAYS				
FROM	TO	PB	ZN	AG		AG
		%	%	GM/TON		OZ/TON
0.00	59.90	N/A	N/A	N/A		-
59.90	60.30	9.30 ✓	18.66 ✓	139.52	127.20	-
60.30	61.10	.75 ✓	1.05 ✓	18.85	17.14	-
61.10	63.00	7.69 ✓	12.72 ✓	116.89		3.41
63.00	64.30	6.10 ✓	12.87 ✓	110.04		3.21
64.30	65.80	2.03 ✓	8.23 ✓	36.34		1.06
65.80	67.10	3.40 ✓	6.38 ✓	45.25		1.32
67.10	106.70	N/A	N/A	N/A		-

HOLE NO: U-17
 HOLE LENGTH: 125.00

LATITUDE: 10727.20
 DEPARTURE: 7639.60
 ELEVATION: 1151.80

AZIMUTH: 43.48 ✓
 DIP: -60.00 ✓

INTERVAL		ASSAYS			
FROM	TO	PB	ZN	AG	
		%	%	GM/TON	AG 02/TON
0.00	35.70	N/A	N/A	N/A	-
35.70	36.60	1.28 ✓	2.00 ✓	23.31	1.68
36.60	38.60	3.18 ✓	5.70 ✓	59.30	1.73
38.60	41.60	4.40 ✓	6.38 ✓	64.45	1.88
41.60	42.40	6.81 ✓	13.53 ✓	115.87	3.38
42.40	43.20	3.05 ✓	4.20 ✓	40.45	1.18
43.20	45.20	3.90 ✓	7.63 ✓	68.56	2.00
45.20	47.20	4.15 ✓	7.65 ✓	71.65	2.09
47.20	49.20	4.75 ✓	7.65 ✓	81.59	2.38
49.20	50.90	8.22 ✓	15.35 ✓	130.95	3.82
50.90	52.90	1.20 ✓	1.75 ✓	30.17	0.88
52.90	54.90	3.95 ✓	5.35 ✓	57.59	1.68
54.90	56.20	.43 ✓	.55 ✓	18.17	.53
56.20	114.00	N/A	N/A	N/A	-
114.00	116.10	2.00 ✓	2.28 ✓	38.39	1.12
116.10	117.70	N/A	N/A	N/A	-
117.70	120.00	4.10 ✓	7.86 ✓	60.33	1.76
120.00	125.00	N/A	N/A	N/A	-



SPECIAL MOORE BUSINESS FORMS 4

HOLE NO: U-18 LATITUDE: 10686.00 AZIMUTH: 44.00 ✓
 HOLE LENGTH: 88.40 DEPARTURE: 7600.50 DIP: -46.00 ✓
 ELEVATION: 1153.00

INTERVAL		ASSAYS			AG
FROM	TO	PB	ZN	AG	02/TON
		%	%	GM/TON	
0.00	14.40	N/A	N/A	N/A	
14.40	16.30	8.92 ✓	15.05 ✓	146.03	4.26
16.30	17.90	10.48 ✓	12.08 ✓	137.12	4.00
17.90	19.60	11.75 ✓	14.37 ✓	138.15	4.03
19.60	21.30	6.51 ✓	12.75 ✓	99.75	2.91
21.30	22.90	6.46 ✓	12.84 ✓	87.76	2.56
22.90	24.40	4.15 ✓	8.99 ✓	71.65	2.09
24.40	25.90	5.00 ✓	8.13 ✓	83.64	2.44
25.90	27.40	2.83 ✓	3.95 ✓	56.56	1.65
27.40	29.00	1.30 ✓	1.65 ✓	25.37	.74
29.00	30.50	4.35 ✓	9.65 ✓	70.62	2.06
30.50	32.00	6.53 ✓	11.83 ✓	73.70	2.15
32.00	33.50	9.50 ✓	17.93 ✓	117.92	3.44
33.50	35.10	4.40 ✓	10.72 ✓	71.65	2.09
35.10	36.60	3.23 ✓	5.99 ✓	63.42	1.85
36.60	38.60	4.70 ✓	7.97 ✓	77.82	2.27
38.60	51.90	N/A	N/A	N/A	-
51.90	53.30	2.58 ✓	4.40 ✓	220.08	6.42
53.30	57.60	N/A	N/A	N/A	-
57.60	58.10	.73 ✓	.75	12.00	10.97
58.10	59.50	2.38 ✓	4.90 ✓	44.22	1.29
59.50	61.00	2.53 ✓	4.20 ✓	44.22	1.29
61.00	62.50	2.08 ✓	3.78 ✓	31.19	.91
62.50	64.40	1.90 ✓	4.35 ✓	54.51	1.59
64.40	65.50	1.93 ✓	3.48 ✓	42.51	1.24
65.50	67.10	4.93 ✓	10.05 ✓	83.64	2.44
67.10	68.60	4.15 ✓	8.50 ✓	83.64	76.78
68.60	70.10	3.45 ✓	8.27 ✓	59.30	1.73
70.10	71.60	3.50 ✓	8.07 ✓	61.36	1.79
71.60	73.90	3.20 ✓	4.85 ✓	55.53	1.62
73.90	75.10	6.00 ✓	9.24 ✓	90.84	2.65
75.10	76.30	2.45 ✓	3.75 ✓	42.51	1.24
76.30	77.70	3.38 ✓	5.10 ✓	64.45	1.88
77.70	79.90	3.58 ✓	5.40 ✓	61.36	1.79
79.90	84.40	3.30 ✓	4.00 ✓	49.36	45.26
84.40	88.40	N/A	N/A	N/A	-

80.40



SPELFO LO MOORE BUSINESS FORMS 4

HOLE NO: U-19 LATITUDE: 10684.01 AZIMUTH: 223.48 ✓
 HOLE LENGTH: 59.40 DEPARTURE: 7598.68 DIP: 31.00 ✓
 ELEVATION: 1155.27

INTERVAL		ASSAYS			
FROM	TO	PB	ZN	AG	
		%	%	GM/TON	
0.00	20.30	N/A	N/A	N/A	AG 021 TOP —
20.30	22.90	2.90 ✓	2.15 ✓	45.25	1.32
22.90	29.30	N/A	N/A	N/A	—
29.30	30.50	2.28 ✓	2.05 ✓	35.31	1.03
30.50	32.00	2.13 ✓	1.98 ✓	39.42	1.15
32.00	33.50	3.85 ✓	3.10 ✓	59.30	1.73
33.50	35.10	4.90 ✓	4.75 ✓	73.70	2.15
35.10	36.60	6.78 ✓	6.22 ✓	95.64	2.79
36.60	38.10	7.10 ✓	7.52 ✓	102.84	3.00
38.10	39.60	4.80 ✓	3.55 ✓	65.47	1.91
39.60	40.80	4.30 ✓	3.10 ✓	55.53	1.62
40.80	42.20	8.10 ✓	7.09 ✓	126.15	3.68
42.20	44.20	6.35 ✓	7.29 ✓	97.70	2.85
44.20	45.70	5.85 ✓	7.29 ✓	103.87	3.03
45.70	47.20	5.94 ✓	8.07 ✓	111.07	3.24
47.20	50.00	4.88 ✓	3.55 ✓	70.62	2.06
50.00	59.40	N/A	N/A	N/A	—

SPECIAL MOORE BUSINESS FORMS 4

HOLE NO: U-20 LATITUDE: 10685.03 AZIMUTH: 223.48 ✓
 HOLE LENGTH: 74.70 DEPARTURE: 7599.64 DIP: -80.00 ✓
 ELEVATION: 1152.92

INTERVAL		ASSAYS				
FROM	TO	PB	ZN	AG		
		%	%	GM/TON	AG	
					02/TON	
0.00	18.30	N/A	N/A	N/A	-	
18.30	19.80	6.75 ✓	9.96 ✓	119.98	3.50	
19.80	21.40	7.79 ✓	13.41 ✓	121.01	3.53	
21.40	23.00	7.96 ✓	11.72 ✓	129.92	3.79	
23.00	59.40	N/A	N/A	N/A	-	
59.40	60.40	5.88 ✓	6.98 ✓	82.61	2.41	<i>k</i>
60.40	71.30	N/A	N/A	N/A	-	
71.30	72.80	6.68 ✓	7.47 ✓	93.93	2.74	
72.80	74.70	N/A	N/A	N/A	-	

HOLE NO: U-21 LATITUDE: 10716.85 AZIMUTH: 227.00 ✓
 HOLE LENGTH: 76.20 DEPARTURE: 7628.66 DIP: 55.00 ✓
 ELEVATION: 1155.64

INTERVAL		ASSAYS			
FROM	TO	PB	ZN	AG	
		%	%	GM/TON	
0.00	3.00	2.45 ✓	2.95 ✓	30.17	AG 02/TON .88
3.00	6.10	5.05 ✓	5.10 ✓	60.33	1.76
6.10	9.10	5.91 ✓	7.91 ✓	70.62	2.06
9.10	11.80	3.45 ✓	5.92 ✓	46.28	1.35
11.80	13.50	10.37 ✓	14.64 ✓	149.12	4.35
13.50	14.70	2.53 ✓	4.60 ✓	39.42	1.15
14.70	15.90	10.67 ✓	18.93 ✓	156.32	4.56
15.90	39.60	N/A	N/A	N/A	-
39.60	41.10	7.85 ✓	7.25 ✓	113.12	3.30
41.10	43.00	11.80 ✓	6.31 ✓	127.18	3.71
43.00	45.90	2.58 ✓	1.75 ✓	32.22	.94
45.90	72.60	N/A	N/A	N/A	-

HOLE NO: U-22 LATITUDE: 10720.18 AZIMUTH: 227.00 ✓
 HOLE LENGTH: 99.10 DEPARTURE: 7631.99 DIP: -47.00 ✓
 ELEVATION: 1151.71

INTERVAL		ASSAYS				
FROM	TO	PB	ZN	AG		AG
		%	%	GM/TON		OZ/TON
0.00	3.00	N/A	N/A	N/A		-
3.00	4.60	1.63 ✓	2.03 ✓	26.74	24.34	-
4.60	10.70	N/A	N/A	N/A		-
10.70	12.20	3.40 ✓	1.25 ✓	41.14	37.37	-
12.20	21.30	N/A	N/A	N/A		-
21.30	22.20	2.20 ✓	.93 ✓	26.74	24.34	-
22.20	22.90	4.00 ✓	2.20 ✓	55.19	50.40	-
22.90	24.40	8.11 ✓	9.81 ✓	98.73		2.88
24.40	26.50	1.20 ✓	1.48 ✓	25.37		.74
26.50	27.50	5.15 ✓	5.97 ✓	116.89		3.41
27.50	29.20	9.84 ✓	16.77 ✓	171.40		5.00
29.20	30.40	5.36 ✓	9.05 ✓	60.33		1.76
30.40	32.00	9.37 ✓	18.66 ✓	114.15		3.33
32.00	34.50	6.91 ✓	12.10 ✓	87.76		2.56
34.50	37.10	1.90 ✓	2.45 ✓	25.37		.74
37.10	39.60	4.45 ✓	9.49 ✓	69.59		2.03
39.60	41.20	3.75 ✓	5.80 ✓	53.48		1.56
41.20	63.60	N/A	N/A	N/A		-
63.60	65.30	9.10 ✓	7.32 ✓	129.24		3.77
65.30	66.90	5.92 ✓	9.00 ✓	90.84		2.65
66.90	68.60	4.95 ✓	8.85 ✓	78.84		2.30
68.60	70.10	4.85 ✓	5.55 ✓	68.56		2.00
70.10	72.30	7.44 ✓	8.29 ✓	97.70		2.85
72.30	73.90	2.33 ✓	3.18 ✓	35.31		1.03
73.90	75.50	5.31 ✓	2.38 ✓	84.67		2.47
75.50	77.30	5.31 ✓	7.07 ✓	71.65		2.09
77.30	79.20	5.10 ✓	4.60 ✓	80.56		2.35
79.20	80.80	5.71 ✓	4.25 ✓	86.73		2.53
80.80	82.30	2.95 ✓	.90 ✓	48.33		1.41
82.30	83.80	6.37 ✓	4.80 ✓	96.67		2.82
83.80	85.60	3.88 ✓	4.05 ✓	55.53		1.62
85.60	99.10	N/A	N/A	N/A		-

SPECIAL TO MOORE BUSINESS FORMS 4

HOLE NO: U-23
 HOLE LENGTH: 70.10

LATITUDE: 10720.80
 DEPARTURE: 7632.89
 ELEVATION: 1151.70

AZIMUTH: 47.00
 DIP: -68.00

INTERVAL		ASSAYS			
FROM	TO	PB	ZN	AG	AG
		%	%	GM/TON	OZ/TON
0.00	1.90	2.03✓	2.55✓	26.74	24.34
1.90	8.80	N/A	N/A	N/A	-
8.80	11.70	1.42✓	2.55✓	18.85	17.14
11.70	19.30	N/A	N/A	N/A	-
19.30	22.30	1.18✓	3.50✓	16.45	15.09
22.30	23.90	1.94✓	2.50✓	16.45	15.09
23.90	31.80	N/A	N/A	N/A	-
31.80	33.50	4.90✓	5.90✓	71.65	2.09
33.50	35.10	3.73✓	5.92✓	60.33	1.76
35.10	36.60	4.30✓	7.65✓	74.73	2.18
36.60	38.10	5.60✓	10.01✓	97.70	2.85
38.10	39.60	5.20✓	9.18✓	88.79	2.59
39.60	41.10	1.40✓	3.20✓	24.34	.71
41.10	42.70	3.10✓	6.15✓	45.25	1.32
42.70	44.20	4.33✓	7.47✓	81.59	2.38
44.20	45.70	2.73✓	3.48✓	44.22	1.29
45.70	47.20	4.15✓	8.54✓	79.19	2.31
47.20	48.80	2.23✓	2.28✓	45.25	1.32
48.80	51.20	2.75✓	3.70✓	51.42	1.50
51.20	52.90	.40✓	.55✓	13.03	2.38
52.90	54.90	1.43✓	1.63✓	28.45	.83
54.90	56.70	2.78✓	3.58✓	44.22	1.29
56.70	57.90	2.73✓	4.55✓	46.28	1.35
57.90	67.10	N/A	N/A	N/A	-
67.10	67.80	.48✓	.93✓	17.83	16.11
67.80	70.10	4.00✓	7.55✓	66.50	1.94

SPECIAL ORDER BUSINESS FORMS 4

HOLE NO: U-24
HOLE LENGTH: 59.40

LATITUDE: 10726.67 ✓
DEPARTURE: 7640.42 ✓
ELEVATION: 1155.16 ✓

AZIMUTH: 47.24 ✓
DIP: 34.30 ✓

INTERVAL
FROM TO

ASSAYS
PB ZN AG
% % GM/TON
N/A N/A N/A

0.00 59.40

HOLE NO: U-25
 HOLE LENGTH: 114.30

LATITUDE: 10726.67
 DEPARTURE: 7640.42
 ELEVATION: 1155.16

AZIMUTH: 47.24 ✓
 DIP: 34.00 ✓

INTERVAL		ASSAYS			
FROM	TO	PB	ZN	AG	
		%	%	GM/TON	AG O2/TON
0.00	59.50	N/A	N/A	N/A	-
59.50	61.00	2.18 ✓	3.10 ✓	46.62	42.51
61.00	62.50	.88 ✓	2.85 ✓	15.43	14.06
62.50	65.50	3.35 ✓	11.52 ✓	65.47	68.49
65.50	68.60	1.70 ✓	3.25 ✓	34.28	1.91
68.60	72.30	1.63 ✓	4.03 ✓	35.31 ✓	1.00
72.30	90.70	N/A	N/A	N/A	1.03
90.70	93.00	1.78 ✓	3.43 ✓	29.14 ✓	-
93.00	95.80	1.83 ✓	3.85 ✓	30.17 ✓	-
95.80	97.50	2.58 ✓	5.28 ✓	39.42 ✓	1.15
97.50	99.50	2.35 ✓	3.58 ✓	39.42 ✓	1.15
99.50	101.90	8.18 ✓	15.27 ✓	121.01 ✓	3.53
101.90	114.30	N/A	N/A	N/A	-

HOLE NO: U-26
 HOLE LENGTH: 76.20

LATITUDE: 10777.49
 DEPARTURE: 7689.09
 ELEVATION: 1156.85

AZIMUTH: 235.18 ✓
 DIP: 69.00 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	1.25 ✓	.48 ✓	27.42 27.43
1.50	3.00	.25 ✓	2.20 ✓	8.23 ✓
3.00	4.60	1.75 ✓	4.40 ✓	31.19 31.20
4.60	6.10	4.70 ✓	11.21 ✓	83.64 83.66
6.10	7.60	2.00 ✓	3.43 ✓	33.25 33.26
7.60	9.10	1.42 ✓	2.73 ✓	23.31 ✓
9.10	10.70	1.67 ✓	4.20 ✓	27.42 27.43
10.70	12.20	2.90 ✓	7.69 ✓	48.33 48.34
12.20	13.70	3.65 ✓	7.61 ✓	56.56 56.57
13.70	15.20	2.80 ✓	7.79 ✓	47.31 ✓
15.20	16.80	4.08 ✓	7.81 ✓	61.36 61.37
16.80	18.30	1.65 ✓	4.75 ✓	23.31 ✓
18.30	19.80	3.10 ✓	6.01 ✓	41.48 41.49
19.80	21.30	2.90 ✓	6.42 ✓	45.25 45.26
21.30	22.90	3.10 ✓	5.71 ✓	50.39 50.40
22.90	24.40	1.35 ✓	3.80 ✓	28.80 28.80
24.40	25.90	.98 ✓	3.05 ✓	14.40 13.03
25.90	27.40	.85 ✓	1.18 ✓	10.97 9.94
27.40	29.00	2.60 ✓	2.33 ✓	43.19 39.43
29.00	30.50	1.78 ✓	3.53 ✓	33.25 30.17
30.50	32.00	1.88 ✓	4.13 ✓	43.19 39.43
32.00	33.50	1.88 ✓	3.55 ✓	38.74 35.31
33.50	35.10	2.05 ✓	1.88 ✓	30.17 27.43
35.10	36.60	1.17 ✓	1.85 ✓	17.83 16.11
36.60	38.60	.68 ✓	1.63 ✓	8.91 8.23
38.60	40.00	4.20 ✓	5.53 ✓	119.64 109.03
40.00	48.10	N/A	N/A	N/A
48.10	50.30	3.25 ✓	8.20 ✓	55.19 50.40
50.30	52.40	2.90 ✓	7.64 ✓	57.59 52.46
52.40	55.10	4.70 ✓	8.12 ✓	71.99 65.49
55.10	56.40	1.73 ✓	4.13 ✓	31.88 29.14
56.40	59.00	1.40 ✓	2.68 ✓	20.91 19.20
59.00	76.20	N/A	N/A	N/A

SPECIFIC TO MOORE BUSINESS FORMS 4

HOLE NO: U-27
 HOLE LENGTH: 106.10

LATITUDE: 10781.03 ✓
 DEPARTURE: 7693.72 ✓
 ELEVATION: 1157.39 ✓

AZIMUTH: 48.25 ✓
 DIP: 62.00 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	6.85 ✓	10.29 ✓	84.69 ✓
1.50	3.00	2.83 ✓	4.50 ✓	40.46 ✓
3.00	4.60	3.35 ✓	3.20 ✓	42.51 ✓
4.60	6.10	3.10 ✓	1.95 ✓	50.40 ✓
6.10	7.60	.98 ✓	.60 ✓	25.37 ✓
7.60	9.10	2.25 ✓	2.90 ✓	46.29 ✓
9.10	11.20	2.23 ✓	4.15 ✓	36.34 ✓
11.20	13.60	N/A	N/A	N/A
13.60	15.20	1.20 ✓	2.05 ✓	26.40 ✓
15.20	16.80	2.88 ✓	3.10 ✓	36.34 ✓
16.80	18.30	1.25 ✓	2.35 ✓	24.34 ✓
18.30	19.80	3.35 ✓	3.62 ✓	43.54 ✓
19.80	23.00	5.56 ✓	5.45 ✓	69.60 ✓
23.00	24.10	N/A	N/A	N/A
24.10	25.90	2.18 ✓	5.39 ✓	38.40 ✓
25.90	27.40	2.43 ✓	4.30 ✓	40.46 ✓
27.40	29.40	N/A	N/A	N/A
29.40	30.50	1.55 ✓	2.70 ✓	28.46 ✓
30.50	32.00	3.68 ✓	7.68 ✓	65.49 ✓
32.00	33.50	1.63 ✓	3.95 ✓	29.14 ✓
33.50	35.10	1.93 ✓	4.30 ✓	30.17 ✓
35.10	36.60	1.25 ✓	2.10 ✓	24.34 ✓
36.60	38.10	2.65 ✓	2.55 ✓	41.49 ✓
38.10	39.60	2.20 ✓	5.50 ✓	45.26 ✓
39.60	41.10	2.68 ✓	7.18 ✓	53.49 ✓
41.10	42.70	3.90 ✓	6.16 ✓	61.51 ✓
42.70	45.70	1.45 ✓	3.45 ✓	34.29 ✓
45.70	48.80	1.75 ✓	3.15 ✓	32.23 ✓
48.80	51.80	2.75 ✓	5.93 ✓	41.49 ✓
51.80	54.90	3.45 ✓	6.92 ✓	56.57 ✓
54.90	57.90	1.70 ✓	3.18 ✓	31.20 ✓
57.90	61.00	1.75 ✓	2.40 ✓	30.17 ✓
61.00	64.00	2.73 ✓	4.80 ✓	40.46 ✓
64.00	67.10	5.90 ✓	10.84 ✓	82.63 ✓
67.10	69.70	.33 ✓	3.95 ✓	9.94 ✓
69.70	71.60	8.35 ✓	13.94 ✓	117.94 ✓
71.60	73.20	7.27 ✓	12.32 ✓	93.94 ✓
73.20	75.40	4.00 ✓	7.89 ✓	65.49 ✓
75.40	92.70	N/A	N/A	N/A
92.70	94.50	3.88 ✓	8.03 ✓	75.77 ✓
94.50	96.00	2.23 ✓	3.60 ✓	33.26 ✓
96.00	97.50	5.70 ✓	6.84 ✓	81.60 ✓
97.50	99.10	2.05 ✓	2.95 ✓	33.26 ✓
99.10	100.60	1.20 ✓	2.35 ✓	18.17 ✓
100.60	102.10	2.80 ✓	3.30 ✓	34.29 ✓
102.10	103.50	.90 ✓	2.33 ✓	12.00 ✓
103.50	103.90	1.93 ✓	4.35 ✓	31.20 ✓
103.90	106.10	4.18 ✓	6.32 ✓	66.51 ✓

3.65

7.69

66.51

SPECIFIC MOORE BUSINESS FORMS 4

HOLE NO: U-28
HOLE LENGTH: 64.00

LATITUDE: 10708.75 ✓
DEPARTURE: 7538.75 ✓
ELEVATION: 1166.52 ✓

AZIMUTH: 48.42 ✓
DIP: -39.30 ✓

-39.12 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	7.40	N/A	N/A	N/A
7.40	9.00	.58 ✓	.48 ✓	8.23 ✓
9.00	10.70	.97 ✓	.70 ✓	15.09 ✓
10.70	13.20	.04	.03 ✓	.34 ✓
13.20	14.80	.68 ✓	.20 ✓	25.37 ✓
14.80	15.50	7.24 ✓	4.75 ✓	102.86 ✓
15.50	17.60	7.50 ✓	5.75 ✓	95.66 ✓
17.60	19.80	11.85 ✓	8.71 ✓	146.74 ✓
19.80	21.30	14.95 ✓	9.52 ✓	186.52 ✓
21.30	22.10	4.83 ✓	3.60 ✓	64.46 ✓
22.10	55.30	N/A	N/A	N/A
55.30	56.70	.22 ✓	.63 ✓	4.11 ✓
56.70	57.90	8.50 ✓	13.85 ✓	179.66 ✓
57.90	59.40	7.53 ✓	10.08 ✓	116.92 ✓
59.40	61.00	7.78 ✓	12.37 ✓	151.20 ✓
61.00	62.50	6.75 ✓	12.62 ✓	109.94 ✓
62.50	64.00	6.82 ✓	10.46	110.06 ✓
				10.64

SPECIFIC MOORE BUSINESS FORMS

HOLE NO: U-30
 HOLE LENGTH: 36.60
 LATITUDE: 10709.04
 DEPARTURE: 7538.30
 ELEVATION: 1169.60

AZIMUTH: 51.50
 DIP: 43.22

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	3.00	N/A	N/A	N/A
3.00	4.60	3.80 ✓	3.65 ✓	65.49 ✓
4.60	6.00	.40 ✓	.03 ✓	15.09 ✓
6.00	6.50	1.30 ✓	.23 ✓	35.31 ✓
6.50	7.40	7.60 ✓	6.93 ✓	98.74 ✓
7.40	8.10	4.65 ✓	2.45 ✓	73.71 ✓
8.10	9.60	9.40 ✓	8.70 ✓	145.03 ✓
9.60	10.70	.90 ✓	.60 ✓	10.97 ✓
10.70	11.90	.60 ✓	.50 ✓	7.20 ✓
11.90	15.20	1.43 ✓	1.23 ✓	17.14 ✓
15.20	18.30	2.05 ✓	1.65 ✓	24.34 ✓
18.30	20.30	.80 ✓	.93 ✓	9.94 ✓
20.30	21.40	N/A	N/A	N/A
21.40	23.40	.83 ✓	.68 ✓	10.97 ✓
23.40	24.20	N/A	N/A	N/A
24.20	25.90	4.15 ✓	3.20 ✓	49.37 ✓
25.90	26.90	2.50 ✓	1.88 ✓	36.34 ✓
26.90	29.00	6.92 ✓	5.39 ✓	77.83 ✓
29.00	36.60	N/A	N/A	N/A
	36.60			

HOLE NO: U-31 LATITUDE: 10702.96 ✓
 HOLE LENGTH: 61.00 DEPARTURE: 7535.11 ✓
 ELEVATION: 1166.86 ✓ AZIMUTH: ~~97.75~~ 92.35 ✓
 DIP: -15.45 ✓

DIP TESTS: DEPTH DIP AZIMUTH
 8.20 -16.30 76.00

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	13.70	N/A	N/A	N/A
13.70	15.20	.23 ✓	.18 ✓	2.06 ✓
15.20	16.80	1.40 ✓	1.10 ✓	20.23 ✓
16.80	17.80	.85 ✓	.50 ✓	13.03 ✓
17.80	18.10	1.03 ✓	.73 ✓	16.11 ✓
18.10	19.80	2.83 ✓	2.05 ✓	35.31 ✓
19.80	21.00	2.20 ✓	1.10 ✓	31.20 ✓
21.00	22.00	1.40 ✓	1.13 ✓	17.14 ✓
22.00	22.60	.38 ✓	.35 ✓	4.11 ✓
22.60	27.30	N/A	N/A	N/A
27.30	28.50	1.43 ✓	.93 ✓	19.20 ✓
28.50	29.20	N/A	N/A	N/A
29.20	29.60	1.03 ✓	.60 ✓	27.43 ✓
29.60	30.70	8.11 ✓	5.17 ✓	103.89 ✓
30.70	32.00	2.25 ✓	1.63 ✓	27.43 ✓
32.00	33.50	2.05 ✓	.83 ✓	24.34 ✓
33.50	35.10	11.12 ✓	3.88 ✓	132.00 ✓
35.10	35.80	3.60 ✓	1.55 ✓	55.54 ✓
35.80	38.10	10.12 ✓	4.35 ✓	121.03 ✓
38.10	38.90	5.71 ✓	3.95 ✓	67.54 ✓
38.90	39.60	N/A	N/A	N/A
39.60	39.90	.68 ✓	.45 ✓	8.91 ✓
39.90	61.00	N/A	N/A	N/A

SPECIFIC TO MOORE BUSINESS FORMS 4

HOLE NO: U-32 LATITUDE: 10703.10 AZIMUTH: 222.33
HOLE LENGTH: 121.90 DEPARTURE: 7532.66 DIP: -72.51
ELEVATION: 1166.37

DIP TESTS:	DEPTH	DIP	AZIMUTH
	33.50	-79.00	217.00
	67.00	-82.00	224.00
	97.50	-85.30	252.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.80	2.48 ✓	4.98 ✓	38.40 ✓
1.80	28.20	N/A	N/A	N/A
28.20	29.30	.48 ✓	.33 ✓	8.23 ✓
29.30	30.50	2.43 ✓	1.90 ✓	41.49 ✓
30.50	53.40	N/A	N/A	N/A
53.40	54.70	5.12 ✓	8.92 ✓	98.74 ✓
54.70	90.10	N/A	N/A	N/A
90.10	92.30	3.90 ✓	4.50 ✓	49.37 ✓
92.30	93.00	.25 ✓	.23 ✓	9.94 ✓
93.00	107.90	N/A	N/A	N/A
107.90	109.70	1.90 ✓	1.90 ✓	25.37 ✓
109.70	111.30	1.30 ✓	.88 ✓	17.14 ✓
111.30	113.00	.50 ✓	.95 ✓	9.94 ✓
113.00	121.90	N/A	N/A	N/A

HOLE NO: U-33 LATITUDE: 10700.57 AZIMUTH: 224.00 ✓
 HOLE LENGTH: 21.90 DEPARTURE: 7530.24 DIP: 45.00 ✓
 ELEVATION: 1169.41

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	2.80	N/A	N/A	N/A
2.80	3.40	4.43 ✓	3.25 ✓	71.66 ✓
3.40	5.10	1.10 ✓	1.13 ✓	19.20 ✓
5.10	6.20	N/A	N/A	N/A
6.20	7.80	6.05 ✓	7.93 ✓	88.80 ✓
7.80	21.90	N/A	N/A	N/A

HOLE NO: U-34
 HOLE LENGTH: 126.50

LATITUDE: 10767.51 ✓
 DEPARTURE: 7589.08 ✓
 ELEVATION: 1144.61 ✓

153.51 ✓
 AZIMUTH: 153.32 ✓
 DIP: -86.18 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.90	2.88 ✓	3.65 ✓	35.31 ✓
1.90	4.40	.72 ✓	.13 ✓	8.23 ✓
4.40	6.10	1.53 ✓	1.50 ✓	15.09 ✓
6.10	8.30	2.20 ✓	4.08 ✓	32.23 ✓
8.30	46.70	N/A	N/A	N/A
46.70	48.40	.63 ✓	.93 ✓	15.09 ✓
48.40	50.30	7.51 ✓	12.47 ✓	140.23 ✓
50.30	51.80	2.95 ✓	3.73 ✓	44.23 ✓
51.80	53.30	5.63 ✓	8.08 ✓	120.00 ✓
53.30	54.90	4.13 ✓	6.84 ✓	71.66 ✓
54.90	56.40	3.40 ✓	6.24 ✓	50.40 ✓
56.40	57.90	2.65 ✓	6.23 ✓	42.51 ✓
57.90	59.40	4.10 ✓	8.08 ✓	69.60 ✓
59.40	61.00	3.40 ✓	5.14 ✓	57.60 ✓
61.00	62.50	3.63 ✓	5.69 ✓	73.71 ✓
62.50	64.00	6.22 ✓	9.60 ✓	114.17 ✓
64.00	65.50	5.40 ✓	9.15 ✓	105.94 ✓
65.50	67.10	2.73 ✓	6.41 ✓	38.40 ✓
67.10	68.60	5.62 ✓	9.50 ✓	100.80 ✓
68.60	70.10	3.13 ✓	6.01 ✓	44.23 ✓
70.10	71.60	4.55 ✓	7.88 ✓	73.71 ✓
71.60	73.20	3.23 ✓	5.06 ✓	57.60 ✓
73.20	74.70	2.60 ✓	5.37 ✓	44.23 ✓
74.70	76.20	3.45 ✓	6.67 ✓	60.34 ✓
76.20	77.70	3.00 ✓	4.90 ✓	41.49 ✓
77.70	79.20	4.00 ✓	4.23 ✓	52.46 ✓
79.20	80.80	3.65 ✓	6.41 ✓	59.31 ✓
80.80	82.30	4.27 ✓	7.35 ✓	62.40 ✓
82.30	83.80	5.51 ✓	7.98 ✓	70.63 ✓
83.80	85.30	4.58 ✓	7.25 ✓	71.66 ✓
85.30	86.90	3.25 ✓	5.47 ✓	50.40 ✓
86.90	88.40	4.50 ✓	6.28 ✓	57.60 ✓
88.40	89.90	6.79 ✓	11.13 ✓	100.80 ✓
89.90	91.40	3.98 ✓	3.78 ✓	60.34 ✓
91.40	93.00	4.48 ✓	7.83 ✓	63.43 ✓
93.00	94.50	4.46 ✓	6.81 ✓	63.43 ✓
94.50	96.00	4.36 ✓	8.85 ✓	55.54 ✓
96.00	97.50	6.36 ✓	8.08 ✓	80.57 ✓
97.50	99.10	4.31 ✓	6.02 ✓	55.54 ✓
99.10	100.60	.05 ✓	.35 ✓	6.17 ✓
100.60	102.10	.25 ✓	1.75 ✓	17.14 ✓
102.10	103.60	.10 ✓	1.53 ✓	8.23 ✓
103.60	105.20	.15 ✓	.33 ✓	8.91 ✓
105.20	106.70	1.30 ✓	1.10 ✓	25.37 ✓
106.70	108.10	2.00 ✓	1.45 ✓	33.26 ✓
108.10	126.50	N/A	N/A	N/A

SPEED TO MOORE BUSINESS FORMS 4

HOLE NO: U-35 LATITUDE: 10768.05 ✓
 HOLE LENGTH: 147.80 DEPARTURE: 7589.41 ✓
 ELEVATION: 1144.64 ✓ AZIMUTH: 57.10 ✓
 DIP: -63.23 ✓

DIP TESTS: DEPTH DIP AZIMUTH
 60.80 -76.00 48.00
 108.20 -78.00 60.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.50	1.89 ✓	3.70 ✓	30.17 ✓
1.50	4.40	1.04 ✓	2.28 ✓	16.11 ✓
4.40	6.70	2.10 ✓	4.20 ✓	34.29 ✓
6.70	8.00	.58 ✓	1.00 ✓	10.97 ✓
8.00	51.00	N/A	N/A	N/A
51.00	52.10	2.58 ✓	5.87 ✓	41.49 ✓
52.10	59.40	N/A	N/A	N/A
59.40	61.50	1.05 ✓	2.00 ✓	25.37 ✓
61.50	62.50	3.75 ✓	5.00 ✓	66.51 ✓
62.50	64.00	2.93 ✓	4.55 ✓	54.51 ✓
64.00	65.50	3.95 ✓	6.48 ✓	68.57 ✓
65.50	67.10	3.45 ✓	5.49 ✓	55.54 ✓
67.10	68.60	4.03 ✓	5.59 ✓	53.49 ✓
68.60	70.10	5.80 ✓	7.35 ✓	101.83 ✓
70.10	71.60	2.83 ✓	1.98 ✓	41.49 ✓
71.60	73.20	6.30 ✓	9.47 ✓	81.60 ✓
73.20	74.70	6.60 ✓	9.95 ✓	100.80 ✓
74.70	76.20	6.50 ✓	11.90 ✓	110.06 ✓
76.20	77.70	6.36 ✓	11.64 ✓	125.14 ✓
77.70	79.20	1.70 ✓	2.33 ✓	29.14 ✓
79.20	81.10	4.25 ✓	9.44 ✓	72.69 ✓
81.10	85.30	N/A	N/A	N/A
85.30	86.90	2.60 ✓	3.10 ✓	30.17 ✓
86.90	88.40	2.80 ✓	2.75 ✓	33.26 ✓
88.40	90.50	.94 ✓	1.65 ✓	14.06 ✓
90.50	106.70	N/A	N/A	N/A
106.70	108.20	1.10 ✓	1.93 ✓	15.09 ✓
108.20	147.80	N/A	N/A	N/A

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-36

LATITUDE: ~~10630.20~~ ^{10631.98}
 DEPARTURE: ~~7679.73~~ ^{7679.73}
 ELEVATION: ~~1167.93~~ ^{1167.93}

AZIMUTH: ~~130.48~~ ^{223.25}
 DIP: 7.44

INTERVAL
 FROM TO

ASSAYS
 PB ZN AG
 % % GM/TON

lat: 10,629.59
 dep: 7678.69
 el: 1167.93

FROM	TO	PB %	ZN %	AG GM/TON
0.00	15.20	N/A	N/A	N/A
15.20	16.80	8.17 ✓	10.82 ✓	133.00 ✓
16.80	19.80	N/A	N/A	N/A

MOORE
 SPECTRO A

HOLE NO: U-37 LATITUDE: ~~10633.28~~ ^{10633.28} AZIMUTH: ~~95.35~~ ^{95.35}
 DEPARTURE: ~~7678.68~~ ^{7678.65} DIP: 9.12
 ELEVATION: 1167.74 ✓

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	10.10	N/A	N/A	N/A
10.10	10.70	2.15 ✓	5.07 ✓	32.23 ✓
10.70	12.20	2.10 ✓	4.98 ✓	49.37 ✓
12.20	13.70	2.60 ✓	5.68 ✓	47.31 ✓
13.70	15.20	4.70 ✓	13.68 ✓	97.72 ✓
15.20	16.80	4.93 ✓	12.76 ✓	80.57 ✓
16.80	18.30	4.80 ✓	10.26 ✓	86.74 ✓
18.30	19.80	6.51 ✓	13.27 ✓	98.74 ✓
19.80	21.30	6.36 ✓	13.12 ✓	99.77 ✓
21.30	22.90	4.65 ✓	6.77 ✓	80.57 ✓
22.90	24.40	1.43 ✓	1.68 ✓	24.34 ✓
24.40	25.90	1.18 ✓	1.75 ✓	24.34 ✓
25.90	53.30	N/A	N/A	N/A

lat: 10,630.8⁷
 dep: 7679.57
 el: 1167.70

13.37

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-38 LATITUDE: ~~10632.65~~ ^{10630.51} AZIMUTH: ~~256.27~~ 106.00
 DEPARTURE: ~~7678.25~~ ^{7681.27} DIP: 9.49
 ELEVATION: ~~1167.83~~ 9.41

INTERVAL		ASSAYS			lat: 10,630.15 dep: 7679.16 el: 1167.79
FROM	TO	PB %	ZN %	AG GM/TON	
0.00	11.10	N/A	N/A	N/A	
11.10	12.20	2.35 ✓	5.52 ✓	33.26 ✓	
12.20	13.70	1.70 ✓	4.13 ✓	31.20 ✓	
13.70	15.20	4.63 ✓	11.80 ✓	76.80 ✓	
15.20	16.80	5.63 ✓	15.15	85.72 ✓	15.13
16.80	18.30	2.48 ✓	6.28 ✓	46.29 ✓	
18.30	19.80	3.73 ✓	10.77 ✓	62.40 ✓	
19.80	21.30	3.45 ✓	7.99 ✓	60.34 ✓	
21.30	22.90	4.03 ✓	9.46 ✓	93.94 ✓	
22.90	24.40	6.20 ✓	12.50 ✓	104.92 ✓	
24.40	25.90	5.42 ✓	10.15 ✓	75.77 ✓	
25.90	27.40	4.25 ✓	6.02 ✓	71.66 ✓	
27.40	29.00	.65 ✓	1.18 ✓	13.03 ✓	
29.00	85.30	N/A	N/A	N/A	

MOORE
SPECIALTY

HOLE NO: U-39
 HOLE LENGTH: 110.30

LATITUDE: 10767.25 ✓
 DEPARTURE: 7588.40 ✓
 ELEVATION: 1144.62 ✓

AZIMUTH: 230.24 ✓
 DIP: -73.15 ✓

DIP TESTS: DEPTH DIP AZIMUTH
 30.48 -75.00 241.00
 56.39 -75.00 240.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.50	1.74 ✓	1.43 ✓	21.26 ✓
1.50	3.00	1.18 ✓	1.30 ✓	17.14 ✓
3.00	4.00	1.53	2.78	36.34 ✓
4.00	6.10	.14 ✓	.08 ✓	3.09 ✓
6.10	8.10	1.85 ✓	.20 ✓	18.17 ✓
8.10	9.50	1.95 ✓	2.43 ✓	24.34 ✓
9.50	11.00	1.35	2.00 ✓	21.26 ✓
11.00	17.20	N/A	N/A	N/A
17.20	20.20	1.18 ✓	1.43 ✓	13.03 ✓
20.20	22.90	1.98 ✓	3.25 ✓	25.37 ✓
22.90	25.90	.65 ✓	1.15 ✓	6.17 ✓
25.90	28.40	1.88 ✓	1.00 ✓	15.09 ✓
28.40	38.90	N/A	N/A	N/A
38.90	41.00	.58 ✓	1.33 ✓	8.91 ✓
41.00	42.70	.19 ✓	.28 ✓	3.09 ✓
42.70	44.40	7.59 ✓	13.05 ✓	122.06 ✓
44.40	48.80	N/A	N/A	N/A
48.80	50.30	.63 ✓	1.00 ✓	15.09 ✓
50.30	51.80	4.75 ✓	5.45 ✓	75.77 ✓
51.80	53.30	5.70 ✓	7.70 ✓	90.86 ✓
53.30	54.90	4.90 ✓	8.77 ✓	82.63 ✓
54.90	56.40	7.69 ✓	13.76 ✓	75.77 ✓
56.40	57.90	4.48 ✓	6.42 ✓	67.54 ✓
57.90	59.40	3.95 ✓	7.26 ✓	62.40 ✓
59.40	61.00	4.30 ✓	6.94 ✓	78.86 ✓
61.00	62.50	3.05 ✓	3.90 ✓	49.37 ✓
62.50	64.00	1.85 ✓	2.10 ✓	36.34 ✓
64.00	65.50	.55 ✓	.70 ✓	12.00 ✓
65.50	67.10	2.55 ✓	1.58 ✓	50.40 ✓
67.10	68.60	4.75 ✓	4.95 ✓	62.40 ✓
68.60	70.10	2.30 ✓	2.28 ✓	43.54 ✓
70.10	71.60	1.30 ✓	1.85 ✓	25.37 ✓
71.60	73.20	1.78 ✓	3.23 ✓	25.37 ✓
73.20	74.70	2.90 ✓	6.86 ✓	57.60 ✓
74.70	76.20	2.23 ✓	4.70 ✓	44.23 ✓
76.20	77.70	2.50 ✓	4.75 ✓	54.51 ✓
77.70	79.20	3.48 ✓	7.68 ✓	100.80 ✓
79.20	80.80	2.90 ✓	5.75 ✓	45.26 ✓
80.80	82.30	7.36 ✓	16.65 ✓	125.14 ✓
82.30	83.80	8.28 ✓	14.95 ✓	129.94 ✓
83.80	85.30	5.10 ✓	8.24 ✓	80.57 ✓
85.30	86.90	4.68 ✓	7.88 ✓	59.31 ✓
86.90	88.40	2.80 ✓	5.15 ✓	41.49 ✓
88.40	89.90	2.90 ✓	4.80 ✓	44.23 ✓
89.90	91.40	1.25 ✓	2.13 ✓	28.46 ✓
91.40	93.00	3.88 ✓	2.95 ✓	60.34 ✓

278 1.53

1.34

SPEECH TO MOORE BUSINESS FORMS 4

HOLE NO: U-39

INTERVAL

ASSAYS

FROM	TO	PB %	ZN %	AG GM/TON
93.00	94.50	2.15 ✓	13.32 ✓	36.34 ✓
94.50	96.50	4.08 ✓	11.03 ✓	60.34 ✓
96.50	110.30	N/A	N/A	N/A

HOLE NO: U-40 LATITUDE: 10767.05 ✓
HOLE LENGTH: 108.80 DEPARTURE: 7588.31 ✓
ELEVATION: 1144.60 ✓ AZIMUTH: 225.20 ✓
DIP: -53.58 ✓
-53.48

DIP TESTS: DEPTH DIP AZIMUTH
45.70 -59.00 234.00
91.40 -59.00 249.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	42.70	N/A	N/A	N/A
42.70	43.40	.07 ✓	.48 ✓	5.14 ✓
43.40	45.00	6.10 ✓	9.92 ✓	85.72 ✓
45.00	46.70	6.10 ✓	9.20 ✓	95.66 ✓
46.70	54.70	N/A	N/A	N/A
54.70	56.20	2.23 ✓	4.03 ✓	60.34 ✓
56.20	57.80	N/A	N/A	N/A
57.80	59.40	5.20 ✓	7.17 ✓	93.94 ✓
59.40	61.00	.48 ✓	.70 ✓	8.23 ✓
61.00	62.50	6.15 ✓	10.43 ✓	102.86 ✓
62.50	64.00	3.70 ✓	6.15 ✓	58.63 ✓
64.00	65.50	1.55 ✓	1.70 ✓	37.37 ✓
65.50	67.10	3.20 ✓	5.20 ✓	61.37 ✓
67.10	68.60	3.75 ✓	7.50 ✓	55.54 ✓
68.60	70.10	3.98 ✓	6.66 ✓	85.72 ✓
70.10	71.60	3.90 ✓	6.62 ✓	92.92 ✓
71.60	73.20	4.80 ✓	7.55 ✓	98.74 ✓
73.20	74.70	5.18 ✓	8.40 ✓	117.94 ✓
74.70	85.80	N/A	N/A	N/A
85.80	88.40	.43 ✓	.93 ✓	8.91 ✓
88.40	89.90	.15 ✓	.75 ✓	5.14 ✓
89.90	91.40	.30 ✓	1.70 ✓	12.00 ✓
91.40	93.00	1.68 ✓	2.95 ✓	32.23 ✓
93.00	94.50	1.68 ✓	3.10 ✓	37.37 ✓
94.50	96.00	.80 ✓	4.10 ✓	13.03 ✓
96.00	97.50	1.43 ✓	2.53 ✓	20.23 ✓
97.50	99.10	.08 ✓	.65 ✓	5.14 ✓
99.10	100.60	.35 ✓	1.50 ✓	8.91 ✓
100.60	102.10	4.50 ✓	12.71 ✓	90.86 ✓
102.10	103.60	6.90 ✓	10.86 ✓	106.97 ✓
103.60	104.60	.99 ✓	3.20 ✓	22.29 ✓
104.60	108.80	N/A	N/A	N/A

SHEET NO. MOORE BUSINESS FORMS 4

HOLE NO: U-42
 HOLE LENGTH: 53.30

LATITUDE: 10767.69 ✓
 DEPARTURE: 7590.11 ✓
 ELEVATION: 1148.63 ✓

AZIMUTH: 45.29 ✓
 DIP: 68.18 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	3.00	.93 ✓	1.38 ✓	13.03 ✓
3.00	6.10	.79 ✓	1.23 ✓	12.00 ✓
6.10	7.30	.90 ✓	.83 ✓	13.03 ✓
7.30	9.10	5.95 ✓	5.49 ✓	70.63 ✓
9.10	10.70	2.85 ✓	4.75 ✓	42.51 ✓
10.70	12.20	4.10 ✓	7.98 ✓	62.40 ✓
12.20	13.70	6.41 ✓	9.94 ✓	87.77 ✓
13.70	15.20	3.45 ✓	4.65 ✓	45.26 ✓
15.20	16.80	1.14 ✓	2.00 ✓	19.20 ✓
16.80	18.30	2.60 ✓	4.73 ✓	36.34 ✓
18.30	19.80	2.00 ✓	3.85 ✓	27.43 ✓
19.80	21.30	.68 ✓	1.35 ✓	12.00 ✓
21.30	22.90	2.20 ✓	3.50 ✓	31.20 ✓
22.90	24.40	2.13 ✓	4.00 ✓	30.17 ✓
24.40	25.90	1.58 ✓	1.90 ✓	22.29 ✓
25.90	27.40	1.25 ✓	1.80 ✓	18.17 ✓
27.40	29.00	2.70 ✓	3.90 ✓	42.51 ✓
29.00	30.50	6.33 ✓	12.51 ✓	91.89 ✓
30.50	32.00	4.90 ✓	9.00 ✓	82.63 ✓
32.00	33.80	8.98 ✓	18.92 ✓	156.34 ✓
33.80	53.30	N/A	N/A	N/A

HOLE NO: U-43
 HOLE LENGTH: 45.70

LATITUDE: 10767.24 ✓
 DEPARTURE: 7589.51 ✓
 ELEVATION: 1148.76 ✓

AZIMUTH: 206.33 ✓
 DIP: 89.15 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	3.00	1.15 ✓	1.75 ✓	14.06 ✓
3.00	5.00	1.35 ✓	1.40 ✓	17.14 ✓
5.00	6.60	N/A	N/A	N/A
6.60	9.10	2.88 ✓	3.00 ✓	35.31 ✓
9.10	10.70	4.55 ✓	5.21 ✓	53.49 ✓
10.70	12.20	4.78 ✓	8.14 ✓	72.69 ✓
12.20	13.70	10.78 ✓	19.02 ✓	166.29 ✓
13.70	15.20	11.93 ✓	21.05 ✓	173.49 ✓
15.20	16.80	9.80 ✓	18.15 ✓	145.03 ✓
16.80	18.30	12.61 ✓	21.91 ✓	224.92 ✓
18.30	19.80	14.30 ✓	22.73 ✓	177.60 ✓
19.80	21.30	8.05 ✓	12.76 ✓	115.89 ✓
21.30	22.90	9.43 ✓	16.24 ✓	143.32 ✓
22.90	24.60	7.28 ✓	13.87 ✓	117.94 ✓
24.60	25.40	.15 ✓	.30 ✓	4.11 ✓
25.40	45.70	N/A	N/A	N/A

SPECIFIC TO MOORE BUSINESS FORMS 4

HOLE NO: U-44 LATITUDE: 10767.80 ✓
 HOLE LENGTH: 45.70 DEPARTURE: 7587.31 ✓
 ELEVATION: 1148.79 ✓

AZIMUTH: 235.57 ✓
 DIP: 60.46 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	3.00	1.23 ✓	1.70 ✓	17.14 ✓
3.00	4.60	2.43 ✓	2.40 ✓	29.14 ✓
4.60	6.10	2.20 ✓	3.20 ✓	25.37 ✓
6.10	7.60	4.35 ✓	5.19 ✓	52.46 ✓
7.60	9.10	3.90 ✓	7.17 ✓	48.34 ✓
9.10	10.70	3.10 ✓	6.18 ✓	40.46 ✓
10.70	12.20	1.93 ✓	3.33 ✓	31.20 ✓
12.20	13.70	7.74 ✓	12.24 ✓	114.17 ✓
13.70	15.20	10.86 ✓	16.86 ✓	169.37 ✓
15.20	16.80	6.16 ✓	13.86 ✓	89.83 ✓
16.80	18.30	3.90 ✓	5.85 ✓	60.34 ✓
18.30	19.80	8.60 ✓	15.24 ✓	133.03 ✓
19.80	33.40	N/A	N/A	N/A
33.40	34.80	1.35 ✓	1.15 ✓	21.36 ✓
34.80	36.10	7.37 ✓	5.95 ✓	89.83 ✓
36.10	45.70	N/A	N/A	N/A

HOLE NO: U-45 LATITUDE: 10831.00 AZIMUTH: 44.00 ✓
 HOLE LENGTH: 62.50 DEPARTURE: 7647.00 DIP: -80.00 ✓
 ELEVATION: 1143.25

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	2.75 ✓	6.25 ✓	48.34 ✓
1.50	3.00	4.68 ✓	6.68 ✓	65.49 ✓
3.00	4.60	7.19 ✓	5.74 ✓	75.77 ✓
4.60	6.10	4.40 ✓	4.60 ✓	53.49 ✓
6.10	7.60	6.47 ✓	11.27 ✓	97.72 ✓
7.60	9.10	2.37 ✓	7.01 ✓	39.43 ✓
9.10	11.00	2.80 ✓	5.79 ✓	48.34 ✓
11.00	12.90	.03 ✓	.18 ✓	1.03 ✓
12.90	14.40	3.90 ✓	6.65 ✓	54.51 ✓
14.40	16.20	2.30 ✓	6.48 ✓	38.40 ✓
16.20	34.30	N/A	N/A	N/A
34.30	35.10	.04 ✓	.13 ✓	1.03 ✓
35.10	36.60	5.81 ✓	11.17 ✓	94.63 ✓
36.60	38.10	1.65 ✓	2.70 ✓	26.40 ✓
38.10	39.60	3.53 ✓	6.10 ✓	49.37 ✓
39.60	41.30	5.44 ✓	5.54 ✓	68.57 ✓
41.30	45.70	N/A	N/A	N/A
45.70	47.20	2.83 ✓	3.30 ✓	40.46 ✓
47.20	48.80	6.64 ✓	7.32 ✓	92.92 ✓
48.80	50.30	7.67 ✓	13.16 ✓	114.17 ✓
50.30	51.80	5.86 ✓	7.90 ✓	94.63 ✓
51.80	53.30	6.15 ✓	9.70 ✓	98.74 ✓
53.30	54.90	8.44 ✓	13.26 ✓	122.06 ✓
54.90	56.40	4.03 ✓	5.79 ✓	69.60 ✓
56.40	57.90	1.28 ✓	2.10 ✓	16.11 ✓
57.90	59.40	.40 ✓	.83 ✓	7.20 ✓
59.40	61.50	N/A	N/A	N/A
61.50	62.50	1.34 ✓	1.38 ✓	18.17 ✓

HOLE NO: U-46 LATITUDE: 10831.00 AZIMUTH: 44.00 ✓
 HOLE LENGTH: 83.80 DEPARTURE: 7647.00 DIP: -50.00 ✓
 ELEVATION: 1143.25

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	2.10	5.76 ✓	10.87 ✓	97.72 ✓
2.10	4.10	1.78 ✓	2.48 ✓	29.14 ✓
4.10	5.50	4.38 ✓	7.86 ✓	75.77 ✓
5.50	7.40	5.00 ✓	9.15 ✓	78.86 ✓
7.40	10.00	.97 ✓	3.00 ✓	15.09 ✓
10.00	11.10	5.64 ✓	9.80 ✓	88.80 ✓
11.10	12.40	.53 ✓	3.03 ✓	13.03 ✓
12.40	14.20	N/A	N/A	N/A
14.20	15.50	3.60 ✓	5.55 ✓	60.34 ✓
15.50	16.80	.23 ✓	.35 ✓	5.14 ✓
16.80	41.20	N/A	N/A	N/A
41.20	42.70	2.68 ✓	3.35 ✓	45.26 ✓
42.70	44.20	3.13 ✓	2.40 ✓	51.43 ✓
44.20	45.70	4.55 ✓	4.05 ✓	68.57 ✓
45.70	46.90	4.20 ✓	3.40 ✓	65.49 ✓
46.90	49.10	N/A	N/A	N/A
49.10	51.40	1.35 ✓	1.98 ✓	21.26 ✓
51.40	60.70	N/A	N/A	N/A
60.70	62.50	6.64 ✓	10.77 ✓	111.09 ✓
62.50	64.00	4.80 ✓	7.14 ✓	99.77 ✓
64.00	65.50	3.45 ✓	5.87 ✓	74.74 ✓
65.50	67.10	5.44 ✓	8.64 ✓	79.54 ✓
67.10	68.60	5.50 ✓	9.50 ✓	83.66 ✓
68.60	70.10	4.28 ✓	8.49 ✓	73.71 ✓
70.10	71.10	5.50 ✓	10.47 ✓	100.80 ✓
71.10	83.80	N/A	N/A	N/A

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-47 LATITUDE: 10831.00 AZIMUTH: 224.00 ✓
 DEPARTURE: 7647.00 DIP: -80.00 ✓
 ELEVATION: 1143.25

INTERVAL		ASSAYS				
FROM	TO	PB	ZN	AG		
		%	%	GM/TON		
0.00	1.80	9.27✓	9.80	135.00	9.86	135.09
1.80	3.00	7.64✓	6.71✓	87.77✓		
3.00	5.00	4.40✓	2.35✓	48.34✓		
5.00	6.40	1.68✓	2.40✓	26.40✓		
6.40	8.30	.39✓	.95✓	7.20✓		
8.30	9.10	4.20✓	1.80✓	39.43✓		
9.10	10.70	4.53✓	2.45✓	64.22		44.23
10.70	12.20	4.10✓	5.88✓	53.49✓		
12.20	13.70	3.43✓	6.36✓	54.51✓		
13.70	15.00	2.63✓	4.30✓	45.26✓		
15.00	16.80	8.20✓	14.39✓	133.03✓		
16.80	18.30	8.60✓	17.73✓	146.06✓		
18.30	19.80	6.95✓	21.00✓	125.14✓		
19.80	21.30	7.90✓	20.19✓	123.09✓		
21.30	22.20	11.45✓	26.28✓	209.83✓		
22.20	29.50	N/A	N/A	N/A		
29.50	30.30	.10✓	.15✓	.69✓		
30.30	31.30	2.75✓	3.48✓	41.49✓		
31.30	32.90	6.92✓	12.45✓	112.12✓		
32.90	34.40	4.28✓	9.82✓	63.46		63.43
34.40	37.60	N/A	N/A	N/A		
37.60	39.50	4.13✓	5.49✓	58.63✓		
39.50	57.50	N/A	N/A	N/A		
57.50	59.40	6.32✓	7.40✓	82.63✓		
59.40	61.00	3.48✓	4.20✓	58.63✓		
61.00	62.50	6.22✓	7.72✓	85.72✓		
62.50	64.00	6.75✓	11.03✓	112.12✓		
64.00	65.50	3.68✓	6.23✓	82.63✓		
65.50	80.80	N/A	N/A	N/A		

MOORE SHELF 4

HOLE NO: U-48 LATITUDE: 10826.65 ✓ AZIMUTH: 214.35 ✓
 HOLE LENGTH: 120.70 DEPARTURE: 7645.32 ✓ DIP: -55.30 ✓
 ELEVATION: 1143.34 ✓ -55.34

DIP TESTS:	DEPTH	DIP	AZIMUTH
	30.50	-60.00	207.48
	76.20	-62.30	201.00
	118.90	-68.30	208.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.50	4.93 ✓	9.76 ✓	93.94 ✓
1.50	2.90	8.85 ✓	7.27 ✓	121.03 ✓
2.90	4.60	6.95 ✓	3.10 ✓	80.57 ✓
4.60	6.10	4.88 ✓	3.60 ✓	57.60 ✓
6.10	8.10	2.98 ✓	5.21 ✓	49.37 ✓
8.10	10.70	1.09 ✓	2.39 ✓	22.29 ✓
10.70	12.20	1.60 ✓	2.95 ✓	29.14 ✓
12.20	14.50	2.68 ✓	4.48 ✓	40.46 ✓
14.50	22.30	N/A	N/A	N/A
22.30	24.40	2.70 ✓	6.31 ✓	55.54 ✓
24.40	25.90	4.40 ✓	9.74 ✓	90.86 ✓
25.90	27.20	2.98 ✓	6.97 ✓	55.54 ✓
27.20	28.70	N/A	N/A	N/A
28.70	29.80	1.74 ✓	4.48 ✓	26.40 ✓
29.80	31.10	2.48 ✓	6.26 ✓	33.26 ✓
31.10	32.10	N/A	N/A	N/A
32.10	35.10	2.40 ✓	4.90 ✓	43.54 ✓
35.10	38.10	2.68 ✓	6.54 ✓	45.26 ✓
38.10	39.60	5.87 ✓	10.03 ✓	85.72 ✓
39.60	41.10	10.13 ✓	12.15 ✓	157.37 ✓
41.10	42.70	4.95 ✓	11.34 ✓	77.83 ✓
42.70	44.20	7.80 ✓	14.06 ✓	112.12 ✓
44.20	46.20	1.30 ✓	1.55 ✓	23.31 ✓
46.20	48.00	.58 ✓	1.20 ✓	8.91 ✓
48.00	61.50	N/A	N/A	N/A
61.50	64.00	.33 ✓	1.63 ✓	4.11 ✓
64.00	65.50	1.40 ✓	2.63 ✓	10.97 ✓
65.50	67.10	1.20 ✓	2.40 ✓	18.17 ✓
67.10	68.60	7.49 ✓	13.76 ✓	130.97 ✓
68.60	70.50	3.10 ✓	5.10 ✓	54.51 ✓
70.50	73.20	3.43 ✓	4.70 ✓	50.40 ✓
73.20	74.70	6.99 ✓	12.08 ✓	104.92 ✓
74.70	76.20	6.02 ✓	10.65 ✓	111.09 ✓
76.20	77.70	5.41 ✓	9.07 ✓	84.69 ✓
77.70	80.80	1.20 ✓	1.13 ✓	19.20 ✓
80.80	120.70	N/A	N/A	N/A

2.38

SPEED TO MOORE BUSINESS FORMS 4

HOLE NO: U-49 LATITUDE: 10825.93 ✓
 HOLE LENGTH: 82.30 DEPARTURE: 7643.09 ✓ AZIMUTH: 222.39 ✓
 ELEVATION: 1144.54 ✓ DIP: 0.50 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	2.08 ✓	3.80 ✓	35.31 ✓
1.50	4.70	1.28 ✓	2.55 ✓	21.26 ✓
4.70	6.10	2.05 ✓	3.90 ✓	32.23 ✓
6.10	7.60	2.28 ✓	3.85 ✓	35.31 ✓
7.60	9.10	.93 ✓	1.60 ✓	17.14 ✓
9.10	12.20	1.65 ✓	4.85 ✓	21.26 ✓
12.20	13.70	1.75 ✓	3.60 ✓	25.37 ✓
13.70	15.30	2.28 ✓	3.20 ✓	31.20 ✓
15.30	16.70	2.10 ✓	3.30 ✓	31.20 ✓
16.70	18.20	1.73 ✓	2.78 ✓	27.43 ✓
18.20	19.80	2.25 ✓	5.60 ✓	42.51 ✓
19.80	21.30	2.95 ✓	9.63 ✓	53.49 ✓
21.30	76.20	N/A	N/A	N/A
76.20	77.70	2.15 ✓	5.15 ✓	33.26 ✓
77.70	79.20	1.65 ✓	2.15 ✓	20.23 ✓
79.20	80.70	1.35 ✓	.38 ✓	12.00 ✓
80.70	82.30	1.35 ✓	.20 ✓	10.97 ✓

SPEDIFIED MOORE BUSINESS FORMS 4

HOLE NO: U-51 LATITUDE: 10826.00 AZIMUTH: 224.00 ✓
 HOLE LENGTH: 70.10 DEPARTURE: 7643.00 DIP: 48.00 ✓
 ELEVATION: 1146.00

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	2.10 ✓	4.45 ✓	35.31 ✓
1.50	3.00	3.20 ✓	10.14 ✓	49.37 ✓
3.00	4.50	3.15 ✓	6.93 ✓	56.57 ✓
4.50	6.00	2.93 ✓	4.10 ✓	46.29 ✓
6.00	7.60	2.45 ✓	4.20 ✓	44.23 ✓
7.60	9.10	1.60 ✓	2.90 ✓	25.37 ✓
9.10	10.60	1.53 ✓	3.75 ✓	30.17 ✓
10.60	12.10	1.68 ✓	1.28 ✓	25.37 ✓
12.10	13.70	1.48 ✓	1.43 ✓	23.31 ✓
13.70	15.20	2.65 ✓	2.30 ✓	38.40 ✓
15.20	22.90	N/A	N/A	N/A
22.90	24.30	3.93 ✓	5.39 ✓	74.74 ✓
24.30	25.90	1.95 ✓	5.14 ✓	28.46 ✓
25.90	27.40	2.75 ✓	7.93 ✓	42.51 ✓
27.40	28.90	2.20 ✓	3.50 ✓	33.31 ✓
28.90	30.50	1.08 ✓	2.50 ✓	17.14 ✓
30.50	32.00	1.58 ✓	1.68 ✓	20.23 ✓
32.00	33.50	1.08 ✓	1.83 ✓	14.06 ✓
33.50	35.00	.65 ✓	1.45 ✓	13.03 ✓
35.00	36.50	1.88 ✓	1.55 ✓	31.20 ✓
36.50	38.00	3.18 ✓	6.62 ✓	55.54 ✓
38.00	39.60	1.65 ✓	2.83 ✓	30.17 ✓
39.60	41.10	5.61 ✓	8.99 ✓	98.74 ✓
41.10	41.60	6.30 ✓	10.14 ✓	94.63 ✓
41.60	70.10	N/A	N/A	N/A

35.31

SPEED LOG MOORE BUSINESS FORMS 4

HOLE NO: U-52 LATITUDE: 10826.40 ✓
HOLE LENGTH: 57.90 DEPARTURE: 7643.19 ✓
ELEVATION: 1147.30 ✓ AZIMUTH: 229.23 ✓
DIP: 65.13 ✓

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	3.00	2.33 ✓	7.21 ✓	45.26 ✓
3.00	6.10	2.15 ✓	5.81 ✓	41.49 ✓
6.10	9.10	2.05 ✓	4.50 ✓	31.20 ✓
9.10	12.10	2.18 ✓	3.55 ✓	34.29 ✓
12.10	13.70	1.73 ✓	2.45 ✓	27.43 ✓
13.70	15.20	2.55 ✓	2.80 ✓	35.31 ✓
15.20	16.00	2.78 ✓	3.60 ✓	36.34 ✓
16.00	19.80	N/A	N/A	N/A
19.80	20.80	5.26 ✓	8.25 ✓	83.66 ✓
20.80	25.90	N/A	N/A	N/A
25.90	28.40	2.43 ✓	4.75 ✓	38.40 ✓
28.40	29.80	N/A	N/A	N/A
29.80	32.00	1.30 ✓	1.50 ✓	17.14 ✓
32.00	35.10	2.80 ✓	1.18 ✓	24.34 ✓
35.10	36.60	2.68 ✓	3.05 ✓	32.26 ✓
36.60	38.10	1.93 ✓	3.15 ✓	34.29 ✓
38.10	39.40	1.70 ✓	2.30 ✓	29.14 ✓
39.40	40.40	6.01 ✓	9.96 ✓	95.66 ✓
40.40	57.90	N/A	N/A	N/A

SPECIAL MOORE BUSINESS FORMS 4

HOLE NO: U-53 LATITUDE: 10827.04✓
 HOLE LENGTH: 60.90 DEPARTURE: 7643.68✓
 ELEVATION: 1147.51✓

255.01✓
 AZIMUTH: 225.01✓
 DIP: 83.00✓
 82.55✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.80	2.00✓	3.55✓	38.40✓
1.80	3.00	3.20✓	6.46✓	50.40✓
3.00	4.50	1.70✓	3.55✓	30.17✓
4.50	6.00	2.98✓	6.24✓	54.51✓
6.00	7.60	2.63✓	7.80✓	50.40✓
7.60	9.10	2.30✓	5.58✓	42.51✓
9.10	10.60	1.85✓	4.30✓	28.46✓
10.60	12.20	1.50✓	3.43✓	30.17✓
12.20	13.70	2.68✓	4.20✓	45.26✓
13.70	15.20	2.83✓	5.00✓	50.40✓
15.20	16.70	2.63✓	2.90✓	40.46✓
16.70	18.20	1.55✓	2.65✓	26.40✓
18.20	19.80	.80✓	1.38✓	14.06✓
19.80	21.30	.15✓	.25✓	4.11✓
21.30	28.90	N/A	N/A	N/A
28.90	30.00	2.20✓	5.70✓	41.49✓
30.00	33.50	3.33✓	6.60✓	55.54✓
33.50	35.00	1.55✓	2.63✓	25.37✓
35.00	36.50	1.78✓	2.08✓	24.34✓
36.50	38.10	3.68✓	2.20✓	40.46✓
38.10	39.60	2.30✓	4.05✓	37.37✓
39.60	41.10	1.75✓	3.70✓	30.17✓
41.10	42.60	2.25✓	4.30✓	36.34✓
42.60	44.20	2.28✓	4.10✓	35.31✓
44.20	45.70	6.29✓	10.50✓	93.94✓
45.70	60.90	N/A	N/A	N/A

SPECIAL TO MOORE BUSINESS FORMS 4

DIAMOND DRILL LOG MA

STER FILE

HOLE NO: U-54

LATITUDE: 10829.44 ✓

AZIMUTH: 33.12 ✓

HOLE LENGTH: 150.90

DEPARTURE: 7645.42 ✓

DIP: 60.00 ✓

ELEVATION: 1148.12 ✓

DIP TESTS:	DEPTH	DIP	AZIMUTH
	30.50	62.00	34.00
	61.00	64.00	33.00
	91.50	68.00	21.00
	122.00	72.00	7.00

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	3.00	1.83 ✓	3.55 ✓	36.34 ✓
3.00	6.10	1.80 ✓	3.10 ✓	40.26 ✓
6.10	9.10	1.65 ✓	4.58 ✓	34.29 ✓
9.10	12.20	2.48 ✓	4.80 ✓	50.40 ✓
12.20	15.20	1.88 ✓	3.15 ✓	27.43 ✓
15.20	18.30	1.35 ✓	1.95 ✓	29.14 ✓
18.30	21.30	2.58 ✓	5.00 ✓	44.23 ✓
21.30	24.40	4.05 ✓	7.75 ✓	65.49 ✓
24.40	27.40	2.65 ✓	7.06 ✓	45.26 ✓
27.40	30.50	5.53 ✓	10.72 ✓	84.69 ✓
30.50	32.00	6.48 ✓	12.34 ✓	97.72 ✓
32.00	33.50	6.28 ✓	10.16 ✓	87.77 ✓
33.50	35.40	6.06 ✓	12.65 ✓	95.66 ✓
35.40	37.40	3.05 ✓	7.27 ✓	57.60 ✓
37.40	40.00	N/A	N/A	N/A
40.00	41.10	4.75 ✓	7.42 ✓	71.66 ✓
41.10	42.70	2.98 ✓	4.00 ✓	45.26 ✓
42.70	45.70	.83 ✓	1.63	14.06 ✓
45.70	47.20	.63 ✓	.73 ✓	18.17 ✓
47.20	48.80	1.13 ✓	1.85 ✓	23.31 ✓
48.80	50.30	2.83 ✓	4.65 ✓	42.51 ✓
50.30	51.80	4.95 ✓	7.55 ✓	74.74 ✓
51.80	54.90	3.60 ✓	7.72 ✓	52.46 ✓
54.90	57.90	2.50 ✓	4.65 ✓	45.26 ✓
57.90	62.50	N/A	N/A	N/A
62.50	65.50	2.68 ✓	4.55 ✓	40.46 ✓
65.50	67.10	3.55 ✓	6.55 ✓	48.34 ✓
67.10	68.70	2.40 ✓	5.64 ✓	39.43 ✓
68.70	69.70	N/A	N/A	N/A
69.70	71.20	2.95 ✓	5.38 ✓	45.26 ✓
71.20	94.10	N/A	N/A	N/A
94.10	96.00	2.20 ✓	3.50 ✓	44.23 ✓
96.00	97.50	2.30 ✓	3.80 ✓	43.20 ✓
97.50	99.10	1.85 ✓	4.10 ✓	35.31 ✓
99.10	100.60	2.10 ✓	3.08 ✓	39.43 ✓
100.60	102.10	2.55 ✓	4.10 ✓	48.34 ✓
102.10	103.50	4.28 ✓	10.82 ✓	96.69 ✓
103.50	105.00	3.75 ✓	7.72 ✓	83.66 ✓
105.00	106.60	4.35 ✓	10.67 ✓	91.89 ✓
106.60	109.30	1.25 ✓	4.00 ✓	25.37 ✓
109.30	115.30	N/A	N/A	N/A
115.30	116.90	1.90 ✓	5.40 ✓	36.34 ✓
116.90	150.90	N/A	N/A	N/A

HOLE NO: U-55 LATITUDE: 10826.03✓
HOLE LENGTH: 36.40 DEPARTURE: 7643.14✓
ELEVATION: 1145.06✓ AZIMUTH: 233.40✓
DIP: 27.00✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	36.40	N/A	N/A	N/A

SPEDIFLO MOORE BUSINESS FORMS 4

HOLE NO: U-56 LATITUDE: 10825.99✓ AZIMUTH: 223.41✓
 HOLE LENGTH: 61.00 DEPARTURE: 7643.19✓ DIP: 28.00✓
 ELEVATION: ~~146.13~~

INTERVAL		ASSAYS <i>N45.13✓</i>		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.80	N/A	N/A	N/A
1.80	3.00	1.38✓	1.73✓	21.26✓
3.00	4.50	.90✓	1.85✓	19.20✓
4.50	6.10	.40✓	1.90✓	10.97✓
6.10	7.60	.75✓	2.98✓	15.09✓
7.60	9.10	1.75✓	4.55✓	31.20✓
9.10	10.60	1.33✓	3.30✓	30.17✓
10.60	12.10	1.35✓	3.53✓	26.40✓
12.10	13.70	1.38✓	4.20✓	30.17✓
13.70	15.20	1.48✓	3.73✓	29.14✓
15.20	16.70	1.15✓	2.68✓	25.37✓
16.70	18.20	2.43✓	4.85✓	46.29✓
18.20	19.80	1.78✓	3.53✓	32.23✓
19.80	21.30	3.23✓	3.75✓	32.23✓
21.30	45.00	N/A	N/A	N/A
45.00	47.20	2.30✓	3.60✓	37.37✓
47.20	48.70	.80✓	1.55✓	20.23✓
48.70	50.20	.90✓	1.28✓	15.09✓
50.20	51.80	1.62✓	.88✓	18.17✓
51.80	53.30	4.25✓	4.35✓	49.37✓
53.30	54.80	3.60✓	7.77✓	41.49✓
54.80	56.30	3.00✓	5.84✓	37.37✓
56.30	61.00	N/A	N/A	N/A

SPECIAL ORDER BUSINESS FORMS 4

DIAMOND DRILL LOG MA

STER FILE

HOLE NO: U-57
 HOLE LENGTH: 53.30

LATITUDE: 10825.90
 DEPARTURE: 7643.08
 ELEVATION: 1143.83

AZIMUTH: 220.16
 DIP: -28.00

-28.12

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	1.70 ✓	4.35 ✓	39.43 ✓
1.50	3.00	2.40 ✓	3.85 ✓	43.54 ✓
3.00	4.50	.70 ✓	2.15 ✓	14.06 ✓
4.50	6.00	1.55 ✓	3.70 ✓	29.14 ✓
6.00	7.60	1.33 ✓	3.58 ✓	23.31 ✓
7.60	9.10	1.33 ✓	4.20 ✓	26.40 ✓
9.10	13.70	1.98 ✓	4.03 ✓	29.14 ✓
13.70	15.20	1.25 ✓	3.78 ✓	20.23 ✓
15.20	16.70	2.40 ✓	5.70 ✓	40.46 ✓
16.70	18.20	2.10 ✓	7.82 ✓	35.31 ✓
18.20	19.80	2.68 ✓	6.15 ✓	42.51 ✓
19.80	21.30	2.33 ✓	5.00 ✓	36.34 ✓
21.30	22.80	2.75 ✓	4.70 ✓	38.40 ✓
22.80	24.30	2.23 ✓	4.15 ✓	29.14 ✓
24.30	25.90	1.15 ✓	3.18 ✓	15.09 ✓
25.90	27.40	N/A	N/A	N/A
27.40	28.90	3.20 ✓	5.60 ✓	50.40 ✓
28.90	30.00	1.35 ✓	3.40 ✓	19.20 ✓
30.00	32.00	3.45 ✓	5.54 ✓	45.26 ✓
32.00	33.50	1.73 ✓	3.98 ✓	24.34 ✓
33.50	45.70	N/A	N/A	N/A
45.70	47.20	.50 ✓	1.05 ✓	8.23 ✓
47.20	48.70	.78 ✓	.55 ✓	13.03 ✓
48.70	50.30	N/A	N/A	N/A
50.30	51.80	.53 ✓	.50 ✓	9.94 ✓
51.80	53.30	.63 ✓	.55 ✓	13.03 ✓

HOLE NO: U-58 LATITUDE: 10797.87✓ AZIMUTH: 223.41✓
 HOLE LENGTH: 106.60 DEPARTURE: 7534.52✓ DIP: 1.40✓
 ELEVATION: 1136.29✓

DIP TESTS:	DEPTH	DIP	AZIMUTH
	76.20	-2.00	230.00
	107.00	-2.00	227.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.50	3.45✓	3.65✓	50.40✓
1.50	3.00	2.38✓	2.60✓	36.34✓
3.00	4.50	7.42✓	11.57✓	85.72✓
4.50	6.00	7.10✓	9.41✓	104.92✓
6.00	7.60	7.30✓	12.68✓	155.32✓
7.60	9.10	8.33✓	13.80✓	111.09✓
9.10	10.60	.85✓	1.25✓	16.11✓
10.60	12.10	1.83✓	2.70✓	31.20✓
12.10	13.70	2.23✓	4.10✓	40.46✓
13.70	15.20	4.98✓	10.85✓	77.83✓
15.20	16.70	6.62✓	15.67✓	98.74✓
16.70	19.00	6.12✓	15.12✓	90.86✓
19.00	86.80	N/A	N/A	N/A
86.80	88.30	5.05✓	2.44✓	57.60✓
88.30	89.90	5.00✓	3.05✓	60.34✓
89.90	91.40	.33✓	.13✓	20.23✓
91.40	93.00	.48✓	.33✓	17.14✓
93.00	94.50	5.15✓	5.05✓	80.57✓
94.50	96.00	2.03✓	.85✓	49.37✓
96.00	97.50	5.00✓	1.83✓	88.00✓
97.50	99.00	2.53✓	2.75✓	41.49✓
99.00	100.50	3.50✓	4.10✓	47.31✓
100.50	106.60	N/A	N/A	N/A

DIAMOND DRILL LOG MA

STER FILE

HOLE NO: U-59

LATITUDE: 10798.16 ✓

AZIMUTH: 227.06 ✓

HOLE LENGTH: 127.20

DEPARTURE: 7534.89 ✓

DIP: -45.22 ✓

ELEVATION: 1135.44 ✓

DIP TESTS:	DEPTH	DIP	AZIMUTH
	30.40	-47.00	228.00
	61.00	-47.00	229.00
	91.40	-57.00	238.00
	121.90	-62.00	241.00

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	3.80 ✓	8.22 ✓	55.54 ✓
1.50	3.00	4.43 ✓	10.12 ✓	66.51 ✓
3.00	4.50	2.70 ✓	4.60 ✓	40.46 ✓
4.50	6.10	4.98 ✓	9.08 ✓	69.60 ✓
6.10	7.60	4.25 ✓	8.60 ✓	60.34 ✓
7.60	9.10	5.70 ✓	10.65 ✓	76.80 ✓
9.10	10.60	8.73 ✓	17.15 ✓	137.14 ✓
10.60	12.10	11.26 ✓	19.08 ✓	163.54 ✓
12.10	13.60	9.63 ✓	15.98 ✓	149.14 ✓
13.60	15.10	10.33 ✓	18.33 ✓	153.26 ✓
15.10	16.50	13.29 ✓	18.52 ✓	197.83 ✓
16.50	18.00	5.49 ✓	6.90 ✓	76.80 ✓
18.00	19.50	13.20 ✓	15.37 ✓	163.54 ✓
19.50	21.00	11.09 ✓	18.22 ✓	153.26 ✓
21.00	22.50	7.20 ✓	9.84 ✓	121.03 ✓
22.50	24.00	7.25 ✓	10.55 ✓	113.14 ✓
24.00	25.50	8.00 ✓	10.96 ✓	129.26 ✓
25.50	27.00	7.15 ✓	10.20 ✓	114.86 ✓
27.00	28.50	7.20 ✓	10.30 ✓	123.09 ✓
28.50	30.00	7.00 ✓	9.90 ✓	123.09 ✓
30.00	31.50	9.20 ✓	12.28 ✓	139.20 ✓
31.50	33.00	7.60 ✓	10.15 ✓	111.09 ✓
33.00	34.50	10.95 ✓	13.95 ✓	151.20 ✓
34.50	36.00	9.50 ✓	13.39 ✓	143.32 ✓
36.00	37.50	7.20 ✓	10.00 ✓	104.92 ✓
37.50	39.00	7.10 ✓	10.45 ✓	100.80 ✓
39.00	40.50	7.70 ✓	10.96 ✓	96.69 ✓
40.50	42.60	6.80 ✓	9.79 ✓	109.03 ✓
42.60	44.20	6.90 ✓	10.60 ✓	104.92 ✓
44.20	45.70	6.92 ✓	12.53 ✓	127.20 ✓
45.70	47.20	8.85 ✓	12.29 ✓	163.54 ✓
47.20	48.70	9.08 ✓	17.70 ✓	139.20 ✓
48.70	50.30	8.53 ✓	13.55 ✓	121.03 ✓
50.30	51.80	1.28 ✓	.43 ✓	25.37 ✓
51.80	53.30	.28 ✓	.53 ✓	12.00 ✓
53.30	54.80	5.82 ✓	8.73 ✓	98.74 ✓
54.80	102.10	N/A ✓	N/A ✓	N/A ✓
102.10	103.60	2.00 ✓	2.38 ✓	27.43 ✓
103.60	105.10	2.40 ✓	2.60 ✓	32.23 ✓
105.10	106.60	.23 ✓	.54 ✓	8.23 ✓
106.60	108.20	.10 ✓	.25 ✓	6.17 ✓
108.20	109.70	.38 ✓	.45 ✓	8.91 ✓
109.70	110.50	1.38 ✓	1.30 ✓	19.20 ✓
110.50	127.20	N/A ✓	N/A ✓	N/A ✓

HOLE NO: U-59

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON

HOLE NO: U-60
 HOLE LENGTH: 122.00

LATITUDE: 10799.37 ✓
 DEPARTURE: 7535.89 ✓
 ELEVATION: 1134.97 ✓

AZIMUTH: 0.00
 DIP: -90.00

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	3.20✓	3.75✓	37.37✓
1.50	3.00	3.90✓	4.95✓	34.29✓
3.00	4.50	2.73✓	4.70✓	29.14✓
4.50	6.10	3.03✓	2.85✓	31.20✓
6.10	7.60	4.08✓	3.70✓	44.23✓
7.60	9.10	2.05✓	3.75✓	27.43✓
9.10	10.60	.43✓	1.58✓	7.20✓
10.60	12.20	3.40✓	4.05✓	40.46✓
12.20	13.70	1.75✓	1.75✓	23.31✓
13.70	15.20	1.10✓	.88✓	17.14✓
15.20	16.70	1.50✓	1.48✓	23.31✓
16.70	18.20	1.63✓	2.13✓	28.46✓
18.20	19.80	.88✓	1.25✓	20.23✓
19.80	21.30	1.25✓	1.50✓	24.34✓
21.30	22.80	1.05✓	1.35✓	20.23✓
22.80	24.40	2.05✓	3.75✓	35.31✓
24.40	26.00	2.08✓	2.05✓	32.23✓
26.00	27.40	3.33✓	4.40✓	47.31✓
27.40	28.90	.35✓	1.40✓	14.06✓
28.90	30.00	4.58✓	7.21✓	68.57✓
30.00	32.00	4.55✓	4.45✓	63.43✓
32.00	33.50	6.10✓	8.46✓	89.83✓
33.50	35.00	4.08✓	5.55✓	70.63✓
35.00	42.60	N/A	N/A	N/A
42.60	44.10	3.85✓	4.90✓	55.54✓
44.10	56.30	N/A	N/A	N/A
56.30	57.90	1.28✓	2.10	39.43✓
57.90	59.40	.45✓	.80	9.94✓
59.40	61.00	7.20✓	13.64✓	114.86✓
61.00	62.50	4.88✓	8.49✓	74.74✓
62.50	105.10	N/A	N/A	N/A
105.10	106.60	5.80✓	8.90	90.86✓
106.60	108.20	3.05✓	5.00	51.43✓
108.20	109.70	4.53✓	6.85✓	76.80✓
109.70	111.20	1.13✓	2.78✓	26.40✓
111.20	112.70	2.80✓	4.20	48.34✓
112.70	122.00	N/A	N/A	N/A

SHEED TO MOORE BUSINESS FORMS 4

HOLE NO: U-61 LATITUDE: 10799.08 ✓
HOLE LENGTH: 120.30 DEPARTURE: 7535.68 ✓
ELEVATION: 1135.00 ✓ AZIMUTH: 224.00 ✓
DIP: -70.00 ✓

DIP TESTS: DEPTH DIP AZIMUTH
 45.72 -73.00 231.00
 91.44 -79.00 232.00
 120.30 -81.00 232.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.50	4.88 ✓	8.08 ✓	80.57 ✓
1.50	3.00	3.78 ✓	5.55 ✓	38.40 ✓
3.00	4.50	2.83 ✓	4.10 ✓	30.17 ✓
4.50	6.10	3.40 ✓	4.45 ✓	38.40 ✓
6.10	7.60	4.13 ✓	5.25 ✓	53.49 ✓
7.60	9.10	4.08 ✓	5.35 ✓	70.63 ✓
9.10	10.60	.83 ✓	1.10 ✓	26.40 ✓
10.60	12.10	.10 ✓	.45 ✓	12.00 ✓
12.10	13.70	.90 ✓	.95 ✓	38.40 ✓
13.70	15.20	.75 ✓	1.23 ✓	22.29 ✓
15.20	16.70	2.04 ✓	3.55 ✓	43.54 ✓
16.70	18.20	.58 ✓	.63 ✓	26.40 ✓
18.20	19.80	.10 ✓	.33 ✓	12.00 ✓
19.80	21.30	.20 ✓	.58 ✓	16.11 ✓
21.30	22.80	.08 ✓	.19 ✓	8.91 ✓
22.80	24.30	.12 ✓	.17 ✓	9.94 ✓
24.30	25.90	7.17 ✓	7.16 ✓	109.03 ✓
25.90	27.40	11.16 ✓	8.41 ✓	161.49 ✓
27.40	28.90	9.63 ✓	5.10 ✓	147.09 ✓
28.90	30.00	1.23 ✓	.51 ✓	31.20 ✓
30.00	32.00	7.27 ✓	8.79 ✓	90.86 ✓
32.00	33.50	2.83 ✓	4.00 ✓	50.40 ✓
33.50	54.80	N/A	N/A	N/A
54.80	56.30	1.75 ✓	2.40 ✓	30.17 ✓
56.30	59.40	N/A	N/A	N/A
59.40	60.90	5.80 ✓	9.41 ✓	94.63 ✓
60.90	86.80	N/A	N/A	N/A
86.80	88.30	1.70 ✓	2.03 ✓	27.43 ✓
88.30	89.90	1.80 ✓	2.03 ✓	35.31 ✓
89.90	91.40	2.78 ✓	2.85 ✓	40.56 ✓
91.40	92.90	1.28 ✓	1.80 ✓	24.34 ✓
92.90	94.40	.25 ✓	.48 ✓	8.91 ✓
94.40	96.00	.40 ✓	.16 ✓	8.23 ✓
96.00	111.20	N/A	N/A	N/A
111.20	112.70	4.03 ✓	6.82 ✓	70.63 ✓
112.70	114.30	8.43 ✓	17.14 ✓	129.26 ✓
114.30	115.80	4.80 ✓	9.69 ✓	72.69 ✓
115.80	120.30	N/A	N/A	N/A

40.46

HOLE NO: U-62 LATITUDE: 10798.09 ✓
 HOLE LENGTH: 109.70 DEPARTURE: 7534.80 ✓
 ELEVATION: 1135.60 ✓

AZIMUTH: 222.17 ✓
 DIP: -21.00 ✓

-20.57

DIP TESTS:	DEPTH	DIP	AZIMUTH
	30.48	-24.00	223.00
	60.96	-31.00	233.00
	100.58	-35.00	222.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.50	7.27 ✓	9.25 ✓	106.97 ✓
1.50	3.00	6.40 ✓	5.60 ✓	96.69 ✓
3.00	4.50	4.50 ✓	4.35 ✓	65.49 ✓
4.50	6.00	3.70 ✓	4.00 ✓	63.43 ✓
6.00	7.10	6.72 ✓	9.23 ✓	130.97 ✓
7.10	9.10	6.00 ✓	8.00 ✓	137.14 ✓
9.10	10.60	4.63 ✓	7.26 ✓	101.83 ✓
10.60	12.10	6.90 ✓	12.57 ✓	116.92 ✓
12.10	13.70	5.25 ✓	9.58 ✓	76.80 ✓
13.70	89.90	N/A	N/A	N/A
89.90	91.40	4.30 ✓	6.55 ✓	85.72 ✓
91.40	92.90	5.85 ✓	8.79 ✓	109.03 ✓
92.90	94.40	6.60 ✓	8.94 ✓	118.97 ✓
94.40	96.00	5.50 ✓	9.19 ✓	116.92 ✓
96.00	97.50	4.00 ✓	5.95 ✓	76.80 ✓
97.50	109.70	N/A	N/A	N/A

8.90

HOLE NO: U-63
 HOLE LENGTH: 106.60

LATITUDE: 10798.01 ✓
 DEPARTURE: 7534.77 ✓
 ELEVATION: 1137.45 ✓

AZIMUTH: 222.14 ✓
 DIP: 32.30 ✓
 130.32

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	8.50 ✓	14.87 ✓	96.69 ✓
1.50	3.00	7.60 ✓	10.27 ✓	88.80 ✓
3.00	4.50	5.97 ✓	8.48 ✓	135.09 ✓
4.50	6.00	5.79 ✓	10.58 ✓	121.03 ✓
6.00	7.60	6.25 ✓	11.70 ✓	104.92 ✓
7.60	9.10	7.77 ✓	12.73 ✓	100.80 ✓
9.10	10.60	6.65 ✓	20.48 ✓	80.57 ✓
10.60	12.10	3.30 ✓	14.21 ✓	48.34 ✓
12.10	39.60	N/A	N/A	N/A
39.60	41.10	7.92 ✓	4.10 ✓	70.63 ✓
41.10	42.60	7.10 ✓	3.90 ✓	68.57 ✓
42.60	56.30	N/A	N/A	N/A
56.30	57.90	3.88 ✓	4.35 ✓	54.51 ✓
57.90	59.40	3.15 ✓	2.60 ✓	47.31 ✓
59.40	60.90	4.70 ✓	6.42 ✓	71.66 ✓
60.90	62.40	7.30 ✓	8.18 ✓	113.14 ✓
62.40	64.00	15.00 ✓	12.57 ✓	221.83 ✓
64.00	106.60	N/A	N/A	N/A

SPEER/LO MOORE BUSINESS FORMS 4

HOLE NO: U-64 LATITUDE: 10799.51
 HOLE LENGTH: 57.90 DEPARTURE: 7537.07
 ELEVATION: 1138.80 AZIMUTH: 221.23
 DIP: 63.50

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	4.23 ✓	8.23 ✓	54.51 ✓
1.50	3.00	9.00 ✓	13.85 ✓	109.03 ✓
3.00	4.50	6.40 ✓	9.41 ✓	114.86 ✓
4.50	6.00	7.05 ✓	9.92 ✓	153.26 ✓
6.00	7.60	6.45 ✓	9.77 ✓	129.26 ✓
7.60	9.10	7.40 ✓	11.75 ✓	137.14 ✓
9.10	10.60	9.56 ✓	15.49 ✓	147.09 ✓
10.60	12.10	5.30 ✓	4.60 ✓	86.74 ✓
12.10	13.70	6.07 ✓	8.33 ✓	90.86 ✓
13.70	15.20	2.68 ✓	5.40 ✓	41.49 ✓
15.20	16.70	5.65 ✓	10.10 ✓	118.97 ✓
16.70	38.10	N/A	N/A	N/A
38.10	39.60	9.41 ✓	7.26 ✓	100.80 ✓
39.60	41.10	4.78 ✓	4.70 ✓	50.40 ✓
41.10	57.90	N/A	N/A	N/A

SPECIAL TO MOORE BUSINESS FORMS 4

HOLE NO: U-65
 HOLE LENGTH: 59.40

LATITUDE: 10799.57✓
 DEPARTURE: 7535.98✓
 ELEVATION: 1139.03✓

AZIMUTH: ~~339.16~~✓
 DIP: 88.09✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	4.23✓	8.84✓	63.43-
1.50	3.00	7.69✓	11.06✓	91.89-
3.00	4.50	8.33✓	12.65✓	146.06-
4.50	6.00	6.49✓	8.98✓	121.03-
6.00	7.60	6.10✓	10.05✓	111.09-
7.60	9.10	8.55✓	14.59✓	161.49-
9.10	10.60	8.65✓	14.69✓	169.37-
10.60	12.10	8.43✓	14.38✓	117.94-
12.10	13.70	4.85✓	12.80✓	87.77✓
13.70	15.20	4.58✓	10.20✓	79.20-
15.20	16.70	4.38✓	4.70✓	75.77✓
16.70	18.20	10.55✓	16.57✓	161.49✓
18.20	19.80	8.63✓	12.13✓	126.17✓
19.80	21.30	1.30✓	2.23✓	14.06✓
21.30	42.60	N/A	N/A	N/A
42.60	44.10	3.45✓	2.95✓	45.26✓
44.10	45.70	14.33✓	11.98✓	179.66✓
45.70	47.20	15.28✓	8.98✓	188.57✓
47.20	48.70	15.53	11.47✓	157.37✓
48.70	50.20	4.95✓	3.70✓	70.63✓
50.20	59.40	N/A	N/A	N/A

12.53

SPEER LTD MOORE BUSINESS FORMS 4

HOLE NO: U-66 LATITUDE: 10797.70 ✓
 HOLE LENGTH: 99.00 DEPARTURE: 7536.37 ✓
 ELEVATION: 1136.90 ✓

AZIMUTH: 176.26 ✓
 DIP: 23.00 ✓
~~185.34~~
~~22.57~~

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	10.12 ✓	13.52 ✓	143.32 ✓
1.50	3.00	8.17 ✓	15.09 ✓	108.00 ✓
3.00	4.50	5.51 ✓	10.89 ✓	84.69 ✓
4.50	6.00	4.28 ✓	8.52 ✓	50.40 ✓
6.00	7.60	7.00 ✓	10.20 ✓	77.83 ✓
7.60	9.10	6.80 ✓	9.44 ✓	129.26 ✓
9.10	10.60	5.90 ✓	9.54 ✓	126.17 ✓
10.60	12.10	5.20 ✓	8.95 ✓	94.63 ✓
12.10	13.70	3.58 ✓	8.06 ✓	73.71 ✓
13.70	15.20	5.44 ✓	8.93 ✓	89.83 ✓
15.20	16.70	3.55 ✓	6.17 ✓	64.46 ✓
16.70	18.20	3.88 ✓	4.20 ✓	56.57 ✓
18.20	19.80	2.75 ✓	1.40 ✓	34.29 ✓
19.80	21.30	8.77 ✓	13.21 ✓	101.83 ✓
21.30	22.80	7.59 ✓	14.69 ✓	111.09 ✓
22.80	24.30	7.25 ✓	14.25 ✓	98.74 ✓
24.30	25.90	5.59 ✓	21.24 ✓	69.60 ✓
25.90	39.20	N/A	N/A	N/A
39.20	41.10	4.68 ✓	3.10 ✓	56.57 ✓
41.10	42.60	1.33 ✓	1.05 ✓	21.26 ✓
42.60	44.10	1.43 ✓	1.13 ✓	19.20 ✓
44.10	45.70	1.20 ✓	.98 ✓	14.06 ✓
45.70	47.20	N/A	N/A	N/A
47.20	48.70	2.35 ✓	1.68 ✓	30.17 ✓
48.70	71.60	N/A	N/A	N/A
71.60	73.10	2.53 ✓	.53 ✓	45.26 ✓
73.10	74.60	3.98 ✓	4.85 ✓	60.34 ✓
74.60	76.20	2.08 ✓	1.55 ✓	37.37 ✓
76.20	77.70	6.70 ✓	5.64 ✓	111.09 ✓
77.70	79.20	5.80 ✓	7.10 ✓	84.69 ✓
79.20	80.70	6.55 ✓	8.07 ✓	80.57 ✓
80.70	82.20	9.33 ✓	10.08 ✓	138.17 ✓
82.20	83.80	2.70 ✓	1.55 ✓	37.37 ✓
83.80	85.30	1.80 ✓	1.00 ✓	26.40 ✓
85.30	86.80	4.18 ✓	3.45 ✓	72.69 ✓
86.80	88.30	4.50 ✓	3.80 ✓	54.51 ✓
88.30	89.90	5.75 ✓	7.45 ✓	73.71 ✓
89.90	91.40	6.10 ✓	8.78 ✓	100.80 ✓
91.40	92.90	6.80 ✓	7.72 ✓	98.74 ✓
92.90	94.40	2.48 ✓	2.35 ✓	35.31 ✓
94.40	96.00	5.25 ✓	6.21 ✓	79.54 ✓
96.00	97.50	5.90 ✓	8.02 ✓	100.80 ✓
97.50	99.00	6.20 ✓	8.88 ✓	105.94 ✓

SPEIDT LO MOORE BUSINESS FORMS 4

HOLE NO: U-67
 HOLE LENGTH: 76.20

LATITUDE: 10842.75 ✓
 DEPARTURE: 7493.68 ✓
 ELEVATION: 1126.59 ✓

AZIMUTH: 225.28 ✓
 DIP: ~~1.00~~ ✓

0.53 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	1.33 ✓	.95 ✓	20.23 ✓
1.50	3.00	3.23 ✓	2.50 ✓	36.34 ✓
3.00	4.50	.95 ✓	.40 ✓	14.00 ✓
4.50	6.00	3.93 ✓	4.40 ✓	40.46 ✓
6.00	7.60	2.68 ✓	4.95 ✓	33.26 ✓
7.60	9.10	3.30 ✓	3.90 ✓	42.51 ✓
9.10	10.60	2.78 ✓	4.00 ✓	32.23 ✓
10.60	12.10	.79 ✓	2.05 ✓	18.17 ✓
12.10	13.70	.78 ✓	1.70 ✓	15.09 ✓
13.70	15.20	2.30 ✓	2.75 ✓	39.43 ✓
15.20	16.70	2.68 ✓	5.82 ✓	42.51 ✓
16.70	18.20	4.93 ✓	10.11 ✓	67.54 ✓
18.20	19.80	9.45 ✓	13.79 ✓	128.23 ✓
19.80	21.30	10.51 ✓	13.81 ✓	100.80 ✓
21.30	22.80	8.20 ✓	12.82 ✓	114.17 ✓
22.80	24.30	2.23 ✓	5.00 ✓	41.49 ✓
24.30	25.90	3.43 ✓	8.12 ✓	65.49 ✓
25.90	27.40	6.12 ✓	13.01 ✓	100.80 ✓
27.40	28.90	2.63 ✓	17.20 ✓	36.34 ✓
28.90	30.40	5.40 ✓	21.54 ✓	58.63 ✓
30.40	32.00	5.50 ✓	22.72 ✓	67.54 ✓
32.00	33.50	5.95 ✓	22.18 ✓	80.57 ✓
33.50	35.00	5.15 ✓	17.52 ✓	121.03 ✓
35.00	36.50	2.50 ✓	5.00 ✓	50.40 ✓
36.50	76.20	N/A	N/A	N/A

14.06

HOLE NO: U-68
HOLE LENGTH: 53.30

LATITUDE: 10841.81 ✓
DEPARTURE: 7493.52 ✓
ELEVATION: 1127.79 ✓

AZIMUTH: 223.26 ✓
DIP: 33.00 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	.58 ✓	.53 ✓	12.00 ✓
1.50	3.00	1.00 ✓	.53 ✓	20.23 ✓
3.00	4.50	2.28 ✓	1.23 ✓	28.46 ✓
4.50	6.00	2.35 ✓	1.00 ✓	26.40 ✓
6.00	7.60	3.05 ✓	4.95 ✓	33.26 ✓
7.60	9.10	2.13 ✓	4.73 ✓	32.23 ✓
9.10	10.60	3.55 ✓	5.83 ✓	50.50 ✓
10.60	12.10	8.20 ✓	14.72 ✓	113.14 ✓
12.10	13.70	8.93 ✓	15.43 ✓	166.29 ✓
13.70	15.20	10.48 ✓	19.44 ✓	133.03 ✓
15.20	16.70	7.92 ✓	14.84 ✓	132.00 ✓
16.70	18.20	3.78 ✓	9.33 ✓	74.74 ✓
18.20	19.80	6.77 ✓	13.09 ✓	105.94 ✓
19.80	21.30	3.18 ✓	3.10 ✓	49.37 ✓
21.30	22.80	3.20 ✓	4.35 ✓	52.46 ✓
22.80	53.30	N/A	N/A	N/A

50.40

HOLE NO: U-69
HOLE LENGTH: 38.10

LATITUDE: 10843.02 ✓
DEPARTURE: 7494.45 ✓
ELEVATION: 1130.21 ✓

AZIMUTH: 226.53 ✓
DIP: 60.00 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	.31 ✓	.48 ✓	7.20 ✓
1.50	3.00	2.32 ✓	1.65 ✓	30.17 ✓
3.00	4.50	2.55 ✓	3.58 ✓	28.46 ✓
4.50	6.00	2.08 ✓	3.78 ✓	34.29 ✓
6.00	7.60	4.25 ✓	6.62 ✓	66.51 ✓
7.60	9.10	9.15 ✓	16.71 ✓	130.97 ✓
9.10	10.60	6.99 ✓	12.62 ✓	146.06 ✓
10.60	12.10	5.20 ✓	10.33 ✓	74.74 ✓
12.10	13.70	2.20 ✓	4.58 ✓	36.34 ✓
13.70	15.20	2.58 ✓	5.16 ✓	40.46 ✓
15.20	16.70	4.08 ✓	10.07 ✓	65.49 ✓
16.70	18.20	5.30 ✓	12.06 ✓	87.77 ✓
18.20	19.80	5.73 ✓	12.93 ✓	90.86 ✓
19.80	21.30	5.68 ✓	10.22 ✓	86.74 ✓
21.30	22.80	6.74 ✓	13.40 ✓	110.06 ✓
22.80	24.30	6.04 ✓	8.82 ✓	98.81 ✓
24.30	25.90	6.84 ✓	12.93 ✓	140.23 ✓
25.90	38.10	N/A	N/A	N/A

HOLE NO: U-70
 HOLE LENGTH: 39.60

LATITUDE: 10844.05 ✓
 DEPARTURE: 7495.38 ✓
 ELEVATION: 1130.00 ✓

AZIMUTH: 14.08 ✓
 DIP: 85.45 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	.95 ✓	.48 ✓	16.11 ✓
1.50	3.00	1.00 ✓	1.48 ✓	16.11 ✓
3.00	4.50	3.05 ✓	2.85 ✓	37.37 ✓
4.50	6.10	1.48 ✓	2.85 ✓	28.46 ✓
6.10	7.60	4.90 ✓	6.80 ✓	65.49 ✓
7.60	9.10	7.79 ✓	10.69 ✓	103.89 ✓
9.10	10.60	10.75 ✓	16.19 ✓	149.14 ✓
10.60	12.10	9.00 ✓	18.27 ✓	114.17 ✓
12.10	13.70	12.10 ✓	21.36 ✓	<u>152.26</u>
13.70	15.20	9.38 ✓	16.56 ✓	123.09 ✓
15.20	16.70	9.12 ✓	17.94 ✓	163.20 ✓
16.70	18.20	.13 ✓	1.65 ✓	2.06 ✓
18.20	19.80	.88 ✓	2.08 ✓	15.09 ✓
19.80	21.30	4.20 ✓	8.04 ✓	68.57 ✓
21.30	22.80	6.05 ✓	8.18 ✓	91.89 ✓
22.80	24.30	7.14 ✓	14.11 ✓	126.17 ✓
24.30	25.90	3.40 ✓	8.40 ✓	81.60 ✓
25.90	39.60	N/A	N/A	N/A

153.26

HOLE NO: U-71 LATITUDE: 10844.37✓
HOLE LENGTH: 45.70 DEPARTURE: 7495.55✓
ELEVATION: 1129.90 AZIMUTH: 41.39✓
DIP: 65.00✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	.33✓	.19✓	7.20✓
1.50	3.00	2.50✓	1.50✓	32.23✓
3.00	4.50	3.75✓	4.35✓	44.23✓
4.50	6.00	1.28	2.80✓	20.23✓
6.00	7.60	2.45✓	4.45✓	40.46✓
7.60	9.10	1.98✓	3.80✓	31.20✓
9.10	10.60	6.47	11.66✓	82.63✓
10.60	12.10	15.03✓	23.74✓	223.89✓
12.10	13.70	4.95✓	11.00✓	72.69✓
13.70	15.20	1.73✓	3.80✓	27.43✓
15.20	16.70	2.63✓	5.96✓	36.34✓
16.70	18.20	4.18✓	9.32✓	59.31✓
18.20	19.80	4.37✓	8.76✓	74.74✓
19.80	21.30	4.42✓	12.28✓	66.51✓
21.30	22.80	6.14✓	13.10✓	94.63✓
22.80	24.30	7.94✓	11.97✓	114.17✓
24.30	25.90	3.58✓	6.93✓	45.26✓
25.90	45.70	N/A	N/A	N/A

6.74

HOLE NO: U-72 LATITUDE: 10842.74 ✓
HOLE LENGTH: 137.30 DEPARTURE: 7494.99 ✓
ELEVATION: 1124.62 ✓ AZIMUTH: 224.08 ✓
DIP: -56.15 ✓

DIP TESTS: DEPTH DIP AZIMUTH
45.72 -71.00 224.08
112.70 -82.00 224.08

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.50	2.08 ✓	1.32 ✓	22.29 ✓
1.50	3.00	2.50 ✓	1.00 ✓	25.37 ✓
3.00	4.50	3.00 ✓	1.44 ✓	38.40 ✓
4.50	6.10	2.10 ✓	.66 ✓	29.14 ✓
6.10	7.60	1.25 ✓	.52 ✓	16.11 ✓
7.60	9.10	1.15 ✓	.78 ✓	17.14 ✓
9.10	10.60	.60 ✓	.39 ✓	10.97 ✓
10.60	12.10	.58 ✓	.70 ✓	9.94 ✓
12.10	13.70	.31 ✓	.45 ✓	4.11 ✓
13.70	15.20	.35 ✓	.67 ✓	6.17 ✓
15.20	16.70	.44 ✓	.63 ✓	5.14 ✓
16.70	18.20	.27 ✓	.54 ✓	6.17 ✓
18.20	19.80	.27 ✓	.45 ✓	5.14 ✓
19.80	21.30	1.50 ✓	2.80 ✓	23.31 ✓
21.30	22.80	1.58 ✓	1.20 ✓	27.43 ✓
22.80	24.30	2.35 ✓	3.65 ✓	45.26 ✓
24.30	25.90	.79 ✓	1.15 ✓	26.40 ✓
25.90	27.40	2.50 ✓	3.94 ✓	33.26 ✓
27.40	28.90	1.27 ✓	1.92 ✓	23.31 ✓
28.90	30.40	5.81 ✓	7.71 ✓	74.74 ✓
30.40	40.80	N/A	N/A	N/A
40.80	42.70	1.40 ✓	2.25 ✓	29.14 ✓
42.70	63.70	N/A	N/A	N/A
63.70	65.50	3.05 ✓	5.05 ✓	60.34 ✓
65.50	103.00	N/A	N/A	N/A
103.00	105.10	1.74 ✓	2.25 ✓	28.46 ✓
105.10	106.60	3.08 ✓	3.00 ✓	39.43 ✓
106.60	108.20	2.23 ✓	2.54 ✓	30.17 ✓
108.20	109.70	.70 ✓	.63 ✓	9.94 ✓
109.70	111.20	2.98 ✓	3.12 ✓	34.29 ✓
111.20	112.70	2.95 ✓	3.20 ✓	36.34 ✓
112.70	115.20	.25 ✓	.46 ✓	4.11 ✓
115.20	117.30	.64 ✓	1.35 ✓	9.94 ✓
117.30	118.80	.99 ✓	1.21 ✓	15.09
118.80	120.30	1.23 ✓	2.40 ✓	17.14 ✓
120.30	121.90	1.33 ✓	1.43 ✓	23.31 ✓
121.90	123.40	1.40 ✓	1.55 ✓	28.46 ✓
123.40	124.90	2.88 ✓	3.90 ✓	45.26 ✓
124.90	126.40	10.09 ✓	19.85 ✓	181.37 ✓
126.40	128.00	9.32 ✓	20.36 ✓	156.34 ✓
128.00	129.50	8.71 ✓	18.60 ✓	141.26 ✓
129.50	131.00	7.57 ✓	15.47 ✓	102.86 ✓
131.00	132.50	1.78 ✓	3.38 ✓	37.37 ✓
132.50	134.10	2.60 ✓	6.03 ✓	59.31 ✓
134.10	135.60	9.20 ✓	14.85 ✓	146.06 ✓
135.60	137.30	9.47 ✓	14.00 ✓	153.26 ✓

7.79

SPECIFIC MOORE BUSINESS FORMS 4

HOLE NO: U-72

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON

HOLE NO: U-73
 HOLE LENGTH: 121.90

LATITUDE: 10841.07 ✓
 DEPARTURE: 7494.76 ✓
 ELEVATION: 1126.00 ✓

AZIMUTH: 196.17 ✓
 DIP: 1.16 ✓

AT THE COLLAR

AZ: 194.17

DIP: 1.00

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	2.90	2.15 ✓	1.64 ✓	24.34 ✓
2.90	4.40	.66 ✓	.45 ✓	10.97 ✓
4.40	5.30	3.28 ✓	2.70 ✓	35.31 ✓
5.30	7.60	4.45 ✓	7.84 ✓	52.46 ✓
7.60	9.00	4.20 ✓	7.84 ✓	49.37 ✓
9.00	10.70	3.70 ✓	5.75 ✓	40.46 ✓
10.70	12.00	3.30 ✓	3.90 ✓	34.29 ✓
12.00	14.40	.60 ✓	.88 ✓	12.00 ✓
14.40	15.20	2.28 ✓	4.36 ✓	40.46 ✓
15.20	17.10	2.75 ✓	4.75 ✓	50.40 ✓
17.10	19.10	2.98 ✓	6.80 ✓	46.29 ✓
19.10	20.70	4.03 ✓	9.32 ✓	59.31 ✓
20.70	23.20	3.58 ✓	7.94 ✓	53.49 ✓
23.20	24.40	7.09 ✓	10.64 ✓	108.00 ✓
24.40	25.90	7.64 ✓	10.23 ✓	105.94 ✓
25.90	26.80	7.80 ✓	12.93 ✓	111.09 ✓
26.80	29.20	6.20 ✓	12.16 ✓	101.83 ✓
29.20	29.80	7.74 ✓	12.77 ✓	122.06 ✓
29.80	30.20	1.43 ✓	1.60 ✓	16.11 ✓
30.20	31.90	11.82 ✓	23.00 ✓	146.06 ✓
31.90	32.50	9.32 ✓	15.68 ✓	160.46 ✓
32.50	33.30	.26 ✓	.15 ✓	8.91 ✓
33.30	34.50	3.09 ✓	5.40 ✓	48.34 ✓
34.50	35.50	9.12 ✓	13.74 ✓	175.54 ✓
35.50	36.00	.16 ✓	.25 ✓	1.03 ✓
36.00	38.50	N/A	N/A	N/A
38.50	39.20	7.59 ✓	17.61 ✓	55.54 ✓
39.20	41.90	.78 ✓	1.62 ✓	12.00 ✓
41.90	121.90	N/A	N/A	N/A

SPECIAL O-MOUNT BUSINESS FORMS 4

HOLE NO: U-74 LATITUDE: ~~10602.79~~ ^{10599.37} AZIMUTH: 147.35 ✓
 HOLE LENGTH: 107.90 DEPARTURE: ~~7732.38~~ ^{7728.50} DIP: 8.30 ✓
 ELEVATION: ~~1174.98~~ ^{1174.77} ~~7729.05~~ ^{8.67}

DIP TESTS:	DEPTH	DIP	AZIMUTH
	45.70	3.00	149.00
	76.20	1.00	149.00
	106.70	-1.00	149.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	56.50	N/A	N/A	N/A
56.50	57.90	3.38 ✓	3.52 ✓	44.23 ✓
57.90	59.20	.85 ✓	1.40 ✓	13.03 ✓
59.20	60.50	3.33 ✓	5.40 ✓	35.31 ✓
60.50	61.60	1.72 ✓	1.85 ✓	23.31 ✓
61.60	67.90	N/A	N/A	N/A
67.90	69.30	.11 ✓	.68 ✓	10.97 ✓
69.30	70.60	.12 ✓	.45 ✓	8.91 ✓
70.60	71.90	.32 ✓	1.20 ✓	17.14 ✓
71.90	73.10	.07 ✓	1.15 ✓	6.17 ✓
73.10	74.50	.05 ✓	.73 ✓	8.23 ✓
74.50	75.70	.80 ✓	1.90 ✓	30.17 ✓
75.70	77.00	.49 ✓	1.73 ✓	23.31 ✓
77.00	78.60	.45 ✓	1.58 ✓	21.26 ✓
78.60	79.90	.48 ✓	1.40 ✓	16.11 ✓
79.90	81.50	.09 ✓	.60 ✓	10.97 ✓
81.50	82.80	.49 ✓	2.33 ✓	15.09 ✓
82.80	84.30	.08 ✓	.45 ✓	7.20 ✓
84.30	85.60	.07 ✓	.68 ✓	7.20 ✓
85.60	86.80	.10 ✓	.67 ✓	8.91 ✓
86.80	88.20	.08 ✓	.58 ✓	8.91 ✓
88.20	91.40	.50 ✓	.75 ✓	17.14 ✓
91.40	96.80	N/A	N/A	N/A
96.80	97.50	.62 ✓	1.00 ✓	28.46 ✓
97.50	103.10	N/A	N/A	N/A
103.10	104.50	1.67 ✓	2.28 ✓	26.40 ✓
104.50	105.90	2.25 ✓	2.78 ✓	34.29 ✓
105.90	107.90	N/A	N/A	N/A

HOLE NO: U-75 LATITUDE: 10843.47 ✓
HOLE LENGTH: 170.70 DEPARTURE: 7495.47 ✓
ELEVATION: 1124.59 ✓ AZIMUTH: 39.40 ✓
DIP: -75.25 ✓

DIP TESTS: DEPTH DIP AZIMUTH
60.96 -84.00 20.00
106.68 -86.00 302.00
152.40 -86.00 232.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	4.80	N/A	N/A	N/A
4.80	6.90	.75 ✓	1.10 ✓	10.97 ✓
6.90	8.50	2.10 ✓	1.82 ✓	24.34 ✓
8.50	12.10	N/A	N/A	N/A
12.10	13.40	2.93 ✓	1.64 ✓	31.20 ✓
13.40	22.20	N/A	N/A	N/A
22.20	24.60	.40 ✓	.64 ✓	7.20 ✓
24.60	26.30	N/A	N/A	N/A
26.30	29.00	1.30 ✓	.18 ✓	15.09 ✓
29.00	41.10	N/A	N/A	N/A
41.10	42.70	.55 ✓	1.12 ✓	13.03 ✓
42.70	48.70	N/A	N/A	N/A
48.70	50.90	2.03	2.26	32.23
50.90	53.70	.13	.33	10.97
53.70	55.20	5.20	8.30	85.72
55.20	56.70	5.15	8.20	105.94
56.70	57.60	2.35	.90	29.14
57.60	59.60	2.70	3.70	59.31
59.60	60.50	3.80	4.30	50.40
60.50	61.00	6.10	9.22	125.14
61.00	61.50	3.18	4.70	45.26
61.50	62.10	3.18	4.70	45.26
62.10	63.60	8.70	11.66	144.32
63.60	65.50	4.83	8.86	77.83
65.50	67.10	5.30	8.60	87.77
67.10	68.60	4.90	9.01	91.89
68.60	70.10	3.88	8.17	69.60
70.10	71.60	4.60	7.82	70.63
71.60	73.20	4.65	7.61	76.80
73.20	74.50	5.20	8.50	87.77
74.50	127.50	N/A	N/A	N/A
127.50	128.60	3.38	6.57	51.43
128.60	129.50	5.87	11.66	89.83
129.50	131.60	2.03	2.75	35.31
131.60	132.30	.13	.33	14.06
132.30	132.90	2.50	4.10	42.51
132.90	147.80	N/A	N/A	N/A
147.80	149.90	.83	.89	15.09
149.90	151.00	N/A	N/A	N/A
151.00	152.40	.92	.98	14.06
152.40	165.80	N/A	N/A	N/A
165.80	167.40	2.53	2.35	30.17
167.40	170.70	N/A	N/A	N/A

same sample

HOLE NO: U-76
 HOLE LENGTH: 65.50

LATITUDE: ~~10598.61~~ ^{DNA}
~~10602.15~~
 DEPARTURE: ~~7731.64~~ ^{7727.76}
 ELEVATION: 1175.06

AZIMUTH: 169.08
 DIP: 5.40

INTERVAL		ASSAYS			
FROM	TO	PB	ZN	AG	
		%	%	GM/TON	
0.00	18.30	N/A	N/A	N/A	LAT = 10,597.87
18.30	21.10	.30 ✓	1.20 ✓	8.91 ✓	DEP = 7728.26
21.10	27.40	N/A	N/A	N/A	EL = 1174.96
27.40	29.30	3.90 ✓	5.00 ✓	50.40 ✓	
29.30	30.50	5.15 ✓	7.05 ✓	83.66 ✓	
30.50	32.00	4.60 ✓	5.85 ✓	73.71 ✓	
32.00	32.80	6.92 ✓	10.21 ✓	86.74 ✓	
32.80	34.30	4.30 ✓	5.10 ✓	57.60 ✓	
34.30	36.40	12.04 ✓	12.77 ✓	183.43 ✓	
36.40	38.50	2.70 ✓	1.60 ✓	40.46 ✓	
38.50	41.10	1.95 ✓	1.15 ✓	32.23 ✓	
41.10	42.70	1.20 ✓	.25 ✓	20.23 ✓	
42.70	65.50	N/A	N/A	N/A	

HOLE NO: U-77 LATITUDE: 10844.45 ✓
HOLE LENGTH: 167.60 DEPARTURE: 7496.31 ✓
ELEVATION: 1124.89 ✓ AZIMUTH: 44.00 ✓
DIP: -55.37 ✓

DIP TESTS:	DEPTH	DIP	AZIMUTH
	30.48	-59.30	43.00
	60.96	-68.00	38.00
	96.01	-72.00	34.00
	167.60	-84.00	36.00

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.60	N/A	N/A	N/A
1.60	4.60	.98 ✓	1.00 ✓	9.94 ✓
4.60	12.20	N/A	N/A	N/A
12.20	13.70	2.55 ✓	4.00 ✓	30.17 ✓
13.70	65.60	N/A	N/A	N/A
65.60	68.60	1.21 ✓	1.60 ✓	21.26 ✓
68.60	70.10	1.88 ✓	2.50 ✓	25.37 ✓
70.10	71.60	.15 ✓	.60 ✓	24.34 ✓
71.60	73.20	5.75 ✓	10.05 ✓	101.83 ✓
73.20	74.70	7.80 ✓	14.42 ✓	105.94 ✓
74.70	76.20	1.53 ✓	1.60 ✓	30.17 ✓
76.20	77.70	.07 ✓	.27 ✓	8.23 ✓
77.70	79.20	.20 ✓	.75 ✓	9.94 ✓
79.20	80.80	.80 ✓	.55 ✓	24.34 ✓
80.80	82.30	.11 ✓	.41 ✓	5.14 ✓
82.30	83.80	5.83 ✓	8.62 ✓	97.72 ✓
83.80	85.30	2.70 ✓	3.75 ✓	44.23 ✓
85.30	88.40	1.05 ✓	1.45 ✓	13.03 ✓
88.40	90.00	N/A ✓	N/A ✓	N/A ✓
90.00	92.90	.65 ✓	.88 ✓	12.00 ✓
92.90	94.40	1.35 ✓	1.67 ✓	19.20 ✓
94.40	96.00	1.38 ✓	1.44 ✓	21.26 ✓
96.00	97.50	.55 ✓	.60 ✓	8.91 ✓
97.50	99.00	2.03 ✓	2.40 ✓	27.43 ✓
99.00	100.50	.83 ✓	1.25 ✓	12.00 ✓
100.50	102.50	2.23 ✓	4.20 ✓	31.20 ✓
102.50	103.60	4.90 ✓	7.70 ✓	81.60 ✓
103.60	105.10	6.29 ✓	7.52 ✓	63.43 ✓
105.10	106.60	4.98 ✓	6.73 ✓	93.94 ✓
106.60	108.20	4.73 ✓	1.90 ✓	90.85 ✓
108.20	123.00	N/A	N/A	N/A
123.00	125.20	6.06 ✓	6.63 ✓	78.86 ✓
125.20	132.60	N/A	N/A	N/A
132.60	134.10	4.18 ✓	6.89 ✓	66.51 ✓
134.10	135.60	2.20 ✓	4.25 ✓	34.29 ✓
135.60	137.10	2.98 ✓	2.90 ✓	43.54 ✓
137.10	138.60	5.46 ✓	5.71 ✓	63.43 ✓
138.60	140.20	6.96 ✓	9.94 ✓	87.77 ✓
140.20	141.70	1.23 ✓	2.78 ✓	15.09 ✓
141.70	143.20	.08 ✓	1.22 ✓	5.14 ✓
143.20	145.50	3.75 ✓	4.55 ✓	50.40 ✓
145.50	163.00	N/A .00	.00	.00
163.00	163.70	1.50 ✓	1.78 ✓	22.29 ✓
163.70	167.60	N/A	N/A	N/A

18/10/77 KERR ADDISON MINES LTD. - GRUM PROJECT
 DIAMOND DRILL LOG MASTER FILE

PAGE: 196

HOLE NO: U-78

LATITUDE: ~~10599.75~~ ^{10,598.95}

AZIMUTH: ~~135.49~~ ^{133.31}

DEPARTURE: ~~7790.10~~ ^{7729.10}

DIP: ~~8.50~~ ^{7.00}

ELEVATION: ~~1175.07~~ ^{1174.96} ~~7729.65~~ DJH

DIP TESTS:	DEPTH	DIP	AZIMUTH
	45.72	4.00	136.00
	76.20	2.00	136.00
	106.68	0.00	133.00

QUESTIONABLE

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TCN

0.00	38.10	N/A	N/A	N/A
38.10	39.60	.25 ✓	1.20 ✓	17.14 ✓
39.60	44.20	N/A	N/A	N/A
44.20	45.70	.05 ✓	1.00 ✓	9.94 ✓
45.70	50.30	N/A	N/A	N/A
50.30	51.80	.05 ✓	.62 ✓	5.14 ✓
51.80	56.10	N/A	N/A	N/A
56.10	57.60	.40 ✓	.42 ✓	26.40 ✓
57.60	64.00	N/A	N/A	N/A
64.00	65.50	.05 ✓	.25 ✓	4.11 ✓
65.50	70.10	N/A	N/A	N/A
70.10	71.60	.06 ✓	.37 ✓	9.94 ✓
71.60	77.70	N/A	N/A	N/A
77.70	79.20	.14 ✓	.75 ✓	8.23 ✓
79.20	83.80	N/A	N/A	N/A
83.80	85.30	.11 ✓	.55 ✓	18.17 ✓
85.30	89.90	N/A	N/A	N/A
89.90	91.40	.09 ✓	.25 ✓	9.94 ✓
91.40	94.90	N/A	N/A	N/A
94.90	96.50	1.73 ✓	2.20 ✓	28.46 ✓
96.50	97.80	.66 ✓	1.28 ✓	20.23 ✓
97.80	99.40	.13 ✓	.75 ✓	9.94 ✓
99.40	106.70	N/A	N/A	N/A

MOORE
 SPECIFIC 4

HOLE NO: U-79 LATITUDE: 10841.87 ✓
 HOLE LENGTH: 97.50 DEPARTURE: 7494.41 ✓
 ELEVATION: 1125.11 ✓ AZIMUTH: 218.23 ✓
 DIP: -29.51 ✓

DIP TESTS: DEPTH DIP AZIMUTH
 45.70 -35.00 227.00
 96.00 -41.00 228.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.50	1.37 ✓	1.00 ✓	18.17 ✓
1.50	3.00	.44 ✓	.24 ✓	8.91 ✓
3.00	4.60	.50 ✓	.14 ✓	9.94 ✓
4.60	6.10	3.40 ✓	1.78 ✓	35.31 ✓
6.10	7.60	2.93 ✓	2.63 ✓	30.17 ✓
7.60	9.10	3.15 ✓	1.30 ✓	32.22 ✓
9.10	10.70	3.10 ✓	1.00 ✓	29.14 ✓
10.70	12.20	1.53 ✓	.30 ✓	19.20 ✓
12.20	13.70	1.25 ✓	.26 ✓	28.45 ✓
13.70	15.20	.73 ✓	.38 ✓	16.11 ✓
15.20	16.80	2.88 ✓	3.45 ✓	31.20 ✓
16.80	18.30	2.60 ✓	1.32 ✓	29.14 ✓
18.30	19.80	1.89 ✓	1.56 ✓	23.31 ✓
19.80	21.30	2.38 ✓	2.86 ✓	26.40 ✓
21.30	22.90	1.85 ✓	.63 ✓	24.34 ✓
22.90	24.40	4.35 ✓	4.40 ✓	48.34 ✓
24.40	25.90	3.30 ✓	3.80 ✓	40.45 ✓
25.90	27.40	3.65 ✓	4.40 ✓	58.62 ✓
27.40	29.00	5.20 ✓	4.95 ✓	89.82 ✓
29.00	30.50	2.30 ✓	2.54 ✓	45.25 ✓
30.50	32.00	2.70 ✓	3.06 ✓	48.34 ✓
32.00	33.50	4.68 ✓	7.45 ✓	62.40 ✓
33.50	35.10	2.43 ✓	2.10 ✓	40.45 ✓
35.10	36.60	5.00 ✓	9.28 ✓	95.65 ✓
36.60	64.00	N/A	N/A	N/A
64.00	65.50	6.16 ✓	8.64 ✓	70.62 ✓
65.50	67.10	3.90 ✓	7.14 ✓	54.51 ✓
67.10	68.60	8.24 ✓	13.78 ✓	113.14 ✓
68.60	70.10	9.10 ✓	13.22 ✓	132.00 ✓
70.10	71.60	7.92 ✓	8.52 ✓	127.20 ✓
71.60	73.20	6.18 ✓	9.34 ✓	115.88 ✓
73.20	74.70	5.31 ✓	7.67 ✓	118.97 ✓
74.70	76.20	5.35 ✓	7.18 ✓	114.85 ✓
76.20	77.70	4.28 ✓	6.72 ✓	95.65 ✓
77.70	79.20	6.57 ✓	10.25 ✓	110.05 ✓
79.20	97.50	N/A	N/A	N/A

HOLE NO: U-80
 HOLE LENGTH: 76.20

LATITUDE: 10776.53 ✓
 DEPARTURE: 7687.98 ✓
 ELEVATION: 1154.80 ✓

AZIMUTH: ~~205.09~~ 154.50 ✓
 DIP: 10.05 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	.82✓	.35✓	34.29✓
1.50	3.00	2.45✓	1.05✓	52.46✓
3.00	4.60	1.98✓	1.10✓	50.40✓
4.60	5.50	.80✓	.59✓	21.26✓
5.50	6.40	N/A	N/A	N/A
6.40	7.60	.23✓	4.00✓	8.91✓
7.60	9.10	.40✓	2.83✓	15.09✓
9.10	10.70	.83✓	4.70✓	21.26✓
10.70	12.20	2.05✓	5.00✓	39.43✓
12.20	13.70	1.52✓	3.88✓	28.46✓
13.70	15.20	1.77✓	5.65✓	28.46✓
15.20	16.80	5.20✓	7.11✓	72.69✓
16.80	18.30	2.40✓	5.15✓	37.37✓
18.30	19.80	2.10✓	4.38✓	34.29✓
19.80	21.30	2.10✓	2.88✓	30.17✓
21.30	22.90	1.00✓	2.55✓	16.11✓
22.90	24.40	1.29✓	2.43✓	21.26✓
24.40	25.90	1.04✓	2.92✓	19.20✓
25.90	27.40	1.05✓	2.65✓	17.14✓
27.40	29.00	3.35✓	6.07✓	50.40✓
29.00	30.50	3.30✓	8.49✓	56.57✓
30.50	32.00	2.50✓	5.48✓	39.43✓
32.00	33.50	1.45✓	1.65✓	22.29✓
33.50	35.10	.15✓	1.18✓	9.94✓
35.10	36.60	.35✓	1.40✓	13.03✓
36.60	38.10	1.14✓	1.95✓	22.29✓
38.10	39.60	2.65✓	4.50✓	37.37✓
39.60	41.10	5.05✓	9.52✓	65.49✓
41.10	42.70	3.45✓	5.15✓	52.46✓
42.70	44.20	4.95✓	2.95✓	89.83✓
44.20	45.70	4.40✓	8.98✓	65.49✓
45.70	47.20	2.43✓	2.13✓	35.31✓
47.20	48.80	5.65✓	4.30✓	71.66✓
48.80	50.30	2.33✓	3.80✓	32.23✓
50.30	51.80	1.45✓	3.78✓	26.40✓
51.80	53.30	5.35✓	5.20✓	72.69✓
53.30	54.90	2.78✓	4.90✓	39.43✓
54.90	56.40	3.05✓	6.70✓	50.40✓
56.40	57.90	3.00✓	6.98✓	39.43✓
57.90	59.40	1.00✓	2.53✓	20.23✓
59.40	60.50	3.43✓	7.80✓	55.54✓
60.50	76.20	N/A	N/A	N/A

SPECFIC MOORE BUSINESS FORMS 4

HOLE NO: U-81	LATITUDE: 10835.04	AZIMUTH: 0.00
HOLE LENGTH: 38.10	DEPARTURE: 7570.33	DIP: -90.00
	ELEVATION: 1137.79	

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	9.10	N/A	N/A	N/A
9.10	10.70	3.38✓	5.60✓	59.31✓
10.70	12.20	4.35✓	5.40✓	68.57✓
12.20	15.20	2.95✓	2.38✓	45.25✓
15.20	18.30	1.61✓	1.15✓	16.11✓
18.30	21.30	1.62✓	.85✓	19.20✓
21.30	24.40	2.03✓	.78✓	22.28✓
24.40	27.40	1.55✓	1.95✓	18.17✓
27.40	38.10	N/A	N/A	N/A

SPECIAL ORDER BUSINESS FORMS 4

HOLE NO: U-82 LATITUDE: 10776.09 ✓
 HOLE LENGTH: 45.70 DEPARTURE: 7686.96 ✓
 ELEVATION: 1154.67 ✓ AZIMUTH: ~~186.54~~ ✓
 DIP: 9.38 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	2.70	N/A	N/A	N/A
2.70	4.90	2.58 ✓	5.39 ✓	36.34 ✓
4.90	6.90	N/A	N/A	N/A
6.90	9.10	.84 ✓	1.83 ✓	13.03 ✓
9.10	11.40	1.03 ✓	3.48 ✓	19.20 ✓
11.40	13.70	2.05 ✓	3.70 ✓	29.14 ✓
13.70	15.20	2.40 ✓	3.95 ✓	40.46 ✓
15.20	16.80	2.05 ✓	4.95 ✓	31.20 ✓
16.80	18.30	1.15 ✓	2.28 ✓	18.17 ✓
18.30	19.80	1.15 ✓	3.00 ✓	20.23 ✓
19.80	21.30	.91 ✓	3.20 ✓	15.09 ✓
21.30	22.90	1.48 ✓	2.80 ✓	27.43 ✓
22.90	24.40	2.05 ✓	3.80 ✓	41.49 ✓
24.40	25.90	6.29 ✓	11.52 ✓	112.12 ✓
25.90	27.40	2.88 ✓	5.82 ✓	60.34 ✓
27.40	29.00	3.40 ✓	5.50 ✓	61.37 ✓
29.00	30.50	4.28 ✓	3.15 ✓	61.37 ✓
30.50	32.00	3.90 ✓	1.76 ✓	50.40 ✓
32.00	33.50	5.48 ✓	3.02 ✓	69.60 ✓
33.50	35.10	.14 ✓	.86 ✓	2.05 ✓
35.10	36.60	.53 ✓	.20 ✓	7.88 ✓
36.60	38.10	.20 ✓	.10 ✓	3.08 ✓
38.10	39.60	.63 ✓	.22 ✓	9.94 ✓
39.60	41.10	.28 ✓	.82 ✓	5.14 ✓
41.10	42.50	.45 ✓	1.40 ✓	5.14 ✓
42.50	44.20	.15 ✓	.34 ✓	.34 ✓
44.20	45.70	1.28 ✓	2.64 ✓	23.31 ✓

SPECIAL MOORE BUSINESS FORMS 4

HOLE NO: U-83 LATITUDE: 10835.15 ✓
HOLE LENGTH: 38.10 DEPARTURE: 7570.73 ✓
ELEVATION: 1142.06 ✓ AZIMUTH: 0.00
DIP: 90.00 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	6.00	N/A	N/A	N/A
6.00	7.60	3.83 ✓	6.40 ✓	63.42 ✓
7.60	9.10	.75 ✓	1.75 ✓	14.05 ✓
9.10	10.70	1.05 ✓	1.20 ✓	18.17 ✓
10.70	12.20	1.35 ✓	2.10 ✓	17.14 ✓
12.20	13.70	1.08 ✓	1.40 ✓	18.17 ✓
13.70	15.20	1.00 ✓	1.78 ✓	15.08 ✓
15.20	16.80	3.60 ✓	7.28 ✓	56.57 ✓
16.80	18.30	6.92 ✓	12.97 ✓	96.68 ✓
18.30	19.80	3.48 ✓	7.44 ✓	55.54 ✓
19.80	21.30	7.81 ✓	15.59 ✓	128.22 ✓
21.30	22.90	6.62 ✓	12.81 ✓	103.88 ✓
22.90	24.40	4.59 ✓	8.56 ✓	66.51 ✓
24.40	38.10	N/A	N/A	N/A

1.73

SPEEDY LO MOORE BUSINESS FORMS A

HOLE NO: U-84
HOLE LENGTH: 76.20LATITUDE: 10780.56 ✓
DEPARTURE: 7687.55 ✓
ELEVATION: 1153.23 ✓AZIMUTH: 49.27 ✓
DIP: -55.03 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	3.00	5.51 ✓	6.68 ✓	66.51 ✓
3.00	4.60	3.80 ✓	8.13 ✓	56.57 ✓
4.60	6.20	3.83 ✓	7.96 ✓	61.37 ✓
6.20	10.20	.05 ✓	.14 ✓	.34 ✓
10.20	12.50	8.27 ✓	13.41 ✓	136.12 ✓
12.50	13.00	.10 ✓	2.10 ✓	2.06 ✓
13.00	13.70	6.99 ✓	14.17 ✓	99.77 ✓
13.70	15.20	8.37 ✓	13.51 ✓	156.34 ✓
15.20	16.90	8.59 ✓	16.37 ✓	149.14 ✓
16.90	17.30	.05 ✓	.22 ✓	2.06 ✓
17.30	18.60	4.25 ✓	9.69 ✓	77.83 ✓
18.60	41.10	N/A	N/A	N/A
41.10	42.70	8.32 ✓	10.89 ✓	111.09 ✓
42.70	44.20	7.16 ✓	12.41 ✓	106.97 ✓
44.20	45.70	5.20 ✓	13.11 ✓	84.68 ✓
45.70	47.20	4.79 ✓	9.87 ✓	73.71 ✓
47.20	48.80	4.08 ✓	8.46 ✓	66.51 ✓
48.80	50.30	4.50 ✓	8.56 ✓	78.85 ✓
50.30	51.80	5.20 ✓	7.69 ✓	75.77 ✓
51.80	53.30	7.34 ✓	9.41 ✓	100.80 ✓
53.30	54.90	4.30 ✓	7.64	74.74 ✓
54.90	76.20	N/A	N/A	N/A

HOLE NO: U-85
HOLE LENGTH: 44.20

LATITUDE: 10834.14³³
DEPARTURE: 7570.12
ELEVATION: 1142.23

AZIMUTH: 227.02 ✓
DIP: 65.07 ✓
~~79.36~~

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	7.60	N/A	N/A	N/A
7.60	9.10	.83 ✓	1.00 ✓	17.14 ✓
9.10	10.70	.63 ✓	1.13 ✓	13.03 ✓
10.70	12.20	.93 ✓	1.93 ✓	16.11 ✓
12.20	13.70	.58 ✓	1.20 ✓	10.97 ✓
13.70	15.20	4.10 ✓	8.96 ✓	62.40 ✓
15.20	16.80	7.12 ✓	17.45 ✓	114.17 ✓
16.80	18.30	7.22 ✓	22.48 ✓	120.00 ✓
18.30	19.80	5.32 ✓	17.28 ✓	87.77 ✓
19.80	21.30	6.40 ✓	11.30 ✓	98.74 ✓
21.30	23.20	5.63 ✓	11.09 ✓	84.69 ✓
23.20	44.20	N/A	N/A	N/A

HOLE NO: U-86 LATITUDE: 10782.36 ✓
 HOLE LENGTH: 94.50 DEPARTURE: 7693.25 ✓
 ELEVATION: 1153.99 ✓
 AZIMUTH: 41.12 ✓
 DIP: -31.12 ✓

DIP TESTS: DEPTH DIP AZIMUTH
 94.40 -47.00 48.00

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	3.30	3.65 ✓	8.15 ✓	59.31 ✓
3.30	6.10	N/A	N/A	N/A
6.10	7.60	6.70 ✓	17.88 ✓	116.91 ✓
7.60	7.90	N/A	N/A	N/A
7.90	9.10	5.00 ✓	17.62 ✓	100.80 ✓
9.10	9.80	4.28 ✓	9.58 ✓	70.62 ✓
9.80	54.40	N/A	N/A	N/A
54.40	55.40	4.25 ✓	6.84 ✓	69.60 ✓
55.40	81.00	N/A	N/A	N/A
81.00	82.30	2.68 ✓	5.00 ✓	40.45 ✓
82.30	83.80	2.45 ✓	4.10 ✓	39.42 ✓
83.80	85.30	.78 ✓	.52 ✓	9.94 ✓
85.30	94.50	N/A	N/A	N/A

HOLE NO: U-87
HOLE LENGTH: 61.00

LATITUDE: 10833.25 ✓
DEPARTURE: 7568.31 ✓
ELEVATION: 1137.84 ✓

AZIMUTH: 223.41 ✓
DIP: -53.04 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	55.00	N/A	N/A	N/A
55.00	56.50	1.92 ✓	3.23 ✓	35.31 ✓
56.50	61.00	N/A	N/A	N/A

SPECIFIC MOORE BUSINESS FORMS

HOLE NO: U-88
 HOLE LENGTH: 65.50

LATITUDE: 10750.45 ✓
 DEPARTURE: 7733.16 ✓
 ELEVATION: 1156.05 ✓

AZIMUTH: 0.00
 DIP: -90.00 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	10.85 ✓	23.68 ✓	124.11 ✓
1.50	3.00	6.33 ✓	9.54 ✓	55.54 ✓
3.00	4.60	5.35 ✓	8.80 ✓	130.97 ✓
4.60	6.10	1.60 ✓	3.40 ✓	29.14 ✓
6.10	7.60	6.51 ✓	16.00 ✓	109.02 ✓
7.60	9.10	5.45 ✓	11.54 ✓	86.74 ✓
9.10	10.70	6.83 ✓	11.02 ✓	89.82 ✓
10.70	12.20	5.80 ✓	5.10 ✓	83.65 ✓
12.20	13.70	4.40 ✓	6.67 ✓	65.48 ✓
13.70	15.70	7.13 ✓	12.16 ✓	121.02 ✓
15.70	16.80	1.78 ✓	2.70 ✓	36.34 ✓
16.80	44.20	N/A	N/A	N/A
44.20	45.70	5.65 ✓	7.90 ✓	79.54 ✓
45.70	50.40	N/A	N/A	N/A
50.40	51.80	6.05 ✓	9.15 ✓	94.62 ✓
51.80	53.30	7.05 ✓	9.15 ✓	100.80 ✓
53.30	54.70	7.15 ✓	9.15 ✓	104.91 ✓
54.70	56.20	2.83 ✓	4.15 ✓	41.48 ✓
56.20	57.90	6.58 ✓	6.88 ✓	85.71 ✓
57.90	59.40	2.73 ✓	2.00 ✓	27.42 ✓
59.40	61.00	2.85 ✓	1.64 ✓	32.22 ✓
61.00	62.50	5.80 ✓	7.26 ✓	79.54 ✓
62.50	64.00	3.69 ✓	7.16 ✓	60.34 ✓
64.00	65.50	1.90 ✓	4.00 ✓	32.22 ✓

SPECIFIC MOORE BUSINESS FORMS 4

HOLE NO: U-89 LATITUDE: 10820.70✓ AZIMUTH: 201.23✓
HOLE LENGTH: 38.10 DEPARTURE: 7559.00✓ DIP: 54.18✓
ELEVATION: 1141.32✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	.93✓	1.78✓	14.06✓
1.50	3.00	.69✓	1.18✓	13.03✓
3.00	4.60	2.57✓	4.05✓	35.31✓
4.60	6.10	1.90✓	4.45✓	27.43✓
6.10	7.60	1.59✓	2.60✓	23.31✓
7.60	9.10	.73✓	.88✓	13.03✓
9.10	10.70	1.15✓	1.13✓	17.14✓
10.70	12.20	1.45✓	1.65✓	24.34✓
12.20	13.70	2.20✓	3.85✓	32.23✓
13.70	15.20	2.58✓	4.50✓	36.34✓
15.20	16.80	2.35✓	4.70✓	33.26✓
16.80	18.30	1.44✓	2.23✓	20.23✓
18.30	19.80	9.05✓	15.37✓	111.09✓
19.80	21.30	9.91✓	18.46✓	147.09✓
21.30	22.90	9.65✓	20.62✓	169.37✓
22.90	24.40	8.40✓	18.55✓	143.32✓
24.40	25.90	10.59✓	22.50✓	154.29✓
25.90	27.40	6.54✓	12.92✓	103.89✓
27.40	29.00	8.07✓	12.36✓	123.09✓
29.00	30.50	N/A	N/A	N/A
30.50	32.00	6.74	8.51✓	103.89✓
32.00	38.10	N/A	N/A	N/A

SPRINTED MOORE BUSINESS FORMS 4

HOLE NO: U-90
 HOLE LENGTH: 119.70
 LATITUDE: 10752.88 ✓
 DEPARTURE: 7733.46 ✓
 ELEVATION: 1155.99 ✓

AZIMUTH: 38.55 ✓
 DIP: -61.54 ✓

-60.60

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	3.00	9.37 ✓	10.48 ✓	117.94 ✓
3.00	4.60	10.20 ✓	19.89 ✓	137.14 ✓
4.60	6.10	6.59 ✓	13.58 ✓	109.02 ✓
6.10	7.20	3.33 ✓	7.92 ✓	67.54 ✓
7.20	7.60	8.32 ✓	18.91 ✓	145.02 ✓
7.60	9.10	9.12 ✓	12.60 ✓	123.08 ✓
9.10	10.70	7.49 ✓	11.96 ✓	181.37 ✓
10.70	12.20	9.34 ✓	16.30 ✓	154.28 ✓
12.20	13.70	3.86 ✓	5.00 ✓	71.65 ✓
13.70	15.20	.18 ✓	.30 ✓	7.20 ✓
15.20	17.00	8.49 ✓	13.74 ✓	129.26 ✓
17.00	18.70	2.88 ✓	4.50 ✓	53.49 ✓
18.70	59.40	N/A	N/A	N/A
59.40	61.00	1.11 ✓	1.45 ✓	17.14 ✓
61.00	67.10	N/A	N/A	N/A
67.10	68.60	.64 ✓	.48 ✓	7.20 ✓
68.60	73.70	N/A	N/A	N/A
73.70	74.30	2.18 ✓	1.73 ✓	47.31 ✓
74.30	75.00	7.67 ✓	7.84 ✓	139.09
75.00	76.20	N/A	N/A	N/A
76.20	77.40	4.03 ✓	5.30 ✓	53.49 ✓
77.40	79.20	3.63 ✓	4.05 ✓	44.23 ✓

135.09

SPECIAL MOORE BUSINESS FORMS 4

HOLE NO: U-91 LATITUDE: 10926.78 ✓
HOLE LENGTH: 97.50 DEPARTURE: 7571.58 ✓
 ELEVATION: 1124.82 ✓

AZIMUTH: 230.24 ✓
DIP: -8.26 ✓

1125.29

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	1.86 ✓	2.63 ✓	35.31 ✓
1.50	3.00	2.63 ✓	2.35 ✓	50.40 ✓
3.00	4.60	1.73 ✓	3.63 ✓	33.26 ✓
4.60	6.10	.78 ✓	1.83 ✓	17.14 ✓
6.10	7.60	2.38 ✓	4.85 ✓	44.23 ✓
7.60	9.10	1.42 ✓	2.93 ✓	28.46 ✓
9.10	10.70	1.28 ✓	2.50 ✓	22.29 ✓
10.70	12.20	1.96 ✓	3.00 ✓	32.23 ✓
12.20	13.70	1.61 ✓	2.58 ✓	24.34 ✓
13.70	15.20	1.88 ✓	3.75 ✓	26.40 ✓
15.20	16.80	.85 ✓	1.93 ✓	12.00 ✓
16.80	18.30	3.13 ✓	4.65 ✓	42.51 ✓
18.30	19.80	3.23 ✓	4.30 ✓	46.59 ✓
19.80	22.90	2.08 ✓	4.88 ✓	24.40 ✓ 26.40
22.90	25.90	.98 ✓	1.93 ✓	14.06 ✓
25.90	29.00	1.68 ✓	2.83 ✓	25.37 ✓
29.00	30.50	2.33 ✓	2.50 ✓	35.31 ✓
30.50	32.00	1.65 ✓	.98 ✓	23.31 ✓
32.00	33.50	1.60 ✓	1.63 ✓	26.40 ✓
33.50	35.10	1.18 ✓	.98 ✓	17.14 ✓
35.10	38.10	.75 ✓	1.68 ✓	9.94 ✓
38.10	41.10	N/A	N/A	N/A
41.10	42.70	1.20 ✓	2.13 ✓	23.31 ✓
42.70	60.00	N/A	N/A	N/A
60.00	62.50	.78 ✓	1.48 ✓	16.11 ✓
62.50	64.00	3.48 ✓	3.70 ✓	50.40 ✓
64.00	65.50	3.08 ✓	6.65 ✓	49.37 ✓
65.50	67.10	1.50 ✓	3.00 ✓	26.40 ✓
67.10	68.60	1.40 ✓	2.23 ✓	26.34 ✓ 24.34
68.60	70.10	.73 ✓	1.35 ✓	10.97 ✓
70.10	73.20	1.08 ✓	.88 ✓	13.03 ✓
73.20	76.20	.70 ✓	.98 ✓	13.03 ✓
76.20	77.70	1.53 ✓	2.10 ✓	25.37 ✓
77.70	79.20	N/A	N/A	N/A
79.20	80.80	.55 ✓	.75 ✓	17.14 ✓
80.80	82.30	.43 ✓	.93 ✓	8.22 ✓
82.30	83.80	1.08 ✓	1.75 ✓	13.02 ✓
83.80	85.30	4.73 ✓	1.26 ✓	50.40 ✓
85.30	86.90	3.30 ✓	2.86 ✓	41.48 ✓
86.90	88.40	1.03 ✓	1.30 ✓	10.97 ✓
88.40	89.90	.53 ✓	.63 ✓	8.22 ✓
89.90	91.40	.52 ✓	.68 ✓	6.17 ✓
91.40	93.00	.50 ✓	.60 ✓	7.20 ✓
93.00	94.50	.48 ✓	.68 ✓	8.22 ✓
94.50	96.00	2.98 ✓	3.55 ✓	49.37 ✓
96.00	97.50	.83 ✓	.68 ✓	16.11 ✓

HOLE NO: U-92
 HOLE LENGTH: 73.20

LATITUDE: \checkmark 10749.48
 DEPARTURE: \checkmark 7730.37
 ELEVATION: \checkmark 1157.06

AZIMUTH: 223.43
 DIP: \checkmark 0.57

.04

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.80	8.40 \checkmark	16.10 \checkmark	124.12 \checkmark
1.80	3.50	9.85 \checkmark	13.27 \checkmark	160.46 \checkmark
3.50	5.00	8.70 \checkmark	15.02 \checkmark	122.06 \checkmark
5.00	6.40	9.17 \checkmark	15.27 \checkmark	137.14 \checkmark
6.40	7.60	7.07 \checkmark	14.51 \checkmark	103.89 \checkmark
7.60	8.80	10.75 \checkmark	19.12 \checkmark	127.20 \checkmark
8.80	10.40	1.44 \checkmark	7.35 \checkmark	23.31 \checkmark
10.40	11.80	1.09 \checkmark	9.37 \checkmark	17.14 \checkmark
11.80	13.80	1.55 \checkmark	7.01 \checkmark	32.23 \checkmark
13.80	15.20	4.35 \checkmark	10.36 \checkmark	72.69 \checkmark
15.20	16.70	7.90 \checkmark	18.25 \checkmark	94.63 \checkmark
16.70	18.30	8.78 \checkmark	13.59 \checkmark	114.86 \checkmark
18.30	19.80	1.08 \checkmark	5.50 \checkmark	17.14 \checkmark
19.80	21.30	3.05 \checkmark	8.31 \checkmark	42.51 \checkmark
21.30	22.90	.89 \checkmark	3.40 \checkmark	17.14 \checkmark
22.90	24.40	1.14 \checkmark	3.80 \checkmark	21.26 \checkmark
24.40	25.90	1.38 \checkmark	2.93 \checkmark	25.37 \checkmark
25.90	27.60	4.50 \checkmark	7.90 \checkmark	62.40 \checkmark
27.60	29.00	1.33 \checkmark	2.05 \checkmark	34.29 \checkmark
29.00	30.90	1.80 \checkmark	2.23 \checkmark	34.29 \checkmark
30.90	32.80	2.23 \checkmark	3.58 \checkmark	36.34 \checkmark
32.80	34.60	.81 \checkmark	.98 \checkmark	17.14 \checkmark
34.60	36.60	3.23 \checkmark	5.65 \checkmark	48.34 \checkmark
36.60	38.10	3.42 \checkmark	3.50 \checkmark	54.51 \checkmark
38.10	39.60	2.54 \checkmark	3.45 \checkmark	43.54 \checkmark
39.60	41.10	3.88 \checkmark	2.85 \checkmark	42.51 \checkmark
41.10	42.70	1.85 \checkmark	3.38 \checkmark	26.40 \checkmark
42.70	44.20	.77 \checkmark	1.75 \checkmark	17.14 \checkmark
44.20	45.30	1.70 \checkmark	2.78 \checkmark	34.29 \checkmark
45.30	47.50	2.18 \checkmark	4.48 \checkmark	29.14 \checkmark
47.50	73.20	N/A	N/A	N/A

SPECIFIC MOORE BUSINESS FORMS

HOLE NO: U-93 LATITUDE: 10925.53 ✓ AZIMUTH: 225.44 ✓
 HOLE LENGTH: 76.20 DEPARTURE: 7572.89 ✓ DIP: 30.32 ✓
 ELEVATION: 1126.41 / 1126.88 ~~1126.88~~

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	1.78 ✓	2.00 ✓	37.37 ✓
1.50	3.00	1.82 ✓	2.78 ✓	35.31 ✓
3.00	4.60	2.60 ✓	4.55 ✓	50.40 ✓
4.60	7.60	2.53 ✓	3.58 ✓	45.26 ✓
7.60	9.10	2.45 ✓	3.90 ✓	45.26 ✓
9.10	10.70	2.90 ✓	3.80 ✓	53.49 ✓
10.70	12.20	2.10 ✓	4.40 ✓	37.37 ✓
12.20	13.70	1.95 ✓	2.80 ✓	29.14 ✓
13.70	15.20	1.28 ✓	2.93 ✓	10.97 ✓
15.20	16.80	1.13 ✓	3.25 ✓	15.09 ✓
16.80	18.30	1.05 ✓	2.33 ✓	20.23 ✓
18.30	19.80	1.65 ✓	2.88 ✓	23.31 ✓
19.80	21.30	1.68 ✓	2.38 ✓	22.29 ✓
21.30	22.90	2.05 ✓	3.30 ✓	33.26 ✓
22.90	24.40	1.13 ✓	1.08 ✓	16.11 ✓
24.40	25.90	1.35 ✓	1.73 ✓	24.34 ✓
25.90	27.40	1.90 ✓	2.15 ✓	26.40 ✓
27.40	29.00	.68 ✓	.70 ✓	10.97 ✓
29.00	43.90	N/A	N/A	N/A
43.90	45.70	2.85 ✓	6.31 ✓	47.31 ✓
45.70	47.20	2.08 ✓	3.50 ✓	28.46 ✓
47.20	48.80	2.00 ✓	3.80 ✓	28.46 ✓
48.80	50.30	1.48 ✓	3.38 ✓	23.31 ✓
50.30	51.80	1.13 ✓	2.53 ✓	18.17 ✓
51.80	53.30	.68 ✓	1.50 ✓	14.06 ✓
53.30	54.90	.98 ✓	2.08 ✓	17.14 ✓
54.90	57.90	.88 ✓	1.05 ✓	13.03 ✓
57.90	59.40	2.98 ✓	1.85 ✓	35.31 ✓
59.40	61.00	1.78 ✓	4.10 ✓	29.14 ✓
61.00	62.50	.63 ✓	2.03 ✓	24.34 ✓
62.50	64.00	2.68 ✓	5.45 ✓	44.23 ✓
64.00	65.50	3.38 ✓	6.11 ✓	56.57 ✓
65.50	67.10	6.86 ✓	12.32 ✓	104.92 ✓
67.10	68.00	N/A	N/A	N/A
68.00	69.50	4.62 ✓	9.59 ✓	74.74 ✓
69.50	76.20	N/A	N/A	N/A

SPECIFIC LOG MOORE BUSINESS FORMS 4

HOLE NO: U-94
 HOLE LENGTH: 26.20

LATITUDE: 10968.13 ✓
 DEPARTURE: 7378.32 ✓
 ELEVATION: 1099.79 ✓

AZIMUTH: 347.28 ✓
 DIP: 5.00 ✓

.09 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.70	4.35 ✓	7.44 ✓	62.40 ✓
1.70	2.70	N/A	N/A	N/A
2.70	5.10	1.48 ✓	4.43 ✓	24.34 ✓
5.10	6.10	N/A	N/A	N/A
6.10	7.60	.28 ✓	1.05 ✓	5.14 ✓
7.60	9.10	.43 ✓	1.05 ✓	7.20 ✓
9.10	10.70	.33 ✓	.63 ✓	5.14 ✓
10.70	13.90	.55 ✓	.60 ✓	10.97 ✓
13.90	14.70	N/A	N/A	N/A
14.70	16.80	.68 ✓	.98 ✓	13.03 ✓
16.80	18.30	.23 ✓	.38 ✓	5.14 ✓
18.30	20.10	1.05 ✓	.75 ✓	16.11 ✓
20.10	21.60	.35 ✓	.59 ✓	7.20 ✓
21.60	23.30	.35 ✓	.34 ✓	5.14 ✓
23.30	24.60	N/A	N/A	N/A
24.60	26.20	.73 ✓	.60 ✓	10.97 ✓

HOLE NO: U-95
HOLE LENGTH: 121.90

LATITUDE: 10926.50 ✓
DEPARTURE: 7572.53 ✓
ELEVATION: 1124.08 ^{1124.55}

✓ AZIMUTH: 224.52 ✓
✓ DIP: -49.34 ✓

DIP TESTS:	DEPTH	DIP	AZIMUTH
	60.90	-56.00	227.00
	106.68	-60.00	226.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.50	3.28 ✓	6.14 ✓	57.60 ✓
1.50	3.00	4.63 ✓	3.85 ✓	73.71 ✓
3.00	4.60	2.45 ✓	5.35 ✓	41.49 ✓
4.60	6.70	3.50 ✓	5.90 ✓	54.51 ✓
6.70	9.10	2.20 ✓	4.97 ✓	40.46 ✓
9.10	10.70	2.93 ✓	4.28 ✓	33.26 ✓
10.70	12.20	2.15 ✓	3.60 ✓	32.23 ✓
12.20	13.70	4.50 ✓	8.41 ✓	73.71 ✓
13.70	15.20	4.05 ✓	6.14 ✓	70.63 ✓
15.20	16.80	1.96 ✓	3.35 ✓	34.29 ✓
16.80	18.30	1.28 ✓	2.95 ✓	26.40 ✓
18.30	19.80	2.80 ✓	4.55 ✓	46.29 ✓
19.80	21.30	6.92 ✓	9.48 ✓	88.80 ✓
21.30	22.90	6.55 ✓	5.90 ✓	90.86 ✓
22.90	24.40	5.40 ✓	10.22 ✓	55.54 ✓
24.40	25.50	N/A	N/A	N/A
25.50	27.10	3.55 ✓	11.25 ✓	65.49 ✓
27.10	28.60	1.43 ✓	3.53 ✓	26.40 ✓
28.60	30.90	1.98 ✓	7.16 ✓	31.20 ✓
30.90	38.20	N/A	N/A	N/A
38.20	41.10	6.10 ✓	13.70 ✓	87.77 ✓
41.10	42.70	6.45 ✓	11.70 ✓	93.94 ✓
42.70	44.20	5.96 ✓	8.36 ✓	78.86 ✓
44.20	45.70	3.55 ✓	4.20 ✓	50.40 ✓
45.70	47.20	2.38 ✓	2.65 ✓	38.40 ✓
47.20	50.30	N/A	N/A	N/A
50.30	51.80	3.35 ✓	5.40 ✓	52.46 ✓
51.80	53.60	2.13 ✓	2.60 ✓	30.17 ✓
53.60	110.50	N/A	N/A	N/A
110.50	112.80	.20 ✓	.33 ✓	8.23 ✓
112.80	114.30	1.08 ✓	1.38 ✓	18.17 ✓
114.30	115.80	3.85 ✓	6.67 ✓	66.51 ✓
115.80	117.30	7.00 ✓	8.23 ✓	74.74 ✓
117.30	119.50	5.19 ✓	4.70 ✓	92.92 ✓
119.50	121.90	N/A	N/A	N/A

HOLE NO: U-96 LATITUDE: 10749.52 ✓
 HOLE LENGTH: 121.90 DEPARTURE: 7730.76 ✓
 ELEVATION: 1158.03 ✓ AZIMUTH: 223.17 ✓
 DIP: 19.27 ✓

DIP TESTS:	DEPTH	DIP	AZIMUTH
	83.82	17.00	225.00
	120.40	15.00	228.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.50	2.90 ✓	8.50 ✓	53.49 ✓
1.50	3.00	6.26 ✓	11.49 ✓	129.26 ✓
3.00	4.60	4.80 ✓	14.44 ✓	47.31 ✓
4.60	6.10	5.73 ✓	16.23 ✓	60.34 ✓
6.10	7.40	4.45 ✓	12.05 ✓	63.43 ✓
7.40	9.30	10.01 ✓	18.35 ✓	135.09 ✓
9.30	10.70	6.94 ✓	14.60 ✓	103.89 ✓
10.70	12.20	7.19 ✓	14.61 ✓	105.94 ✓
12.20	13.70	6.70 ✓	10.20 ✓	91.89 ✓
13.70	15.20	5.00 ✓	11.17 ✓	73.71 ✓
15.20	16.70	5.46 ✓	11.15 ✓	80.57 ✓
16.70	18.70	.59 ✓	4.40 ✓	14.06 ✓
18.70	19.80	2.20 ✓	4.30 ✓	39.43 ✓
19.80	21.70	1.18 ✓	2.28 ✓	23.31 ✓
21.70	22.90	.66 ✓	1.68 ✓	13.03 ✓
22.90	24.40	.58 ✓	.90 ✓	9.94 ✓
24.40	25.90	1.10 ✓	2.58 ✓	16.11 ✓
25.90	27.40	3.70 ✓	7.15 ✓	56.57 ✓
27.40	29.00	3.13 ✓	3.55 ✓	42.51 ✓
29.00	30.50	3.40 ✓	3.35 ✓	43.54 ✓
30.50	32.00	1.43 ✓	1.80 ✓	32.23 ✓
32.00	33.50	1.10 ✓	3.80 ✓	16.11 ✓
33.50	35.30	1.80 ✓	3.38 ✓	23.31 ✓
35.30	36.20	.23 ✓	3.50 ✓	3.09 ✓
36.20	38.10	2.78 ✓	5.50 ✓	40.46 ✓
38.10	39.60	2.53 ✓	5.67 ✓	39.43 ✓
39.60	41.10	.68 ✓	.60 ✓	12.00 ✓
41.10	42.70	.95 ✓	1.75 ✓	15.09 ✓
42.70	44.20	3.23 ✓	4.15 ✓	73.71 ✓
44.20	45.70	2.83 ✓	4.12 ✓	64.46 ✓
45.70	47.20	.05 ✓	.13 ✓	.00 ✓
47.20	48.80	1.48 ✓	2.80 ✓	27.43 ✓
48.80	50.30	.73 ✓	1.93 ✓	14.06 ✓
50.30	56.40	N/A	N/A	N/A
56.40	57.90	.50 ✓	1.25 ✓	7.20 ✓
57.90	98.10	N/A	N/A	N/A
98.10	99.90	3.45 ✓	4.70 ✓	48.34 ✓
99.90	101.40	8.84 ✓	20.27 ✓	116.92 ✓
101.40	102.70	6.41 ✓	15.49 ✓	95.66 ✓
102.70	104.40	7.20 ✓	13.54 ✓	98.74 ✓
104.40	121.90	N/A	N/A	N/A

SPECIFIC MOORE BUSINESS FORMS 4

HOLE NO: U-97 LATITUDE: 10926.18 ✓ AZIMUTH: 219.02 ✓
 HOLE LENGTH: 62.50 DEPARTURE: 7572.66 ✓ DIP: -31.00 ✓
 ELEVATION: 1124.22

1124.69

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	3.00	3.03 ✓	5.65 ✓	51.43 ✓
3.00	4.60	2.93 ✓	4.60 ✓	50.40 ✓
4.60	6.10	2.20 ✓	2.75 ✓	39.43 ✓
6.10	7.60	2.43 ✓	4.90 ✓	46.29 ✓
7.60	9.10	1.73 ✓	4.03 ✓	34.29 ✓
9.10	10.70	1.13 ✓	3.03 ✓	21.26 ✓
10.70	12.20	1.58 ✓	2.98 ✓	27.43 ✓
12.20	13.70	1.53 ✓	4.65 ✓	26.40 ✓
13.70	15.20	1.28 ✓	4.78 ✓	24.34 ✓
15.20	16.80	1.43 ✓	5.47 ✓	28.46 ✓
16.80	18.30	2.98 ✓	4.35 ✓	55.54 ✓
18.30	21.30	2.23 ✓	8.02 ✓	40.46 ✓
21.30	22.90	1.65 ✓	5.15 ✓	28.46 ✓
22.90	24.40	1.68 ✓	5.07 ✓	39.43 ✓
24.40	25.90	1.75 ✓	4.50 ✓	37.37 ✓
25.90	27.40	1.85 ✓	5.08 ✓	44.23 ✓
27.40	29.00	1.98 ✓	4.05 ✓	46.29 ✓
29.00	30.50	2.13 ✓	3.40 ✓	52.46 ✓
30.50	32.00	1.83 ✓	4.90 ✓	42.51 ✓
32.00	33.50	2.81 ✓	4.65 ✓	56.57 ✓
33.50	35.10	3.78 ✓	6.55 ✓	69.60 ✓
35.10	36.60	1.63 ✓	4.84 ✓	33.26 ✓
36.60	38.10	3.35 ✓	8.20 ✓	62.40 ✓
38.10	39.60	3.23 ✓	7.65 ✓	64.46 ✓
39.60	40.80	3.58 ✓	7.13 ✓	66.51 ✓
40.80	42.00	3.80 ✓	8.95 ✓	74.74 ✓
42.00	44.20	3.13 ✓	10.48 ✓	43.54 ✓
44.20	45.70	3.58 ✓	7.85 ✓	58.63 ✓
45.70	47.20	1.30 ✓	2.88 ✓	20.23 ✓
47.20	49.30	1.15 ✓	2.80 ✓	20.23 ✓
49.30	62.50	N/A	N/A	N/A

SPECIAL MOORE BUSINESS FORMS 4

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-98 LATITUDE: 10749.23 ✓
 DEPARTURE: 7731.64 ✓ AZIMUTH: 215.59 ✓
 ELEVATION: 1156.09 ✓ DIP: -66.42 ✓

INTERVAL		ASSAYS			
FROM	TO	PB %	ZN %	AG GM/TON	
0.00	2.00	4.75 ✓	8.61 ✓	70.60	70.63
2.00	3.80	8.37 ✓	19.67 ✓	145.00	145.03
3.80	5.80	9.17 ✓	23.91 ✓	152.20	152.23
5.80	8.10	2.10 ✓	4.65 ✓	43.50	43.54
8.10	10.20	7.02 ✓	9.74 ✓	121.00	121.03
10.20	12.60	5.46 ✓	11.55 ✓	76.80	
12.60	14.20	3.10 ✓	4.05 ✓	46.30	46.29
14.20	15.60	5.26 ✓	7.44 ✓	94.60	94.63
15.60	17.10	2.68 ✓	4.70 ✓	45.30	45.26
17.10	18.30	1.13 ✓	1.78 ✓	14.10	14.06
18.30	21.50	N/A	N/A	N/A	
21.50	22.90	.68 ✓	1.30 ✓	9.94 ✓	
22.90	24.40	.73 ✓	.75 ✓	18.17 ✓	
24.40	25.90	1.80 ✓	2.80 ✓	29.14 ✓	
25.90	27.40	3.78 ✓	7.05 ✓	46.29 ✓	
27.40	63.80	N/A	N/A	N/A	

MOORE SHEET NO. 4

HOLE NO: U-99 LATITUDE: 10935.22 ✓ AZIMUTH: 217.15 ✓
 HOLE LENGTH: 182.90 DEPARTURE: 7583.25 ✓ DIP: -60.17 ✓
 ELEVATION: 1123.95 1124.43

DIP TESTS:	DEPTH	DIP	AZIMUTH
	60.96	-68.00	218.00
	106.60	-73.00	223.00
	152.40	-76.00	222.00
	182.80	-79.00	214.00

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	5.81 ✓	6.40 ✓	68.57 ✓
1.50	3.00	4.18 ✓	9.07 ✓	63.43 ✓
3.00	4.60	4.90 ✓	12.40 ✓	78.86 ✓
4.60	6.10	3.00 ✓	8.22 ✓	83.66 ✓
6.10	7.60	2.60 ✓	6.27 ✓	43.54 ✓
7.60	49.20	.00	.00	.00
49.20	50.60	4.09 ✓	5.78 ✓	62.40 ✓
50.60	114.30	.00	.00	.00
114.30	115.80	6.20 ✓	11.25 ✓	108.00 ✓
115.80	117.30	4.30 ✓	6.93 ✓	55.54 ✓
117.30	119.70	6.47 ✓	9.15 ✓	104.92 ✓
119.70	121.00	6.16 ✓	8.77 ✓	80.57 ✓
121.00	123.40	3.10 ✓	4.50 ✓	44.23 ✓
123.40	125.00	2.98 ✓	4.35 ✓	39.43 ✓
125.00	126.50	.85 ✓	1.38 ✓	10.97 ✓
126.50	132.90	N/A	N/A	N/A
132.90	135.60	.55 ✓	.63 ✓	15.09 ✓
135.60	139.50	.38 ✓	.58 ✓	8.91 ✓
139.50	143.30	.35 ✓	.38 ✓	8.91 ✓
143.30	145.30	.18 ✓	.60 ✓	7.20 ✓
145.30	147.00	.23 ✓	.60 ✓	7.20 ✓
147.00	148.70	.28 ✓	.43 ✓	13.03 ✓
148.70	150.30	N/A	N/A	N/A
150.30	153.30	3.00 ✓	3.75 ✓	49.37 ✓
153.30	182.90	N/A	N/A	N/A

N/A

142.30 145.30 142.30

SPECIFIC TO MOORE BUSINESS FORMS

HOLE NO: U-100
 HOLE LENGTH: 121.90

LATITUDE: 10748.85
 DEPARTURE: 7731.50
 ELEVATION: 1159.02

AZIMUTH: 222.29
 DIP: 35.07
~~34.31~~

DIP TESTS: DEPTH DIP AZIMUTH
 61.00 33.00 223.00
 120.40 37.00 233.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	3.00	5.75✓	11.65✓	96.69✓
3.00	4.60	7.70✓	14.97✓	111.09✓
4.60	6.10	11.77✓	21.01✓	164.57✓
6.10	7.60	9.26✓	16.97✓	127.20✓
7.60	9.10	7.30✓	13.60✓	90.86✓
9.10	10.70	6.75✓	13.13✓	92.92✓
10.70	12.20	2.85✓	6.01✓	37.37✓
12.20	13.70	6.15✓	10.53✓	78.86✓
13.70	15.20	2.00✓	4.24✓	33.26✓
15.20	16.80	1.03✓	3.50✓	23.31✓
16.80	18.30	1.73✓	4.38✓	33.26✓
18.30	19.80	4.74✓	10.17✓	68.57✓
19.80	21.30	3.78✓	4.10✓	52.46✓
21.30	22.90	1.23✓	1.88✓	17.14✓
22.90	24.40	2.50✓	3.05✓	33.26✓
24.40	25.90	2.78✓	4.55✓	36.34✓
25.90	26.70	1.63✓	2.88✓	25.37✓
26.70	27.40	2.18✓	5.93✓	30.17✓
27.40	29.80	1.23✓	2.73✓	19.20✓
29.80	31.50	3.14✓	5.60✓	50.40✓
31.50	33.50	2.83✓	6.49✓	40.46✓
33.50	35.10	1.38✓	2.55✓	17.14✓
35.10	36.60	2.38✓	5.90✓	34.29✓
36.60	38.10	1.13✓	4.94✓	17.14✓
38.10	39.60	3.08✓	3.50✓	41.49✓
39.60	41.10	1.70✓	7.00✓	25.37✓
41.10	42.70	1.05✓	2.63✓	15.09✓
42.70	44.20	4.89✓	10.94✓	86.74✓
44.20	47.20	2.43✓	3.15✓	37.37✓
47.20	48.80	4.89✓	2.75✓	71.66✓
48.80	50.30	5.54✓	4.50✓	72.69✓
50.30	51.80	1.90✓	1.83✓	26.40✓
51.80	54.00	1.43✓	.68✓	18.17✓
54.00	56.50	.00	.13	.00✓
56.50	58.70	1.10✓	2.45✓	15.09✓
58.70	80.20	N/A	N/A	N/A
80.20	82.00	2.20✓	5.20✓	31.20✓
82.00	83.20	1.38✓	3.70✓	22.29✓
83.20	86.40	.48✓	1.23✓	7.20✓
86.40	89.40	.55✓	1.53✓	7.20✓
89.40	90.40	3.28✓	5.50✓	45.26✓
90.40	92.20	3.43✓	6.97✓	47.31✓
92.20	121.90	N/A	N/A	N/A

.13 .00

MOORE
 SERIAL NO. 4

HOLE NO: U-101 LATITUDE: 10936.50 AZIMUTH: 44.00 ✓
 HOLE LENGTH: 175.30 DEPARTURE: 7583.50 DIP: -85.00 ✓
 ELEVATION: 1123.90

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	2.70	4.98 ✓	7.46 ✓	74.74 ✓
2.70	4.20	2.88 ✓	5.40 ✓	46.29 ✓
4.20	54.90	N/A	N/A	N/A
54.90	56.40	7.77 ✓	13.02 ✓	126.17 ✓
56.40	57.90	2.80 ✓	2.76 ✓	41.49 ✓
57.90	59.40	3.38 ✓	3.06 ✓	49.37 ✓
59.40	61.00	4.65 ✓	3.10 ✓	72.69 ✓
61.00	62.50	4.08 ✓	4.86 ✓	64.46 ✓
62.50	64.00	3.50 ✓	2.80 ✓	50.40 ✓
64.00	65.60	4.35 ✓	5.84 ✓	66.51 ✓
65.60	67.30	N/A	N/A	N/A
67.30	70.10	1.93 ✓	2.70 ✓	28.46 ✓
70.10	71.60	2.60 ✓	3.66 ✓	40.46 ✓
71.60	73.20	3.08 ✓	2.46 ✓	45.26 ✓
73.20	74.70	2.05 ✓	2.60 ✓	32.23 ✓
74.70	77.70	.13 ✓	.60 ✓	3.09 ✓
77.70	80.80	1.48 ✓	3.00 ✓	24.34 ✓
80.80	83.80	1.03 ✓	1.20 ✓	19.20 ✓
83.80	86.90	1.30 ✓	1.88 ✓	20.23 ✓
86.90	89.90	.33 ✓	.46 ✓	6.17 ✓
89.90	91.40	1.48 ✓	2.18 ✓	24.34 ✓
91.40	93.00	1.98 ✓	2.80 ✓	31.20 ✓
93.00	95.50	.85 ✓	.90 ✓	10.97 ✓
95.50	98.10	1.18 ✓	1.20 ✓	13.03 ✓
98.10	99.20	8.05 ✓	13.43 ✓	130.97 ✓
99.20	130.60	N/A	N/A	N/A
130.60	132.60	.05 ✓	.13 ✓	2.06 ✓
132.60	134.10	.02 ✓	.03 ✓	.00 ✓
134.10	137.20	.03 ✓	.05 ✓	.00 ✓
137.20	140.20	.48 ✓	.73 ✓	6.17 ✓
140.20	141.70	.08 ✓	.18 ✓	3.09 ✓
141.70	143.30	.03 ✓	.13 ✓	.00 ✓
143.30	144.80	1.60 ✓	2.06 ✓	26.40 ✓
144.80	145.90	4.88 ✓	6.03 ✓	65.49 ✓
145.90	147.50	4.96 ✓	10.11 ✓	72.69 ✓
147.50	149.00	1.53 ✓	2.68 ✓	23.31 ✓
149.00	175.30	N/A	N/A	N/A

HOLE NO: U-102 LATITUDE: 10749.74 ✓
 HOLE LENGTH: 47.20 DEPARTURE: 7731.80 ✓
 ELEVATION: 1160.64 ✓

AZIMUTH: 222.40 ✓
 DIP: 65.27 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	3.00	8.08 ✓	16.53 ✓	114.17 ✓
3.00	4.60	7.74 ✓	15.98 ✓	128.23 ✓
4.60	6.10	7.67 ✓	17.00 ✓	112.12 ✓
6.10	8.10	9.90 ✓	19.64 ✓	127.20 ✓
8.10	12.00	.95 ✓	1.68 ✓	12.00 ✓
12.00	13.70	6.15 ✓	8.89 ✓	74.74 ✓
13.70	15.20	3.05 ✓	5.95 ✓	46.29 ✓
15.20	18.30	2.80 ✓	3.05 ✓	35.31 ✓
18.30	19.80	6.97 ✓	5.20 ✓	87.77 ✓
19.80	22.20	.05 ✓	.03 ✓	.00 ✓
22.20	22.70	7.72 ✓	14.54 ✓	145.03 ✓
22.70	24.40	.55 ✓	1.05 ✓	13.03 ✓
24.40	25.90	.88 ✓	1.20 ✓	13.03 ✓
25.90	29.00	2.58 ✓	4.00 ✓	44.23 ✓
29.00	33.50	2.58 ✓	4.40 ✓	35.31 ✓
33.50	37.90	N/A	N/A	N/A
37.90	39.60	2.48 ✓	6.25 ✓	27.43 ✓
39.60	41.10	2.33 ✓	2.90 ✓	34.29 ✓
41.10	42.70	2.98 ✓	7.45 ✓	43.54 ✓
42.70	44.20	3.78 ✓	7.90 ✓	50.40 ✓
44.20	45.70	2.98 ✓	5.45 ✓	40.46 ✓
45.70	47.20	N/A	N/A	N/A

MOORE
 SPEDIFLO 4

HOLE NO: U-103 LATITUDE: 10936.34 ✓ ✓ AZIMUTH: 42.19 ✓
 HOLE LENGTH: 129.50 DEPARTURE: 7583.72 ✓ ✓ DIP: -46.42 ✓
 ELEVATION: 1123.93 // 124.40

DIP TESTS:	DEPTH	DIP	AZIMUTH
	59.40	-59.00	56.00
	99.10	-62.00	60.00
	129.50	-63.00	67.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.50	5.56 ✓	8.35 ✓	81.60 ✓
1.50	3.00	4.43 ✓	7.20 ✓	64.46 ✓
3.00	4.60	3.23 ✓	4.45 ✓	42.51 ✓
4.60	129.50	N/A	N/A	N/A

HOLE NO: U-105
HOLE LENGTH: 38.10

LATITUDE: 10937.42 ✓
DEPARTURE: 7585.37 ✓
ELEVATION: 1125(00).69

43.16
AZIMUTH: 44.00 ✓
DIP: 0.00 ✓
- 0.47

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	.15 ✓	.13 ✓	5.14 ✓
1.50	3.00	.33 ✓	.20 ✓	6.17 ✓
3.00	5.60	1.38 ✓	3.23 ✓	22.29 ✓
5.60	38.10	N/A	N/A	N/A

HOLE NO: U-106
 HOLE LENGTH: 137.20
 LATITUDE: 10752.19 ✓
 DEPARTURE: 7734.48 ✓
 ELEVATION: 1157.25 ✓

45.55
~~41.00~~
 AZIMUTH: ~~46.00~~ ✓
 ✓ DIP: 0.00 ✓

DIP TESTS: DEPTH 111.30 DIP -1.00 AZIMUTH 46.00

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	9.86 ✓	22.57 ✓	168.34 ✓
1.50	3.50	8.40 ✓	19.86 ✓	137.14 ✓
3.50	4.60	4.58 ✓	12.62 ✓	78.86 ✓
4.60	6.20	8.81 ✓	19.97 ✓	137.14 ✓
6.20	9.20	9.20 ✓	15.20 ✓	150.17 ✓
9.20	10.70	9.74 ✓	13.95 ✓	130.97 ✓
10.70	13.90	9.41 ✓	14.72 ✓	146.06 ✓
13.90	15.20	.63 ✓	.48 ✓	14.06 ✓
15.20	16.80	.30 ✓	.45 ✓	6.17 ✓
16.80	94.50	N/A	N/A	N/A
94.50	97.50	.08 ✓	.00 ✓	.00 ✓
97.50	100.00	.78 ✓	.53 ✓	9.94 ✓
100.00	102.10	4.98 ✓	5.70 ✓	78.86 ✓
102.10	103.60	8.88 ✓	10.50 ✓	111.09 ✓
103.60	105.20	2.63 ✓	5.74 ✓	34.29 ✓
105.20	106.70	2.23 ✓	4.35 ✓	32.23 ✓
106.70	108.20	2.00 ✓	3.90 ✓	30.17 ✓
108.20	109.70	2.03 ✓	3.85 ✓	30.17 ✓
109.70	111.30	1.64 ✓	3.68 ✓	26.40 ✓
111.30	112.80	1.23 ✓	2.90 ✓	21.26 ✓
112.80	114.30	.75 ✓	1.40 ✓	15.09 ✓
114.30	115.80	1.45 ✓	2.58 ✓	22.29 ✓
115.80	117.30	1.28 ✓	3.40 ✓	17.14 ✓
117.30	118.90	1.10 ✓	2.43 ✓	16.11 ✓
118.90	120.40	1.30 ✓	3.68 ✓	21.26 ✓
120.40	121.90	1.10 ✓	2.80 ✓	20.23 ✓
121.90	123.40	1.25 ✓	4.78 ✓	24.34 ✓
123.40	125.10	1.58 ✓	5.20 ✓	34.29 ✓
125.10	127.50	.13 ✓	.25 ✓	.00 ✓
127.50	129.90	.10 ✓	.13 ✓	.00 ✓
129.90	137.20	N/A	N/A	N/A

1.65

MOORE SPECIALTY 4

HOLE NO: U-107 LATITUDE: 10936.50 AZIMUTH: 0.00 ✓
 HOLE LENGTH: 70.10 DEPARTURE: 7583.50 DIP: 90.00 ✓
 ELEVATION: 1127.60

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	3.00	1.78 ✓	2.60 ✓	28.46 ✓
3.00	7.60	.10 ✓	.18 ✓	.00 ✓
7.60	10.70	.01 ✓	.00 ✓	.00 ✓
10.70	12.20	2.03 ✓	3.46 ✓	31.20 ✓
12.20	13.70	1.55 ✓	2.55 ✓	23.31 ✓
13.70	15.20	1.68 ✓	2.85 ✓	26.40 ✓
15.20	16.80	1.60 ✓	3.45 ✓	30.17 ✓
16.80	18.30	1.00 ✓	2.13 ✓	18.17 ✓
18.30	19.80	1.38 ✓	2.00 ✓	21.26 ✓
19.80	21.30	1.53 ✓	1.88 ✓	24.34 ✓
21.30	22.90	2.75 ✓	3.40 ✓	38.40 ✓
22.90	24.40	3.80 ✓	5.00 ✓	53.49 ✓
24.40	25.90	4.20 ✓	5.55 ✓	55.54 ✓
25.90	27.40	2.85 ✓	4.85 ✓	38.40 ✓
27.40	29.00	4.50 ✓	8.36	73.71 ✓
29.00	30.50	7.35 ✓	12.75 ✓	100.80 ✓
30.50	32.00	6.08 ✓	9.91 ✓	84.69 ✓
32.00	33.50	3.30 ✓	7.82 ✓	54.51 ✓
33.50	35.00	3.65 ✓	9.70 ✓	48.34 ✓
35.00	36.50	3.15 ✓	4.95 ✓	52.46 ✓
36.50	38.60	2.89 ✓	3.35 ✓	38.40 ✓
38.60	42.00	N/A	N/A	N/A
42.00	44.20	3.60 ✓	6.43 ✓	60.34 ✓
44.20	45.70	1.15 ✓	2.18 ✓	22.29 ✓
45.70	47.20	2.08 ✓	2.45 ✓	30.17 ✓
47.20	48.80	1.95 ✓	1.76 ✓	28.11 ✓
48.80	50.30	1.55 ✓	3.30 ✓	39.14
50.30	52.00	1.85 ✓	2.05 ✓	26.40 ✓
52.00	57.50	N/A	N/A	N/A
57.50	59.40	2.70 ✓	4.40 ✓	41.49 ✓
59.40	61.00	1.78 ✓	3.00 ✓	34.29 ✓
61.00	62.50	6.26 ✓	9.96 ✓	97.72 ✓
62.50	70.10	N/A	N/A	N/A

MOORE
 SPEEDFILE 4

HOLE NO: U-108
 HOLE LENGTH: 72.50

LATITUDE: 10751.56 ✓
 DEPARTURE: 7734.92 ✓
 ELEVATION: 1156.25 ✓

AZIMUTH: 44.31 ✓
 DIP: -30.57 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	3.00	9.31 ✓	21.22 ✓	144.23 ✓
3.00	4.60	3.70 ✓	6.91 ✓	55.54 ✓
4.60	6.10	4.19 ✓	6.74 ✓	83.66 ✓
6.10	7.80	5.98 ✓	10.61 ✓	85.72 ✓
7.80	9.10	6.38 ✓	9.64 ✓	88.80 ✓
9.10	10.70	.88	1.03 ✓	17.14 ✓
10.70	12.80	.83 ✓	1.15 ✓	17.14 ✓
12.80	53.90	N/A	N/A	N/A
53.90	54.90	8.30 ✓	9.87 ✓	117.60 ✓
54.90	56.40	7.85 ✓	9.51 ✓	111.09 ✓
56.40	58.60	6.75 ✓	8.44 ✓	92.92 ✓
58.60	61.00	6.54 ✓	8.64 ✓	84.69 ✓
61.00	62.50	2.73 ✓	2.35 ✓	34.29 ✓
62.50	64.00	1.65 ✓	1.50 ✓	23.31 ✓
64.00	65.50	3.60 ✓	2.78 ✓	37.37 ✓
65.50	67.10	1.80 ✓	1.48 ✓	20.23 ✓
67.10	68.60	1.05 ✓	.60 ✓	16.11 ✓
68.60	70.10	.10 ✓	.43 ✓	4.11 ✓
70.10	72.50	.43 ✓	.68 ✓	10.97 ✓

MOORE SPEED PLO 4

HOLE NO: U-109 LATITUDE: 10936.75 ✓ AZIMUTH: 38.43 ✓
 HOLE LENGTH: 116.70 DEPARTURE: 7585.23 ✓ DIP: 53.40 ✓
 ELEVATION: ~~1127.59~~ 1128.06 ✓

DIP TESTS:	DEPTH	DIP	AZIMUTH
	35.10	58.00	34.00
	65.50	62.00	31.00
	96.00	65.00	31.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.50	1.73 ✓	5.35 ✓	30.17 ✓
1.50	3.00	1.83 ✓	4.48 ✓	34.29 ✓
3.00	4.60	5.62 ✓	11.02 ✓	108.00 ✓
4.60	50.80	N/A	N/A	N/A
50.80	53.30	4.90 ✓	8.12 ✓	70.63 ✓
53.30	67.30	N/A	N/A	N/A
67.30	70.10	2.40 ✓	3.36 ✓	43.54 ✓
70.10	71.60	3.38 ✓	5.64 ✓	50.40 ✓
71.60	73.20	1.60 ✓	3.68 ✓	20.23 ✓
73.20	74.70	.35 ✓	.20 ✓	3.09 ✓
74.70	76.20	2.20 ✓	3.66 ✓	37.37 ✓
76.20	77.70	4.55 ✓	8.36 ✓	72.69 ✓
77.70	79.20	3.20 ✓	6.60 ✓	57.60 ✓
79.20	81.00	.68 ✓	1.18 ✓	8.91 ✓
81.00	90.80	N/A	N/A	N/A
90.80	93.00	1.63 ✓	1.88 ✓	21.26 ✓
93.00	94.50	2.15 ✓	3.30 ✓	33.26 ✓
94.50	96.00	2.43 ✓	4.10 ✓	38.40 ✓
96.00	97.50	1.70 ✓	3.95 ✓	28.11 ✓
97.50	99.10	.73 ✓	1.15 ✓	9.94 ✓
99.10	100.60	1.55 ✓	2.98 ✓	20.23 ✓
100.60	115.80	N/A	N/A	N/A
115.80	116.70	1.83 ✓	1.85 ✓	31.20 ✓

MOORE SPECIFICO 4

HOLE NO:	U-110	LATITUDE:	10894.58 ✓	AZIMUTH:	0.00 ✓
HOLE LENGTH:	90.80	DEPARTURE:	7627.34 ✓	DIP:	-90.00 ✓
		ELEVATION:	1132.98 ✓		

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	55.70	N/A	N/A	N/A
55.70	57.90	2.25 ✓	3.35 ✓	35.31 ✓
57.90	59.40	3.98 ✓	5.76 ✓	61.37 ✓
59.40	61.00	2.85 ✓	3.35 ✓	40.46 ✓
61.00	62.50	2.53 ✓	2.25 ✓	33.26 ✓
62.50	64.00	2.93 ✓	4.40 ✓	44.23 ✓
64.00	65.50	3.00 ✓	2.30 ✓	50.40 ✓
65.50	66.80	1.58 ✓	3.00 ✓	15.09 ✓
66.80	90.80	N/A	N/A	N/A

HOLE NO: U-111 LATITUDE: 10749.23 AZIMUTH: 0.00 ✓
 HOLE LENGTH: 122.80 DEPARTURE: 7731.63 DIP: -90.00 ✓
 ELEVATION: 1156.10

DIP TESTS:	DEPTH	DIP	AZIMUTH
	46.00	-89.00	202.00
	91.00	-86.00	122.00
	123.00	-83.00	122.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	59.80	N/A	N/A	N/A
59.80	61.30	6.20 ✓	6.00 ✓	67.54 ✓
61.30	62.80	5.10 ✓	6.37 ✓	63.43 ✓
62.80	64.30	2.35 ✓	3.46 ✓	31.20 ✓
64.30	65.80	.40 ✓	.68 ✓	7.89 ✓
65.80	67.30	.55 ✓	.73 ✓	9.94 ✓
67.30	68.80	.38 ✓	.35 ✓	5.14 ✓
68.80	70.30	1.70 ✓	2.80 ✓	18.17 ✓
70.30	71.80	.85 ✓	1.10 ✓	13.03 ✓
71.80	73.30	.28 ✓	.43 ✓	6.17 ✓
73.30	74.80	.55 ✓	.73 ✓	7.20 ✓
74.80	76.30	.78 ✓	.23 ✓	8.23 ✓
76.30	77.80	.33 ✓	.63 ✓	5.14 ✓
77.80	79.30	.28 ✓	.73 ✓	6.17 ✓
79.30	80.80	.13 ✓	.25 ✓	5.14 ✓
80.80	82.30	.28 ✓	.70 ✓	6.17 ✓
82.30	83.80	.13 ✓	.20 ✓	2.06 ✓
83.80	85.30	.10 ✓	.30 ✓	2.06 ✓
85.30	86.80	.00 ✓	.00 ✓	.00 ✓
86.80	88.30	.38 ✓	.25 ✓	7.20 ✓
88.30	89.80	.05 ✓	.03 ✓	3.09 ✓
89.80	91.30	.00 ✓	.00 ✓	.00 ✓
91.30	92.80	.00 ✓	.00 ✓	.00 ✓
92.80	105.80	N/A	N/A	N/A
105.80	107.50	.02 ✓	.10 ✓	.00 ✓
107.50	122.80	N/A	N/A	N/A

OK

MOORE SPECIFIC 4

HOLE NO:	U-112	LATITUDE:	10893.52 ✓	AZIMUTH:	220.17 ✓
HOLE LENGTH:	45.70	DEPARTURE:	7626.34 ✓	DIP:	-59.25 ✓
		ELEVATION:	1132.96 ✓		

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	45.70	N/A	N/A	N/A

D I A M O N D D R I L L L O G M A S T E R F I L E

10751.02

HOLE NO: U-113
HOLE LENGTH: 102.70

LATITUDE: 10752.87
DEPARTURE: 7733.46 .97
ELEVATION: 1155.90

✓ AZIMUTH: 44.00
✓ DIP: -58.00

1156.56

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	62.10	N/A	N/A	N/A
62.10	63.60	5.56✓	4.36✓	67.54✓
63.60	65.10	2.90✓	2.50✓	43.54✓
65.10	66.60	7.23✓	5.15✓	85.72✓
66.60	68.10	.15✓	.15✓	.00✓
68.10	69.60	1.33✓	1.23✓	18.17✓
69.60	71.10	4.60✓	8.74✓	64.46✓
71.10	72.60	2.60✓	3.40✓	32.23✓
72.60	74.10	4.00✓	3.36✓	53.49✓
74.10	75.60	10.26✓	5.90✓	114.86✓
75.60	77.10	11.27✓	7.56✓	116.92✓
77.10	78.60	6.96✓	5.36✓	73.71✓
78.60	80.10	3.63✓	3.16✓	35.31✓
80.10	81.60	3.65✓	3.80✓	42.51✓
81.60	83.10	4.05✓	4.80✓	50.40
83.10	84.60	4.10✓	4.30✓	49.37✓
84.60	86.10	5.61✓	7.91✓	80.57✓
86.10	87.60	3.55✓	8.75✓	58.63✓
87.60	89.10	2.98✓	4.00✓	40.46✓
89.10	91.60	.80✓	1.28✓	13.03✓
91.60	93.60	.50✓	.53✓	9.94✓
93.60	102.70	N/A	N/A	N/A

MOORE SPECIAL 4

DIAMOND DRILL LOG MA

STER FILE

HOLE NO: U-114
HOLE LENGTH: 45.70

LATITUDE: 10891.95 ✓
DEPARTURE: 7625.06 ✓
ELEVATION: 1134.22 ✓

AZIMUTH: 222.04 ✓
DIP: 0.00 ✓

0.31

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	4.22 ✓	10.25 ✓	67.54 ✓
1.50	3.00	4.14 ✓	8.21 ✓	66.51 ✓
3.00	4.60	5.76 ✓	8.87 ✓	86.74 ✓
4.60	5.20	.68 ✓	1.45 ✓	8.23 ✓
5.20	6.10	4.15 ✓	6.76 ✓	58.63 ✓
6.10	7.60	5.55 ✓	5.86 ✓	78.86 ✓
7.60	9.10	3.08 ✓	5.15 ✓	55.54 ✓
9.10	10.70	.55 ✓	.45 ✓	10.97 ✓
10.70	13.70	.18 ✓	.28 ✓	3.09 ✓
13.70	16.50	.18 ✓	.30 ✓	3.09 ✓
16.50	18.30	4.80 ✓	8.26 ✓	71.66 ✓
18.30	19.80	3.13 ✓	6.73 ✓	50.40 ✓
19.80	21.30	2.73 ✓	3.45 ✓	44.23 ✓
21.30	22.90	1.93 ✓	3.33 ✓	32.23 ✓
22.90	24.40	2.33 ✓	3.85 ✓	35.31 ✓
24.40	25.90	1.48 ✓	3.10 ✓	28.46 ✓
25.90	27.40	2.20 ✓	4.35 ✓	40.46 ✓
27.40	29.00	1.53 ✓	2.18 ✓	28.46 ✓
29.00	30.50	.98 ✓	1.88 ✓	17.14 ✓
30.50	32.00	1.80 ✓	3.75 ✓	35.31 ✓
32.00	33.50	2.98 ✓	5.00 ✓	48.34 ✓
33.50	35.10	3.25 ✓	3.90 ✓	52.46 ✓
35.10	36.60	4.00 ✓	6.74 ✓	51.60 ✓
36.60	38.40	3.20 ✓	4.25 ✓	51.43 ✓
38.40	41.00	1.30 ✓	2.95 ✓	19.20 ✓
41.00	42.70	2.00 ✓	3.96 ✓	31.20 ✓
42.70	44.20	1.75 ✓	4.20 ✓	27.43 ✓
44.20	45.70	1.93 ✓	2.58 ✓	25.37 ✓

57.60

HOLE NO: U-115 LATITUDE: 10749.32 ✓ AZIMUTH: 226.02 ✓
 HOLE LENGTH: 74.00 DEPARTURE: 7732.82 ✓ DIP: -65.20 ✓
 ELEVATION: 1155.98 ✓


INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	27.00	N/A	N/A	N/A
27.00	28.50	3.85 ✓	6.22 ✓	55.54 ✓
28.50	31.30	1.65 ✓	2.65 ✓	24.34 ✓
31.30	74.00	N/A	N/A	N/A

MOORE
 SPEEDFLO 4

HOLE NO: U-116 LATITUDE: 10891.83 ✓
HOLE LENGTH: 68.60 DEPARTURE: 7625.10 ✓
ELEVATION: 1136.46 ✓ AZIMUTH: 225.03 ✓
DIP: 44.52 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	5.46 ✓	10.31 ✓	91.89 ✓
1.50	3.20	2.28 ✓	4.36 ✓	47.31 ✓
3.20	4.10	.18 ✓	.33 ✓	6.17 ✓
4.10	5.40	.45 ✓	.75 ✓	18.17 ✓
5.40	7.10	.02 ✓	.05 ✓	1.03 ✓
7.10	9.20	.01 ✓	.08 ✓	.00 ✓
9.20	11.10	4.34 ✓	6.13 ✓	70.63 ✓
11.10	19.10	N/A	N/A	N/A
19.10	21.30	2.53 ✓	3.66 ✓	41.49 ✓
21.30	22.90	1.60 ✓	2.48 ✓	28.46 ✓
22.90	24.40	4.43 ✓	6.90 ✓	67.54 ✓
24.40	26.00	4.85 ✓	4.90 ✓	70.63 ✓
26.00	43.40	N/A	N/A	N/A
43.40	45.00	.13 ✓	.23 ✓	3.09 ✓
45.00	47.20	4.50 ✓	7.69 ✓	63.43 ✓
47.20	48.80	3.78 ✓	7.21 ✓	55.54 ✓
48.80	50.30	3.10 ✓	6.51 ✓	51.43 ✓
50.30	51.80	.73 ✓	1.38 ✓	15.09 ✓
51.80	53.30	2.00 ✓	4.25 ✓	27.43 ✓
53.30	54.90	1.75 ✓	2.33 ✓	27.43 ✓
54.90	56.40	1.25 ✓	1.83 ✓	14.06 ✓
56.40	57.90	2.68 ✓	1.80 ✓	25.37 ✓
57.90	59.40	2.18 ✓	4.20 ✓	29.14 ✓
59.40	61.00	1.98 ✓	3.25 ✓	29.14 ✓
61.00	62.50	3.55 ✓	4.75 ✓	52.46 ✓
62.50	64.00	5.29 ✓	9.89 ✓	75.77 ✓
64.00	68.60	N/A	N/A	N/A

11.10 21.30
21.30 22.00
22.00 22.90



HOLE NO: U-117
 HOLE LENGTH: 61.00

LATITUDE: 10832.50
 DEPARTURE: 7651.50
 ELEVATION: 1125.22

AZIMUTH: 43.16
 DIP: -0.47

~~#31 est.~~
 1143.7 est. DJW.

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	3.00	2.38✓	5.00✓	44.23✓
3.00	4.60	1.40✓	4.20✓	33.26✓
4.60	6.10	1.10✓	2.80✓	26.40✓
6.10	7.60	1.70✓	3.63✓	28.46✓
7.60	9.60	3.00✓	6.05✓	53.49✓
9.60	15.50	N/A	N/A	N/A
15.50	17.00	1.00✓	1.30✓	23.31✓
17.00	18.50	4.20✓	7.96✓	70.63✓
18.50	20.00	2.70✓	2.70✓	36.34✓
20.00	21.50	3.00✓	5.93✓	50.40✓
21.50	23.40	2.55✓	4.56✓	40.46✓
23.40	61.00	N/A	N/A	N/A

MOORE
 SPEC'D TO 4

HOLE NO: U-118 LATITUDE: 10892.67✓
 HOLE LENGTH: 76.20 DEPARTURE: 7626.49✓
 ELEVATION: 1138.16✓ AZIMUTH: 248.24✓
 DIP: 74.34✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	.45✓	1.28✓	9.94✓
1.50	3.00	5.69✓	10.20✓	77.83✓
3.00	4.60	2.08✓	6.74✓	38.40✓
4.60	6.10	2.78✓	6.25✓	45.26✓
6.10	7.60	5.00✓	10.71✓	90.86✓
7.60	9.10	8.40✓	16.54✓	168.34✓
9.10	10.70	9.30✓	18.49✓	208.80✓
10.70	13.70	N/A	N/A	N/A
13.70	15.20	4.05✓	9.66✓	66.51✓
15.20	16.80	3.75✓	6.15✓	59.31✓
16.80	21.30	N/A	N/A	N/A
21.30	22.90	1.45✓	2.66✓	27.43✓
22.90	24.40	1.08✓	4.10✓	24.34✓
24.40	25.90	6.36✓	9.65✓	94.63✓
25.90	27.40	6.40✓	12.35✓	100.80✓
27.40	29.00	4.15✓	4.00✓	55.54✓
29.00	31.00	.15✓	.50✓	3.09✓
31.00	39.60	N/A	N/A	N/A
39.60	41.10	6.10✓	10.37✓	68.57
41.10	42.70	3.45✓	7.86✓	46.29✓
42.70	44.20	1.33✓	2.20✓	24.34✓
44.20	45.70	1.33✓	3.40✓	23.31✓
45.70	47.20	1.40✓	3.86✓	25.37✓
47.20	48.80	2.13✓	2.86✓	27.43✓
48.80	50.30	4.28✓	3.86✓	50.40✓
50.30	51.80	1.48✓	2.70✓	17.14✓
51.80	53.30	1.98✓	2.00✓	26.40✓
53.30	54.90	1.13✓	1.36✓	16.11✓
54.90	56.50	4.08✓	7.69✓	61.37✓
56.50	76.20	N/A	N/A	N/A

MOORE SPEIDRLO 4

HOLE NO: U-119 LATITUDE: 10656.15 ✓
 HOLE LENGTH: 103.60 DEPARTURE: 7650.75 ✓
 ELEVATION: 1160.60 ✓
 AZIMUTH: 0.00 ✓
 DIP: -90.00 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	4.60	6.56/	13.19/	130.97/
4.60	6.10	4.98/	8.60/	87.77/
6.10	7.60	4.98/	9.46/	80.57/
7.60	8.60	6.30/	9.89/	106.97/
8.60	57.90	N/A	N/A	N/A
57.90	59.40	3.08/	4.70/	50.40/
59.40	61.00	1.63/	2.43/	26.40/
61.00	62.50	7.53/	11.05/	111.09/
62.50	64.00	3.40/	4.86/	53.49/
64.00	65.50	.13/	1.05/	8.23/
65.50	67.10	3.50/	3.30/	55.54/
67.10	68.60	1.28/	.65/	27.43/
68.60	70.10	.75/	1.42/	21.26/
70.10	71.60	.10/	.40/	8.91/
71.60	73.20	.08/	.55/	12.00/
73.20	76.20	1.98/	2.60/	30.17/
76.20	103.60	N/A	N/A	N/A

S T E R F I L E

HOLE NO: U-120 LATITUDE: 10895.72 ✓
HOLE LENGTH: 61.00 DEPARTURE: 7628.35 ✓
 ELEVATION: 1134.22 ✓

AZIMUTH: 40.07 ✓
DIP: 0.00 ✓
 - 0.12 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	61.00	N/A	N/A	N/A

MOORE SHEDFILO 4

D I A M O N D D R I L L L O G M A S T E R F I L E

HOLE NO: U-121

LATITUDE: 10655.20
 DEPARTURE: 7649.75
 ELEVATION: 1160.60

AZIMUTH: 226.12 ✓
 DIP: -60.00

226.12

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	2.70	3.15 ✓	5.10 ✓	58.63 ✓
2.70	30.50	N/A	N/A	N/A
30.50	32.00	.38 ✓	.78 ✓	9.94 ✓
32.00	37.80	N/A	N/A	N/A
37.80	40.70	.28 ✓	.50 ✓	8.23 ✓

MOORE SHEET PLO 4

HOLE NO: U-122 LATITUDE: 10895.70 AZIMUTH: 44.00 ✓
 HOLE LENGTH: 91.40 DEPARTURE: 7628.30 DIP: -55.00 ✓
 ELEVATION: 1133.00

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	91.40	N/A	N/A	N/A

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-123

LATITUDE: 10657.80

10658.02

DEPARTURE: 7651.75

7652.82

AZIMUTH: 44.00

44.00

ELEVATION: 1160.61

DIP: -45.00

46.12

.58

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	3.00	4.25✓	8.75✓	80.57✓
3.00	4.60	5.26✓	10.09✓	89.83✓
4.60	6.10	3.88✓	7.72✓	70.63✓
6.10	7.60	4.98✓	8.27✓	91.89✓
7.60	9.10	6.10✓	9.44✓	99.77✓
9.10	10.70	2.20✓	4.80✓	54.51✓
10.70	12.20	2.38✓	6.50✓	34.29✓
12.20	13.70	2.85✓	6.33✓	54.51✓
13.70	15.20	2.38✓	6.82✓	39.43✓
15.20	16.80	3.08✓	6.17✓	69.60✓
16.80	18.30	4.48✓	7.45✓	85.72✓
18.30	21.30	2.11✓	2.13✓	43.54✓
21.30	22.90	.10✓	.15✓	2.74✓
22.90	24.40	4.50✓	5.15✓	92.92✓
24.40	25.90	2.85✓	2.68✓	55.54✓
25.90	31.00	N/A	N/A	N/A
31.00	32.50	4.65✓	8.35✓	75.77✓
32.50	34.00	4.55✓	7.97✓	62.40✓
34.00	45.70	N/A	N/A	N/A
45.70	47.20	10.75✓	19.60✓	174.52✓
47.20	48.80	11.06✓	23.63✓	185.49✓
48.80	50.30	4.98✓	8.82✓	60.34✓
50.30	51.80	5.82✓	9.35✓	82.63✓
51.80	53.30	4.45✓	7.98✓	60.34✓
53.30	54.90	9.53✓	18.75✓	124.12✓
54.90	56.40	.09✓	.30✓	15.09✓
56.40	57.90	.20✓	.15✓	18.17✓
57.90	59.40	.08✓	.45✓	9.94✓
59.40	61.00	.15✓	.60✓	15.09✓
61.00	62.50	.35✓	.78✓	15.09✓
62.50	64.00	1.33✓	1.83✓	21.26✓
64.00	65.50	6.82✓	9.68✓	78.86✓
65.50	67.10	1.00✓	1.40✓	20.23✓
67.10	68.60	.45✓	.70✓	19.20✓
68.60	70.10	.93✓	1.10✓	17.14✓
70.10	71.60	.10✓	.33✓	5.14✓
71.60	73.20	.15✓	.58✓	10.97✓
73.20	74.70	.08✓	.30✓	7.20✓
74.70	76.20	.10✓	.50✓	7.20✓
76.20	77.70	.12✓	.35✓	6.17✓
77.70	79.20	.13✓	.68✓	7.20✓
79.20	80.80	1.30✓	2.53✓	27.43✓
80.80	82.00	3.65✓	6.14✓	65.49✓
82.00	101.50	N/A	N/A	N/A
101.50	103.60	4.85✓	6.24✓	70.36✓
103.60	105.20	2.00✓	1.36✓	30.17✓
105.20	106.70	3.95✓	1.73✓	28.46✓
106.70	108.20	7.37✓	3.75✓	77.83✓
108.20	109.70	2.30✓	1.33✓	28.46✓
109.70	111.30	.40✓	.30✓	9.94✓

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-123

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
111.30	112.80	.15 ✓	.10 ✓	8.91 ✓
112.80	114.30	.23 ✓	.30 ✓	12.00 ✓
114.30	115.80	.22 ✓	.10 ✓	13.03 ✓
115.80	117.30	.20 ✓	.15 ✓	12.00
117.30	118.90	2.40 ✓	2.80 ✓	31.20 ✓

HOLE NO: U-124 LATITUDE: 10863.50 AZIMUTH: 0.00✓
 HOLE LENGTH: 91.40 DEPARTURE: 7597.70 DIP: -90.00✓
 ELEVATION: 1138.00

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	2.00✓	2.15✓	27.43✓
1.50	3.00	2.08✓	3.65✓	27.43✓
3.00	4.60	2.63✓	4.60✓	40.46✓
4.60	6.10	1.43✓	4.00✓	21.26✓
6.10	7.60	1.75✓	4.30✓	25.37✓
7.60	9.10	2.00✓	3.65✓	24.34✓
9.10	10.70	2.00✓	3.75✓	26.40✓
10.70	12.20	2.73✓	5.68✓	43.54✓
12.20	13.70	3.13✓	7.39✓	52.46✓
13.70	15.20	4.35✓	8.13✓	67.54✓
15.20	16.80	5.90✓	6.36✓	75.77✓
16.80	18.30	5.79✓	9.36✓	89.83✓
18.30	19.50	5.36✓	7.21✓	77.83✓
19.50	20.80	1.35✓	2.73✓	20.23✓
20.80	25.90	N/A	N/A	N/A
25.90	27.40	1.58✓	2.74✓	32.23✓
27.40	29.00	2.58✓	4.35✓	59.31✓
29.00	30.50	.73✓	1.25✓	17.14✓
30.50	32.00	1.45✓	1.05✓	22.29✓
32.00	33.50	1.48✓	2.95✓	33.26✓
33.50	35.10	1.87✓	3.85✓	38.40✓
35.10	36.60	1.78✓	2.88✓	43.54✓
36.60	37.60	5.75✓	6.77✓	85.72✓
37.60	38.70	N/A	N/A	N/A
38.70	41.10	8.09✓	17.89✓	126.17✓
41.10	42.70	14.98✓	22.56✓	226.97✓
42.70	45.00	N/A	N/A	N/A
45.00	47.20	6.71✓	14.90✓	125.14✓
47.20	48.80	6.27✓	5.15✓	80.57✓
48.80	50.30	5.24✓	6.32✓	70.63✓
50.30	51.80	3.15✓	3.85✓	45.26✓
51.80	91.40	N/A	N/A	N/A

MOORE SPEEDIFLO 4

HOLE NO: U-125
 HOLE LENGTH: 92.30

LATITUDE: 10748.61 ✓
 DEPARTURE: 7731.64 ✓
 ELEVATION: 1156.65 ✓

✓ AZIMUTH: 227.38 ✓
 ✓ DIP: -30.06 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	13.26 ✓	30.48 ✓	147.09 ✓
1.50	3.00	5.92 ✓	10.11 ✓	116.92 ✓
3.00	4.60	4.10 ✓	9.96 ✓	85.72 ✓
4.60	6.10	6.96 ✓	11.38 ✓	141.26 ✓
6.10	8.10	6.01 ✓	8.95 ✓	103.89 ✓
8.10	10.10	5.72 ✓	9.92 ✓	105.94 ✓
10.10	12.10	4.15 ✓	9.96 ✓	58.63 ✓
12.10	14.10	6.27 ✓	13.89 ✓	100.80 ✓
14.10	16.10	7.71 ✓	19.90 ✓	126.17 ✓
16.10	18.10	9.26 ✓	17.66 ✓	157.37 ✓
18.10	20.10	8.71 ✓	24.30 ✓	149.14 ✓
20.10	22.10	9.81 ✓	26.75 ✓	162.52 ✓
22.10	24.10	7.71 ✓	14.10 ✓	142.29 ✓
24.10	26.10	5.70 ✓	14.15 ✓	77.83 ✓
26.10	28.10	5.92 ✓	12.78 ✓	92.92 ✓
28.10	30.10	6.25 ✓	12.57 ✓	99.77 ✓
30.10	32.10	8.66 ✓	14.50 ✓	146.06 ✓
32.10	34.10	10.75 ✓	19.40 ✓	184.46 ✓
34.10	36.10	5.20 ✓	11.07 ✓	81.60 ✓
36.10	38.10	4.88 ✓	8.15 ✓	59.31 ✓
38.10	40.10	6.76 ✓	9.20 ✓	93.94 ✓
40.10	42.10	4.95 ✓	10.11 ✓	75.77 ✓
42.10	45.10	.48 ✓	.70 ✓	5.14 ✓
45.10	52.10	N/A	N/A	N/A
52.10	53.60	6.37 ✓	8.46 ✓	87.77 ✓
53.60	55.60	7.35 ✓	13.99 ✓	120.00 ✓
55.60	57.30	4.70 ✓	7.80 ✓	78.86 ✓
57.30	58.80	7.36 ✓	11.80 ✓	114.86 ✓
58.80	60.30	4.05 ✓	6.54 ✓	67.54 ✓
60.30	61.80	6.80 ✓	12.63 ✓	110.06 ✓
61.80	63.30	2.15 ✓	2.90 ✓	35.31 ✓
63.30	64.80	1.85 ✓	2.78 ✓	30.17 ✓
64.80	66.30	.83 ✓	1.38 ✓	22.29 ✓
66.30	67.80	.23 ✓	.83 ✓	14.06 ✓
67.80	69.30	.65 ✓	.78 ✓	20.23 ✓
69.30	71.30	.60 ✓	1.05 ✓	9.94 ✓
71.30	72.80	.20 ✓	.25 ✓	10.97 ✓
72.80	74.30	6.43 ✓	11.36 ✓	100.80 ✓
74.30	75.80	6.57 ✓	10.85 ✓	91.89 ✓
75.80	77.30	3.50 ✓	6.06 ✓	35.31 ✓
77.30	78.80	3.38 ✓	8.38 ✓	50.40 ✓
78.80	80.30	5.63 ✓	16.35 ✓	82.63 ✓
80.30	81.80	7.07 ✓	19.28 ✓	96.69 ✓
81.80	83.30	14.46 ✓	25.37 ✓	209.83 ✓
83.30	84.80	4.00 ✓	9.86 ✓	54.51 ✓
84.80	86.30	4.75 ✓	13.50 ✓	78.51 ✓
86.30	87.80	9.71 ✓	21.69 ✓	151.20 ✓
87.80	89.30	4.10 ✓	10.77 ✓	76.80 ✓
89.30	90.80	8.66 ✓	18.01 ✓	114.86 ✓
90.80	92.30	2.98 ✓	1.26 ✓	43.54 ✓

MOORE SPECIFIC 4

HOLE NO: U-125

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON

MOORE
SPEEDFILE 4

HOLE NO: U-126 LATITUDE: 10862.50 AZIMUTH: 224.00
 HOLE LENGTH: 144.80 DEPARTURE: 7597.00 DIP: -60.00
 ELEVATION: 1138.00

DIP TESTS: DEPTH DIP AZIMUTH
 112.70 -68.00 227.00
 144.80 -68.00 227.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	4.60	1.53✓	3.13✓	19.20✓
4.60	6.10	2.00✓	6.08✓	32.23✓
6.10	7.60	2.40✓	3.65✓	37.37✓
7.60	9.10	1.93✓	2.53✓	28.46✓
9.10	10.70	1.63✓	3.38✓	31.20✓
10.70	12.20	2.05✓	4.65	37.37✓
12.20	13.70	2.70✓	4.30✓	34.29✓
13.70	15.20	2.90✓	6.32✓	45.26✓
15.20	16.80	2.80✓	4.68✓	40.46✓
16.80	18.30	2.45✓	4.20✓	37.37✓
18.30	19.80	2.49✓	5.15✓	39.43✓
19.80	21.30	5.94✓	6.05✓	74.74✓
21.30	22.90	6.71✓	3.95✓	77.83✓
22.90	24.40	4.50✓	2.90✓	50.40✓
24.40	25.90	4.39✓	3.45✓	55.54✓
25.90	27.40	7.56✓	3.80✓	95.66✓
27.40	29.00	5.99✓	9.37✓	87.77✓
29.00	30.50	4.45✓	8.34✓	65.49✓
30.50	32.00	4.65✓	9.61✓	70.63✓
32.00	33.50	4.10✓	8.23✓	84.69✓
33.50	35.10	4.85✓	9.08✓	83.66✓
35.10	36.60	4.70✓	7.98✓	74.74✓
36.60	38.10	4.70✓	8.38✓	77.83✓
38.10	39.60	4.48✓	6.70✓	65.49✓
39.60	41.10	4.21✓	7.62✓	65.49✓
41.10	42.70	7.36✓	13.69✓	114.17✓
42.70	44.20	4.51✓	7.41✓	65.49✓
44.20	45.70	5.42✓	7.93✓	78.86✓
45.70	47.20	3.73✓	4.80✓	67.54✓
47.20	48.80	5.71✓	10.07✓	82.63✓
48.80	50.30	7.34✓	10.12✓	100.80✓
50.30	51.80	3.48✓	3.30✓	46.29✓
51.80	54.90	.61✓	1.30✓	8.91✓
54.90	58.30	1.12✓	2.33✓	17.14✓
58.30	74.00	N/A	N/A	N/A
74.00	76.20	.48✓	.98✓	8.91✓
76.20	77.70	1.20✓	2.20✓	22.29✓
77.70	79.20	5.53✓	9.58✓	93.94✓
79.20	80.80	4.63✓	7.31✓	70.63✓
80.80	82.30	2.10✓	3.40✓	40.46✓
82.30	83.80	3.53✓	4.70✓	45.26✓
83.80	85.30	2.93✓	4.95✓	42.51✓
85.30	86.90	.44✓	.48✓	12.00✓
86.90	88.40	1.42✓	2.43✓	21.26✓
88.40	89.90	3.10✓	4.70✓	51.43✓
89.90	91.40	6.38✓	9.96✓	88.80✓

4.55

No D.D. Record

HOLE NO: U-126

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
91.40	93.00	3.15✓	4.05✓	42.51✓
93.00	94.50	1.67✓	1.08✓	21.26✓
94.50	96.00	4.10✓	4.90✓	47.31✓
96.00	97.50	4.73✓	8.45✓	98.74✓
97.50	99.10	3.18✓	5.50✓	50.40✓
99.10	100.60	3.28✓	7.06✓	48.34✓
100.60	102.10	6.70✓	9.36✓	113.14✓
102.10	103.60	6.35✓	6.07✓	82.63✓
103.60	105.20	3.38✓	3.10✓	58.63✓
105.20	107.50	3.63✓	2.95✓	51.43✓
107.50	111.00	N/A	N/A	N/A
111.00	112.80	1.00✓	1.33✓	20.23✓
112.80	118.50	N/A	N/A	N/A
118.50	120.40	2.00✓	2.80✓	29.14✓
120.40	121.90	4.38✓	5.05✓	69.60✓
121.90	123.40	3.10✓	4.65✓	44.23✓
123.40	125.00	4.55✓	7.51✓	72.69✓
125.00	126.50	5.88✓	8.98✓	87.77✓
126.50	128.00	2.18✓	3.30✓	44.23✓
128.00	129.50	3.88✓	5.50✓	52.46✓
129.50	131.10	2.83✓	5.30✓	42.51✓
131.10	132.60	1.73	3.00	26.40
132.60	134.10	.08✓	.50✓	8.91✓
134.10	135.60	.13✓	.40✓	9.94✓
135.60	137.20	1.55✓	1.88✓	27.43✓
137.20	144.80	N/A	N/A	N/A

→ ? .70 1.65 20.23

CF

MOORE SPECIAL 4

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-127

LATITUDE: 10658.25

10657.61

45.46

4400

DEPARTURE: 7651.50

7652.47

AZIMUTH: 46.04

ELEVATION: 1161.82

.77

DIP: 1.29

0.0

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	3.00	9.41✓	13.98✓	140.23✓
3.00	4.60	10.72✓	18.36✓	137.14✓
4.60	5.80	1.28✓	2.48✓	17.14✓
5.80	7.30	.25✓	.40✓	5.14✓
7.30	8.70	7.30✓	10.76✓	93.94✓
8.70	10.20	6.20✓	15.01✓	96.69✓
10.20	11.70	1.53✓	2.50✓	30.17✓
11.70	13.70	8.26✓	12.41✓	87.77✓
13.70	15.20	4.80✓	10.51✓	95.66✓
15.20	16.80	6.90✓	12.04✓	80.57✓
16.80	18.30	5.80✓	11.07✓	65.49✓
18.30	19.80	2.65✓	5.15✓	36.34✓
19.80	21.30	6.28✓	12.48✓	63.09✓
21.30	22.90	5.85✓	10.77✓	99.77✓
22.90	24.40	6.18✓	12.90✓	96.69✓
24.40	25.90	7.27✓	15.27✓	100.80✓
25.90	27.40	.55✓	1.63✓	20.23✓
27.40	29.00	.15✓	.73✓	8.23✓
29.00	30.50	4.70✓	6.83✓	60.34✓
30.50	32.00	1.88✓	2.15✓	24.40✓
32.00	33.50	.38✓	.68✓	8.91✓
33.50	35.10	.15✓	.50✓	4.11✓
35.10	36.60	.28✓	.55✓	5.14✓
36.60	38.20	.53✓	.80✓	8.23✓
38.20	45.70	N/A	N/A	N/A

HOLE NO: U-128
HOLE LENGTH: 83.80

LATITUDE: 10863.30
DEPARTURE: 7598.00
ELEVATION: 1138.00

AZIMUTH: 44.00 ✓
DIP: -60.00 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	4.60	3.10✓	4.55✓	47.31✓
4.60	6.10	3.15✓	5.10✓	49.37✓
6.10	7.60	2.03✓	4.25✓	35.31✓
7.60	9.10	1.98✓	3.70✓	32.23✓
9.10	10.70	3.35✓	4.60✓	47.31✓
10.70	12.20	1.80✓	2.88✓	25.37✓
12.20	13.70	1.73✓	3.00✓	26.40✓
13.70	15.20	1.75✓	4.23✓	29.14✓
15.20	16.80	1.60✓	4.75✓	28.11✓
16.80	18.30	6.55✓	9.33✓	85.72✓
18.30	19.80	5.55✓	3.88✓	63.43✓
19.80	24.50	N/A	N/A	N/A
24.50	26.40	3.30✓	3.25✓	49.03✓
26.40	67.50	N/A	N/A	N/A
67.50	70.10	1.68✓	2.33	22.29✓
70.10	71.60	4.83✓	5.20✓	70.63✓
71.60	73.20	5.80✓	7.26✓	76.80✓
73.20	74.70	6.40✓	8.75✓	78.86✓
74.70	76.20	6.40✓	9.23✓	76.80✓
76.20	77.70	5.65✓	8.40✓	69.60✓
77.70	79.20	2.88✓	3.25✓	37.37✓
79.20	80.80	4.85✓	8.87✓	77.83✓
80.80	82.30	6.08✓	10.92✓	95.66✓
82.30	83.80	7.80✓	11.69✓	102.86✓

MOORE
SPEECHFIELD 4

HOLE NO: U-129 LATITUDE: 10850.00 AZIMUTH: 224.00 ✓
 HOLE LENGTH: 142.30 DEPARTURE: 7584.80 DIP: -55.00 ✓
 ELEVATION: 1137.60

DIP TESTS: DEPTH DIP AZIMUTH
 79.90 -61.00 226.00
 110.30 -63.00 226.00
 140.80 -64.00 227.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	5.00	N/A	N/A	N/A
5.00	6.70	3.65✓	4.70✓	53.49✓
6.70	8.70	4.20✓	4.15✓	70.63✓
8.70	10.70	3.00✓	2.75✓	40.46✓
10.70	12.70	2.98✓	2.10✓	38.40✓
12.70	14.70	1.23✓	.95✓	20.23✓
14.70	16.70	1.38✓	1.13✓	21.26✓
16.70	19.70	2.25✓	2.05✓	24.34✓
19.70	22.70	2.30✓	1.75✓	23.31✓
22.70	25.70	1.23✓	2.10✓	14.06✓
25.70	53.90	N/A	N/A	N/A
53.90	55.90	.33✓	.70✓	7.20✓
55.90	58.50	1.03✓	2.10✓	17.14✓
58.50	68.50	N/A	N/A	N/A
68.50	70.50	.23✓	.50✓	5.14✓
70.50	72.00	1.15✓	2.23✓	20.23✓
72.00	73.50	1.60✓	2.40✓	26.40✓
73.50	75.00	1.10✓	1.08✓	25.37✓
75.00	76.50	2.23✓	4.20✓	76.80✓
76.50	78.00	3.40✓	3.65✓	43.54✓
78.00	79.50	3.80✓	6.76✓	55.54✓
79.50	81.00	1.73✓	5.70✓	30.17✓
81.00	82.50	1.65✓	3.58✓	28.46✓
82.50	84.00	3.58✓	6.43✓	55.54✓
84.00	85.50	5.25✓	10.06✓	88.80✓
85.50	87.00	3.88✓	7.24✓	67.54✓
87.00	89.00	2.45✓	2.75✓	42.51✓
89.00	92.00	2.18	4.15✓	50.40
92.00	121.30	N/A	N/A	N/A
121.30	122.80	6.82✓	10.10✓	97.72✓
122.80	124.30	6.18✓	9.51✓	87.77✓
124.30	125.80	3.10✓	6.17✓	55.54✓
125.80	127.30	2.10✓	3.30✓	42.51✓
127.30	128.80	1.73✓	1.98✓	39.43✓
128.80	130.30	1.77✓	2.48✓	36.34✓
130.30	131.80	4.25✓	5.75✓	79.54✓
131.80	134.60	5.00✓	7.03✓	72.69✓
134.60	142.30	N/A	N/A	N/A

MOORE SPEEDFILE 4

HOLE NO: U-130 LATITUDE: 10862.88 ✓
 HOLE LENGTH: 45.70 DEPARTURE: 7597.28 ✓
 ELEVATION: 1142.72 ✓

✓ AZIMUTH: 250.47 ✓
 ✓ DIP: 84.40 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	3.00	1.75 ✓	1.08 ✓	25.37 ✓
3.00	8.50	N/A	N/A	N/A
8.50	11.00	2.55 ✓	4.35 ✓	40.46 ✓
11.00	18.00	N/A	N/A	N/A
18.00	19.50	3.25 ✓	6.17 ✓	45.26 ✓
19.50	21.30	4.33 ✓	7.86 ✓	64.46 ✓
21.30	22.90	3.80 ✓	6.95 ✓	54.51 ✓
22.90	24.40	1.70 ✓	3.30 ✓	29.14 ✓
24.40	25.90	1.78 ✓	2.03 ✓	24.34 ✓
25.90	27.40	3.48 ✓	3.05 ✓	47.31 ✓
27.40	29.00	4.13 ✓	3.15 ✓	59.31 ✓
29.00	30.50	2.03 ✓	3.25 ✓	33.26 ✓
30.50	32.00	1.18 ✓	1.40 ✓	10.97 ✓
32.00	33.50	2.20 ✓	1.33 ✓	20.23 ✓
33.50	34.70	1.43 ✓	1.66 ✓	16.11 ✓
34.70	36.60	2.43 ✓	4.43 ✓	39.43 ✓
36.60	37.80	3.45 ✓	6.00 ✓	54.51 ✓
37.80	45.70	N/A	N/A	N/A

D I A M O N D D R I L L L O G M A S T E R F I L E

HOLE NO: U-131

LATITUDE: 10655.40^{.19}

AZIMUTH: 225.46^{.30}

DEPARTURE: 7649.00 7650.00

DIP: -0.56

ELEVATION: 1161.75 72

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	3.00	4.88	8.55	79.54
3.00	4.60	5.26 ✓	8.80 ✓	90.86 ✓
4.60	5.50	6.26 ✓	11.88 ✓	96.69 ✓
5.50	15.40	N/A	N/A	N/A
15.40	16.80	4.80 ✓	6.63 ✓	72.69 ✓
16.80	45.70	N/A	N/A	N/A

4.55 8.58

①

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-132

LATITUDE: 10895.40

AZIMUTH: 44.00 ✓

DEPARTURE: 7628.70

DIP: 63.00 ✓

ELEVATION: 1138.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	15.00	N/A	N/A	N/A
15.00	16.80	3.38✓	6.45✓	67.54✓
16.80	43.50	N/A	N/A	N/A
43.50	44.60	1.85✓	3.05✓	27.43✓
44.60	51.80	N/A	N/A	N/A
51.80	53.50	3.25✓	7.08✓	51.43✓
53.50	62.00	N/A	N/A	N/A
62.00	64.00	3.93✓	4.65✓	59.31✓
64.00	65.50	3.65✓	6.35✓	52.46✓
65.50	67.10	1.05✓	1.55✓	15.09✓
67.10	68.60	.80✓	.90✓	9.94✓
68.60	70.10	.83✓	1.73✓	13.03✓
70.10	72.40	3.38✓	4.76✓	55.54✓
72.40	76.20	.78✓	1.25✓	17.14✓
76.20	83.70	N/A	N/A	N/A
83.70	85.30	2.18✓	4.00✓	42.51✓
85.30	86.90	2.78✓	4.76✓	55.54✓
86.90	88.40	2.25✓	4.90✓	43.54✓
88.40	89.90	2.65✓	4.46✓	58.63✓
89.90	91.40	3.28✓	4.80✓	53.49✓
91.40	93.00	2.10✓	3.10✓	35.31✓
93.00	94.50	1.80✓	3.90✓	25.37✓
94.50	96.00	2.33✓	4.46✓	32.23✓
96.00	97.50	3.00✓	2.66✓	43.54✓
97.50	99.10	2.13	2.70✓	32.23✓
99.10	100.60	3.00✓	4.96✓	43.54✓
100.60	102.10	2.88✓	3.16✓	39.43✓
102.10	103.60	2.08✓	5.25✓	33.26✓
103.60	105.20	.65✓	3.10✓	9.94✓
105.20	108.00	1.53✓	2.68✓	24.34✓
108.00	132.50	N/A	N/A	N/A

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-133

LATITUDE: 10657.⁷³
 DEPARTURE: 7652.⁵⁴
 ELEVATION: 1160.⁵³

→ 44.00 ✓
 AZIMUTH: ~~45.17~~
 ✓ DIP: -60.00 ✓

DIP TESTS: DEPTH 103.60 DIP -65.00 AZIMUTH 54.00

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	3.00	5.36✓	8.42✓	87.77✓
3.00	4.60	4.38✓	9.28✓	88.80✓
4.60	6.10	3.90✓	7.44✓	73.71✓
6.10	7.60	4.18✓	7.89✓	83.66✓
7.60	9.10	6.40✓	9.26✓	110.06✓
9.10	10.70	4.25✓	9.26✓	75.77✓
10.70	12.20	5.37✓	7.84✓	85.71✓
12.20	13.70	3.08✓	5.80✓	60.34✓
13.70	15.20	3.75✓	5.97✓	70.63✓
15.20	16.80	4.83✓	8.52✓	83.66✓
16.80	18.30	4.88✓	5.75✓	111.09✓
18.30	47.20	N/A	N/A	N/A
47.20	48.80	9.71✓	18.51✓	161.49✓
48.80	50.30	9.74✓	19.50✓	164.57✓
50.30	51.80	7.10✓	15.43✓	111.09✓
51.80	53.30	11.10✓	11.58✓	168.34✓
53.30	54.40	N/A	N/A	N/A
54.40	56.40	4.70✓	5.45✓	75.77✓
56.40	57.90	2.80✓	5.35✓	45.26✓
57.90	59.40	4.48✓	9.56✓	62.40✓
59.40	61.00	.83✓	1.85✓	14.74✓
61.00	62.50	.20✓	.98✓	8.91✓
62.50	64.00	.15✓	1.60✓	13.03✓
64.00	67.10	.10✓	.68✓	15.09✓
67.10	70.10	.18✓	.68✓	9.94✓
70.10	93.00	N/A	N/A	N/A
93.00	95.80	2.15✓	3.05✓	23.34✓
95.80	114.30	N/A	N/A	N/A
114.30	115.80	6.30✓	9.03✓	104.92✓
115.80	117.60	3.13✓	3.45✓	40.46✓
117.60	126.50	N/A	N/A	N/A

MOORE SPECIFIC 4

HOLE NO: U-135 LATITUDE: 10978.34 ✓ AZIMUTH: 44.00 ✓
 HOLE LENGTH: 190.50 DEPARTURE: 7540.54 ✓ DIP: -85.00 ✓
 ELEVATION: ~~1110.88~~ 1119.00 DJA.

DIP TESTS:	DEPTH	DIP	AZIMUTH
	89.90	-83.30	111.00
	137.20	-83.00	109.00
	182.90	-82.00	122.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.50	5.27 ✓	8.10 ✓	77.83 ✓
1.50	3.50	4.05 ✓	6.78 ✓	55.54 ✓
3.50	43.50	N/A	N/A	N/A
43.50	45.70	6.26 ✓	10.87 ✓	125.14 ✓
45.70	48.20	5.00 ✓	7.71 ✓	82.63 ✓
48.20	49.50	N/A	N/A	N/A
49.50	51.80	.20 ✓	.03 ✓	17.14 ✓
51.80	55.00	N/A	N/A	N/A
55.00	57.90	3.35 ✓	4.75 ✓	52.46 ✓
57.90	59.40	3.35 ✓	5.15 ✓	57.60 ✓
59.40	61.00	4.33 ✓	7.84 ✓	76.80 ✓
61.00	62.50	3.98 ✓	5.20 ✓	61.37 ✓
62.50	64.50	N/A	N/A	N/A
64.50	67.20	1.73 ✓	2.13 ✓	22.28 ✓
67.20	68.90	N/A	N/A	N/A
68.90	71.60	.81 ✓	1.25 ✓	8.91 ✓
71.60	74.30	.33 ✓	.50 ✓	3.09 ✓
74.30	82.00	N/A	N/A	N/A
82.00	83.80	.98 ✓	2.00 ✓	13.03 ✓
83.80	86.90	.68 ✓	1.28 ✓	7.20 ✓
86.90	105.30	N/A	N/A	N/A
105.30	108.20	3.45 ✓	5.15 ✓	65.49 ✓
108.20	111.30	2.10 ✓	3.65 ✓	29.14 ✓
111.30	125.50	N/A	N/A	N/A
125.50	128.50	.53 ✓	1.00 ✓	10.97 ✓
128.50	131.50	.25 ✓	.13 ✓	5.14 ✓
131.50	134.20	N/A	N/A	N/A
134.20	135.60	7.02 ✓	8.07 ✓	96.69 ✓
135.60	137.30	4.20 ✓	8.25 ✓	63.43 ✓
137.30	138.70	2.15 ✓	4.45 ✓	34.29 ✓
138.70	141.70	.05 ✓	.00 ✓	2.06 ✓
141.70	144.80	1.28 ✓	1.50 ✓	20.23 ✓
144.80	169.50	N/A	N/A	N/A
169.50	172.20	2.08 ✓	3.85 ✓	38.40 ✓
172.20	173.70	5.66 ✓	8.04 ✓	90.86 ✓
173.70	175.30	4.15 ✓	4.25 ✓	53.49 ✓
175.30	176.80	1.30 ✓	1.33 ✓	25.37 ✓
176.80	178.30	2.13 ✓	1.20 ✓	18.17 ✓
178.30	179.80	1.93 ✓	1.85 ✓	24.34 ✓
179.80	181.40	2.83 ✓	2.35 ✓	51.43 ✓
181.40	182.90	3.35 ✓	3.05 ✓	54.51 ✓
182.90	184.40	2.60 ✓	2.35 ✓	40.46 ✓
184.40	186.00	1.13 ✓	1.18 ✓	22.29 ✓
186.00	190.50	N/A	N/A	N/A

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-136

LATITUDE: 10655.91
10656.00

AZIMUTH: ~~246.0~~ 224
226.12

DEPARTURE: 7649.75 7650.78

✓DIP: 48.00

ELEVATION: 1163.49 .46

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	32.00	N/A	N/A	N/A
32.00	33.50	5.76✓	5.40✓	75.77✓
33.50	35.10	5.36✓	5.45✓	72.69✓
35.10	39.00	N/A	N/A	N/A
39.00	41.10	2.55✓	1.90✓	52.46✓
41.10	42.70	3.95✓	2.45✓	70.63✓
42.70	45.70	7.15✓	7.13✓	103.87✓
45.70	48.80	6.40✓	6.53✓	100.80✓
48.80	50.30	7.36✓	7.79✓	104.92✓
50.30	51.80	6.10✓	6.63✓	95.66✓
51.80	53.30	7.06✓	6.75✓	89.93 89.83
53.30	54.90	4.45✓	3.75✓	60.34✓
54.90	56.40	1.70✓	1.23✓	25.37✓
56.40	57.90	1.93✓	1.00✓	32.23✓
57.90	59.40	2.05✓	1.25✓	34.29✓
59.40	61.50	1.85✓	1.40✓	35.31✓
61.50	76.20	N/A	N/A	N/A

MOORE
SERIAL NO. 4

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-137

LATITUDE: 10658.⁴⁶₆₀

AZIMUTH: ~~44.23~~^{43.56}

DEPARTURE: ^{7651.45}_{7650.25}

✓DIP: ^{64.00}_{64.00}

ELEVATION: ^{1163.97}_{1164.00}

+ 65.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	61.00	N/A	N/A	N/A

MOORE SPEED PLO 4

HOLE NO: U-138 LATITUDE: 10808.03 ✓ AZIMUTH: 47.15 ✓
 HOLE LENGTH: 122.20 DEPARTURE: 7544.56 ✓ DIP: -48.54 ✓
 ELEVATION: 1133.91 ✓

DIP TESTS:	DEPTH	DIP	AZIMUTH
	45.70	-52.00	42.00
	91.40	-59.00	41.00
	121.90	-62.00	42.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	3.90	1.07 ✓	1.43 ✓	18.17 ✓
3.90	6.20	N/A	N/A	N/A
6.20	7.50	2.28 ✓	3.25 ✓	36.34 ✓
7.50	30.70	N/A	N/A	N/A
30.70	33.80	1.25 ✓	1.08 ✓	14.06 ✓
33.80	36.60	1.03 ✓	1.18 ✓	16.11 ✓
36.60	39.80	2.80 ✓	2.45 ✓	37.37 ✓
39.80	42.70	1.08 ✓	.45 ✓	17.14 ✓
42.70	46.00	N/A	N/A	N/A
46.00	49.00	2.38 ✓	1.05 ✓	26.40 ✓
49.00	52.10	1.00 ✓	1.35 ✓	15.09 ✓
52.10	55.10	1.93 ✓	.63 ✓	23.31 ✓
55.10	56.60	N/A	N/A	N/A
56.60	59.70	1.85 ✓	1.95 ✓	27.43 ✓
59.70	63.00	.54 ✓	.53 ✓	8.23 ✓
63.00	77.00	N/A	N/A	N/A
77.00	79.50	1.14 ✓	1.68 ✓	25.37 ✓
79.50	81.00	.09 ✓	.23 ✓	13.03 ✓
81.00	82.60	2.65 ✓	3.45 ✓	38.40 ✓
82.60	84.10	1.90 ✓	3.20 ✓	29.14 ✓
84.10	85.60	.35 ✓	.63 ✓	4.11 ✓
85.60	107.50	N/A	N/A	N/A
107.50	109.00	4.25 ✓	.82 ✓	61.37 ✓
109.00	110.50	.90 ✓	1.10 ✓	13.03 ✓
110.50	112.00	.65 ✓	1.08 ✓	9.94 ✓
112.00	113.50	.58 ✓	1.75 ✓	8.23 ✓
113.50	117.60	1.13 ✓	2.10 ✓	14.06 ✓
117.60	122.20	N/A	N/A	N/A

L05

8.23

MOORE SPEED LOG 4

D I A M O N D D R I L L L O G M A S T E R F I L E

HOLE NO: U-139

LATITUDE: 10657.10 ✓

AZIMUTH: 226.12 ✓

DEPARTURE: 7651.00 ✓

DIP: 75.00 ✓

ELEVATION: 1164.00 ✓

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	37.00	N/A	N/A	N/A
37.00	39.60	6.35 ✓	6.50 ✓	86.74 ✓
39.60	41.10	2.58 ✓	.75 ✓	36.34 ✓
41.10	42.70	3.70 ✓	3.40 ✓	65.49 ✓
42.70	44.20	5.97 ✓	5.15 ✓	82.63 ✓
44.20	47.00	4.55 ✓	3.77 ✓	59.31 ✓
47.00	64.50	N/A	N/A	N/A
64.50	67.50	4.10 ✓	3.25 ✓	54.51 ✓
67.50	76.20	N/A	N/A	N/A

3.75

HOLE NO: U-140
 HOLE LENGTH: 123.40

LATITUDE: 10978.48 ✓
 DEPARTURE: 7540.69 ✓
 ELEVATION: ~~1110.90~~ 1114.02 ✓

✓ AZIMUTH: 50.09 ✓
 ✓ DIP: -58.45 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	3.00	4.08 ✓	8.19 ✓	63.43 ✓
3.00	55.80	N/A	N/A	N/A
55.80	56.80	7.05 ✓	16.64 ✓	114.86 ✓
56.80	59.80	N/A	N/A	N/A
59.80	62.50	5.48 ✓	7.84 ✓	77.83 ✓
62.50	83.40	N/A	N/A	N/A
83.40	86.40	.88 ✓	1.46 ✓	58.63 ✓
86.40	87.50	3.98 ✓	5.20 ✓	16.11 ✓
87.50	98.00	N/A	N/A	N/A
98.00	100.00	3.63 ✓	6.53 ✓	53.49 ✓
100.00	100.60	N/A	N/A	N/A
100.60	102.10	.91 ✓	.80 ✓	17.14 ✓
102.10	104.30	.35 ✓	.53 ✓	5.14 ✓
104.30	123.40	N/A	N/A	N/A

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-141

LATITUDE: 10576.89
10577.30

✓ AZIMUTH: 227.05

DEPARTURE: 7744.00 7743.62

✓ DIP: 0.19

ELEVATION: 1178.56 1178.46

DIP TESTS:	DEPTH	DIP	AZIMUTH
	42.70	-1.00	231.00
	94.50	0.00	238.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	3.00	.58✓	1.45✓	20.23✓
3.00	4.60	.18✓	1.33✓	12.00✓
4.60	6.10	.60✓	.85✓	25.37✓
6.10	7.60	.45✓	1.35✓	12.00✓
7.60	9.10	4.65✓	6.03✓	54.51✓
9.10	10.70	7.64✓	13.31✓	106.97✓
10.70	12.20	9.64✓	13.74✓	122.06✓
12.20	13.70	7.11✓	11.16✓	106.97✓
13.70	15.20	6.40✓	11.44✓	89.83✓
15.20	16.80	7.36✓	10.92✓	106.97✓
16.80	18.30	4.48✓	3.56✓	55.54✓
18.30	19.80	5.56✓	4.68✓	70.63✓
19.80	21.30	6.64✓	6.22✓	94.63✓
21.30	24.00	5.99✓	7.62✓	84.69✓
24.00	59.80	N/A	N/A	N/A
59.80	61.30	5.51✓	9.25✓	86.74✓
61.30	62.70	4.45✓	8.64✓	75.77✓
62.70	96.30	N/A	N/A	N/A

MOORE SPEED FILE 4

HOLE NO: U-142 LATITUDE: 10976.42 ✓ AZIMUTH: 223.02 ✓
 HOLE LENGTH: 152.40 DEPARTURE: 7538.10 ✓ DIP: -29.33 ✓
 ELEVATION: ~~1111.22~~ 1114.31 ✓ DVA

DIP TESTS: DEPTH DIP AZIMUTH
 56.40 -33.00 225.00
 140.20 -46.00 220.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	2.10	10.76✓	14.99✓	190.63✓
2.10	4.50	8.44✓	10.61✓	141.26✓
4.50	6.10	1.98✓	3.05✓	33.26✓
6.10	7.60	6.66✓	10.56✓	100.80✓
7.60	9.10	3.93✓	7.14✓	58.29✓
9.10	11.70	4.60✓	7.46✓	73.71✓
11.70	21.30	N/A	N/A	N/A
21.30	22.90	.25✓	.15✓	7.20✓
22.90	24.40	2.48✓	6.25	44.23✓
24.40	25.90	4.58✓	10.66✓	106.97✓
25.90	27.40	1.68✓	3.55✓	28.11✓
27.40	29.00	.65✓	.83✓	14.06✓
29.00	30.50	.53✓	.60✓	9.94✓
30.50	33.50	.73✓	.73✓	15.09✓
33.50	36.60	.33✓	.15✓	7.89✓
36.60	39.60	.33✓	.70✓	8.91✓
39.60	41.10	3.80✓	8.23✓	72.69✓
41.10	42.70	4.18✓	9.60✓	76.80✓
42.70	44.20	4.05✓	8.40✓	68.57✓
44.20	45.70	5.25✓	10.66	93.94✓
45.70	47.20	5.92✓	14.33✓	114.86✓
47.20	48.80	.75✓	2.55✓	16.11✓
48.80	50.30	1.90✓	5.65✓	36.34✓
50.30	51.80	5.67✓	12.95✓	109.03✓
51.80	53.30	6.56✓	14.47✓	103.89✓
53.30	54.90	8.76✓	20.63✓	164.57✓
54.90	56.40	5.81✓	7.29✓	81.60✓
56.40	57.90	2.28✓	2.55✓	34.29✓
57.90	59.60	1.50✓	4.60✓	30.17✓
59.60	67.00	N/A	N/A	N/A
67.00	70.20	2.24✓	4.45✓	36.34
70.20	97.00	N/A	N/A	N/A
97.00	99.10	.90	1.45✓	15.09✓
99.10	100.60	.55✓	1.03✓	9.94✓
100.60	102.10	.70✓	.90✓	14.06✓
102.10	103.60	.63✓	.98✓	13.03✓
103.60	105.20	1.94✓	1.63✓	26.40✓
105.20	106.70	5.20✓	1.70✓	58.63✓
106.70	108.20	.80✓	.90✓	22.29✓
108.20	109.70	.05✓	.23✓	20.23✓
109.70	111.30	.05✓	.30✓	18.17✓
111.30	112.80	.08✓	.25✓	8.91✓
112.80	114.30	3.30✓	4.10✓	48.34✓
114.30	115.80	.04✓	.20✓	8.23✓
115.80	117.30	2.63✓	4.15✓	46.29✓
117.30	118.90	4.00✓	6.38✓	64.46✓

HOLE NO: U-142

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
118.90	120.40	2.13✓	4.05✓	25.37✓
120.40	121.90	2.38✓	4.30✓	45.26✓
121.90	123.40	5.20✓	8.89✓	70.63✓
123.40	125.00	6.69✓	12.04✓	91.89✓
125.00	126.50	4.65✓	8.13✓	71.66
126.50	128.70	3.78✓	8.43✓	64.46✓
128.70	152.40	N/A	N/A	N/A

MOORE SPEEDFILE 4

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-143

LATITUDE: 10579.20

10,580.14

AZIMUTH: 44.0

DJH

DEPARTURE: 7746.00 7747.12

DIP: -25.00

ELEVATION: 1177.58 1177.48

DIP TESTS:	DEPTH	DIP	AZIMUTH
	67.00	-34.00	47.00
	121.90	-44.00	54.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	4.60	.18	.63	7.20
4.60	7.60	.07	.43	5.14
7.60	10.30	.17	.45	7.20
10.30	13.40	.08	.10	4.11
13.40	16.80	.10	.23	28.11
16.80	19.80	.23	.58	7.89
19.80	22.90	.15	.43	5.14
22.90	25.90	.18	.13	7.89
25.90	29.00	.03	.23	2.06
29.00	32.00	.20	.43	7.20
32.00	35.10	.63	.48	15.09
35.10	38.10	.10	.23	5.14
38.10	42.70	.18	.63	5.14
42.70	76.80	N/A	N/A	N/A
76.80	79.20	1.40	2.13	20.23
79.20	80.80	2.05	2.50	45.26
80.80	82.30	N/A	N/A	N/A
82.30	83.80	3.40	2.85	48.34
83.80	85.30	7.75	8.86	100.80
85.30	86.90	6.40	4.55	63.43
86.90	88.40	4.30	3.65	47.31
88.40	89.90	.90	.93	9.94
89.90	91.40	.18	.35	6.17
91.40	93.00	1.73	1.90	20.23
93.00	94.50	2.90	3.40	32.23
94.50	96.00	3.10	2.10	35.31
96.00	97.50	.40	.08	8.23
97.50	99.10	5.93	6.95	68.57
99.10	100.60	4.38	7.46	67.54
100.60	102.10	3.08	6.52	42.51
102.10	105.20	.68	.84	9.94
105.20	108.20	.43	.60	8.91
108.20	111.30	1.03	1.15	10.97
111.30	114.30	.55	1.03	8.23
114.30	117.30	1.08	.70	18.17
117.30	120.40	.28	.40	7.20
120.40	123.40	.18	.50	4.11
123.40	126.50	.30	.60	3.09
126.50	132.60	N/A	N/A	N/A

MOORE SPEED PLO 4

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-145

LATITUDE: 10580.50

AZIMUTH: ^{44.0}46.12

DEPARTURE: 7746.50

DIP: -65.00

ELEVATION: 1178.50

DIP TESTS:	DEPTH	DIP	AZIMUTH
	45.72	-67.00	59.00
	91.44	-72.00	67.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	4.60	.08 ✓	.90 ✓	6.17 ✓
4.60	7.60	.07 ✓	1.28 ✓	5.14 ✓
7.60	10.70	.35 ✓	1.68 ✓	9.94 ✓
10.70	13.70	.25 ✓	.70 ✓	14.06 ✓
13.70	16.80	.05 ✓	.43 ✓	6.17 ✓
16.80	19.80	.18 ✓	.85 ✓	6.17 ✓
19.80	22.90	.13 ✓	.53 ✓	7.20 ✓
22.90	38.30	N/A	N/A	N/A
38.30	42.70	.04 ✓	.35 ✓	3.06 ✓
42.70	45.70	.04 ✓	.45 ✓	5.14 ✓
45.70	47.20	.75 ✓	2.75 ✓	15.09 ✓
47.20	48.80	.90 ✓	2.58 ✓	18.17 ✓
48.80	50.30	2.60 ✓	3.55 ✓	30.17 ✓
50.30	51.80	1.65 ✓	2.23 ✓	30.17 ✓
51.80	90.50	N/A	N/A	N/A
90.50	93.00	3.30 ✓	5.94 ✓	54.51 ✓
93.00	94.50	2.48 ✓	4.10 ✓	38.40 ✓
94.50	97.50	N/A	N/A	N/A
97.50	99.10	1.38 ✓	1.88 ✓	20.23 ✓
99.10	100.60	2.40 ✓	2.20 ✓	27.43 ✓
100.60	102.10	1.50 ✓	.75 ✓	19.20 ✓
102.10	103.60	.63 ✓	1.08 ✓	9.94 ✓
103.60	106.70	2.65 ✓	4.25 ✓	42.51 ✓
106.70	121.90	N/A	N/A	N/A

90
85
55

HOLE NO: U-146
 HOLE LENGTH: 73.70

LATITUDE: 10977.39 ✓
 DEPARTURE: 7539.85 ✓
 ELEVATION: 1115.61

✓ AZIMUTH: 245.56 ✓
 ✓ DIP: 88.38 ✓

1118.73 DJM

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	15.20	N/A	N/A	N/A
15.20	18.30	1.30 ✓	2.10 ✓	24.34 ✓
18.30	21.30	1.10 ✓	1.55 ✓	24.34 ✓
21.30	22.90	1.43 ✓	2.13 ✓	26.40 ✓
22.90	24.40	1.93 ✓	2.80 ✓	28.46 ✓
24.40	25.90	3.30 ✓	4.60 ✓	45.26 ✓
25.90	27.40	1.40 ✓	3.40 ✓	21.26 ✓
27.40	29.00	5.49 ✓	7.16 ✓	77.83 ✓
29.00	30.50	3.20 ✓	6.00 ✓	49.37 ✓
30.50	32.30	4.23 ✓	5.66 ✓	70.63 ✓
32.30	39.00	N/A	N/A	N/A
39.00	41.60	2.35 ✓	4.25 ✓	38.40 ✓
41.60	44.00	N/A	N/A	N/A
44.00	45.70	1.90 ✓	3.68 ✓	35.31 ✓
45.70	47.20	1.68 ✓	1.18 ✓	35.31 ✓
47.20	49.10	3.90 ✓	5.20 ✓	65.49 ✓
49.10	73.70	N/A	N/A	N/A

MOORE SPEEDFLO 4

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-147

LATITUDE: 10576.60

10577.50 ✓

AZIMUTH: 229.14

~~227.01~~

DEPARTURE: 7743.25

7744.22

DIP: 46.09

ELEVATION: 1180.90

1180.79

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	6.10	.17✓	2.23✓	5.14✓
6.10	9.10	.13✓	.88✓	7.20✓
9.10	12.20	.18✓	1.15✓	10.97✓
12.20	15.20	.10✓	.93✓	7.20✓
15.20	18.30	.13✓	.80✓	8.23✓
18.30	19.80	1.65✓	3.00✓	31.20✓
19.80	21.30	6.98✓	14.88✓	93.94✓
21.30	22.90	7.08✓	12.80✓	108.00✓
22.90	24.40	4.83✓	9.95✓	80.57✓
24.40	25.90	5.63✓	12.29✓	98.74✓
25.90	27.40	4.33✓	8.66✓	72.69✓
27.40	29.00	4.70✓	9.19✓	81.60✓
29.00	30.50	5.46✓	11.48✓	94.63✓
30.50	32.00	3.30✓	5.60	42.51✓
32.00	33.50	4.88✓	8.66	80.57✓
33.50	35.10	3.65✓	7.82✓	61.37✓
35.10	37.00	1.90✓	4.25✓	25.37✓
37.00	50.30	N/A	N/A	N/A
50.30	53.30	.09✓	1.05✓	32.23✓
53.30	54.90	.20✓	.85✓	18.17✓
54.90	56.40	.08✓	.45✓	10.97✓
56.40	57.90	.88✓	1.80✓	20.23✓
57.90	76.20	N/A	N/A	N/A

5.66
8.86

MOORE SPEED-FLO 4

HOLE NO: U-148
 HOLE LENGTH: 68.60

LATITUDE: 10848.99 ✓
 DEPARTURE: 7500.08 ✓
 ELEVATION: 1124.87 ✓

✓ AZIMUTH: 47.24 ✓
 ✓ DIP: -36.28 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	6.10	N/A	N/A	N/A
6.10	9.10	1.63 ✓	2.65 ✓	23.31 ✓
9.10	27.30	N/A	N/A	N/A
27.30	30.50	2.08 ✓	2.65 ✓	33.26 ✓
30.50	33.50	2.35 ✓	4.10 ✓	34.29 ✓
33.50	38.10	N/A	N/A	N/A
38.10	39.60	3.68 ✓	3.95 ✓	46.29 ✓
39.60	41.10	2.93 ✓	3.50 ✓	36.34 ✓
41.10	42.70	3.20 ✓	4.70 ✓	41.49 ✓
42.70	44.20	5.94 ✓	7.87 ✓	73.71 ✓
44.20	45.70	5.77 ✓	6.85 ✓	77.83 ✓
45.70	47.20	2.28 ✓	3.10 ✓	32.23 ✓
47.20	51.80	N/A	N/A	N/A
51.80	54.90	2.68 ✓	4.20 ✓	38.40 ✓
54.90	56.40	2.30 ✓	5.15 ✓	40.46 ✓
56.40	57.90	3.70 ✓	7.13 ✓	62.40 ✓
57.90	59.40	4.00 ✓	7.00 ✓	66.51 ✓
59.40	61.00	3.38 ✓	6.10 ✓	59.31 ✓
61.00	62.50	4.13 ✓	5.51 ✓	55.54 ✓
62.50	64.00	2.13 ✓	2.90 ✓	28.46 ✓
64.00	68.60	N/A	N/A	N/A

MOORE SPECIFIC 4

DIAMOND DRILL LOG MA

STER FILE

HOLE NO: U-149 LATITUDE: 10939.53 ✓ AZIMUTH: 0.00 ✓
 HOLE LENGTH: 182.90 DEPARTURE: 7502.63 ✓ ✓ DIP: -90.00 ✓
 ELEVATION: 1116.93 ✓

DIP TESTS: DEPTH DIP AZIMUTH
 106.60 -84.00 197.00
 152.40 -83.00 192.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	4.60	.73 ✓	.85 ✓	9.94 ✓
4.60	7.60	1.83 ✓	1.13 ✓	19.20 ✓
7.60	10.70	.58 ✓	.78 ✓	7.20 ✓
10.70	14.00	1.13 ✓	2.10 ✓	16.11 ✓
14.00	16.80	1.68 ✓	4.38 ✓	30.17 ✓
16.80	18.30	.73 ✓	2.55 ✓	20.23 ✓
18.30	19.80	1.78 ✓	4.20 ✓	35.31 ✓
19.80	21.30	2.90 ✓	6.15 ✓	48.34 ✓
21.30	22.90	2.60 ✓	4.35 ✓	44.23 ✓
22.90	24.40	5.11 ✓	9.54 ✓	97.72 ✓
24.40	25.90	3.70 ✓	6.60 ✓	58.63 ✓
25.90	28.00	N/A	N/A	N/A
28.00	30.50	1.93 ✓	2.20 ✓	31.20 ✓
30.50	33.00	5.49 ✓	9.65 ✓	90.86 ✓
33.00	38.10	N/A	N/A	N/A
38.10	40.00	2.30 ✓	2.80 ✓	36.34 ✓
40.00	97.40	N/A	N/A	N/A
97.40	100.00	.73 ✓	.68 ✓	14.06 ✓
100.00	104.50	N/A	N/A	N/A
104.50	106.40	2.05 ✓	3.60 ✓	30.17 ✓
106.40	108.20	6.57 ✓	8.48 ✓	106.97 ✓
108.20	109.70	2.23 ✓	2.75 ✓	34.29 ✓
109.70	111.30	2.90 ✓	3.20 ✓	40.46 ✓
111.30	112.80	2.65 ✓	1.55 ✓	48.34 ✓
112.80	121.00	N/A	N/A	N/A
121.00	122.00	4.80 ✓	7.40 ✓	70.63 ✓
122.00	123.00	N/A	N/A	N/A
123.00	124.00	3.78 ✓	3.40 ✓	50.40 ✓
124.00	125.30	N/A	N/A	N/A
125.30	128.00	4.30 ✓	5.50 ✓	64.46 ✓
128.00	129.50	3.18 ✓	4.85 ✓	47.31 ✓
129.50	131.60	5.20 ✓	8.17 ✓	79.54 ✓
131.60	134.10	1.45 ✓	2.03 ✓	25.37 ✓
134.10	137.20	.63 ✓	1.00 ✓	9.94 ✓
137.20	138.70	2.28 ✓	4.00 ✓	43.54 ✓
138.70	140.20	4.93 ✓	8.89 ✓	82.63 ✓
140.20	141.70	.38 ✓	.20 ✓	19.20 ✓
141.70	144.40	N/A	N/A	N/A
144.40	146.30	1.28 ✓	1.45 ✓	22.29 ✓
146.30	147.80	.53 ✓	.93 ✓	17.14 ✓
147.80	149.40	5.71 ✓	9.55 ✓	79.54 ✓
149.40	150.90	1.60 ✓	3.20 ✓	30.17 ✓
150.90	152.40	1.58 ✓	3.50 ✓	28.46 ✓
152.40	153.90	1.33 ✓	1.73 ✓	30.17 ✓
153.90	155.40	2.03 ✓	2.60 ✓	36.34 ✓
155.40	180.40	N/A	N/A	N/A

HOLE NO: U-150 LATITUDE: 10880.40 ✓ AZIMUTH: 218.15 ✓
 HOLE LENGTH: 152.40 DEPARTURE: 7445.21 ✓ DIP: -73.29 ✓
 ELEVATION: 1112.59 ^{1115.59} _{DJA.}

DIP TESTS: DEPTH DIP AZIMUTH
 60.96 -77.00 217.00
 121.90 -84.00 202.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	3.00	3.78 ✓	5.00 ✓	41.49 ✓
3.00	6.10	2.30 ✓	1.83 ✓	25.37 ✓
6.10	9.10	1.04 ✓	.35 ✓	16.11 ✓
9.10	12.20	.65 ✓	.35 ✓	13.03 ✓
12.20	15.20	.40 ✓	.63 ✓	6.17 ✓
15.20	18.30	1.65 ✓	2.23 ✓	20.23 ✓
18.30	21.30	2.23 ✓	2.35 ✓	26.40 ✓
21.30	22.90	1.70 ✓	3.80 ✓	20.23 ✓
22.90	24.40	1.20 ✓	1.85 ✓	17.14 ✓
24.40	25.90	5.19 ✓	7.49 ✓	70.63 ✓
25.90	27.40	1.20 ✓	1.10 ✓	30.17 ✓
27.40	29.00	4.60 ✓	5.10 ✓	71.66 ✓
29.00	31.50	6.52 ✓	9.90 ✓	110.06 ✓
31.50	47.50	N/A	N/A	N/A
47.50	49.40	4.88 ✓	10.51 ✓	91.89 ✓
49.40	92.50	N/A	N/A	N/A
92.50	94.50	1.53 ✓	2.78 ✓	23.31 ✓
94.50	137.20	N/A	N/A	N/A
137.20	138.70	2.08 ✓	4.10 ✓	31.20 ✓
138.70	140.20	9.19 ✓	16.37 ✓	143.32 ✓
140.20	141.70	2.60 ✓	6.26 ✓	46.29 ✓
141.70	152.40	N/A	N/A	N/A

MOORE SPEEDFILE 4

HOLE NO: U-151
 HOLE LENGTH: 76.20

LATITUDE: 10879.29 ✓
 DEPARTURE: 7443.32 ✓
 ELEVATION: 1115.77 / 1118.77

✓ AZIMUTH: 224.00 ✓
 ✓ DIP: 43.00 ✓

DJA.

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	5.58 ✓	9.55 ✓	86.74 ✓
1.50	3.00	8.25 ✓	11.51 ✓	113.14 ✓
3.00	4.60	10.42 ✓	15.28 ✓	143.32 ✓
4.60	6.10	12.23 ✓	20.76 ✓	185.49 ✓
6.10	7.60	1.40 ✓	3.00 ✓	23.31 ✓
7.60	9.10	2.25 ✓	4.30 ✓	35.31 ✓
9.10	10.70	2.58 ✓	4.25 ✓	37.37 ✓
10.70	12.20	2.53 ✓	4.50 ✓	39.43 ✓
12.20	13.70	3.10 ✓	5.95 ✓	51.43 ✓
13.70	15.20	2.28 ✓	4.35 ✓	39.43 ✓
15.20	16.80	9.19 ✓	11.71 ✓	132.00 ✓
16.80	18.30	6.17 ✓	5.80 ✓	94.63 ✓
18.30	20.40	4.05 ✓	4.65 ✓	60.34 ✓
20.40	54.50	N/A	N/A	N/A
54.50	56.40	4.89 ✓	3.70 ✓	71.66 ✓
56.40	57.90	1.93 ✓	2.30 ✓	47.31 ✓
57.90	59.40	4.80 ✓	4.70 ✓	70.63 ✓
59.40	61.00	10.44 ✓	8.57 ✓	124.46 ✓
61.00	62.50	15.89 ✓	12.42 ✓	192.69 ✓
62.50	65.10	6.62 ✓	5.00 ✓	111.09 ✓
65.10	76.20	N/A	N/A	N/A

MOORE SHEET 10 4

HOLE NO: U-152
HOLE LENGTH: 61.00

LATITUDE: 10939.20 ✓
DEPARTURE: 7502.38 ✓
ELEVATION: 1121.60 ✓

✓ AZIMUTH: 141.20 ✓
✓ DIP: 87.22 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	18.70	N/A	N/A	N/A
18.70	21.30	1.33 ✓	2.58 ✓	17.14 ✓
21.30	24.40	2.88 ✓	3.30 ✓	33.26 ✓
24.40	27.40	.78 ✓	.90 ✓	9.94 ✓
27.40	30.50	.33 ✓	.43 ✓	5.14 ✓
30.50	33.50	N/A	N/A	N/A
33.50	36.60	1.68 ✓	2.68 ✓	25.37 ✓
36.60	38.10	2.43 ✓	4.00 ✓	35.31 ✓
38.10	39.60	2.48 ✓	4.95 ✓	42.51 ✓
39.60	41.10	2.45 ✓	5.40 ✓	45.26 ✓
41.10	42.70	1.65 ✓	3.15 ✓	28.46 ✓
42.70	44.20	3.13 ✓	4.00 ✓	47.31 ✓
44.20	46.60	6.74 ✓	9.04 ✓	99.77 ✓
46.60	61.00	N/A	N/A	N/A

MOORE SPECIFIED 4

DIAMOND DRILL LOG MASTER FILE

224.00

HOLE NO: U-155

LATITUDE: 10575.20

AZIMUTH: 226.12

DEPARTURE: 7746.00

DIP: -56.00

ELEVATION: 1177.40


INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.50	N/A	N/A	N/A
1.50	4.60	.10✓	.30✓	5.14✓
4.60	7.60	.20✓	1.00✓	8.23✓
7.60	9.10	1.78✓	1.95✓	30.17✓
9.10	10.70	1.23✓	2.30✓	17.14✓
10.70	12.20	1.30✓	2.25✓	18.17✓
12.20	13.70	.55✓	1.35✓	12.00✓
13.70	15.20	.43✓	.58✓	10.97✓
15.20	16.80	.08✓	.98✓	4.11✓
16.80	19.80	.18✓	.60✓	8.91✓
19.80	22.90	.05✓	.98✓	4.11✓
22.90	25.90	.18✓	.73✓	8.23✓
25.90	29.00	.48✓	.73✓	8.91✓
29.00	32.00	.05✓	.78✓	9.94✓
32.00	35.10	.10✓	1.13✓	12.00✓
35.10	38.10	.13✓	2.08✓	13.03✓
38.10	41.10	.20✓	1.65✓	14.06✓
41.10	44.20	.63✓	1.88✓	22.29✓
44.20	47.20	.20✓	1.33✓	15.09✓
47.20	50.30	1.08✓	1.53✓	22.29✓
50.30	53.00	1.80✓	3.65✓	38.40✓
53.00	61.00	N/A	N/A	N/A

D I A M O N D D R I L L L O G M A S T E R F I L E

HOLE NO: U-157 LATITUDE: 10578.55 AZIMUTH: 0.00 ✓
 DEPARTURE: 7745.00 DIP: -90.00 ✓
 ELEVATION: 1177.40

DIP TESTS: DEPTH DIP AZIMUTH
 56.40 -84.00 105.00
 117.30 -79.00 79.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	4.60	.53✓	1.80✓	10.97✓
4.60	6.10	.83✓	1.70✓	16.11✓
6.10	7.60	2.25✓	2.75✓	30.17✓
7.60	9.10	1.30✓	1.08✓	22.29✓
9.10	10.70	.45✓	1.18✓	8.91✓
10.70	12.20	.08✓	.40✓	4.11✓
12.20	13.70	.13	1.95✓	7.20✓
13.70	15.20	.15✓	1.00✓	7.20✓
15.20	16.80	.13✓	.63✓	10.97✓
16.80	18.30	.65✓	1.10✓	22.29✓
18.30	22.90	.10✓	.18✓	6.17✓
22.90	24.40	.13✓	.13✓	6.17✓
24.40	27.40	.10✓	1.35✓	5.14✓
27.40	30.50	.02✓	.18✓	3.09✓
30.50	33.50	.05✓	.63✓	4.11✓
33.50	36.60	.02✓	.33✓	5.14✓
36.60	39.60	.02✓	.20✓	3.09✓
39.60	42.70	.05✓	.23✓	2.06✓
42.70	44.20	1.15✓	2.80✓	20.23✓
44.20	46.00	2.50✓	3.15✓	40.46✓
46.00	121.30	N/A	N/A	N/A
121.30	123.40	6.00✓	9.39✓	108.00✓
123.40	125.00	6.30✓	7.78✓	100.80✓
125.00	127.00	2.28✓	2.45✓	35.31✓
127.00	132.60	N/A	N/A	N/A
	129.40			
129.40	131.1	0.33	0.38	6.17
131.10	132.60	N/A	N/A	N/A



HOLE NO: U-158
 HOLE LENGTH: 74.30

LATITUDE: 10930.92 ✓
 DEPARTURE: 7409.54 ✓
 ELEVATION: 1108.33 ✓

AZIMUTH: 224.00 ✓
 DIP: 45.00 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	3.00	3.03 ✓	5.95 ✓	46.29 ✓
3.00	4.60	2.98 ✓	6.03 ✓	48.34 ✓
4.60	6.10	7.68 ✓	10.09 ✓	124.12 ✓
6.10	7.60	9.45 ✓	16.21 ✓	138.17 ✓
7.60	9.10	5.30 ✓	11.85 ✓	78.86 ✓
9.10	10.70	1.93 ✓	3.40 ✓	34.29 ✓
10.70	12.20	3.95 ✓	6.71 ✓	60.34 ✓
12.20	13.70	3.93 ✓	9.69 ✓	58.63 ✓
13.70	16.80	1.53 ✓	2.60 ✓	25.37 ✓
16.80	39.50	N/A	N/A	N/A ✓
39.50	42.70	2.00 ✓	1.78 ✓	25.37 ✓
42.70	45.50	N/A	N/A	N/A
45.50	47.20	6.30 ✓	6.45 ✓	95.66 ✓
47.20	68.60	N/A	N/A	N/A
68.60	70.20	.45	.58 ✓	10.97 ✓
70.20	74.30	N/A	N/A	N/A

.75

MOORE SPEEDFILE 4

D I A M O N D D R I L L L O G M A S T E R F I L E

HOLE NO: U-159

LATITUDE: 10579.20

10578.55

AZIMUTH: 32.20

DEPARTURE: 7746.00 7746.51

DIP: 66.53

ELEVATION: 1181.58

1181.48

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	19.70	N/A	N/A	N/A
19.70	21.30	.20✓	.20✓	8.91✓
21.30	22.90	.18✓	1.05✓	15.09✓
22.90	25.90	.05✓	.25✓	9.94✓
25.90	29.00	1.45✓	2.08✓	25.37✓
29.00	30.50	6.76✓	9.76✓	82.63✓
30.50	32.00	5.81✓	11.17✓	93.94✓
32.00	51.80	N/A	N/A	N/A
51.80	53.30	4.20✓	5.96✓	50.40✓
53.30	54.90	5.00✓	7.00✓	66.51✓
54.90	56.40	1.05✓	2.68✓	22.29✓
56.40	57.90	2.75✓	2.85✓	49.37✓
57.90	59.40	1.28✓	2.95✓	22.29✓
59.40	61.00	3.88✓	5.20✓	58.63✓
61.00	62.50	1.63✓	3.68✓	26.40✓
62.50	64.00	1.55✓	4.55✓	25.37✓
64.00	65.50	.50✓	1.13✓	10.97✓
65.50	67.10	1.50✓	2.63✓	26.40✓
67.10	68.60	2.53✓	3.60✓	48.34✓
68.60	70.10	1.05✓	2.10✓	21.26✓
70.10	71.60	1.20✓	3.20✓	20.23✓
71.60	73.20	5.84	2.45	30.17✓
73.20	74.70	2.30✓	5.30✓	33.26✓
74.70	76.20	3.23✓	7.57✓	47.31✓

245 5.84

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-161

LATITUDE: 10576.75 0577.30

✓ AZIMUTH: 225.04

DEPARTURE: 7744.00 7743.71

✓ DIP: -31.54

ELEVATION: 1177.48 1177.38

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	4.60	.33 ✓	.58 ✓	10.97 ✓
4.60	7.60	.18 ✓	.80 ✓	8.91 ✓
7.60	9.10	.13 ✓	.58 ✓	7.20 ✓
9.10	10.70	.55 ✓	1.10 ✓	12.00 ✓
10.70	12.20	1.18 ✓	2.73 ✓	20.23 ✓
12.20	13.70	3.48 ✓	3.48 ✓	52.46 ✓
13.70	15.20	1.75 ✓	1.75 ✓	28.46 ✓
15.20	16.80	7.86 ✓	9.22 ✓	95.66 ✓
16.80	18.30	3.18 ✓	3.60 ✓	44.23 ✓
18.30	19.80	1.70 ✓	.78 ✓	30.17 ✓
19.80	21.30	3.90 ✓	2.60 ✓	54.51 ✓
21.30	22.90	7.66 ✓	10.30 ✓	103.89 ✓
22.90	24.40	8.66 ✓	17.08 ✓	158.40 ✓
24.40	25.90	6.61 ✓	9.30 ✓	100.80 ✓
25.90	27.40	6.10 ✓	10.70 ✓	108.00 ✓
27.40	29.00	9.20 ✓	10.60 ✓	140.23 ✓
29.00	30.50	6.50 ✓	8.89 ✓	91.89 ✓
30.50	32.00	6.28 ✓	8.40 ✓	88.80 ✓
32.00	33.50	7.20 ✓	9.65 ✓	96.69 ✓
33.50	35.10	2.90 ✓	3.35 ✓	38.40 ✓
35.10	36.60	3.10 ✓	4.15 ✓	42.51 ✓
36.60	38.10	3.48 ✓	4.75 ✓	46.29 ✓
38.10	40.20	2.05 ✓	2.90 ✓	21.26 ✓
40.20	42.20	3.25 ✓	4.65 ✓	34.29 ✓
42.20	44.20	.23 ✓	.30 ✓	8.23 ✓
44.20	46.20	.08 ✓	.48 ✓	9.94 ✓
46.20	48.20	.18 ✓	.70 ✓	13.03 ✓
48.20	50.20	.88 ✓	1.00 ✓	20.23 ✓
50.20	53.30	5.15 ✓	4.80 ✓	70.63 ✓
53.30	54.40	N/A	N/A	N/A
54.40	56.10	6.01 ✓	8.40 ✓	72.69 ✓
56.10	59.40	N/A	N/A	N/A

HOLE NO: U-162
 HOLE LENGTH: 153.90

LATITUDE: 10930.50
 DEPARTURE: 7409.50
 ELEVATION: 1105.00

AZIMUTH: 224.00
 DIP: -65.00

DIP TESTS:	DEPTH	DIP	AZIMUTH
	38.10	-66.00	227.00
	77.70	-71.00	213.00
	123.40	-76.00	192.00

~~70.00~~
 -65.00
 DFB SURVEY

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	10.10	N/A	N/A	N/A
10.10	12.20	1.90✓	.43✓	27.43✓
12.20	15.20	.63✓	.33✓	12.00✓
15.20	18.30	1.55✓	.98✓	24.34✓
18.30	21.30	.78✓	1.25✓	9.94✓
21.30	24.40	1.20✓	2.05✓	16.11✓
24.40	25.90	.60✓	1.55✓	10.97✓
25.90	27.60	4.18✓	5.93✓	67.54✓
27.60	34.60	N/A	N/A	N/A
34.60	35.50	4.48✓	8.93✓	85.72✓
35.50	49.20	N/A	N/A	N/A
49.20	50.30	7.45✓	12.72✓	134.06✓
50.30	51.80	8.25✓	18.54✓	139.20✓
51.80	53.30	4.18✓	8.68✓	68.57✓
53.30	54.90	7.45✓	11.31✓	186.52✓
54.90	100.40	N/A	N/A	N/A
100.40	102.10	1.55✓	2.18✓	21.26✓
102.10	103.60	2.00✓	2.75✓	28.46✓
103.60	105.20	1.05✓	1.28✓	15.09✓
105.20	106.70	2.00✓	2.70✓	28.46✓
106.70	108.20	.93✓	1.08✓	15.09✓
108.20	109.70	.13✓	.13✓	5.14✓
109.70	111.30	.98✓	1.03✓	10.97✓
111.30	112.80	1.68✓	2.50✓	23.31✓
112.80	142.10	N/A	N/A	N/A
142.10	143.60	2.48✓	4.85✓	44.23✓
143.60	145.10	1.00✓	2.35✓	16.11✓
145.10	146.60	5.00✓	7.06✓	75.77✓
146.60	153.90	N/A	N/A	N/A

MOORE SPEEDFILE 4

D I A M O N D D R I L L L O G M A S T E R F I L E

HOLE NO: U-163

LATITUDE: 10527.35
 DEPARTURE: 7781.60 .06
 ELEVATION: 1185.49 ✓

10528.50
 224.07
 AZIMUTH: 226.19
 ✓ DIP: -1.01

DIP TESTS: DEPTH 61.00 DIP 0.00 AZIMUTH 229.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	3.00	.10 ✓	1.68 ✓	6.17 ✓
3.00	6.10	.33 ✓	1.13 ✓	13.03 ✓
6.10	8.00	2.15 ✓	3.75 ✓	35.31 ✓
8.00	60.50	N/A	N/A	N/A
60.50	63.10	4.75 ✓	8.64 ✓	77.83 ✓
63.10	86.90	N/A	N/A	N/A
86.90	90.10	2.50 ✓	1.90 ✓	33.26 ✓
90.10	93.10	3.95 ✓	2.40 ✓	39.43 ✓
93.10	96.00	1.73 ✓	1.45 ✓	24.34 ✓
96.00	112.10	N/A	N/A	N/A

MOORE
 SPECIFIC 4

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-165

LATITUDE: 10527.50
 DEPARTURE: 7781.10 .08
 ELEVATION: 1184.90 ✓

AZIMUTH: 228.19
 ✓ DIP: -38.58

10528.77

~~228.19~~

4410

az = 226.07

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	3.00	2.85 ✓	3.59 ✓	31.20 ✓
3.00	6.10	.75 ✓	1.15 ✓	9.94 ✓
6.10	7.60	.10 ✓	.70 ✓	7.20 ✓
7.60	9.50	.85 ✓	1.55 ✓	25.37 ✓
9.50	18.20	N/A	N/A	N/A
18.20	21.30	.73 ✓	.78 ✓	23.31 ✓
21.30	24.40	.13 ✓	1.13 ✓	12.00 ✓
24.40	27.40	1.15 ✓	1.30 ✓	25.37 ✓
27.40	30.50	.08 ✓	.70 ✓	13.03 ✓
30.50	33.50	.03 ✓	.48 ✓	10.97 ✓
33.50	36.60	.25 ✓	.75 ✓	10.97 ✓
36.60	38.10	2.23 ✓	2.95 ✓	38.40 ✓
38.10	39.60	1.83 ✓	2.23 ✓	32.23 ✓
39.60	41.60	1.10 ✓	.98 ✓	24.34 ✓
41.60	53.30	N/A	N/A	N/A

MOORE SPECIFIC 4

HOLE NO: U-166 LATITUDE: 11020.25
HOLE LENGTH: 182.90 DEPARTURE: 7495.50
ELEVATION: 1105.50 AZIMUTH: 0.00
DIP: -90.00

DIP TESTS: DEPTH DIP AZIMUTH
62.48 -84.00 214.00
108.20 -83.00 184.00
152.40 -84.00 150.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.80	2.23✓	4.48✓	52.46✓
1.80	3.00	3.38✓	6.88✓	66.51✓
3.00	4.60	.83✓	1.13✓	15.09✓
4.60	35.10	N/A	N/A	N/A
35.10	36.60	4.45✓	7.34✓	67.54✓
36.60	38.10	2.15✓	1.90✓	34.29✓
38.10	40.20	1.73✓	2.18✓	25.37✓
40.20	47.50	N/A	N/A	N/A
47.50	49.00	1.20✓	1.35✓	20.23✓
49.00	51.60	N/A	N/A	N/A
51.60	53.30	.95✓	1.70✓	17.14✓
53.30	54.90	.88✓	2.00✓	14.06✓
54.90	112.80	N/A	N/A	N/A
112.80	114.00	.70✓	.90✓	10.97✓
114.00	115.80	3.18✓	4.75✓	59.31✓
115.80	117.30	3.53✓	4.40✓	53.49✓
117.30	118.90	3.18✓	3.85✓	49.03✓
118.90	120.40	2.78✓	4.10✓	50.40✓
120.40	122.10	N/A	N/A	N/A
122.10	123.60	.98✓	1.68✓	15.09✓
123.60	131.10	N/A	N/A	N/A
131.10	132.60	.58✓	.55✓	9.94✓
132.60	134.10	1.45✓	2.48✓	22.29✓
134.10	135.60	.80✓	1.45✓	15.09✓
135.60	138.20	N/A	N/A	N/A
138.20	140.20	2.98✓	4.25✓	41.49✓
140.20	141.70	5.81✓	7.52✓	75.77✓
141.70	143.30	4.28✓	5.55✓	55.54✓
143.30	144.80	.22✓	.60✓	14.06✓
144.80	146.30	.65✓	.50✓	19.20✓
146.30	148.30	.56✓	.58✓	21.26✓
148.30	149.70	1.50✓	.95✓	29.14✓
149.70	150.50	4.05✓	6.01✓	56.57✓
150.50	169.10	N/A	N/A	N/A
169.10	170.70	.70✓	.75✓	8.91✓
170.70	182.90	N/A	N/A	N/A

MOORE SPEEDIFLO 4

HOLE NO: U-167

LATITUDE: 10527.00
 DEPARTURE: 7781.50.26
 ELEVATION: 1187.51 ✓

AZIMUTH: 227.46
 ✓ DIP: 42.56

10528.78

+38.0

az = 225.7
 224.26


INTERVAL		ASSAYS			
FROM	TO	PB %	ZN %	AG GM/TON	
0.00	3.00	.14	.78 ✓	7.20 ✓	.15
3.00	4.60	.78 ✓	1.28 ✓	22.29 ✓	
4.60	6.10	1.63 ✓	2.68 ✓	29.14 ✓	
6.10	11.60	N/A	N/A	N/A	
11.60	12.70	5.89 ✓	7.30 ✓	84.69 ✓	
12.70	32.00	N/A	N/A	N/A	
32.00	33.50	5.40 ✓	9.79 ✓	73.71 ✓	
33.50	35.10	4.73 ✓	6.76 ✓	68.57 ✓	
35.10	36.60	4.65 ✓	7.92 ✓	68.57 ✓	
36.60	38.10	4.05 ✓	4.25 ✓	69.60 ✓	
38.10	39.60	4.51	6.41 ✓	82.63 ✓	4.58
39.60	41.10	3.80 ✓	6.24 ✓	66.51 ✓	
41.10	42.70	4.30 ✓	6.93 ✓	73.71 ✓	
42.70	44.20	6.00 ✓	10.81 ✓	87.77 ✓	
44.20	45.70	5.40 ✓	6.74 ✓	70.63 ✓	
45.70	47.20	8.70 ✓	13.62 ✓	124.12 ✓	
47.20	48.80	7.03 ✓	14.71	104.92 ✓	14.77
48.80	61.80	N/A	N/A	N/A	

MOORE SPEEDFO 4

HOLE NO:	U-168	LATITUDE:	11018.00 ✓	✓ AZIMUTH:	224.00 ✓
HOLE LENGTH:	166.70	DEPARTURE:	7495.33 ✓	✓ DIP:	-60.00 ✓
		ELEVATION:	1105.49 ✓		

DIP TESTS:	DEPTH	DIP	AZIMUTH
	68.58	-71.00	210.00
	100.58	-74.00	203.00
	131.06	-75.00	192.00
	161.54	-76.30	117.00

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.80	7.51 ✓	19.38 ✓	161.49 ✓
1.80	3.70	2.58 ✓	8.03 ✓	48.34 ✓
3.70	4.60	3.40 ✓	7.47 ✓	63.43 ✓
4.60	6.10	4.73 ✓	10.95 ✓	74.74 ✓
6.10	7.60	2.43 ✓	7.95 ✓	44.23 ✓
7.60	9.10	.07 ✓	.10 ✓	1.03 ✓
9.10	16.40	.00 <i>N/A</i>	.00 <i>N/A</i>	.00 <i>N/A</i>
16.40	17.50	2.25 ✓	4.50 ✓	39.43 ✓
17.50	19.60	.00 <i>N/A</i>	.00 <i>N/A</i>	.00 <i>N/A</i>
19.60	20.60	.40 ✓	.73 ✓	12.00 ✓
20.60	30.90	.00 <i>N/A</i>	.00 <i>N/A</i>	.00 <i>N/A</i>
30.90	32.00	6.47 ✓	13.80 ✓	106.97 ✓
32.00	33.50	.96 ✓	1.75 ✓	12.00 ✓
33.50	35.10	4.50 ✓	8.02 ✓	73.71 ✓
35.10	36.60	4.13 ✓	7.62 ✓	70.63 ✓
36.60	38.10	3.35 ✓	6.26 ✓	56.57 ✓
38.10	115.00	.00 <i>N/A</i>	.00 <i>N/A</i>	.00 <i>N/A</i>
115.00	116.50	1.15 ✓	1.43 ✓	21.26 ✓
116.50	118.00	4.65 ✓	7.55 ✓	79.54 ✓
118.00	119.50	5.00 ✓	8.68 ✓	87.77 ✓
119.50	121.00	5.46 ✓	8.91 ✓	85.72 ✓
121.00	122.50	5.45 ✓	9.03 ✓	90.86 ✓
122.50	124.50	5.10 ✓	7.16 ✓	96.69 ✓
124.50	133.90	.00 <i>N/A</i>	.00 <i>N/A</i>	.00 <i>N/A</i>
133.90	135.60	3.28 ✓	2.70 ✓	53.49 ✓
135.60	137.20	2.13 ✓	1.30 ✓	33.26 ✓
137.20	138.70	4.50 ✓	7.08 ✓	65.49 ✓
138.70	140.20	4.00 ✓	8.06 ✓	61.37 ✓
140.20	141.70	5.20 ✓	9.24 ✓	95.66 ✓
141.70	143.30	5.90 ✓	9.59 ✓	90.86 ✓
143.30	144.80	5.00 ✓	8.01 ✓	83.66 ✓
144.80	146.30	.63 ✓	1.05 ✓	13.03 ✓
146.30	147.80	.20 ✓	.55 ✓	9.94 ✓
147.80	150.00	.00 <i>N/A</i>	.00 <i>N/A</i>	.00 <i>N/A</i>
150.00	150.90	.10 ✓	.18 ✓	7.20 ✓
150.90	152.40	1.00 ✓	1.05 ✓	20.23 ✓
152.40	153.90	3.85 ✓	6.93 ✓	56.57 ✓
153.90	155.40	3.90 ✓	6.53 ✓	65.49 ✓
155.40	156.50	4.65 ✓	6.35 ✓	65.49 ✓
156.50	166.70	N/A	N/A	N/A



DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-169

LATITUDE: 10484.50³⁵

AZIMUTH: ~~46.10~~ 43.59 DJA

DEPARTURE: 7822.00 7821.42

✓DIP: -0.14

ELEVATION: 1193.07✓

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	2.10	N/A	N/A	N/A
2.10	3.00	.05✓	.43✓	6.17✓
3.00	4.60	.04✓	.93✓	7.20✓
4.60	6.10	.50✓	.68✓	9.94✓
6.10	7.60	.08✓	.25✓	5.14✓
7.60	9.10	.08✓	.58✓	8.91✓
9.10	10.70	.05✓	.50✓	9.94✓
10.70	13.70	N/A	N/A	N/A
13.70	15.20	.04✓	.18✓	7.20✓
15.20	16.80	.15✓	.38✓	8.91✓
16.80	18.30	.05✓	.15✓	5.14✓
18.30	19.80	.18✓	.33✓	8.23✓
19.80	21.90	.13✓	.18✓	5.14✓
21.90	23.50	.08✓	.08✓	2.06✓
23.50	45.70	N/A	N/A	N/A

DIAMOND DRILL LOG MASTER FILE

223.00

HOLE NO: U-171

LATITUDE: 10481.25
 DEPARTURE: 7818.80.33
 ELEVATION: 1192.87

AZIMUTH: 225.12
 ✓DIP: 0.20

10480.99

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.50	.03 ✓	.15 ✓	9.94 ✓
1.50	3.00	.04 ✓	.30 ✓	10.97 ✓
3.00	4.60	.05 ✓	.58 ✓	12.00 ✓
4.60	6.60	.03 ✓	.45 ✓	5.14 ✓
6.60	15.10	N/A	N/A	N/A
15.10	16.80	1.60 ✓	1.70 ✓	27.43 ✓
16.80	18.30	4.48 ✓	5.70 ✓	73.71 ✓
18.30	30.50	N/A	N/A	N/A

MOORE
 SPECIFIED 4

HOLE NO: U-172 LATITUDE: 11017.45 ✓ AZIMUTH: 224.00 ✓
 HOLE LENGTH: 121.90 DEPARTURE: 7494.88 ✓ DIP: -24.00 ✓
 ELEVATION: 1105.82 ✓

DIP TESTS: DEPTH DIP AZIMUTH
 45.72 -28.00 221.00
 91.44 -40.00 219.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.80	N/A	N/A	N/A
1.80	3.30	6.87 ✓	15.93 ✓	146.06 ✓
3.30	4.60	9.43 ✓	20.32 ✓	175.53 ✓
4.60	6.10	4.05 ✓	6.90 ✓	85.72 ✓
6.10	7.20	3.80 ✓	13.66 ✓	67.54 ✓
7.20	14.00	.00 ✓	.00 ✓	.00 ✓
14.00	15.20	6.89 ✓	12.60 ✓	122.06 ✓
15.20	16.80	7.47 ✓	13.10 ✓	146.06 ✓
16.80	18.30	5.49 ✓	9.90 ✓	93.94 ✓
18.30	19.80	4.35 ✓	6.70 ✓	67.54 ✓
19.80	21.30	2.80 ✓	3.85 ✓	45.26 ✓
21.30	22.90	3.55 ✓	7.43 ✓	65.49 ✓
22.90	24.40	3.18 ✓	6.38 ✓	54.52 ✓
24.40	25.90	1.30 ✓	3.10 ✓	22.29 ✓
25.90	27.40	3.78 ✓	8.27 ✓	60.34 ✓
27.40	29.00	3.60 ✓	8.09 ✓	54.51 ✓
29.00	30.50	1.28 ✓	2.70 ✓	19.20 ✓
30.50	32.00	4.50 ✓	8.25 ✓	63.43 ✓
32.00	33.50	5.21 ✓	9.00 ✓	82.63 ✓
33.50	35.10	.53 ✓	.15 ✓	8.23 ✓
35.10	36.60	2.80 ✓	5.35 ✓	43.51 ✓
36.60	38.10	3.30 ✓	8.05 ✓	60.34 ✓
38.10	39.60	3.75 ✓	7.85 ✓	64.46 ✓
39.60	40.60	2.30 ✓	4.25 ✓	46.29 ✓
40.60	40.90	.00 ✓	.00 ✓	.00 ✓
40.90	41.30	1.50 ✓	2.03 ✓	30.17 ✓
41.30	49.20	.00 ✓	.00 ✓	.00 ✓
49.20	50.30	4.23 ✓	6.40 ✓	62.06 ✓
50.30	51.80	6.23 ✓	8.84 ✓	85.72 ✓
51.80	53.30	6.28 ✓	9.24 ✓	89.83 ✓
53.30	54.90	4.00 ✓	8.76 ✓	61.37 ✓
54.90	56.40	3.28 ✓	7.50 ✓	55.54 ✓
56.40	57.90	2.40 ✓	5.83 ✓	41.49 ✓
57.90	59.40	5.56 ✓	8.50 ✓	82.63 ✓
59.40	61.00	1.38 ✓	2.55 ✓	23.31 ✓
61.00	62.50	.50 ✓	1.08 ✓	9.94 ✓
62.50	64.00	.68 ✓	1.88 ✓	12.00 ✓
64.00	65.00	.50 ✓	1.00 ✓	8.23 ✓
65.00	70.10	.00 ✓	.00 ✓	.00 ✓
70.10	71.60	1.55 ✓	2.43 ✓	20.23 ✓
71.60	73.20	1.10 ✓	2.10 ✓	17.14 ✓
73.20	94.50	.00 ✓	.00 ✓	.00 ✓
94.50	96.00	3.43 ✓	3.90 ✓	49.37 ✓
96.00	97.50	3.08 ✓	4.00 ✓	35.31 ✓
97.50	99.10	1.13 ✓	1.20 ✓	21.26 ✓
99.10	100.60	.50 ✓	.65 ✓	17.14 ✓

175.54

43.54

HOLE NO: U-172

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
100.60	102.10	1.20✓	1.15✓	28.11✓
102.10	103.60	4.05✓	4.30✓	44.23✓
103.60	105.20	2.18✓	2.05✓	25.37✓
105.20	106.70	1.83✓	3.03✓	27.43✓
106.70	108.20	2.30✓	2.15✓	40.46✓
108.20	109.70	.50✓	1.00✓	10.97✓
109.70	111.30	.55✓	.85✓	13.03✓
111.30	112.80	1.78✓	.93✓	24.34✓
112.80	114.30	1.68✓	.65✓	23.31✓
114.30	115.80	.98✓	1.53✓	25.37✓
115.80	117.30	6.73✓	11.29✓	120.00✓
117.30	118.90	2.65✓	2.85✓	46.29✓
118.90	120.40	2.48✓	2.65✓	40.46✓
120.40	121.90	4.65✓	9.13✓	66.51✓

MOORE
SPEEDIFLO 4

DIAMOND DRILL LOG MASTER FILE

22612

HOLE NO: U-173

LATITUDE: 10481.25

AZIMUTH: 226.12

DEPARTURE: 7818.80

DIP: -53.00

ELEVATION: 1192.80

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	3.00	3.10✓	7.48✓	55.54✓
3.00	14.30	N/A	N/A	N/A
14.30	15.30	.35✓	.80✓	8.91✓
15.30	18.30	.45✓	.70✓	7.89✓
18.30	21.30	N/A	N/A	N/A
21.30	22.90	.23✓	.65✓	5.14✓
22.90	24.40	.05✓	.38✓	2.06✓
24.40	33.50	N/A	N/A	N/A
33.50	34.50	.10✓	.08✓	4.11✓
34.50	36.60	1.25✓	.25✓	21.26✓
36.60	38.10	1.70✓	1.40✓	22.29✓
38.10	39.60	1.63✓	1.25✓	17.14✓
39.60	41.10	.05✓	.13✓	4.11✓
41.10	42.70	.55✓	.33✓	15.09✓
42.70	44.20	1.60✓	1.38✓	28.46✓
44.20	45.70	2.40✓	2.00✓	47.31✓
45.70	47.20	.50✓	.28✓	14.06✓
47.20	48.80	1.03✓	.75✓	21.26✓
48.80	50.30	1.35✓	1.55✓	19.20✓
50.30	51.80	N/A	N/A	N/A
51.80	54.00	.28✓	.38✓	8.23✓
54.00	57.90	N/A	N/A	N/A

1.33

MOORE
SPECIFIC 4

D I A M O N D D R I L L L O G M A S T E R F I L E

HOLE NO: U-174

LATITUDE: 11020.50

AZIMUTH: 0.00 ✓

DEPARTURE: 7495.50

DIP: 90.00 ✓

ELEVATION: 1109.30

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	18.30	N/A	N/A	N/A
18.30	20.30	2.98 ✓	4.85 ✓	40.46 ✓
20.30	26.50	.00	.00	.00
26.50	28.00	2.28 ✓	4.90 ✓	39.43 ✓

MOORE
SPECIFIC

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-175

LATITUDE: 10484.⁰⁵~~00~~ DJH


AZIMUTH: 44.39^{12.28} DJH

DEPARTURE: ~~7822.00~~ 7821.38 DJH

✓DIP: -35.11

ELEVATION: 1192.32

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.20	.13	.73	12.00
1.20	2.70	.25	1.50	10.97
2.70	4.60	.10	.38	8.23
4.60	6.10	.08	.68	9.94
6.10	42.70	N/A	N/A	N/A
42.70	43.70	.58	.30	10.97
43.70	44.60	3.43	4.40	53.49
44.60	45.60	1.08	.90	20.23
45.60	53.30	N/A	N/A	N/A



HOLE NO: U-176 LATITUDE: 11052.88 ✓
 HOLE LENGTH: 170.70 DEPARTURE: 7445.67 ✓
 ELEVATION: 1100.72 ✓
 AZIMUTH: 224.00 ✓
 DIP: -70.00 ✓

DIP TESTS: DEPTH DIP AZIMUTH
 76.20 -72.00 204.00
 152.40 -70.00 182.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	28.00	N/A	N/A	N/A
28.00	30.80	4.00 ✓	8.64 ✓	80.57 ✓
30.80	58.50	.00	.00	.00
58.50	60.60	4.88 ✓	8.33 ✓	67.54 ✓
60.60	62.80	2.55 ✓	3.80 ✓	44.23 ✓
62.80	109.70	.00	.00	.00
109.70	111.30	.55 ✓	1.08 ✓	12.00 ✓
111.30	112.80	.70 ✓	.95 ✓	14.06 ✓
112.80	114.30	1.00 ✓	.83 ✓	20.23 ✓
114.30	115.80	1.80 ✓	3.03 ✓	34.29 ✓
115.80	117.30	5.25 ✓	7.51 ✓	72.69 ✓
117.30	150.80	.00	.00	.00
150.80	152.40	4.23 ✓	6.87 ✓	72.69 ✓
152.40	153.90	5.49 ✓	7.93 ✓	102.86 ✓
153.90	155.40	5.33 ✓	7.04 ✓	75.77 ✓
155.40	157.00	2.95 ✓	4.05 ✓	48.34 ✓
157.00	158.50	1.63 ✓	1.78 ✓	29.14 ✓
158.50	160.00	2.60 ✓	3.80 ✓	41.49 ✓
160.00	162.00	4.68 ✓	9.37 ✓	69.60 ✓
162.00	170.70	N/A	N/A	N/A

MOORE SPEEDFILE 4

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-177

LATITUDE: 10483.⁹⁵85 DJH

AZIMUTH: 53.53 51.41 DJH

DEPARTURE: 7825.00 7821.13 DJH

ELEVATION: 1195.12 ✓

✓DIP: 42.22

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	3.00	.15 ✓	.45 ✓	8.91 ✓
3.00	4.60	1.21 ✓	.98 ✓	20.23 ✓
4.60	6.10	.94 ✓	1.43 ✓	16.11 ✓
6.10	7.60	.65 ✓	.60 ✓	15.09 ✓
7.60	10.70	.30 ✓	.85 ✓	10.97 ✓
10.70	13.70	.14 ✓	.58 ✓	8.91 ✓
13.70	16.70	.49 ✓	.63 ✓	13.03 ✓
16.70	19.70	.35 ✓	.35 ✓	10.97 ✓
19.70	30.50	N/A	N/A	N/A
30.50	33.50	.08 ✓	.18 ✓	6.17 ✓
33.50	36.60	N/A	N/A	N/A
36.60	38.10	2.68 ✓	3.35 ✓	34.29 ✓
38.10	39.60	.58 ✓	1.30 ✓	9.94 ✓
39.60	42.70	N/A	N/A	N/A
42.70	44.20	.06 ✓	.10 ✓	5.14 ✓
44.20	45.70	N/A	N/A	N/A
45.70	47.20	.83 ✓	.85 ✓	13.03 ✓
47.20	48.80	.10 ✓	.08 ✓	5.14 ✓
48.80	50.30	2.38 ✓	3.58 ✓	38.40 ✓
50.30	51.80	.08 ✓	.18 ✓	5.14 ✓
51.80	53.30	.05 ✓	.08 ✓	5.14 ✓
53.30	65.50	N/A	N/A	N/A

MOORE SPEED-FLO 4

HOLE NO: U-178
 HOLE LENGTH: 70.10

LATITUDE: 11053.12 ✓
 DEPARTURE: 7446.15 ✓
 ELEVATION: 1104.90 ✓

✓ AZIMUTH: 56.15 ✓
 ✓ DIP: 77.04 ✓
 76.49

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	4.60	4.51 ✓	7.36 ✓	60.34 ✓
4.60	6.10	2.15 ✓	4.65 ✓	35.31 ✓
6.10	7.60	1.90 ✓	4.10 ✓	28.46 ✓
7.60	9.10	4.55 ✓	10.77 ✓	74.74 ✓
9.10	10.70	5.24 ✓	9.66 ✓	87.77 ✓
10.70	12.20	2.35 ✓	3.44 ✓	33.26 ✓
12.20	13.70	1.60 ✓	1.90 ✓	23.31 ✓
13.70	15.20	.23 ✓	.36 ✓	5.14 ✓
15.20	16.80	2.78 ✓	.75 ✓	29.14 ✓
16.80	18.30	3.30 ✓	1.25 ✓	37.37 ✓
18.30	20.50	.00	.00	.00
20.50	22.50	3.79 ✓	2.65 ✓	45.26 ✓
22.50	23.50	.00	.00	.00
23.50	24.50	3.83 ✓	4.05 ✓	50.40 ✓
24.50	25.90	.00	.00	.00
25.90	29.00	2.45 ✓	3.80 ✓	36.34 ✓
29.00	36.70	.00	.00	.00
36.70	39.70	2.80 ✓	5.00 ✓	41.49 ✓
39.70	70.10	N/A	N/A	N/A

36.60

MOORE SPEEDFILE 4

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-179

LATITUDE: 10482.⁰⁸00AZIMUTH: 224.⁵⁵07 *DH*

DEPARTURE: 7819.50.068

✓DIP: 59.18

ELEVATION: 1195.71 ✓

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.50	.05 ✓	.20 ✓	7.20 ✓
1.50	3.00	.08 ✓	.53 ✓	14.06 ✓
3.00	4.60	.38 ✓	.88 ✓	14.06 ✓
4.60	6.10	2.13 ✓	2.20 ✓	30.17 ✓
6.10	7.60	6.54 ✓	7.24 ✓	92.92 ✓
7.60	9.10	7.78 ✓	9.98 ✓	105.94 ✓
9.10	10.70	9.63 ✓	17.24 ✓	142.49 ✓
10.70	12.20	6.27 ✓	16.59 ✓	100.80 ✓
12.20	13.70	N/A	N/A	N/A
13.70	15.20	9.73 ✓	23.77 ✓	144.34 ✓
15.20	16.10	9.97 ✓	22.30 ✓	155.32 ✓
16.10	17.50	N/A	N/A	N/A
17.50	18.30	2.95 ✓	4.85 ✓	42.51 ✓
18.30	29.70	N/A	N/A	N/A
29.70	32.00	5.43 ✓	11.50 ✓	85.72 ✓
32.00	33.50	2.33 ✓	4.90 ✓	40.46 ✓
33.50	35.10	.95 ✓	2.58 ✓	10.97 ✓
35.10	36.60	2.28 ✓	5.72 ✓	29.14 ✓
36.60	38.10	3.73 ✓	5.98 ✓	59.31 ✓
38.10	39.60	3.98 ✓	4.55 ✓	73.71 ✓
39.60	41.10	2.70 ✓	3.75 ✓	39.43 ✓
41.10	42.70	3.68 ✓	2.55 ✓	48.34 ✓
42.70	44.20	.43 ✓	1.00 ✓	8.23 ✓
44.20	45.70	N/A	N/A	N/A

HOLE NO: U-180 : LATITUDE: 11021.75 ✓
HOLE LENGTH: 30.50 : DEPARTURE: 7412.56 ✓
ELEVATION: 1104.04 ✓ AZIMUTH: ~~332.14~~ ✓
DIP: 87.21 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	3.00	2.40 ✓	4.25 ✓	35.31 ✓
3.00	6.00	.50 ✓	.80 ✓	8.23 ✓
6.00	9.00	.40 ✓	.73 ✓	7.20 ✓
9.00	12.00	.90 ✓	1.60 ✓	13.03 ✓
12.00	15.00	.87 ✓	.55 ✓	9.94 ✓
15.00	16.50	1.58 ✓	2.23 ✓	25.37 ✓
16.50	18.00	2.23 ✓	2.90 ✓	35.31 ✓
18.00	19.50	.68 ✓	.83 ✓	16.11 ✓
19.50	21.00	4.78 ✓	6.84 ✓	71.66 ✓
21.00	22.20	3.68 ✓	4.55 ✓	52.46 ✓
22.20	30.50	N/A	N/A	N/A

MOORE SPCIDR110 4

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-181

LATITUDE: 10623.25

AZIMUTH: 224.00

DEPARTURE: 7704.20 7703.95

DIP: 3.00

ELEVATION: 1172.01

10622.81

224.00

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON

0.00	1.50	1.5	6.12✓	11.95✓	78.86✓
1.50	3.00	1.5	8.91✓	16.86✓	129.94✓
3.00	4.60	1.6	7.13✓	11.60✓	90.84✓
4.60	6.10	1.5	4.80✓	9.14✓	78.86✓
6.10	7.60	1.5	7.41✓	14.53✓	87.77✓
7.60	9.10	1.5	6.31✓	15.14✓	117.94✓
9.10	10.70	1.6	10.41✓	22.56✓	184.46✓
10.70	11.80	1.1	10.41✓	20.77✓	171.43✓
11.80	49.80		N/A	N/A	N/A
49.80	51.30	1.5	5.40✓	9.30✓	91.89✓
51.30	52.80	1.5	7.05✓	11.92✓	87.77✓
52.80	54.30	1.5	5.70✓	10.16✓	84.69✓
54.30	55.80	1.5	4.58✓	8.09✓	85.72✓
55.80	57.10	1.3	2.40✓	5.48✓	37.37✓
57.10	58.60	1.5	5.65✓	8.67✓	103.89✓
58.60	60.40	1.8	7.80✓	10.21✓	150.17✓
60.40	68.60		N/A	N/A	N/A

90.86

D I A M O N D D R I L L L O G M A S T E R F I L E

HOLE NO: U-183 LATITUDE: ^{10622.86} 10623.25 AZIMUTH: ^{229.39} 231.50
 DEPARTURE: 7704.20 ^{7703.86} ✓DIP: -29.56
 ELEVATION: 1171.19 ✓

INTERVAL		ASSAYS			
FROM	TO	PB	ZN	AG	
		%	%	GM/TON	
0.00	1.50	1.5	6.27✓	13.71✓	110.06✓
1.50	3.00	1.5	3.50✓	2.55✓	47.34
3.00	4.50	1.5	1.68✓	2.55✓	30.17
4.50	6.00	1.5	2.13✓	4.00✓	35.34
6.00	7.50	1.5	3.33✓	3.65✓	43.54
7.50	8.50	1.0	1.05✓	2.45✓	22.29
8.50	9.70	1.2	6.11✓	8.16✓	70.63
9.70	11.20	1.5	5.91✓	11.75✓	76.80
11.20	12.70	1.5	7.46✓	<u>14.83</u>	103.89
12.70	14.20	1.5	7.28✓	12.71✓	114.17
14.20	15.70	1.5	3.80✓	7.95✓	67.54
15.70	17.20	1.5	4.98✓	8.08✓	69.60
17.20	18.70	1.5	5.68✓	12.05✓	74.74
18.70	20.20	1.5	7.61✓	21.12✓	134.06
20.20	21.80	1.6	8.72✓	19.99✓	151.20
21.80	76.20	N/A	N/A	N/A	

14.93

DIAMOND DRILL LOG MASTER FILE

HOLE NO: U-185

LATITUDE: 10600.75^{.81}

AZIMUTH: 224.29^{222.17}

DEPARTURE: 7723.40^{7724.12}

✓DIP: 1.36

ELEVATION: 1175.36 ✓

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	6.10	N/A	N/A	N/A
6.10	7.60	1.23 ✓	1.85 ✓	20.23 ✓
7.60	9.10	6.43 ✓	14.02 ✓	93.94 ✓
9.10	10.70	6.83 ✓	15.27 ✓	110.06 ✓
10.70	12.20	5.86 ✓	11.84 ✓	66.51 ✓
12.20	13.70	7.81 ✓	15.99 ✓	84.69 ✓
13.70	15.20	6.43 ✓	11.59 ✓	84.69 ✓
15.20	16.80	8.11 ✓	17.43 ✓	104.92 ✓
16.80	18.30	10.47 ✓	26.45 ✓	172.46 ✓
18.30	19.80	6.23 ✓	17.52 ✓	90.86 ✓
19.80	20.50	9.69 ✓	20.65 ✓	141.26 ✓
20.50	57.90	.00	.00	.00
57.90	58.60	5.50 ✓	9.70 ✓	80.57 ✓
58.60	91.40	N/A	N/A	N/A

MOORE SPEED PLO 4

224.29 DJA

HOLE NO: U-187

LATITUDE: 10601.00^{.24}
 DEPARTURE: 7723.65^{.86}
 ELEVATION: 1174.78✓

AZIMUTH: 226.41✓
 ✓DIP: -35.35✓

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	16.80	N/A	N/A	N/A
16.80	18.30	.10✓	.70✓	4.11✓
18.30	19.80	.43✓	.78✓	15.09✓
19.80	21.30	1.48✓	2.85✓	20.23✓
21.30	22.90	3.05✓	3.55✓	40.46✓
22.90	24.40	1.23✓	1.33✓	17.14✓
24.40	25.90	1.10✓	1.48✓	15.09✓
25.90	27.40	1.93✓	1.85✓	20.23✓
27.40	29.00	.98✓	2.05✓	31.20✓
29.00	30.50	.60✓	1.33✓	8.23✓
30.50	32.00	1.63✓	2.93✓	22.29✓
32.00	33.50	1.03✓	1.68✓	14.06✓
33.50	35.10	.33✓	1.25✓	9.94✓
35.10	45.70	.00	.00	.00
45.70	47.20	.47✓	4.90✓	7.20✓
47.20	48.80	.05✓	1.33✓	5.14✓
48.80	50.30	.03✓	.93✓	5.14✓
50.30	51.80	.04✓	2.35✓	9.94✓
51.80	53.30	.04✓	5.00✓	8.23✓
53.30	54.90	.10✓	2.13✓	8.91✓
54.90	56.40	.09✓	2.08✓	12.00✓
56.40	57.90	.13✓	1.95✓	10.97✓
57.90	59.40	.28✓	1.80✓	8.91✓
59.40	60.30	1.95✓	3.98✓	42.51✓
60.30	91.40	N/A	N/A	N/A

MOORE SPECIFIC 4

DIAMOND DRILL LOG MASTER FILE

51.28 DJA

HOLE NO: U-189

LATITUDE: 10604.20^{.38}

AZIMUTH: ~~55.50~~

DEPARTURE: 7727.50^{.27}

DIP: -43.56

ELEVATION: 1174.79 ✓

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	36.60	N/A	N/A	N/A
36.60	38.10	.04 ✓	.10 ✓	4.11 ✓
38.10	39.60	.04 ✓	.05 ✓	3.09 ✓
39.60	46.00	.00	.00	.00
46.00	47.20	.03 ✓	.20 ✓	2.06 ✓
47.20	48.80	.02 ✓	.08 ✓	2.06 ✓
48.80	50.30	.05 ✓	.20	3.09 ✓
50.30	51.80	.05 ✓	.15 ✓	3.09 ✓
51.80	53.30	.03 ✓	.13 ✓	3.09 ✓
53.30	54.90	.05 ✓	.38 ✓	5.14 ✓
54.90	56.40	.01 ✓	.50 ✓	1.03 ✓
56.40	58.40	2.65 ✓	5.40 ✓	32.23 ✓
58.40	60.40	1.18 ✓	3.40 ✓	21.26 ✓
60.40	61.00	1.05 ✓	1.80 ✓	25.37 ✓
61.00	62.50	.18 ✓	1.10 ✓	3.09 ✓
62.50	82.90	.00	.00	.00
82.90	85.30	3.20 ✓	1.80 ✓	29.14 ✓
85.30	87.50	1.08 ✓	.85 ✓	16.11 ✓
87.50	88.40	.55 ✓	.90 ✓	14.06 ✓
88.40	89.90	1.03 ✓	1.43 ✓	18.17 ✓
89.90	90.80	1.25 ✓	1.23 ✓	17.14 ✓
90.80	93.00	1.85 ✓	2.15 ✓	27.43 ✓
93.00	93.90	1.05 ✓	1.43 ✓	12.00 ✓
93.90	95.40	.40 ✓	.38 ✓	8.23 ✓
95.40	96.30	.53 ✓	.85 ✓	5.14 ✓
96.30	97.80	.55 ✓	.98 ✓	6.17 ✓
97.80	100.30	2.78 ✓	2.13 ✓	24.34 ✓
100.30	101.80	3.68 ✓	2.03 ✓	32.23 ✓
101.80	103.60	1.85 ✓	1.20 ✓	20.23 ✓
103.60	105.20	2.48 ✓	2.63 ✓	29.14 ✓
105.20	106.70	4.45 ✓	4.95 ✓	67.54 ✓
106.70	108.20	1.53 ✓	1.13 ✓	25.37 ✓
108.20	109.70	1.03 ✓	.83 ✓	15.09 ✓
109.70	111.30	.30 ✓	.33 ✓	9.94 ✓
111.30	112.80	.25 ✓	.35 ✓	9.94 ✓
112.80	114.30	2.03 ✓	2.65 ✓	36.34 ✓
114.30	115.80	.38 ✓	.45 ✓	7.20 ✓
115.80	117.30	.20 ✓	.35 ✓	12.00 ✓
117.30	118.90	.10 ✓	.20 ✓	5.14 ✓
118.90	120.40	.20 ✓	.40 ✓	3.09 ✓
120.40	121.90	.05 ✓	.05 ✓	1.03 ✓
121.90	123.40	.05 ✓	.05 ✓	1.03 ✓

MOORE
SERIAL FLO 4

DIAMOND DRILL LOG MASTER FILE

256.26

HOLE NO: U-191

LATITUDE: 10602.58 ✓

AZIMUTH: 258.37

DEPARTURE: 7725.65 ✓

✓DIP: 88.31

ELEVATION: 1178.89 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	6.10	N/A	N/A	N/A
6.10	9.10	.45 ✓	.80 ✓	9.94 ✓
9.10	12.20	.60 ✓	1.30 ✓	25.37 ✓
12.20	13.70	3.35 ✓	3.75 ✓	50.40 ✓
13.70	15.20	7.15 ✓	12.83 ✓	94.63 ✓
15.20	16.80	5.00 ✓	9.60 ✓	83.66 ✓
16.80	18.30	6.62 ✓	12.28 ✓	86.74 ✓
18.30	19.80	6.85 ✓	13.69 ✓	103.89 ✓
19.80	21.30	8.96 ✓	14.71 ✓	126.17 ✓
21.30	24.30	6.95 ✓	12.53 ✓	109.03 ✓
24.30	50.30	.00	.00	.00
50.30	53.30	5.82	15.46 ✓	75.77 ✓
53.30	56.40	4.40 ✓	13.20 ✓	67.54 ✓
56.40	57.90	7.05 ✓	16.45 ✓	114.17 ✓
57.90	61.00	N/A	N/A	N/A

5.33

MOORE SPECIFIC 4

HOLE NO: U-194
 HOLE LENGTH: 128.00

LATITUDE: 10785.41 ✓
 DEPARTURE: 7565.13 ✓
 ELEVATION: 1141.48 ✓

AZIMUTH: 132.32 ✓
 DIP: -85.41 ✓

-1140.13 DJA

DIP TESTS: DEPTH DIP AZIMUTH
 61.00 -85.00 272.00
 118.90 -86.00 252.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.20	N/A	N/A	N/A
1.20	4.00	2.35 ✓	3.00 ✓	28.46 ✓
4.00	5.50	1.55 ✓	.93 ✓	19.20 ✓
5.50	7.00	1.03 ✓	1.40 ✓	10.97 ✓
7.00	8.50	1.98 ✓	3.10 ✓	27.43 ✓
8.50	10.00	.90 ✓	1.80 ✓	9.94 ✓
10.00	11.50	1.28 ✓	1.60 ✓	12.00 ✓
11.50	13.00	.93 ✓	1.30 ✓	8.91 ✓
13.00	14.50	.95 ✓	.63 ✓	10.97 ✓
14.50	17.50	2.33 ✓	2.55 ✓	33.26 ✓
17.50	19.80	2.05 ✓	2.75 ✓	28.46 ✓
19.80	39.50	.00	.00	.00
39.50	41.00	.40 ✓	1.00 ✓	8.23 ✓
41.00	42.50	1.08 ✓	2.28 ✓	20.23 ✓
42.50	44.00	.53 ✓	1.13 ✓	12.00 ✓
44.00	45.50	.23 ✓	.78 ✓	6.17 ✓
45.50	47.00	.23 ✓	.73 ✓	7.20 ✓
47.00	48.50	.13 ✓	.43 ✓	7.20 ✓
48.50	50.00	1.90 ✓	3.90 ✓	34.29 ✓
50.00	51.50	3.65 ✓	7.20 ✓	68.57 ✓
51.50	53.40	3.23 ✓	5.82 ✓	59.31 ✓
53.40	57.20	.00	.00	.00
57.20	58.70	3.00 ✓	4.25 ✓	58.63 ✓
58.70	60.20	8.97 ✓	11.07 ✓	114.86 ✓
60.20	61.70	4.23 ✓	7.93 ✓	96.69 ✓
61.70	63.20	3.28 ✓	5.48 ✓	58.63 ✓
63.20	64.70	3.38 ✓	5.71 ✓	48.34 ✓
64.70	66.20	4.90 ✓	6.57 ✓	81.60 ✓
66.20	67.70	3.20 ✓	6.90 ✓	80.57 ✓
67.70	69.20	4.13 ✓	9.21 ✓	74.74 ✓
69.20	70.70	5.00 ✓	8.26 ✓	84.69 ✓
70.70	72.20	3.93 ✓	4.00 ✓	57.60 ✓
72.20	73.70	2.70 ✓	1.50 ✓	43.54 ✓
73.70	75.20	4.94 ✓	5.91 ✓	78.86 ✓
75.20	76.20	3.90 ✓	5.05 ✓	78.86 ✓
76.20	87.20	.00	.00	.00
87.20	88.70	9.71 ✓	18.19 ✓	147.09 ✓
88.70	90.20	6.99 ✓	14.00 ✓	104.92 ✓
90.20	91.70	5.23 ✓	8.04 ✓	79.54 ✓
91.70	93.20	2.73 ✓	5.05 ✓	43.54 ✓
93.20	94.70	.55 ✓	1.05 ✓	15.09 ✓
94.70	96.20	.88 ✓	1.93 ✓	17.14 ✓
96.20	97.70	4.25 ✓	6.19 ✓	63.43 ✓
97.70	99.20	1.00 ✓	2.48 ✓	21.26 ✓
99.20	100.70	1.43 ✓	2.98 ✓	26.40 ✓
100.70	102.20	1.05 ✓	1.28 ✓	25.37 ✓

MOORE SPECIALTY 4

HOLE NO: U-194

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
102.20	103.70	.13	.65	18.17
103.70	106.70	.14	.50	18.17
106.70	108.20	2.28	2.80	37.37
108.20	109.70	3.88	5.00	60.34
109.70	111.40	.70	1.63	25.37
111.40	112.00	2.08	1.93	34.29
112.00	128.00	N/A	N/A	N/A

103.70	105.2	48	50	187
105.2	106.7	228	280	3737

		Pb	Zn	Ag
102.20	103.70	.13	.65	18.17
103.70	105.20	.48	.50	18.17
105.20	106.70	2.28	2.80	37.37
106.70	108.20	3.88	5.00	60.34
108.20	109.70	.70	1.63	25.37
109.70	111.40	2.08	1.93	34.29
111.40	112.00	N/A	N/A	N/A
112.00	128.00	N/A	N/A	N/A

HOLE NO: U-196
 HOLE LENGTH: 129.50

LATITUDE: 10784.53 ✓
 DEPARTURE: 7564.22 ✓
 ELEVATION: 1140.18 ✓

✓ AZIMUTH: 216.41 ✓
 ✓ DIP: -63.39 ✓

~~229.0~~ DD
~~65.00~~ DL

DIP TESTS:	DEPTH	DIP	AZIMUTH
	61.00	-73.00	229.00
	100.60	-75.00	245.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	3.00	1.80 ✓	1.70 ✓	20.23 ✓
3.00	4.50	1.95 ✓	2.93 ✓	26.40 ✓
4.50	6.00	1.63 ✓	1.63 ✓	22.29 ✓
6.00	7.50	1.60 ✓	.88 ✓	22.29 ✓
7.50	9.00	.88 ✓	.35 ✓	12.00 ✓
9.00	10.50	2.20 ✓	2.00 ✓	32.23 ✓
10.50	12.00	2.88 ✓	2.55 ✓	36.34 ✓
12.00	13.50	2.70 ✓	2.95 ✓	32.23 ✓
13.50	15.00	2.80 ✓	1.25 ✓	30.17 ✓
15.00	16.50	3.10 ✓	1.85 ✓	31.20 ✓
16.50	18.00	2.70 ✓	.80 ✓	26.40 ✓
18.00	19.50	.13 ✓	.55 ✓	3.09 ✓
19.50	21.00	.10 ✓	.10 ✓	6.17 ✓
21.00	22.50	.14 ✓	.35 ✓	6.17 ✓
22.50	25.50	.75 ✓	.73 ✓	8.91 ✓
25.50	28.50	.18 ✓	.40 ✓	3.09 ✓
28.50	31.50	.13 ✓	.93 ✓	3.09 ✓
31.50	34.50	.53 ✓	1.23 ✓	8.91 ✓
34.50	36.60	1.95 ✓	3.40 ✓	30.17 ✓
36.60	38.10	2.58 ✓	4.15 ✓	41.49 ✓
38.10	39.60	6.23 ✓	8.77 ✓	92.92 ✓
39.60	40.30	6.10 ✓	8.47 ✓	102.86 ✓
40.30	62.50	.00 ✓	.00 ✓	.00 ✓
62.50	64.00	5.00 ✓	8.21 ✓	93.94 ✓
64.00	65.50	6.85 ✓	5.10 ✓	184.46 ✓
65.50	67.00	5.70 ✓	8.06 ✓	108.00 ✓
67.00	68.50	4.00 ✓	6.80 ✓	69.60 ✓
68.50	70.00	5.00 ✓	8.49 ✓	82.63 ✓
70.00	71.50	4.35 ✓	7.50 ✓	76.80 ✓
71.50	94.50	.00 ✓	.00 ✓	.00 ✓
94.50	96.00	4.28 ✓	19.19 ✓	61.37 ✓
96.00	97.50	9.02 ✓	20.34 ✓	150.17 ✓
97.50	99.00	2.53 ✓	5.65 ✓	42.51 ✓
99.00	100.50	2.03 ✓	4.55 ✓	36.34 ✓
100.50	102.00	4.65 ✓	8.31 ✓	70.63 ✓
102.00	103.50	1.05 ✓	3.68 ✓	25.37 ✓
103.50	105.00	2.23 ✓	3.15 ✓	39.43 ✓
105.00	106.50	1.63 ✓	4.03 ✓	30.17 ✓
106.50	108.00	1.20 ✓	3.18 ✓	25.37 ✓
108.00	109.50	2.58 ✓	2.75 ✓	45.26 ✓
109.50	111.00	3.25 ✓	4.85 ✓	48.34 ✓
111.00	129.50	N/A	N/A	N/A

81
 3/2-17

HOLE NO: U-198 LATITUDE: 10709.24 AZIMUTH: 32.00
 HOLE LENGTH: 153.90 DEPARTURE: 7469.54 DIP: -57.00
 ELEVATION: 1172.84

DIP TESTS:	DEPTH	DIP	AZIMUTH
	10.70	-56.00	33.00
	56.40	-60.00	33.00
	102.10	-66.00	33.00
	150.90	-71.00	23.00

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	42.70	N/A	N/A	N/A
42.70	44.20	.88✓	.33✓	25.37✓
44.20	45.70	.45✓	.10✓	17.14✓
45.70	47.20	2.20✓	1.15✓	39.43✓
47.20	49.00	2.88✓	1.85✓	42.51✓
49.00	90.50	.00	.00	.00
90.50	92.00	5.76✓	8.04✓	101.83✓
92.00	93.50	6.65✓	9.70✓	123.09✓
93.50	94.70	5.44✓	9.70✓	<u>98.89</u>
94.70	134.10	.00	.00	.00
134.10	135.60	2.88✓	2.85✓	36.34✓
135.60	137.10	.88✓	.88✓	13.03✓
137.10	138.60	.08✓	.10✓	4.11✓
138.60	141.60	.20✓	.28✓	5.14✓
141.60	143.90	.00	.00	.00
143.90	146.90	.43✓	.63✓	8.91✓
146.90	148.40	1.28✓	1.50✓	20.23✓
148.40	149.90	.18✓	.70✓	7.20✓
149.90	151.40	1.18✓	1.33✓	23.31✓
151.40	153.90	N/A	N/A	N/A

91.89

HOLE NO: U-199
 HOLE LENGTH: 132.60

LATITUDE: 10677.07✓
 DEPARTURE: 7629.42✓
 ELEVATION: 1156.97✓

✓ AZIMUTH: 228.18✓
 ✓ DIP: 0.45✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	2.10	N/A	N/A	N/A
2.10	3.60	8.39✓	12.65✓	124.12✓
3.60	5.10	7.40✓	10.21✓	114.17✓
5.10	6.60	6.40✓	8.85✓	92.92✓
6.60	8.10	7.85✓	10.31✓	113.14✓
8.10	9.60	6.50✓	8.95✓	75.77✓
9.60	11.10	6.75✓	10.15✓	76.80✓
11.10	12.60	6.97✓	8.69✓	104.92✓
12.60	14.10	3.60✓	8.16✓	46.29✓
14.10	15.60	3.03✓	3.35✓	47.31✓
15.60	17.10	6.75✓	6.52✓	97.72✓
17.10	18.60	8.60✓	11.52✓	156.34✓
18.60	20.10	7.40✓	9.93✓	114.17✓
20.10	21.60	7.00✓	9.70✓	93.94✓
21.60	23.10	7.20✓	9.65✓	100.83
23.10	24.60	4.18✓	6.31✓	79.54✓
24.60	27.00	.00	.00	.00
27.00	28.50	6.10✓	10.21✓	108.00✓
28.50	30.00	5.40✓	9.55✓	98.74✓
30.00	31.50	6.20✓	9.85✓	139.20✓
31.50	33.00	6.40✓	9.25✓	104.92✓
33.00	34.50	5.10✓	9.78✓	85.72✓
34.50	36.00	4.55✓	9.18✓	62.40✓
36.00	103.00	.00	.00	.00
103.00	104.50	3.90✓	3.65✓	49.37✓
104.50	106.00	1.83✓	1.05✓	29.14✓
106.00	107.50	1.13✓	.30✓	27.43✓
107.50	109.00	6.80✓	6.47✓	68.57✓
109.00	110.50	1.95✓	1.73✓	23.31✓
110.50	132.60	N/A	N/A	N/A

MOORE SPEEDFILE 4

HOLE NO: U-201
 HOLE LENGTH: 54.90

LATITUDE: 10718.84 ✓
 DEPARTURE: 7634.56 ✓
 ELEVATION: 1152.84 ✓

✓ AZIMUTH: ~~163.41~~
 ✓ DIP: -0.30 ✓

INTERVAL		ASSAYS			
FROM	TO	PB	ZN	AG	
		%	%	GM/TON	
0.00	3.50	N/A	N/A	N/A	
3.50	6.50	4.05 ✓	4.10 ✓	52.49	53.49
6.50	9.50	2.35 ✓	3.85 ✓	27.43 ✓	
9.50	12.50	1.63 ✓	.50 ✓	16.11 ✓	
12.50	15.50	1.60 ✓	1.15 ✓	16.11 ✓	
15.50	18.50	2.88 ✓	4.05 ✓	35.31 ✓	
18.50	21.50	3.18 ✓	6.29 ✓	38.40 ✓	
21.50	24.50	4.33 ✓	6.75 ✓	50.40 ✓	
24.50	26.00	6.25 ✓	8.29 ✓	77.83 ✓	
26.00	27.50	4.64 ✓	4.68 ✓	59.31 ✓	
27.50	29.00	1.26 ✓	.58 ✓	23.31 ✓	
29.00	30.50	.38 ✓	.63 ✓	12.00 ✓	
30.50	32.00	.60 ✓	.65 ✓	13.03 ✓	
32.00	33.50	2.03 ✓	2.80 ✓	25.37 ✓	
33.50	36.60	4.94 ✓	9.68 ✓	87.77 ✓	
36.60	38.10	4.50 ✓	9.96 ✓	79.54 ✓	
38.10	41.10	4.47 ✓	8.11 ✓	72.69 ✓	
41.10	44.20	4.69 ✓	9.35 ✓	93.94 ✓	
44.20	45.70	5.65 ✓	10.04 ✓	102.86 ✓	
45.70	47.20	5.70 ✓	11.00 ✓	105.94 ✓	
47.20	48.80	5.90 ✓	10.97 ✓	104.92 ✓	
48.80	50.30	5.80 ✓	10.16 ✓	109.03 ✓	
50.30	52.80	3.78 ✓	8.14 ✓	98.74 ✓	
52.80	54.90	N/A	N/A	N/A	

MOORE SPEEDFILE 4

HOLE NO: U-203
 HOLE LENGTH: 73.20

LATITUDE: 10725.97 ✓
 DEPARTURE: 7640.34 ✓
 ELEVATION: 1152.77 ✓

✓ AZIMUTH: 100-0
 81.30 ✓
 ✓ DIP: -0.48 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	36.60	N/A	N/A	N/A
36.60	38.10	.80 ✓	.40 ✓	17.14 ✓
38.10	39.60	2.78 ✓	1.45 ✓	34.29 ✓
39.60	41.10	2.88 ✓	1.25 ✓	24.00 ✓
41.10	42.70	3.05 ✓	2.60 ✓	41.49 ✓
42.70	44.20	4.90 ✓	3.88 ✓	63.43 ✓
44.20	45.70	3.18 ✓	2.00 ✓	43.54 ✓
45.70	47.20	6.87 ✓	5.00 ✓	101.83 ✓
47.20	48.80	6.97 ✓	4.96 ✓	106.97 ✓
48.80	50.30	.98 ✓	2.53 ✓	12.00 ✓
50.30	51.80	1.15 ✓	3.58 ✓	14.06 ✓
51.80	52.50	.00	.00	.00
52.50	53.30	1.53 ✓	.23 ✓	24.34 ✓
53.30	54.90	.93 ✓	.80 ✓	13.03 ✓
54.90	56.40	.38 ✓	2.23 ✓	7.20 ✓
56.40	57.90	1.13 ✓	1.28 ✓	13.03 ✓
57.90	59.40	1.88 ✓	2.23 ✓	24.40 ✓
59.40	61.00	2.75 ✓	2.55 ✓	38.40 ✓
61.00	62.50	2.93 ✓	4.00 ✓	49.37 ✓
62.50	64.00	3.33 ✓	4.85 ✓	47.31 ✓
64.00	66.50	6.01 ✓	8.72 ✓	73.71 ✓
66.50	67.10	1.68 ✓	3.70 ✓	23.31 ✓
67.10	68.60	.93 ✓	2.33 ✓	17.14 ✓
68.60	70.10	.53 ✓	5.56 ✓	8.23 ✓
70.10	71.60	1.88 ✓	5.72 ✓	33.26 ✓
71.60	73.20	3.80 ✓	5.99 ✓	53.49 ✓

26.40

MOORE SPEEDFILE 4

STER FILE

HOLE NO: U-204
 HOLE LENGTH: 36.60

LATITUDE: 10767.17 ✓
 DEPARTURE: 7715.58 ✓
 ELEVATION: 1154.80 ✓

AZIMUTH: 0.00
 DIP: -90.00

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	19.80	N/A	N/A	N/A
19.80	21.30	7.32 ✓	12.90 ✓	102.86 ✓
21.30	22.90	6.48 ✓	13.51 ✓	89.83 ✓
22.90	24.40	2.33 ✓	8.26 ✓	59.31 ✓
24.40	25.90	3.45 ✓	9.60 ✓	49.03 ✓
25.90	27.40	5.51 ✓	9.37 ✓	72.69 ✓
27.40	29.00	11.45 ✓	17.33 ✓	150.17 ✓
29.00	30.70	7.25 ✓	10.67 ✓	114.17 ✓
30.70	32.20	1.60 ✓	2.90 ✓	26.40 ✓
32.20	36.60	N/A	N/A	N/A

MOORE SPEEDFILE 4

HOLE NO: U-206
 HOLE LENGTH: 106.70

LATITUDE: 10766.34 ✓
 DEPARTURE: 7715.96 ✓
 ELEVATION: 1159.65 ✓

✓ AZIMUTH: ~~161.59~~ 161.59 ✓
 ✓ DIP: 87.26 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	1.50	N/A	N/A	N/A
1.50	3.00	4.35 ✓	8.98 ✓	66.51 ✓
3.00	4.60	3.45 ✓	4.60 ✓	45.26 ✓
4.60	6.10	5.70 ✓	4.00 ✓	67.54 ✓
6.10	7.60	9.75 ✓	6.23 ✓	114.17 ✓
7.60	9.10	4.78 ✓	4.25 ✓	58.63 ✓
9.10	12.20	3.65 ✓	4.20 ✓	43.54 ✓
12.20	13.70	6.50 ✓	2.50 ✓	69.60 ✓
13.70	15.20	8.50 ✓	4.40 ✓	89.83 ✓
15.20	16.80	4.03 ✓	2.03 ✓	46.29 ✓
16.80	18.30	5.04 ✓	2.33 ✓	55.54 ✓
18.30	19.80	4.85 ✓	1.63 ✓	55.54 ✓
19.80	21.30	5.70 ✓	1.48 ✓	64.46 ✓
21.30	22.90	8.55 ✓	7.52 ✓	83.66 ✓
22.90	24.40	3.70 ✓	2.70 ✓	41.49 ✓
24.40	25.90	3.33 ✓	4.10 ✓	47.31 ✓
25.90	27.40	2.15 ✓	4.66 ✓	37.37 ✓
27.40	29.00	2.38 ✓	5.00 ✓	44.23 ✓
29.00	30.50	2.15 ✓	4.76 ✓	40.46 ✓
30.50	32.00	1.90 ✓	3.95 ✓	39.43 ✓
32.00	33.50	1.60 ✓	3.73 ✓	33.26 ✓
33.50	35.10	1.90 ✓	4.68 ✓	39.43 ✓
35.10	36.60	1.75 ✓	2.53 ✓	31.20 ✓
36.60	38.10	3.35 ✓	6.48 ✓	57.60 ✓
38.10	39.60	2.48 ✓	4.06 ✓	46.29 ✓
39.60	41.10	3.30 ✓	7.44 ✓	66.51 ✓
41.10	42.70	1.80 ✓	3.30 ✓	29.14 ✓
42.70	44.20	1.15 ✓	1.40 ✓	15.09 ✓
44.20	45.70	1.40 ✓	2.88 ✓	23.31 ✓
45.70	47.20	1.38 ✓	3.25 ✓	26.40 ✓
47.20	48.80	1.68 ✓	4.18 ✓	30.17 ✓
48.80	50.30	1.43 ✓	3.18 ✓	21.26 ✓
50.30	51.80	1.50 ✓	3.00 ✓	24.34 ✓
51.80	53.30	1.58 ✓	4.20 ✓	27.43 ✓
53.30	54.90	1.70 ✓	2.48 ✓	26.40 ✓
54.90	56.40	.63 ✓	1.30 ✓	10.97 ✓
56.40	59.40	1.83 ✓	2.40 ✓	24.34 ✓
59.40	61.00	2.20 ✓	5.50 ✓	30.17 ✓
61.00	62.50	1.35 ✓	2.88 ✓	21.26 ✓
62.50	64.00	5.42 ✓	7.70 ✓	67.54 ✓
64.00	65.50	6.65 ✓	10.55 ✓	80.57 ✓
65.50	67.10	7.61 ✓	11.66 ✓	102.86 ✓
67.10	68.50	9.89 ✓	16.00 ✓	138.17 ✓
68.50	106.70	N/A	N/A	N/A

6.33

MOORE SPECIFICO 4

HOLE NO: U-208 LATITUDE: 10810.30 ✓
 HOLE LENGTH: 140.20 DEPARTURE: 7673.38 ✓
 ELEVATION: 1149.35 ✓

✓ AZIMUTH: 62.04 ✓
 ✓ DIP: 70.40 ✓

DIP TESTS: DEPTH DIP AZIMUTH
 65.50 -74.00 61.00
 126.50 -71.00 66.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.50	6.52✓	8.88✓	75.77✓
1.50	3.00	3.58✓	7.32✓	55.54✓
3.00	4.60	4.60✓	6.87✓	60.34✓
4.60	6.10	4.25✓	8.78✓	66.51✓
6.10	7.50	2.80✓	7.47✓	47.31✓
7.50	8.50	.00✓	.00✓	.00✓
8.50	9.90	5.00✓	11.51✓	68.57✓
9.90	33.00	.00✓	.00✓	.00✓
33.00	34.00	1.85✓	4.88✓	27.43✓
34.00	45.70	.00✓	.00✓	.00✓
45.70	47.20	4.98✓	6.16✓	74.74✓
47.20	48.80	8.50✓	15.65✓	112.12✓
48.80	50.30	4.90✓	8.98✓	85.72✓
50.30	51.80	5.75✓	8.13✓	90.86✓
51.80	53.30	4.28✓	4.55✓	63.43✓
53.30	55.50	4.65✓	7.12✓	81.60✓
55.50	57.10	1.53✓	2.68✓	25.37✓
57.10	129.80	.00✓	.00✓	.00✓
129.80	131.10	3.25✓	3.20✓	41.49✓
131.10	132.60	1.93✓	.75✓	19.20✓
132.60	134.10	4.38✓	5.68✓	65.49✓
134.10	135.60	.58✓	.93✓	14.06✓
135.60	137.20	.33✓	.50✓	8.91✓
137.20	138.70	.63✓	.45✓	9.94✓
138.70	140.20	.65✓	1.63✓	9.94✓

MOORE SPECIALTY 4

HOLE NO: U-209 LATITUDE: 10810.13 ✓
 HOLE LENGTH: 97.50 DEPARTURE: 7672.49 ✓
 ELEVATION: 1149.21 ✓

AZIMUTH: ~~156.02~~ 9
 DIP: ~~-88.50~~ 90.6

DIP TESTS: DEPTH 88.30 DIP -86.00 AZIMUTH 2.00

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	3.00	4.90 ✓	3.55 ✓	48.34 ✓
3.00	4.50	4.28 ✓	3.08 ✓	49.37 ✓
4.50	6.00	4.45 ✓	9.52 ✓	66.51 ✓
6.00	7.50	1.65 ✓	5.45 ✓	27.43 ✓
7.50	9.00	2.55 ✓	5.73 ✓	39.43 ✓
9.00	10.50	6.98 ✓	10.80 ✓	122.06 ✓
10.50	13.80	.00	.00	.00
13.80	16.80	5.33 ✓	10.49 ✓	89.83 ✓
16.80	18.30	6.04 ✓	13.42 ✓	93.94 ✓
18.30	19.80	3.55 ✓	8.91 ✓	53.49 ✓
19.80	21.30	.00	.00	.00
21.30	22.80	5.53 ✓	9.01 ✓	78.86 ✓
22.80	24.30	6.98 ✓	13.58 ✓	102.86 ✓
24.30	26.00	10.25 ✓	19.77 ✓	217.37 ✓
26.00	33.50	.00	.00	.00
33.50	35.10	4.70 ✓	6.92 ✓	65.49 ✓
35.10	39.40	.00	.00	.00
39.40	41.10	3.90 ✓	4.55 ✓	52.46 ✓
41.10	42.70	2.78 ✓	2.90 ✓	40.46 ✓
42.70	44.20	6.23 ✓	10.29 ✓	130.97 ✓
44.20	45.70	5.67 ✓	8.75 ✓	97.72 ✓
45.70	47.20	6.49 ✓	10.25 ✓	108.00 ✓
47.20	48.70	4.55 ✓	6.41 ✓	69.60 ✓
48.70	50.20	3.48 ✓	5.30 ✓	48.34 ✓
50.20	51.90	1.05 ✓	1.90 ✓	16.11 ✓
51.90	57.90	.00	.00	.00
57.90	59.40	1.98 ✓	2.83 ✓	22.29 ✓
59.40	97.50	N/A	N/A	N/A

1.68

MOORE SHEET 4

HOLE NO: U-210 LATITUDE: 10809.00 ✓
HOLE LENGTH: 120.40 DEPARTURE: 7671.17 ✓
ELEVATION: 1149.15 ✓

✓ AZIMUTH: 220.53 ✓
✓ DIP: ~~66.59~~
67.00

DIP TESTS: DEPTH DIP AZIMUTH
109.10 -77.00 217.00

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	3.00	6.42 ✓	4.55 ✓	71.66 ✓
3.00	4.50	.85 ✓	2.70 ✓	14.06 ✓
4.50	6.00	3.73 ✓	8.11 ✓	56.57 ✓
6.00	7.50	3.70 ✓	7.90 ✓	53.49 ✓
7.50	9.00	2.30 ✓	4.80 ✓	33.26 ✓
9.00	10.50	3.78 ✓	6.90 ✓	58.63 ✓
10.50	12.00	3.20 ✓	6.55 ✓	46.29 ✓
12.00	13.50	2.90 ✓	5.30 ✓	48.34 ✓
13.50	15.00	3.82 ✓	9.05 ✓	68.57 ✓
15.00	16.50	4.13 ✓	9.01 ✓	78.86 ✓
16.50	18.00	1.38 ✓	3.13 ✓	23.31 ✓
18.00	19.50	2.88 ✓	6.92 ✓	50.40 ✓
19.50	21.00	7.83 ✓	13.57 ✓	125.14 ✓
21.00	22.50	5.00 ✓	9.74 ✓	80.57 ✓
22.50	24.00	2.63 ✓	5.63 ✓	42.51 ✓
24.00	25.50	.53 ✓	.25 ✓	8.23 ✓
25.50	27.10	1.75 ✓	1.48 ✓	27.43 ✓
27.10	29.80	.00	.00	.00
29.80	32.00	7.68 ✓	16.70 ✓	140.23 ✓
32.00	36.40	.00	.00	.00
36.40	38.40	6.19 ✓	7.87 ✓	79.54 ✓
38.40	59.40	.00	.00	.00
59.40	60.90	6.22 ✓	9.59 ✓	88.80 ✓
60.90	62.40	4.87 ✓	7.52 ✓	71.66 ✓
62.40	63.90	5.00 ✓	7.70 ✓	69.60 ✓
63.90	65.40	5.63 ✓	10.60 ✓	81.60 ✓
65.40	66.90	1.13 ✓	1.45 ✓	15.09 ✓
66.90	89.90	.00	.00	.00
89.90	92.90	.58 ✓	.73 ✓	13.03 ✓
92.90	94.40	.18 ✓	.65 ✓	14.06 ✓
94.40	95.90	.15 ✓	.28 ✓	8.23 ✓
95.90	98.90	.33 ✓	1.08 ✓	8.23 ✓
98.90	100.40	.73 ✓	13.03 ✓	13.03 ✓
100.40	101.90	.05 ✓	.45 ✓	3.09 ✓
101.90	104.90	.05 ✓	.33 ✓	5.14 ✓
104.90	107.90	.07 ✓	1.05 ✓	4.11 ✓
107.90	109.90	1.00 ✓	1.63 ✓	23.31 ✓
109.90	113.20	.00	.00	.00
113.20	114.40	6.99 ✓	12.52 ✓	98.74 ✓
114.40	120.40	N/A	N/A	N/A

1.35

951-74

81-90

HOLE NO: U-212
 HOLE LENGTH: 70.20

LATITUDE: 10743.75 ✓
 DEPARTURE: 7608.68 ✓
 ELEVATION: 1149.52 ✓

✓ AZIMUTH: 58.03 ✓
 ✓ DIP: 85.50 ✓
 700

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	10.70	N/A	N/A	N/A
10.70	11.20	1.30 ✓	2.73 ✓	15.09 ✓
11.20	12.20	1.48 ✓	1.93 ✓	19.20 ✓
12.20	13.70	2.15 ✓	1.60 ✓	24.34 ✓
13.70	15.20	3.40 ✓	3.00 ✓	40.46 ✓
15.20	16.80	2.60 ✓	3.55 ✓	32.23 ✓
16.80	18.30	2.23 ✓	2.75 ✓	28.46 ✓
18.30	19.80	1.68 ✓	2.65 ✓	20.23 ✓
19.80	21.30	.40 ✓	.63 ✓	5.14 ✓
21.30	22.90	1.48 ✓	2.00 ✓	20.23 ✓
22.90	30.00	.00	.00	.00
30.00	32.00	.50 ✓	.78 ✓	8.23 ✓
32.00	33.50	.33 ✓	1.18 ✓	6.17 ✓
33.50	36.00	1.88 ✓	3.73 ✓	29.14 ✓
36.00	38.10	8.05 ✓	15.78 ✓	118.97 ✓
38.10	41.90	.00	.00	.00
41.90	42.70	7.39 ✓	9.26 ✓	114.52 ✓
42.70	44.20	5.75 ✓	6.01 ✓	118.97 ✓
44.20	45.70	4.53 ✓	7.53 ✓	87.77 ✓
45.70	47.20	4.68 ✓	8.60 ✓	68.57 ✓
47.20	48.80	5.30 ✓	8.88 ✓	81.60 ✓
48.80	50.30	2.56 ✓	5.89 ✓	41.49 ✓
50.30	51.80	3.70 ✓	6.65 ✓	59.31 ✓
51.80	53.30	4.95 ✓	7.30 ✓	68.57 ✓
53.30	54.90	.00	.00	.00
54.90	56.40	3.15 ✓	6.06 ✓	51.43 ✓
56.40	59.10	4.20 ✓	8.04 ✓	80.57 ✓
59.10	61.00	6.29 ✓	12.70 ✓	93.94 ✓
61.00	62.50	4.00 ✓	3.60 ✓	57.60 ✓
62.50	64.00	9.15 ✓	15.98 ✓	118.63 ✓
64.00	65.50	3.85 ✓	4.15 ✓	46.29 ✓
65.50	67.10	2.80 ✓	1.70 ✓	39.77 ✓
67.10	68.60	7.58 ✓	14.12 ✓	127.89 ✓
68.60	70.20	3.38 ✓	3.80 ✓	47.31 ✓

HOLE NO: U-213
 HOLE LENGTH: 121.90

LATITUDE: 10744.66 ✓
 DEPARTURE: 7609.87 ✓
 ELEVATION: 1149.50 ✓

✓ AZIMUTH: 46.00 ✓
 ✓ DIP: -64.56 ✓
min

DIP TESTS: DEPTH DIP AZIMUTH
 73.20 -68.00 43.00
 118.90 -73.00 53.00

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	51.20	N/A	N/A	N/A
51.20	52.70	3.83 ✓	6.86 ✓	63.43 ✓
52.70	54.20	2.58 ✓	4.45 ✓	41.49 ✓
54.20	55.70	4.23 ✓	7.70 ✓	58.63 ✓
55.70	57.20	3.23 ✓	6.12 ✓	54.51 ✓
57.20	58.70	4.08 ✓	7.05 ✓	71.66 ✓
58.70	60.20	5.97 ✓	9.17 ✓	94.63 ✓
60.20	61.70	3.85 ✓	6.70 ✓	50.40 ✓
61.70	63.20	5.79 ✓	8.39 ✓	78.86 ✓
63.20	64.70	1.50 ✓	1.63 ✓	31.20 ✓
64.70	66.20	1.28 ✓	1.20 ✓	30.17 ✓
66.20	67.70	2.75 ✓	4.60 ✓	52.46 ✓
67.70	69.20	1.53 ✓	2.45 ✓	28.46 ✓
69.20	70.70	2.93 ✓	5.00 ✓	46.29 ✓
70.70	72.20	.85 ✓	1.53 ✓	17.14 ✓
72.20	73.70	1.83 ✓	4.40 ✓	24.34 ✓
73.70	75.20	.85 ✓	1.83 ✓	13.03 ✓
75.20	76.70	.83 ✓	1.03 ✓	16.11 ✓
76.70	78.20	1.10 ✓	1.88 ✓	27.43 ✓
78.20	79.70	9.14 ✓	15.62 ✓	120.00 ✓
79.70	81.20	4.58 ✓	8.31 ✓	68.57 ✓
81.20	82.70	.88 ✓	1.38 ✓	28.11 ✓
82.70	84.20	.18 ✓	.80 ✓	12.00 ✓
84.20	85.70	6.37 ✓	13.89 ✓	88.80 ✓
85.70	87.20	5.70 ✓	11.23 ✓	70.63 ✓
87.20	88.70	2.43 ✓	4.45 ✓	33.26 ✓
88.70	90.20	.68 ✓	1.30 ✓	20.23 ✓
90.20	91.70	.45 ✓	1.28 ✓	17.14 ✓
91.70	93.20	.30 ✓	1.00 ✓	13.03 ✓
93.20	94.70	.18 ✓	.98 ✓	12.00 ✓
94.70	96.20	.20 ✓	1.28 ✓	6.17 ✓
96.20	97.70	.88 ✓	1.68 ✓	12.00 ✓
97.70	99.20	.43 ✓	2.53 ✓	10.97 ✓
99.20	100.70	.05 ✓	.85 ✓	9.94 ✓
100.70	102.20	.05 ✓	1.03 ✓	9.94 ✓
102.20	103.70	.02 ✓	.43 ✓	8.91 ✓
103.70	105.20	.03 ✓	1.00 ✓	7.89 ✓
105.20	106.70	.02 ✓	.75 ✓	5.14 ✓
106.70	108.90	1.28 ✓	1.63 ✓	29.14 ✓
108.90	113.90	.00 ✓	.00 ✓	.00 ✓
113.90	114.70	6.75 ✓	12.22 ✓	88.80 ✓
114.70	121.90	N/A	N/A	N/A

MOORE SPECTRUM 4

HOLE NO: U-216 LATITUDE: 10858.26 ✓
 HOLE LENGTH: 138.70 DEPARTURE: 7633.34 ✓
 ELEVATION: 1137.98 ✓

✓ AZIMUTH: 225.25 ^{61.0}
 ✓ DIB: -81.23

DIP TESTS: DEPTH DIP AZIMUTH
 61.00 -82.00 204.00
 121.90 -82.00 157.00

DIB 121.9
 DPL

INTERVAL		ASSAYS		
FROM	TO	PB %	ZN %	AG GM/TON
0.00	1.50	3.88 ✓	5.57 ✓	65.49 ✓
1.50	3.00	1.90 ✓	4.30 ✓	37.37 ✓
3.00	4.60	2.93 ✓	6.17 ✓	56.57 ✓
4.60	6.10	3.95 ✓	7.21 ✓	70.63 ✓
6.10	7.60	5.00 ✓	10.06 ✓	80.57 ✓
7.60	9.10	2.58 ✓	5.46 ✓	41.49 ✓
9.10	10.70	2.75 ✓	6.70 ✓	45.26 ✓
10.70	12.50	1.48 ✓	4.38 ✓	26.40 ✓
12.50	35.10	N/A	N/A	N/A
35.10	36.60	9.57 ✓	19.93 ✓	138.17 ✓
36.60	38.10	13.40 ✓	21.48 ✓	215.66 ✓
38.10	39.60	10.43 ✓	18.62 ✓	191.66 ✓
39.60	46.10	N/A	N/A	N/A
46.10	48.10	5.55 ✓	9.52 ✓	96.69 ✓
48.10	49.80	N/A	N/A	N/A
49.80	51.80	3.78 ✓	3.75 ✓	50.40 ✓
51.80	53.30	1.05 ✓	1.35 ✓	17.14 ✓
53.30	62.80	N/A	N/A	N/A
62.80	64.00	1.68 ✓	2.80 ✓	30.17 ✓
64.00	65.50	5.00 ✓	6.30 ✓	77.83 ✓
65.50	67.10	4.15 ✓	6.93 ✓	61.37 ✓
67.10	68.60	2.23 ✓	2.05 ✓	28.46 ✓
68.60	70.10	1.55 ✓	1.83 ✓	20.23 ✓
70.10	71.60	5.60 ✓	10.17 ✓	70.63 ✓
71.60	73.60	3.50 ✓	6.25 ✓	52.46 ✓
73.60	94.00	N/A	N/A	N/A
94.00	96.00	.23 ✓	.35 ✓	5.14 ✓
96.00	97.50	.45 ✓	1.20 ✓	7.20 ✓
97.50	99.10	.08 ✓	.30 ✓	2.06 ✓
99.10	100.60	.00	.00	.00
100.60	102.10	.18 ✓	.30 ✓	3.09 ✓
102.10	103.60	N/A	N/A	N/A
103.60	105.20	.08 ✓	.10 ✓	2.06 ✓
105.20	106.70	.08 ✓	.43	2.06 ✓
106.70	108.20	3.88 ✓	7.34 ✓	45.26 ✓
108.20	109.70	.30 ✓	.88 ✓	5.14 ✓
109.70	123.30	.00	.00	.00
123.30	123.80	9.40 ✓	9.30 ✓	90.86 ✓
123.80	126.50	N/A	N/A	N/A
126.50	128.00	1.88 ✓	1.93 ✓	18.17 ✓
128.00	129.50	2.75 ✓	2.35 ✓	30.17 ✓
129.50	138.70	N/A	N/A	N/A

HOLE NO: U-217
 HOLE LENGTH: 123.60

LATITUDE: 10707.98
 DEPARTURE: 7467.90
 ELEVATION: 1172.83

AZIMUTH: ~~288.00~~
 DIP: ~~85.00~~

244.0
 -82.0

DIP TESTS: DEPTH DIP AZIMUTH
 12.20 -82.00 288.00
 73.10 -87.00 357.00
 118.90 ~~-90.00~~ 0.00

D&B - UNABLE TO READ

INTERVAL		ASSAYS			
FROM	TO	PB %	ZN %	AG GM/TON	
0.00	47.30	N/A	N/A	N/A	
47.30	48.80	6.45✓	3.68✓	74.77	74.74
48.80	50.30	2.85✓	1.85✓	56.57✓	
50.30	51.80	.88✓	.70✓	24.34✓	
51.80	53.70	1.93✓	1.43✓	31.20✓	
53.70	117.20	.00	.00	.00	
117.20	118.70	4.73✓	5.60✓	63.43✓	
118.70	120.20	2.58✓	2.80✓	36.34✓	
120.20	121.70	2.55✓	.63✓	10.63✓	
121.70	123.00	.80✓	.88✓	13.03✓	
123.00	123.60	N/A	N/A	N/A	

MOORE SPEEDFILE 4

HOLE NO: U-218 LATITUDE: 10956.37 ✓
 HOLE LENGTH: 45.70 DEPARTURE: 7382.51 ✓
 ELEVATION: 1100.52 ✓
 AZIMUTH: 231.22 ✓
 DIP: -23.07 ✓

INTERVAL		ASSAYS		
FROM	TO	PB	ZN	AG
		%	%	GM/TON
0.00	3.00	7.70 ✓	11.71 ✓	135.09 ✓
3.00	4.50	5.55 ✓	10.09 ✓	97.72 ✓
4.50	6.00	4.95 ✓	8.60 ✓	88.80 ✓
6.00	7.50	2.10 ✓	5.25 ✓	40.46 ✓
7.50	9.00	1.53 ✓	3.93 ✓	29.14 ✓
9.00	10.50	2.60 ✓	5.35 ✓	47.31 ✓
10.50	12.00	4.15 ✓	6.75 ✓	68.57 ✓
12.00	13.50	6.27 ✓	9.99 ✓	90.86 ✓
13.50	15.00	3.85 ✓	7.65 ✓	50.40 ✓
15.00	16.50	2.70 ✓	5.68 ✓	40.46 ✓
16.50	18.00	5.09 ✓	6.61 ✓	85.72 ✓
18.00	19.50	3.90 ✓	4.60 ✓	64.46 ✓
19.50	21.00	2.45 ✓	3.50 ✓	49.03 ✓
21.00	22.50	5.79 ✓	6.91 ✓	93.94 ✓
22.50	24.00	7.43 ✓	11.15 ✓	141.26 ✓
24.00	25.50	4.20 ✓	6.44 ✓	66.51 ✓
25.50	27.00	6.32 ✓	11.25 ✓	98.74 ✓
27.00	29.10	5.00 ✓	8.52 ✓	77.83 ✓
29.10	32.00	N/A	N/A	N/A
32.00	34.10	2.43 ✓	5.60 ✓	63.43 ✓
34.10	45.70	N/A	N/A	N/A

} a few short?

MOORE SPEEDFILE 4