

HOLE NO. 70-2

N. 10, 197.99

E 13,600.70

COLLAR ELEV. 4205

019237

DEPTH	FROM	TO	FOOTAGE	ANALYSIS				WEIGHTED AV. ANALYSIS				REMARKS
				Pb	Zn	Fe Ag	NO. OF	Pb	Zn	Comb.	Ag	
4065	121	127	6	0.9	40		9040	0.9	4.0	4.9		6' INT. 4084 - 4078
3990	192	195	3	0.4	20		9041	3.35	6.80	10.15		23' INT. 4013 - 3990. AV. 4010 - 3990 20'
	195	200	5	2.3	77		9042					
	200	205	5	3.8	60		9043					
	205	210	5	4.7	71		9044					
	210	215	5	2.6	64		9045					
3950	215	220	5	3.4	72		9046	3.29	6.65	9.94		
	220	225	5	2.1	78		9047					
	225	230	5	2.1	52		9048					
	230	235	5	3.2	79		9049					
	235	240	5	5.0	65		9050					
	240	245	5	3.3	61		9051					
	245	250	5	4.7	75		9052					
	250	255	5	2.5	50		9053					

3910

FROM	TO	FRACTION	ASSAYS				WEIGHTED AV. ASSAY					REMARKS
			Pb	Zn	Fe Ag	No Cu	Pb	Zn	Comb.	Ag	Cu	
255	260	5	2.6	4.6		9054	2.01	3.95	5.96			
260	265	5	1.6	2.1		9055						
265	270	5	3.5	4.2		9056						
270	275	5	2.8	4.2		9057						
275	280	5	1.8	7.7		9058						
280	285	5	2.0	6.1		9059						
285	290	5	1.0	1.5		9060						
290	295	5	0.8	1.2		9061						
295	300	5	0.5	1.0		9062						

3970

300	305	5	1.8	1.0		9063	2.03	3.08	5.11		
305	310	5	0.5	0.5		9064					
310	315	5	1.4	3.1		9065					
315	320	5	3.2	4.0		9066					
320	325	5	2.4	6.1		9067					
325	330	5	2.6	1.3		9068					
330	335	5	3.8	7.6		9069					





HOLE NO. 70-1

N. 10,483.33

E. 13,507.71

COLLAR ELEV. 4175

FROM	TO	FOOTAGE	ASSAYS				WEIGHTED AV. ASSAY					REMARKS	
			Pb	Zn	Fe Ag	Na Cu	Pb	Zn	Comb.	Ag	Cu		
													16' INT.
	169	174	5	0.4	0.5	6.0	9001	0.4	0.5	0.9			AV. 4006-4000
3990	174	175	1	0.3	0.5	5.5	9002						6'
	175	180	5	3.8	7.6	20.5	9003	3.8	7.25	11.05			AV. 4000-3990
	180	185	5	3.8	6.9	21.7	9004						10'
	185	190	5	2.2	6.2	20.8	9005						
	190	195	5	2.5	7.2	11.8	9006						
	195	200	5	1.0	6.6	13.1	9007	2.90	6.79	9.69			
	200	205	5	1.2	6.5	21.8	9008						
3950	205	210	5	2.5	4.4	30.3	9009						
	210	215	5	4.4	7.5	27.1	9010						
	215	220	5	5.3	8.9	24.3	9011						
	220	225	5	4.1	7.0	24.4	9012						
	225	230	5	3.4	5.1	25.3	9013						
	230	235	5	2.0	4.3	24.6	9014						
3910	235	240	5	0.3	1.9	29.8	9015	3.03	5.73	8.76			
	240	245	5	1.7	3.7	27.9	9016						
	245	250	5	2.5	8.1	25.0	9017						
	250	255	5	4.8	8.3	29.5	9018						
	255	260	5	3.1	6.1	30.7	9019						
	260	265	5	6.4	8.3	29.7	9020						

LITCH	FROM	TO	FOOTAGE	ASSAYS				WEIGHTED AV. ASSAY					REMARKS
				Pb	Zn	Fe Ag	Mo Cr	Pb	Zn	Comb.	Ag	Cu	
3370	265	270	5	51	84	28.7	9021	2.84	6.63	9.47			
	270	275	5	50	70	25.8	9022						
	275	280	5	2.0	3.7	20.2	9023						
	280	285	5	2.5	7.0	15.7	9024						
	285	290	5	1.4	5.3	27.7	9025						
	290	295	5	1.7	6.0	30.6	9026						
	295	300	5	2.2	7.7	30.5	9027						
	300	305	5	2.8	7.9	32.4	9028						
3830	305	310	5	2.5	5.5	32.2	9029	3.04	6.86	9.90			
	310	315	5	3.7	7.1	31.5	9030						
	315	320	5	3.9	8.6	23.0	9031						
	320	325	5	1.8	4.6	18.0	9032						
	325	330	5	5.3	9.6	26.9	9033						
	330	335	5	3.3	8.4	26.3	9034						
	335	340	5	2.8	6.7	25.1	9035						
3790	340	345	5	1.0	4.4	8.4	9036	1.03	4.10	5.13			
	<del>345</del>	350	5	1.4	5.2	5.6	9037						
	350	355	5	0.7	3.7	3.7	9038						
	355	360	5	1.0	3.4	4.0	9039						

HOLE NO. 70-3

N. 10,284.00

E. 13,696.64

COLLAR ELEV. 4207

HOLE NO.	FROM	TO	FOOTAGE	AGGREGATE			No. of	ANALYZED BY			AGGREGATE	REMARKS
				Pb	Zn	Ag		Pb	Zn	Comb.		
4065	128	133	5	4.5	8.0		3094	4.02	7.89	11.91		9.5' INT. 4079-4069.5
	133	137.6	4.6	3.4	7.6		3095					
3950	225	227	2	2.0	9.8		3096	2.03	8.22	10.25		32' INT. 3982-3950
	227	232	5	2.1	7.2		3097					
	232	237	5	1.8	7.4		3098					
	237	242	5	2.8	9.7		3099					
	242	247	5	1.5	8.7		3100					
	247	252	5	2.0	8.8		3101					
	252	257	5	2.0	6.9		3102					
3910	257	262	5	1.5	4.4		3103	3.68	6.84	10.52		
	262	267	5	3.8	7.4		3104					
	267	272	5	0.8	1.2		3105					
	272	277	5	1.6	2.6		3106					
	277	282	5	3.2	2.5		3107					
	282	287	5	6.5	12.3		3108					
	287	292	5	5.0	10.1		3109					
292	297	5	7.0	14.2		3110						







SECTION	FROM	TO	FOOTAGE	ASSAYS				WEIGHTED AV.			ASSAY	REMARKS
				Pb	Zn	Ag	Cu	Pb	Zn	Comb.		
3950	214	219	5	22	86			3.60	6.66	10.26		
	219	224	5	2.6	72							
	224	229	5	2.7	65							
	229	234	5	5.5	59							
	234	239	5	2.5	58							
	239	244	5	3.1	58							
	244	249	5	5.9	73							
	249	254	5	4.3	62							
3910	254	259	5	22	66			3.43	6.25	9.68		
	259	264	5	3.2	67							
	264	269	5	2.8	67							
	269	274	5	4.7	65							
	274	279	5	3.2	59							
	279	284	5	2.6	56							
	284	289	5	4.7	65							
	289	294	5	4.0	55							



3790

3750

FROM	TO	FOOTAGE	ASSAY				WEIGHTED AV. ASSAY			REMARKS
			Pb	Zn	Ag	Cu	Pb	Zn	Comb.	
374	379	5	10	2.7						
379	384	5	1.7	3.9						
384	389	5	4.0	5.2						
389	394	5	4.0	6.0		2.68	4.54	7.22		
394	399	5	2.8	4.7						
399	404	5	1.8	3.8						
404	409	5	2.4	5.2						
409	414	5	3.7	4.8						
414	419	5	3.7	5.1						
419	424	5	1.7	2.8						
424	429	5	5.3	5.6						
429	434	5	2.1	3.8		3.04	3.95	6.99		
434	439	5	3.3	2.7						
439	444	5	3.2	4.1						
444	449	5	2.8	3.9						
449	454	5	2.2	3.6						





ID	FROM	TO	FOOTAGE	ANALYSIS				WEIGHTED AV. ANALYSIS			REMARKS	
				Pb	Zn	Ag	Cu	Pb	Zn	Cont.		Ag
3830	227	232	5	5.3	7.2							
	232	237	5	6.6	7.0							
	237	242	5	6.2	6.7							
	242	247	5	4.3	5.7		4.00	6.20	10.20			
	247	252	5	4.9	6.4							
	252	257	5	0.6	4.2							
	257	262	5	0.7	5.7							
	262	267	5	3.4	6.7							
3790	267	272	5	0.4	4.3							
	272	277	5	4.4	5.9							
	277	282	5	0.6	4.0		2.61	5.58	8.19			AV. 3830-3791 39'
	282	287	5	0.6	5.0							
	287	292	5	2.4	4.3							
	292	297	5	3.8	4.56							
	297	302	5	4.0	7.4							
	302	306	4	5.8	10.2							
3750	306	307	1	0.4	0.2							
	307	311	4	0.4	0.2							
	311	316	5	0.4	0.2							



3990

FROM	TO	FOOTAGE	ASSAYS				WEIGHTED A.V.			ASSAY	REMARKS
			Pb	Zn	Ag	Cu	Pb	Zn	Comb.		
67	72	5	1.7	3.0							
72	77	5	0.6	1.0							
77	82	5	1.0	1.4							
82	87	5	0.6	2.4				2.30	4.44	6.74	
87	92	5	2.7	6.7							
92	97	5	4.2	6.9							
97	102	5	5.0	7.3							
102	107	5	2.6	6.8							

3950

107	112	5	4.8	7.1							
112	117	5	4.1	5.9							
117	122	5	3.9	6.0							
122	127	5	3.8	6.9				4.48	6.55	11.03	
127	132	5	5.2	6.9							
132	137	5	5.3	7.3							
137	142	5	4.7	7.0							
142	147	5	4.0	5.3							

FROM	TO	FOOTAGE	ASSAYS				WEIGHTED AT			ASSAY		TOTAL
			Pb	Zn	Ag	Cu	Pb	Zn	Cont.	Ag	Cu	
147	152	5	3.0	5.8								
152	157	5	4.8	11.4								
157	162	5	4.3	14.1				3.03	7.80	10.83		
162	167	5	2.1	7.2								
167	172	5	0.3	1.6								
172	177	5	4.9	10.3								
177	182	5	2.5	5.7								
182	187	5	2.4	6.3								
187	192	5	2.6	7.0								
192	197	5	1.8	5.6								
197	202	5	3.9	6.8				3.26	6.56	9.82		
202	207	5	3.9	7.8								
207	212	5	3.5	6.1								
212	217	5	4.4	7.5								
217	222	5	3.7	7.3								
222	227	5	2.3	4.4								

3910

3870

3830

TRCH	ID	FOOTING	ASSAYS				WEIGHTED AT.			ASSAY	REMARKS
			Pb	Zn	Ag	Cu	Pb	Zn	Comb.		
227	232	5	14	24							
232	237	5	77	94							
237	242	5	15	52							
242	247	5	39	55				4.34	5.91	10.25	
247	252	5	31	35							
252	257	5	50	68							
257	262	5	76	80							
262	267	5	45	65							

3790

267	272	5	39	72							
272	277	5	77	96							
277	282	5	45	86							
282	287	5	50	91				4.29	7.53	11.82	
287	292	5	66	102							
292	297	5	26	61							
297	302	5	27	56							
302	307	5	13	38							

3750

307	312	5	02	22				0.4	2.4	2.8	
312	317	5	06	26							

10' INT.  
3790-3780

HOLE NO. 70-7

N 10.001.87

E. 13,379.81

COLLAR ELEV 4100.

ELEVATION	FROM	TO	FOOTAGE	ASSAYS				WEIGHTED AV. ASSAY			REMARKS	
				Pb	Zn	Ag	Cu	Pb	Zn	Comb.		
	159	165	6	8.9	8.0							31' intersection 3941-3910
	165	170	5	5.7	7.3			6.29	8.16	14.45		
3910	170	175	5	4.7	6.5							
	175	180	5	4.8	8.4							
	180	185	5	5.9	7.3							
	185	190	5	7.2	11.5							
	190	195	5	11.1	13.7			9.04	11.76	20.80		8.5' intersection 3910-3901.5
3870	195	198.5	3.5	6.1	9.0							
<u>LOST HOLE</u>												



DISTRICT	FROM	TO	FOOTAGE	ANALYSIS				ANALYSIS			REMARKS
				Pb	Zn	Ag	Cu	Pb	Zn	Cu	
	292	297	5	5.3	6.4						
	297	302	5	3.6	8.0						
	302	307	5	0.7	8.1			2.46	5.15	7.61	
	307	312	5	3.0	5.8						
	312	317	5	2.1	6.2						
	317	322	5	2.0	2.4						
	322	327	5	2.0	2.9						
3870	327	332	5	1.0	1.4						
	332	337	5	1.8	4.8						
	337	342	5	2.4	6.2			2.30	6.60	8.90	AV. 3870 - 3870 20'
	342	347	5	2.6	8.6						
	347	352	5	2.4	6.8						
	352	357	5	0.5	2.4			0.70	1.80	2.50	AV. 3850 - 3850 20'
	357	362	5	0.7	1.4						
	362	367	5	0.7	1.8						
3830	367	372	5	0.9	1.6						



DATE	FROM	TO	FOOTAGE	ASSAYS			ELEMENTED			AV.	ASSAY	REMARKS
				Pb	Zn	Ag	Pb	Zn	Comb.			
	452	457	5	1.0	2.6		2.81	4.35	7.16			
	457	462	5	1.6	4.1							
	462	467	5	1.5	2.8							
	467	472	5	4.1	5.9							
	472	477	5	4.1	5.4							
	477	482	5	2.0	3.4							
	482	487	5	3.4	4.1							
3710	487	492	5	4.8	6.5							
	492	497	5	3.7	6.3					32' intersection 3710 - 3678		
	497	502	5	3.1	4.6		2.98	4.72	7.70			
	502	507	5	1.8	3.6							
	507	512	5	2.8	4.3							
	512	517	5	3.2	4.2							
	517	522	5	3.3	5.3							
	522	524	2	0.8	3.3							
3670												

HOLE NO. 70-8

N. 10,389.09

E. 13,797.41

COLLAR ELEV 4264

DEPTH	FROM	TO	FOOTAGE	ASSAYS				WEIGHTED AV. ASSAY				REMARKS
				Pb	Zn	Ag	Cu	Pb	Zn	Comb.	Ag	
4030	218	224	6	44	10.8			2.96	8.21	11.17		16' INTER. 4046-4030
	224	229	5	12	65							
	229	234	5	30	68							
3990	234	239	5	26	55			2.93	7.64	10.57		
	239	244	5	22	73							
	244	249	5	22	73							
	249	254	5	44	84							
	254	259	5	34	92							
	259	264	5	44	119							
	264	269	5	25	93							
	269	274	5	17	22							
3950	274	279	5	37	30			3.07	5.00	8.07		AV 3990-3975 15'
	279	284	5	38	79							
	284	289	5	17	41							
	289	294	5	0.1	1.0							
	294	299	5	0.2	11							
	299	304	5	0.9	41							
	304	309	5	0.1	04							
	309	314	5	0.1	05			0.28	1.42	1.70		AV. 3975-3950 25'



HOLE NO. 70-10

N. 10,596.76

E. 13,653.50

COLLAR ELEV. 4259

DEPTH	FROM	TO	FORESAM	ASSAYS				WEIGHTED AV. ASSAY					REMARKS
				Pb	Zn	Ag	Cu	Pb	Zn	Comb.	Ag	Cu	
4100	143	149	6	4.3	8.0			3.89	7.19	11.08			16' INT. 4100-4116
	149	154	5	4.0	9.1								
	154	159	5	3.3	4.3								
4065	159	164	5	4.9	8.6			4.28	10.52	14.80			26' INT. 4100-4074
	164	169	5	3.0	7.8								
	169	174	5	4.3	10.0								
	174	179	5	4.4	12.7								
	179	185	6	4.7	13.0								
3990	262	269	7	1.0	4.2			1.0	4.2	5.2			7' INT. 3997-3990
3950	269	274	5	1.0	5.9			1.8	6.85	8.65			10' INT. 3990-3980
	274	279	5	2.6	7.8								

HOLE NO. 70-11

N. 10, 097.25

E. 13, 894.72

COLLAR ELEV 4232

DEPTH	FROM	TO	FOURCE	ASSAYS				WEIGHTED AV. ASSAY			REMARKS
				Zn	Pb	Ag	Cu	Zn	Pb	Ag	
3990	238	242	4	0.15							
	242	247	5	0.5	23						
	247	252	5	2.8	48						
	252	257	5	5.3	10.8						
3950	257	262	5	0.6	6.5			2.17	7.49	9.66	
	262	267	5	1.0	8.1						
	267	272	5	1.4	8.7						
	272	277	5	2.7	7.5						
	277	282	5	1.4	6.0						
	282	287	5	1.6	3.7						
	287	292	5	0.3	2.9						
	292	297	5	0.3	5.2			0.99	3.59	4.58	
3910	297	302	5	0.7	5.4						
	302	307	5	2.9	4.8						
	307	312	5	1.5	3.3						
	312	317	5	0.3	1.9						
	317	322	5	0.3	1.5						

AV 3985-3950  
35'





3710

NO	FOUNDRY	WEIGHTED	ANALYSIS				AV.			REMARKS
			Pb	Zn	Ag	Cu	Pb	Zn	Comb.	
482	487	5	6.4	99						
487	492	5	4.9	94						
492	497	5	125	194		6.50	10.80	17.30		
497	502	5	5.0	124						
502	507	5	7.1	76						
507	512	5	6.6	107						
512	517	5	6.1	118						
517	522	5	3.4	5.2						

3670

522	527	5	2.1	2.1						
527	532	5	3.4	6.1						
532	537	5	2.1	4.6		2.89	5.13	8.02		
537	541	4	5.7	10.1						
541	545	4	1.4	3.4						

23' INTER.  
3710-3687

HOLE NO. 70-14

N. 9,992.56

E. 13,457.26

COLLAR ELEV 4138

DEPTH	FROM	TO	FOOTAGE	ASSAYS				WEIGHTED AV. ASSAY			REMARKS	
				Pb	Zn	Ag	Cu	Pb	Zn	Comb.		
3950	184	188	4	38	66			3.8	6.6	10.4		4' INT 3914-3910
	188	193	5	49	63							
	<del>193</del>	198	5	80	106							
	198	203	5	52	66			6.34	7.19	13.53		
3910	203	208	5	67	84							
	208	213	5	64	65							
	213	218	5	66	68							
	218	223	5	62	66							
	223	228	5	67	75							
	228	233	5	76	93							
	233	238	5	52	87							
	238	243	5	50	74			5.23	8.55	13.78		
3870	243	248	5	64	88							
	248	253	5	70	93							
	253	258	5	53	84							
	258	263	5	31	81							
	263	268	5	22	84							

ID	FROM	TO	FOOTAGE	ASSAYS				WEIGHTED AV.			AGGATE		REMARKS
				Pb	Zn	Ag	Cu	Pb	Zn	Comb.	Ag	Cu	
3830	268	273	5	44	76			4.88	7.88	12.76			
	273	278	5	46	69								
	278	283	5	51	57								
	283	288	5	32	77								
	288	293	5	31	61								
	293	298	5	59	85								
	298	303	5	62	96								
	303	308	5	65	109								
3790	308	315	7	25	42			2.5	4.2	6.7		7' INT. 3830-3823	
	322.5	328	5.5	0.7	1.3			0.66	1.30	1.96		85' INT. 3758.5-3750.	
	328	331	3	0.6	1.3								
3750	376	378	2	15.3	124			6.80	9.90	16.70			10' INT. 3760-3750
	378	383	5	6.7	122								
	383	386	3	1.3	44								
710	415	416.5	1.5	49	94			4.9	9.4	14.3			15' INT. 3723-3721.5

5013

HOLE NO. 70-16

N. 10,304.15

E 13,498.62

COLLAR ELEV. 4143.

	FROM	TO	FOOTAGE	ASSAYS				WEIGHTED AV. ASSAY			REMARKS
				Pb	Zn	Ag	Cu	Pb	Zn	Comb.	
4030	94	98	4	1.0	6.9						19' INT. 4049-4030
	98	103	5	0.9	5.3			0.87	5.58	6.45	
	103	108	5	1.0	7.2						
	108	113	5	0.6	6.2						
3990	113	118	5	1.7	6.2						
	118	123	5	2.3	6.0						
	123	128	5	7.1	8.6						
	128	133	5	4.9	8.0			3.78	7.60	11.38	
	133	138	5	3.9	8.8						
	138	143	5	3.5	7.6						
	143	148	5	3.7	7.6						
3950	148	153	5	3.1	8.0						
	153	158	5	3.3	9.2						
	158	163	5	2.2	7.6						
	163	168	5	4.4	7.4			3.10	6.76	9.86	
	168	173	5	3.4	7.8						
	173	178	5	3.9	3.6						
	178	183	5	2.3	5.8						
	183	188	5	2.4	6.5						
	188	193	5	2.9	7.2						





