

CYPRUS ANVIL MINING CORPORATION  
DIAMOND DRILL CORE LOG

Hole Number: 65-06

Fabric Orientation Diagram:

Project: \_\_\_\_\_

Location: ZONE 1

Claim: \_\_\_\_\_

Terr. Plane Co-ords.: \_\_\_\_\_ N

\_\_\_\_\_ E

Grid Co-ords.: 9,599.6 N N

14,399.9 V E

All symmetrical terminations looking

Elevation: 4099.8 V

\_\_\_\_\_ with \_\_\_\_\_ dipping

\_\_\_\_\_ with dip azimuth \_\_\_\_\_

Total Depth: 586'

Purpose: \_\_\_\_\_

Logged by: \_\_\_\_\_

Date(s) Logged: \_\_\_\_\_

Drilling Contractor:	Core:	Size	From	To	Collar Cased and Capped:
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Merged with MSC506 FD  
6506.KP1 MS6506 FD →  
6506OK

Started: \_\_\_\_\_ Completed: \_\_\_\_\_

CYPRUS ANVIL MINING CORP.  
GEOCHEMICAL LOG

	FROM	TO	UNIT	Pb %	Zn %	Ag G/MT	Cu %	BaO %	S.G.	Py %	Po %	Mn %	
							0.0					0.0	
							0.0					0.0	
							0.0					0.0	
A	100	2840	1	0.00	0.00	0.0	0.00	0.00	2.75	0.0	0.0	0.00	
A	2840	2900	2	2.30	4.30	19.2	0.07	-0.5	-0.5	-0.5	-0.5	-0.5	
A	2900	2950	3	0.40	5.40	30.2	0.00	-0.5	-0.5	-0.5	-0.5	-0.5	
A	2950	3000	4	1.10	4.00	30.9	0.07	-0.5	-0.5	-0.5	-0.5	-0.5	
A	3000	3050	5	1.50	4.20	30.2	0.15	-0.5	-0.5	-0.5	-0.5	-0.5	
A	3050	3100	6	2.50	7.60	80.9	0.01	-0.5	-0.5	-0.5	-0.5	-0.5	
A	3100	3150	7	3.90	9.20	78.2	0.00	-0.5	-0.5	-0.5	-0.5	-0.5	
A	3150	3200	8	2.10	4.10	12.3	0.07	-0.5	-0.5	-0.5	-0.5	-0.5	
A	3200	3250	9	3.40	3.10	8.2	0.07	-0.5	-0.5	-0.5	-0.5	-0.5	
A	3250	3300	10	1.70	1.60	8.2	0.16	-0.5	-0.5	-0.5	-0.5	-0.5	
A	3300	3350	11	1.70	1.60	3.4	0.07	-0.5	-0.5	-0.5	-0.5	-0.5	
A	3350	3400	12	0.00	0.70	0.0	0.00	-0.5	-0.5	-0.5	-0.5	-0.5	
A	3400	3450	13	0.20	0.20	0.0	0.00	-0.5	-0.5	-0.5	-0.5	-0.5	
A	3450	3500	14	3.90	3.20	0.0	0.00	-0.5	-0.5	-0.5	-0.5	-0.5	
A	3500	3550	15	5.50	6.80	5.5	0.18	-0.5	-0.5	-0.5	-0.5	-0.5	
A	3550	3600	16	2.30	2.70	6.8	0.75	-0.5	-0.5	-0.5	-0.5	-0.5	
A	3600	3650	17	0.70	2.50	0.0	0.00	-0.5	-0.5	-0.5	-0.5	-0.5	
A	3650	3700	18	4.40	2.60	13.7	0.22	-0.5	-0.5	-0.5	-0.5	-0.5	
A	3700	3750	19	1.00	8.60	6.8	0.00	-0.5	-0.5	-0.5	-0.5	-0.5	
A	3750	3800	20	1.60	4.40	12.3	0.27	-0.5	-0.5	-0.5	-0.5	-0.5	
A	3800	3850	21	0.50	0.70	0.0	0.00	-0.5	-0.5	-0.5	-0.5	-0.5	
A	3850	3900	22	6.40	11.80	6.8	0.18	-0.5	-0.5	-0.5	-0.5	-0.5	
A	3900	3950	23	1.60	3.6	0.0	0.37	-0.5	-0.5	-0.5	-0.5	-0.5	



CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 65-09

Fabric Orientation Diagram:

Project: \_\_\_\_\_

Location: ZONE 1

Claim: \_\_\_\_\_

Terr. Plane Co-ords.: \_\_\_\_\_ N

\_\_\_\_\_ E

Grid Co-ords.: 9199.8 ✓ N

13,998.3 ✓ E

All summary determinations looking

\_\_\_\_\_ with \_\_\_\_\_ dipping

Elevation: 4060.5 ✓

\_\_\_\_\_ with dip azimuth \_\_\_\_\_

Total Depth: 477' ✓

Purpose: \_\_\_\_\_

Logged by: \_\_\_\_\_ Date(s) Logged: \_\_\_\_\_

Drilling Contractor:	Core:	Size	From	To	Collar Cased and Capped:
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

*merged with RL659.FD*

*RL659.FD + 6509.KP*

*⇒ 6509.DK*

Started: \_\_\_\_\_ Completed: \_\_\_\_\_

CYPRUS ANVIL MINING CORP.  
GEOCHEMICAL LOG

	FROM	TO	UNIT	Pb %	Zn %	Ag G/MT	Cu %	BaO %	S.G.	Py %	Po %	Mn %	
							0.00					0.00	
							0.00					0.00	
A	3400	3450	1	0.00	0.00	0.00	0.00	0.00	2.75	0.0	0.0	0.00	
A	3450	3500	2	0.26	0.57	6.00	0.24	0.21	2.86	5.3	5.9	0.12	
A	3500	3550	3	0.86	3.01	9.00	0.24	0.13	3.02	17.7	6.4	0.14	
A	3550	3600	4	3.13	3.87	35.00	0.07	4.39	3.25	17.7	6.4	0.14	
A	3600	3650	5	5.00	6.52	70.00	0.19	16.14	4.71	17.7	6.4	0.14	
A	3650	3700	6	5.03	7.28	62.00	0.21	0.17	4.44	17.7	6.4	0.14	
A	3700	3750	7	4.87	6.89	57.00	0.42	1.83	4.15	21.9	11.6	0.16	
A	3750	3800	8	3.04	5.44	46.00	0.45	8.32	2.62	21.9	11.6	0.16	
A	3800	3850	9	4.72	7.45	57.00	0.13	3.98	4.54	21.9	11.6	0.16	
A	3850	3900	10	5.18	6.82	49.00	0.09	0.05	4.46	21.9	11.6	0.16	
A	3900	3950	11	3.72	5.92	30.00	0.12	0.07	4.16	25.8	11.2	0.12	
A	3950	4000	12	5.63	5.92	58.00	0.13	0.07	4.26	25.8	11.2	0.12	
A	4000	4050	13	5.50	7.81	54.00	0.57	0.09	4.46	25.8	11.2	0.12	
A	4050	4100	14	5.30	7.21	44.00	0.25	0.14	4.63	25.8	11.2	0.12	
A	4100	4150	15	6.01	7.28	47.00	0.21	0.07	4.58	25.0	7.0	0.14	
A	4150	4200	16	4.71	5.21	47.00	0.23	9.08	4.76	25.0	7.0	0.14	
A	4200	4250	17	2.28	1.92	24.00	0.22	0.07	4.53	25.0	7.0	0.14	
A	4250	4300	18	5.62	13.10	54.00	0.28	1.19	3.67	25.0	7.0	0.14	
A	4300	4350	19	1.46	4.13	26.00	0.09	0.22	2.91	2.7	3.8	0.05	
A	4350	4400	20	15.00	2.51	82.00	0.06	0.15	3.30	2.7	3.8	0.05	
A	4400	4450	21	1.33	2.68	23.00	0.06	0.17	2.75	2.7	3.8	0.05	
A	4450	4500	22	1.38	2.76	24.00	0.05	0.16	2.64	2.7	3.8	0.05	
A	4500	4550	23	3.92	3.67	67.00	0.09	0.25	3.04	6.0	6.7	0.06	
A	4550	4600	24	9.11	5.68	120.00	0.09	0.18	3.08	6.0	6.7	0.06	



CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 65-17

Fabric Orientation Diagram:

Project: Zone 1 Re-log

Location: \_\_\_\_\_

Claim: \_\_\_\_\_

Terr. Plane  
Co-ords.: \_\_\_\_\_ N

\_\_\_\_\_ E

Grid  
Co-ords.: 9,999.5 N

14,800 E

All symmetry determinations looking

NW with S<sub>2</sub> dipping

Elevation: 4221.8 - (Mine)

SW with dip azimuth 210.

Total Depth: 490'

Purpose: Zone 3 DFN

Logged by: PIC

Date(s) Logged: JAN/78

Drilling Contractor:	Core:	Size	From	To	Collar Cased and Capped:
	<u>AXF</u>	<u>0</u>	<u>EDH</u>		

Started: \_\_\_\_\_ Completed: \_\_\_\_\_

*Replaces RLG517.FD/RLA19.01  
(6517.0K, no assays)*

*Entered 9/30/78*







CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 65-17

Fabric Orientation Diagram: \_\_\_\_\_

Project: \_\_\_\_\_

Location: ZONE 1

Claim: \_\_\_\_\_

Terr. Plane Co-ords.: \_\_\_\_\_ N

\_\_\_\_\_ E

Grid Co-ords.: 9,999.5 N

14,800.0 E

All symmetrical terminations looking  
\_\_\_\_\_ with \_\_\_\_\_ dipping  
\_\_\_\_\_ with dip azimuth \_\_\_\_\_

Elevation: 4221.8

Total Depth: 490'

Purpose: \_\_\_\_\_

Logged by: \_\_\_\_\_ Date(s) Logged: \_\_\_\_\_

Drilling Contractor:	Core:	Size	From	To	Collar Cased and Capped:
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Started: \_\_\_\_\_ Completed: \_\_\_\_\_

6517-01K + 6517-02K →  
6517-01K

CP.  
already entered



CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 65-55

Fabric Orientation Diagram:

Project: \_\_\_\_\_

Location: ZONE 3

Claim: \_\_\_\_\_

Terr. Plane Co-ords.: \_\_\_\_\_ N

\_\_\_\_\_ E

Grid Co-ords.: 7035.3 W N

15,525.7 E

All symmetrical determinations looking  
\_\_\_\_\_ with \_\_\_\_\_ dipping  
\_\_\_\_\_ with dip azimuth \_\_\_\_\_

Elevation: 4009.4 ✓

Total Depth: 233' ✓

Purpose: \_\_\_\_\_

Logged by: \_\_\_\_\_ Date(s) Logged: \_\_\_\_\_

Drilling Contractor: \_\_\_\_\_ Core: \_\_\_\_\_ Size \_\_\_\_\_ From \_\_\_\_\_ To \_\_\_\_\_ Collar Cased and Capped: \_\_\_\_\_


Started: \_\_\_\_\_ Completed: \_\_\_\_\_

RL6555.FD + 6TTS.KP

6TTS.OK

KP

