

CYPRUS ANVIL MINING CORPORATION

4020786

DIAMOND DRILL CORE LOG

Hole Number: 66-07

Fabric Orientation Diagram:

Project: _____

Location: ZONE 3

Claim: _____

Terr. Plane Co-ords.: _____ N

_____ E

Grid Co-ords.: 9,200.6 ✓ N

14,798.3 ✓ E

Elevation: 4,156.7 ✓

All symmetrical terminations looking
_____ with _____ dipping
_____ with dip azimuth _____.

Total Depth: 810'

Purpose: _____

Logged by: _____ Date(s) Logged: _____

Drilling Contractor: _____ Core: _____ Size _____ From _____ To _____ Collar Cased and Capped: _____

ASSAYS

RL667.FD + 6607.KP

→ 6607.OK

Started: _____ Completed: _____

6.6-07

FROM	TO	UNIT	Pb %	Zn %	Ag G/MT	Cu %	BaO %	S.G.	Py %	Po %	Mn %	
						0.					0.	
						0.					0.	
A	00	5880	1	0.00	0.00	0.00	0.00	2.75	0.0	0.0	0.00	
A	5880	5930	2	5.35	16.20	54.3	0.07	10.16	4.18	22.2	17.8	0.13
A	5930	5980	3	2.88	3.87	26.0	0.09	0.10	4.16	22.2	7.8	0.13
A	5980	6030	4	1.78	2.30	19.5	0.07	0.08	3.93	22.2	7.8	0.13
A	6030	6080	5	3.26	5.90	15.10	0.17	0.07	3.60	22.2	7.8	0.13
A	6080	6130	6	3.84	9.76	13.8	0.21	0.05	3.97	25.3	4.9	0.16
A	6130	6180	7	1.18	2.84	7.8	0.25	0.02	4.32	25.3	4.9	0.16
A	6180	6230	8	4.13	8.36	10.0	0.13	0.02	4.84	25.3	4.9	0.16
A	6230	6280	9	4.51	12.51	13.6	0.06	0.05	4.39	25.3	4.9	0.16
A	6280	6330	10	3.97	8.36	20.0	0.02	0.06	3.39	20.1	4.8	0.04
A	6330	6380	11	2.78	6.58	14.0	0.02	0.09	4.01	20.1	4.8	0.04
A	6380	6430	12	8.34	15.00	47.0	0.16	0.06	4.55	20.1	4.8	0.04
A	6430	6480	13	3.78	10.87	27.4	0.06	0.17	3.67	20.1	4.8	0.04
A	6480	6580	14	0.96	2.24	19.2	0.06	0.27	3.03	13.9	3.4	0.03
						0.					0.	
A	6580	6630	15	0.35	2.36	9.5	0.16	0.20	3.20	13.9	3.4	0.03
A	6630	6680	16	0.25	1.66	8.5	0.04	0.17	3.24	13.9	3.4	0.03
A	6680	6730	17	1.06	1.46	29.0	0.04	0.23	3.40	13.9	3.5	0.04
A	6730	6780	18	1.76	4.33	22.7	0.12	0.22	2.95	13.9	3.5	0.04
A	6780	8700	19	0.00	0.00	0.00	0.00	2.75	0.0	0.0	0.00	
						0.					0.	
						0.					0.	
						0.					0.	
						0.					0.	

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66-10

Fabric Orientation Diagram:

Project: _____

Location: ZONE 3

Claim: _____

Terr. Plane Co-ords.: _____ N

_____ E

Grid Co-ords.: 8,799.3 N

14,799.5 E

Elevation: 4121.4

All symmetrical terminations looking

_____ with _____ dipping

_____ with dip azimuth _____.

Total Depth: 849

Purpose: _____

Logged by: _____

Date(s) Logged: _____

Drilling Contractor: _____

Core:	Size	From	To	Collar Cased and Capped:
_____	_____	_____	_____	_____
_____	_____	_____	_____	_____
_____	_____	_____	_____	_____

~~LOG 66-10~~

(merged with RLL661A.FD
RLL661A.FD + 6610.KP
→ 6610.QK (10/12)

Started: _____ Completed: _____

KP

6.6.-1.0.

GEOCHEMICAL LOG

FROM	TO	UNIT	Pb %	Zn %	Ag G/MT	Cu %	BaO %	S.G.	Py %	Po %	Mn %	
						0.					0.	
						0.					0.	
						0.					0.	
						0.					0.	
						0.					0.	
						0.					0.	
						0.					0.	
A	100	5700	1	10.10	10.100	10.0	0.10	10.00	2.75	9.0	0.9	0.00
A	5700	57150	2	4.56	6.110	179.2	0.26	1.77	4.03	8.9	10.7	0.18
A	57150	5800	3	4.25	4.65	94.0	0.17	4.47	3.33	8.9	10.7	0.18
A	5800	5850	4	0.50	0.48	15.7	0.05	1.21	2.82	8.9	10.7	0.18
A	5850	5900	5	0.40	0.24	110.8	0.10	2.42	2.76	8.9	10.7	0.18
A	5900	5950	6	2.00	1.24	41.5	0.46	0.20	3.91	32.1	5.0	0.12
A	5950	6000	7	4.56	4.08	53.3	0.10	0.05	4.66	32.1	5.0	0.12
A	6000	6050	8	1.64	1.10	22.1	0.07	0.06	3.95	32.1	5.0	0.12
A	6050	6100	9	1.60	0.78	22.9	0.20	0.05	4.57	32.1	5.0	0.12
A	6100	6150	10	1.20	0.46	26.4	0.21	0.09	4.94	36.9	2.5	0.05
A	6150	6200	11	1.30	0.46	18.4	0.11	0.04	4.60	36.9	2.5	0.05
A	6200	6250	12	1.22	0.82	63.8	0.18	0.89	3.80	36.9	2.5	0.05
A	6250	6300	13	1.14	0.64	27.8	0.19	0.05	4.34	36.9	2.5	0.05
A	6300	6340	14	0.94	1.16	17.1	0.15	0.88	4.73	35.1	3.9	0.08
A	6340	6380	15	1.52	1.83	21.7	0.15	1.23	4.17	35.1	3.9	0.08
A	6380	6390	16	1.52	1.83	21.7	0.15	1.23	4.17	35.1	3.9	0.08
A	6390	6440	17	2.91	4.57	29.4	0.23	2.48	5.05	31.5	2.4	0.10
A	6440	6490	18	2.75	5.98	27.6	0.00	24.07	4.64	31.5	2.4	0.10
A	6490	6540	19	2.67	4.01	30.0	0.14	5.95	4.69	31.5	2.4	0.10

6.6-1.0

GEOCHEMICAL LOG

	FROM	TO	UNIT	Pb %	Zn %	Ag G/MT	Cu %	BaO %	S.G.	Py %	Po %	Mn %	
A	16540	16590	20	12.03	12.23	21.7	0.12	12.29	4.60	33.8	2.7	0.10	
A	16590	16640	21	10.40	10.22	15.3	0.06	10.13	3.90	33.8	2.7	0.10	
A	16640	16690	22	10.94	10.67	15.8	0.12	10.06	4.21	33.8	2.7	0.10	
A	16690	16740	23	13.44	13.55	15.0	0.26	10.07	5.36	33.8	2.7	0.10	
A	16740	16790	24	13.58	13.16	41.1	0.30	10.12	3.20	34.8	3.0	0.10	
A	16790	16840	25	13.61	12.92	45.0	0.29	10.09	2.72	34.8	3.0	0.10	
A	16840	16890	26	12.11	11.29	26.3	0.17	10.63	4.93	34.8	3.0	0.10	
A	16890	16940	27	13.06	14.61	83.3	0.16	15.63	4.41	34.8	3.0	0.10	
A	16940	16990	28	12.37	13.26	30.9	0.25	11.50	4.57	33.8	5.4	0.18	
A	16990	17040	29	12.42	13.78	29.2	0.21	10.09	4.47	33.8	5.4	0.18	
A	17040	17090	30	11.30	12.55	16.0	0.24	10.08	4.31	33.8	5.4	0.18	
A	17090	17140	31	12.65	14.65	23.8	0.24	10.09	2.34	33.8	5.4	0.18	
A	17140	17190	32	13.04	14.63	18.8	0.18	10.44	3.25	31.0	5.2	0.14	
A	17190	17240	33	12.81	15.14	12.2	0.15	10.02	3.30	31.0	5.2	0.14	
A	17240	17290	34	14.05	17.86	17.8	0.10	10.02	2.78	31.0	5.2	0.14	
A	17290	17340	35	12.96	17.26	13.7	0.20	10.05	4.30	31.0	5.2	0.14	
A	17340	17390	36	10.65	11.82	11.6	0.17	10.24	2.48	3.1	3.0	0.04	
A	17390	17440	37	10.81	11.84	13.2	0.11	10.37	2.65	3.1	3.0	0.04	
A	17440	17490	38	11.13	12.36	14.2	0.04	10.35	2.73	3.1	3.0	0.04	
A	17490	17540	39	11.37	14.42	15.6	0.03	10.31	2.89	3.1	3.0	0.04	
A	17540	17590	40	10.75	12.83	19.6	0.07	10.42	2.84	12.1	4.2	0.04	
A	17590	17640	41	10.74	13.64	13.3	0.24	10.16	3.23	12.1	4.2	0.04	
A	17640	17690	42	11.35	14.73	18.3	0.35	10.70	3.43	12.1	4.2	0.04	
A	17690	17740	43	10.33	11.84	9.4	0.22	10.28	2.94	12.1	4.2	0.04	
A	17740	17790	44	10.98	11.17	15.4	0.03	10.31	2.63	12.1	4.2	0.04	
A	17790	18490	45	0.00	0.00	0.0	0.00	10.00	2.75	0.0	0.0	0.00	

EOT.

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66-11

Fabric Orientation Diagram:

Project: _____

Location: ZONE 3

Claim: _____

Terr. Plane Co-ords.: _____ N

_____ E

Grid Co-ords.: 9199.3 ✓ N

15,199.7 ✓ E

Elevation: 4191.5 ✓

Total Depth: 759.5 ✓

All symmetry determinations looking

_____ with _____ dipping

_____ with dip azimuth _____ →

Purpose: _____

Logged by: _____ Date(s) Logged: _____

Drilling Contractor:	Core:	Size	From	To	Collar Cased and Capped:
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Started: _____ Completed: _____

RL6611-FD + 6611-ICP

→ 6611-OK

KL

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66-22

Fabric Orientation Diagram:

Project: _____

Location: ZONE 1

Claim: _____

Terr. Plane Co-ords.: _____ N

_____ E

Grid Co-ords.: 9797.9 N

14,199.0 E

Elevation: 4124.1

All symmetrical determinations looking
_____ with _____ dipping
_____ with dip azimuth _____.

Total Depth: 430.5

Purpose: _____

Logged by: _____ Date(s) Logged: _____

Drilling Contractor:	Core:	Size	From	To	Collar Cased and Capped:
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

✓ merged with MS6622.FD
MS6622.FD + 6622.KP
→ 6622.OK

Started: _____ Completed: _____

FROM	TO	UNIT	Pb %	Zn %	Ag G/MT	Cu %	BaO %	S.G.	Py %	Po %	Mn %	
A	1,100	2,150	1	0.00	0.00	0.00	0.00	2.75	10.0	0.0	0.00	
A	2,150	2,200	2	0.23	0.76	10.00	0.18	0.39	3.10	15.4	5.9	0.12
A	2,200	2,250	3	0.64	3.30	15.00	0.06	0.86	3.79	15.4	5.9	0.12
A	2,250	2,300	4	3.24	3.39	66.00	0.22	9.37	3.90	15.4	5.9	0.12
A	2,300	2,350	5	2.48	2.65	68.00	0.24	6.46	3.65	15.4	5.9	0.12
A	2,350	2,400	6	4.99	3.62	120.00	0.38	7.11	3.59	8.9	6.9	0.13
A	2,400	2,450	7	1.52	0.56	86.00	0.22	3.19	3.09	8.9	6.9	0.13
A	2,450	2,550	8	3.04	2.38	75.00	0.41	6.43	3.32	8.9	6.9	0.13
A	2,550	2,600	9	4.12	3.79	76.00	0.24	13.18	4.19	18.3	5.4	0.20
A	2,600	2,650	10	3.14	3.82	42.00	0.19	9.14	4.76	18.3	5.4	0.20
A	2,650	2,700	11	4.09	5.26	63.00	0.08	33.17	4.51	18.3	5.4	0.20
A	2,700	2,750	12	6.52	7.19	112.00	0.08	36.66	4.78	18.3	5.4	0.20
A	2,750	2,800	13	5.00	5.71	66.00	0.08	24.12	4.92	25.0	4.2	0.10
A	2,800	2,850	14	4.93	6.93	68.00	0.10	28.49	4.80	25.0	4.2	0.10
A	2,850	2,900	15	2.56	4.76	42.00	0.18	15.67	4.63	25.0	4.2	0.10
A	2,900	2,950	16	2.07	1.97	27.00	0.19	2.59	4.85	25.0	4.2	0.10
A	2,950	3,000	17	3.54	7.56	35.00	0.02	27.63	4.65	33.9	2.2	0.02
A	3,000	3,050	18	1.38	1.06	21.00	0.16	1.22	4.81	33.9	2.2	0.02
A	3,050	3,100	19	1.02	0.67	14.00	0.18	0.04	4.50	33.9	2.2	0.02
A	3,100	3,150	20	0.59	0.41	10.00	0.12	0.05	4.45	33.9	2.2	0.02
A	3,150	3,200	21	3.20	4.85	17.00	0.22	0.05	4.81	31.7	6.1	0.12
A	3,200	3,250	22	2.55	7.10	10.00	0.19	0.03	4.49	31.7	6.1	0.12
A	3,250	3,300	23	1.87	4.42	7.00	0.38	0.05	4.42	31.7	6.1	0.12
A	3,300	3,350	24	1.61	2.15	6.00	0.16	0.12	4.27	31.7	6.1	0.12
A	3,350	3,400	25	3.64	5.67	6.00	0.17	0.02	4.44	29.1	7.4	0.19
A	3,400	3,450	26	1.42	3.26	4.00	0.24	0.01	4.52	29.1	7.4	0.19

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66-30

Fabric Orientation Diagram:

Project: _____

Location: ZONE 1

Claim: _____

Terr. Plane Co-ords.: _____ N

_____ E

Grid Co-ords.: 9,793.0 ✓ N

14,536.3 ✓ E

Elevation: 4124.7 ✓

_____ ✓

Total Depth: 526'

Purpose: _____

Logged by: _____ Date(s) Logged: _____

Drilling Contractor: _____ Core: _____ Size _____ From _____ To _____ Collar Cased and Capped: _____

Started: _____ Completed: _____

merged with RL6630
RL6630.FD + 6630.KP
→ 6630.OK

CYPRUS ANVIL MINING CORP.
GEOCHEMICAL LOG

FROM	TO	UNIT	Pb %	Zn %	Ag G/MT	Cu %	BaO %	S.G.	Py %	Po %	Mn %	
						0.					0.	
						0.					0.	
						0.					0.	
A	00	2150	1	0.00	0.00	0.0	0.00	0.00	2.75	0.0	0.0	0.00
A	2150	2200	2	1.02	1.43	19.2	0.09	1.21	2.80	9.1	7.5	0.06
A	2200	2250	3	1.10	6.11	22.7	0.18	0.64	3.06	9.1	7.5	0.06
A	2250	2300	4	4.44	7.31	48.3	0.29	0.21	3.48	9.1	7.5	0.06
A	2300	2350	5	0.23	0.96	16.0	0.75	0.17	3.31	9.1	7.5	0.06
A	2350	2400	6	0.22	0.48	9.3	0.26	0.11	2.87	6.5	4.7	0.04
A	2400	2450	7	0.04	0.06	0.9	0.01	0.14	2.75	6.5	4.7	0.04
A	2450	2500	8	0.38	0.18	18.0	0.24	0.19	2.75	6.5	4.7	0.04
A	2500	2550	9	1.77	1.76	29.2	0.36	0.07	3.35	6.5	4.7	0.04
A	2550	2600	10	1.06	0.24	17.3	0.22	0.12	2.81	15.0	3.0	0.03
A	2600	2650	11	0.52	1.02	9.9	0.16	0.09	3.19	15.0	3.0	0.03
A	2650	2700	12	0.45	1.50	4.8	0.15	0.08	3.90	15.0	3.0	0.03
A	2700	2750	13	1.57	2.45	13.4	0.17	0.06	4.01	15.0	3.0	0.03
A	2750	2800	14	3.00	5.25	20.3	0.09	0.13	3.91	17.8	3.6	0.06
A	2800	2850	15	2.71	6.74	21.0	0.10	0.18	3.02	17.8	3.6	0.06
A	2850	2900	16	0.32	0.34	8.4	0.06	0.22	1.75	17.8	3.6	0.06
A	2900	2950	17	0.21	0.27	5.0	0.03	0.27	2.79	17.8	3.6	0.06
A	2950	3000	18	2.87	4.41	26.3	0.14	0.21	3.24	16.1	3.1	0.05
A	3000	3050	19	1.90	4.46	19.5	0.17	0.10	3.54	16.1	3.1	0.05
A	3050	3100	20	2.20	7.35	13.2	0.10	0.09	3.66	16.1	3.1	0.05
A	3100	3150	21	1.99	7.16	13.3	0.09	0.11	3.64	16.1	3.1	0.05
A	3150	3200	22	2.91	5.33	19.6	0.04	0.14	3.67	20.6	2.0	0.02
A	3200	3250	23	3.57	5.80	31.0	0.03	0.14	3.55	20.6	2.0	0.02

66-30

GEOCHEMICAL LOG

	FROM	TO	UNIT	Pb %	Zn %	Ag G/MT	Cu %	BaO %	S.G.	Py %	Po %	Mn %	
A	3250	3300	24	11.48	51.07	14.00	0.02	0.13	3.78	20.6	2.0	0.02	
A	3300	3350	25	3.96	6.44	27.00	0.02	0.19	3.67	20.6	2.0	0.02	
A	3350	3400	26	1.22	6.73	14.80	0.04	0.27	3.35	21.1	2.2	0.02	
A	3400	3450	27	1.82	4.64	16.40	0.05	0.11	4.08	21.1	2.2	0.02	
A	3450	3500	28	2.15	5.48	14.60	0.02	0.10	3.83	21.1	2.2	0.02	
A	3500	3550	29	2.89	5.86	24.70	0.05	0.15	3.24	21.1	2.2	0.02	
A	3550	3600	30	4.37	8.09	33.20	0.06	0.17	3.44	15.7	2.3	0.01	
A	3600	3650	31	6.36	12.33	35.20	0.05	0.12	3.40	15.7	2.3	0.01	
A	3650	3700	32	0.54	2.08	15.50	0.04	0.15	3.38	15.7	2.3	0.01	
A	3700	3750	33	0.50	2.80	11.50	0.04	0.11	3.60	15.7	2.3	0.01	
A	3750	3800	34	3.02	10.11	16.40	0.06	0.17	3.51	16.5	2.2	0.01	
A	3800	3850	35	4.26	12.32	18.40	0.03	0.16	3.75	16.5	2.2	0.01	
A	3850	3900	36	1.38	2.46	17.50	0.06	0.20	3.35	16.5	2.2	0.01	
A	3900	3950	37	0.50	0.58	8.30	0.04	0.23	1.96	16.5	2.2	0.01	
A	3950	4000	38	0.08	0.35	7.20	0.00	0.01	3.10	24.1	1.9	0.01	
A	4000	4050	39	0.16	1.11	6.20	0.04	0.18	2.15	24.1	1.9	0.01	
A	4050	4100	40	0.98	4.93	14.40	0.05	0.07	2.29	24.1	1.9	0.01	
A	4100	4150	41	0.54	1.61	11.60	0.08	0.19	3.43	24.1	1.9	0.01	
A	4150	4200	42	1.78	2.78	18.30	0.03	0.17	3.38	14.5	2.7	0.02	
A	4200	4250	43	2.26	6.39	28.60	0.02	0.20	3.31	14.5	2.7	0.02	
A	4250	4300	44	1.86	5.38	24.10	0.03	0.22	3.11	14.5	2.7	0.02	
A	4300	4350	45	2.20	4.03	25.00	0.04	0.20	3.39	14.5	2.7	0.02	
A	4350	4400	46	0.56	1.88	11.50	0.04	0.20	3.38	29.6	2.4	0.02	
A	4400	4450	47	2.68	6.81	21.80	0.01	0.06	4.64	29.6	2.4	0.02	
A	4450	4500	48	6.10	8.36	34.00	0.00	0.01	5.09	29.6	2.4	0.02	
A	4500	4550	49	5.08	10.41	37.50	0.00	0.01	4.93	29.6	2.4	0.02	

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66-31

Fabric Orientation Diagram:

Project: _____

Location: ZONE 1

Claim: _____

Terr. Plane Co-ords.: _____ N

_____ E

Grid Co-ords.: 9399.6 ✓ N

13,797.3 ✓ E

All symmetrical determinations looking

_____ with _____ dipping

_____ with dip azimuth _____

Elevation: 4128.0 ✓

Total Depth: 585' ✓

Purpose: _____

Logged by: _____ Date(s) Logged: _____

Drilling Contractor: _____ Core: _____ Size _____ From _____ To _____ Collar Cased and Capped: _____

Core	Size	From	To

merged with MS 6631.FD

Started: _____ Completed: _____

MS 6631.FD + 6631.KP

→ 6631.OK

66-3.1

FROM	TO	UNIT	Pb %	Zn %	Ag G/MT	Cu %	BaO %	S.G.	Py %	Po %	Mn %	
						0.00					0.00	
						0.00					0.00	
A	00	3,850	1	0.00	0.00	0.00	0.00	2.75	0.0	0.0	0.00	
A	3,850	3,900	2	0.61	1.05	8.00	0.11	2.63	3.7	4.4	0.06	
A	3,900	3,950	3	1.07	0.81	14.00	0.11	2.70	3.7	4.4	0.06	
A	3,950	4,000	4	1.68	2.17	13.00	0.07	2.61	3.7	4.4	0.06	
A	4,000	4,050	5	3.12	5.58	30.00	0.05	3.59	20.4	9.7	0.12	
A	4,050	4,100	6	3.35	6.35	43.00	0.10	3.37	4.18	20.4	9.7	0.12
A	4,100	4,160	7	4.91	6.97	75.00	0.13	7.07	4.19	20.4	9.7	0.12
A	4,160	4,230	8	5.47	7.80	76.00	0.24	3.55	4.29	20.4	9.7	0.12
A	4,230	4,270	9	5.90	8.46	86.00	0.35	0.29	4.10	11.0	22.1	0.13
A	4,270	4,300	10	8.63	9.97	100.00	0.27	0.19	4.20	11.0	22.1	0.13
A	4,300	4,360	11	7.49	7.92	76.00	0.29	0.09	3.94	11.0	22.1	0.13
A	4,360	4,400	12	7.10	7.80	66.00	0.25	0.27	3.78	11.0	22.1	0.13
A	4,400	4,460	13	6.57	6.81	89.00	0.11	1.31	4.67	29.7	6.7	0.22
A	4,460	4,500	14	4.53	7.98	53.00	0.18	5.13	4.44	29.7	6.7	0.22
A	4,500	4,560	15	5.59	5.83	51.00	0.25	0.09	4.83	29.7	6.7	0.22
A	4,560	4,620	16	5.25	5.98	43.00	0.28	0.04	4.69	28.8	5.6	0.17
A	4,620	4,650	17	6.33	6.97	73.00	0.17	4.65	4.71	28.8	5.6	0.17
A	4,650	4,710	18	5.75	7.40	60.00	0.12	13.94	4.81	28.8	5.6	0.17
A	4,710	4,760	19	5.43	8.15	43.00	0.06	0.18	4.70	28.8	5.6	0.17
A	4,760	4,820	20	4.54	6.26	57.00	0.28	0.13	4.43	7.7	16.4	0.04
A	4,820	4,900	21	1.95	2.47	39.00	0.06	0.15	2.71	7.7	16.4	0.04
A	4,900	4,920	22	0.78	1.35	17.00	0.01	0.05	2.61	7.7	16.4	0.04
A	4,920	5,850	23	0.00	0.00	0.00	0.00	2.75	0.0	0.0	0.00	
						0.00					0.00	

NEW LOG

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66-33

Fabric Orientation Diagram:

Project: _____

Location: ZONE 1

Claim: _____

Terr. Plane
Co-ords.: _____ N

_____ E

Co-ords.: 9399.3 UN

14197.3 NE

Elevation: 4078.6 ✓

Total Depth: 4610.5 ✓

All specimens examinations looking
_____ with _____ dipping
_____ with dip azimuth _____

Purpose: _____

Logged by: _____ Date(s) Logged: _____

Drilling Contractor:	Core:	Size	From	To	Collar Cased and Capped:
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

replaced DH6633.FD by this data

Started: _____ Completed: _____

6633.FD → 6633.OK

KP

66-33

'OLD LOG' WITH O.K. CODE

FILE: D46633

* DDH: 66-33 * SUMMARY DRILL LOG -- CORRECTED TO TRUE DEPTH AND

COLLAR COORDINATES -- EAST: 9399.3 NORTH: 14197.3 ELEV: 3968.4

----- STRUCTURAL LOG -----

DDH-FT =====	CODE =====	LITH =====	GEOCHM LOG		FEAT =====	SYM =====	S1		S2
			NO	INT			CA	DIPD	CA
0.	R								
72.0	L	01 #							
162.0	L	02 100							
195.0	L	03 0E8							
206.0	L	04 102							
214.5	L	05 100							
231.5	L	06 102							
296.0	L	07 100							
312.0	L	08 104							
328.0	L	09 200							
336.0	L	10 2H3							
342.0	L	11 2E4							
343.0	L	12 104							
353.5	L	13 204							
355.0	L	14 2H3							
362.0	L	15 2E6							
365.0	L	16 2E6							
380.0	L	17 2E6							
391.0	L	18 2E0							
391.7	L	19 2E8							
403.0	L	20 2E0							
406.5	L	21 2E8							
420.0	L	22 2E6							
430.0	L	23 2F0							
446.5	L	24 2E0							
448.0	L	25 104							
451.0	L	26 2E0							
453.0	L	27 2E6							
455.0	L	28 2E0							
461.5	L	29 2F0							
461.5	R								

FINISHED -- LENGTH = 461.50 ENTRIES = 36

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66-33

Fabric Orientation Diagram:

Project: _____

Location: ZONE 1

Claim: _____

Terr. Plane Co-ords.: _____ N

_____ E

Grid Co-ords.: 9,399.3 W N

14,197.3 W E

All symmetrical terminations looking

_____ with _____ dipping

_____ with dip azimuth _____

Elevation: 4078.6 ✓

Total Depth: 461.5 ✓

Purpose: _____

Logged by: _____ Date(s) Logged: _____

Drilling Contractor: _____ Core: _____ Size _____ From _____ To _____ Collar Cased and Capped: _____

_____	_____	_____
_____	_____	_____
_____	_____	_____

merged with 6633.OK

Started: _____ Completed: _____

CYPRUS ANVIL MINING CORP.
GEOCHEMICAL LOG

FROM	TO	UNIT	Pb %	Zn %	Ag G/MT	Cu %	BaO %	S.G.	Py %	Po %	Mn %	
						0.					0.	
						0.					0.	
						0.					0.	
A	100	3100	1	0.00	0.00	0.00	0.00	2.75	0.0	0.0	0.00	
A	3100	3150	2	0.93	1.22	19.00	0.12	0.14	3.20	10.2	11.9	0.05
A	3150	3200	3	0.29	0.12	5.00	0.26	0.07	3.21	10.2	11.0	0.05
A	3200	3250	4	0.16	0.06	5.00	0.29	0.08	3.15	10.2	11.0	0.05
A	3250	3300	5	2.82	4.98	36.50	0.26	0.16	3.35	10.2	11.0	0.05
A	3300	3350	6	6.61	9.17	77.00	0.33	0.08	4.16	10.4	14.6	0.14
A	3350	3400	7	5.38	8.61	73.00	0.31	1.84	4.04	10.4	14.6	0.14
A	3400	3450	8	3.40	5.69	65.00	0.29	1.48	3.59	10.4	14.6	0.14
A	3450	3500	9	1.93	4.62	33.50	0.06	0.12	2.92	10.4	14.6	0.14
A	3500	3550	10	4.51	8.03	57.00	0.13	0.20	3.37	19.7	6.1	0.13
A	3550	3600	11	7.05	11.69	74.50	0.06	3.30	5.26	19.7	6.1	0.13
A	3600	3650	12	7.72	6.62	106.00	0.22	15.15	4.51	19.7	6.1	0.13
A	3650	3700	13	5.67	7.58	61.00	0.12	17.70	4.70	19.7	6.1	0.13
A	3700	3750	14	2.94	4.91	31.00	0.21	7.18	4.78	30.3	3.6	0.08
A	3750	3800	15	3.96	6.64	42.00	0.07	30.05	4.71	30.3	3.6	0.08
A	3800	3850	16	4.87	4.12	48.00	0.24	4.13	4.63	30.3	3.6	0.08
A	3850	3900	17	2.58	2.60	37.00	0.30	0.08	4.73	30.3	3.6	0.08
A	3900	3950	18	6.75	8.06	48.00	0.31	0.06	4.40	30.4	5.1	0.10
A	3950	4000	19	3.67	3.44	42.00	0.25	0.08	4.76	30.4	5.1	0.10
A	4000	4050	20	5.11	4.84	52.00	0.18	4.75	4.59	30.4	5.1	0.10
A	4050	4100	21	4.83	5.08	37.00	0.18	14.36	4.57	30.4	5.1	0.10
A	4100	4150	22	1.98	2.25	21.00	0.19	2.38	4.43	30.2	3.6	0.06
A	4150	4200	23	4.67	7.17	52.00	0.07	27.16	4.59	30.2	3.6	0.06

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66-43

Fabric Orientation Diagram:

Project: _____

Location: ZONE 1

Claim: _____

Terr. Plane Co-ords.: _____ N

_____ E

Grid Co-ords.: 8995.1 N

13,791.9 E

Elevation: 4034.4

All symmetrical terminations looking

_____ with _____ dipping

_____ with dip azimuth _____.

Total Depth: 410'

Purpose: _____

Logged by: _____ Date(s) Logged: _____

Drilling Contractor:	Core:	Size	From	To	Collar Cased and Capped:
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Started: _____ Completed: _____

RL6643. FN
+ 6643. ~~FN~~ => 6643. UC (10/13)

EP

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66-46

Fabric Orientation Diagram:

Project: _____

Location: ZONE 3

Claim: _____

Terr. Plane Co-ords.: _____ N

_____ E

Grid Co-ords.: 9398.9 ✓

14,599.9 ✓

Elevation: 4161.1 ✓

Total Depth: 800' ✓

All symmetry determinations looking
_____ with _____ dipping
_____ with dip azimuth _____.

Purpose: _____

Logged by: _____ Date(s) Logged: _____

Drilling Contractor:	Core:	Size	From	To	Collar Cased and Capped:
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

*merged with RL6646.FD
RL6646.FD + 6646.KP
→ 6646.OK*

Started: _____ Completed: _____

66-46

GEOCHEMICAL LOG

FROM	TO	UNIT	Pb %	Zn %	Ag G/MT	Cu %	BaO %	S.G.	Py %	Po %	Mn %	
						0.00					0.00	
						0.00					0.00	
A	4800	4810	1	0.00	0.00	0.00	0.00	2.75	0.00	0.00	0.00	
A	4810	4850	2	3.00	2.95	26.50	0.13	3.59	2.96	7.00	13.80	0.24
A	4850	4900	3	4.38	5.65	67.70	0.19	9.16	4.03	7.00	13.80	0.24
A	4900	4950	4	6.03	6.57	29.90	0.10	5.67	3.94	18.50	14.90	0.35
A	4950	5000	5	2.33	3.04	31.90	0.15	2.16	3.86	18.50	14.90	0.35
A	5000	5050	6	1.82	1.69	28.50	0.22	0.93	3.83	18.50	14.90	0.35
A	5050	5100	7	5.32	4.76	56.40	0.30	3.59	4.30	18.50	14.90	0.35
A	5100	5150	8	2.83	3.16	51.60	0.47	7.87	3.85	9.50	17.10	0.35
A	5150	5200	9	3.41	3.16	36.00	0.10	6.78	4.20	9.50	17.10	0.35
A	5200	5250	10	6.85	6.76	90.30	0.13	23.70	4.44	9.50	17.10	0.35
A	5250	5300	11	5.76	6.33	75.50	0.14	23.07	4.61	9.50	17.10	0.35
A	5300	5350	12	8.10	7.30	103.40	0.11	26.06	4.68	21.60	4.30	0.29
A	5350	5400	13	5.68	6.28	77.20	0.10	23.15	4.49	21.60	4.30	0.29
A	5400	5450	14	4.38	5.14	59.40	0.13	17.72	4.75	21.60	4.30	0.29
A	5450	5500	15	3.20	4.63	41.90	0.13	7.91	4.48	21.60	4.30	0.29
A	5500	5550	16	2.41	3.25	37.00	0.16	0.18	3.29	27.90	2.70	0.11
A	5550	5600	17	1.77	0.19	69.10	0.06	0.04	3.28	27.90	2.70	0.11
A	5600	5650	18	0.18	0.14	11.90	0.02	0.04	3.51	27.90	2.70	0.11
A	5650	5700	19	2.50	1.83	27.70	0.12	0.02	4.54	27.90	2.70	0.11
A	5700	5750	20	2.33	1.91	25.80	0.10	0.03	4.66	36.00	4.00	0.12
A	5750	5800	21	1.36	2.61	17.90	0.33	0.08	4.23	36.00	4.00	0.12
A	5800	5850	22	2.37	2.95	20.70	0.21	0.09	4.45	36.00	4.00	0.12
A	5850	5900	23	0.52	0.67	2.17	0.20	0.02	4.69	36.00	4.00	0.12
A	5900	5950	24	1.16	2.33	4.20	0.18	0.03	4.59	31.30	5.00	0.13

66-46

GEOCHEMICAL LOG

	FROM	TO	UNIT	Pb %	Zn %	Ag G/MT	Cu %	BaO %	S.G.	Py %	Po %	Mn %	
A	59.50	60.00	25	4.06	8.82	13.90	0.14	0.02	4.61	31.3	5.0	0.13	
A	60.00	60.50	26	2.11	2.75	20.16	0.44	0.04	4.27	31.3	5.0	0.13	
A	60.50	61.00	27	2.65	6.52	5.80	0.11	0.06	5.12	31.3	5.0	0.13	
A	61.00	61.50	28	3.45	6.99	9.40	0.08	0.34	5.06	35.1	3.0	0.04	
A	61.50	62.00	29	4.88	7.65	18.10	0.07	0.16	5.02	35.1	3.0	0.04	
A	62.00	62.50	30	5.35	9.58	16.80	0.05	0.27	4.73	35.1	3.0	0.04	
A	62.50	63.00	31	1.13	4.85	2.50	0.20	0.03	4.75	35.1	3.0	0.04	
A	63.00	63.50	32	1.82	3.44	4.90	0.23	0.03	4.52	32.0	7.4	0.17	
A	63.50	64.00	33	2.44	4.31	7.80	0.24	0.02	4.52	32.0	7.4	0.17	
A	64.00	64.50	34	0.97	2.30	2.00	0.26	0.02	4.08	32.0	7.4	0.17	
A	64.50	65.00	35	0.64	2.23	4.10	0.56	0.02	4.09	32.0	7.4	0.17	
A	65.00	65.50	36	2.38	4.82	8.20	0.43	0.02	4.56	25.5	10.5	0.07	
A	65.50	66.00	37	4.95	9.64	11.10	0.07	0.02	4.85	25.5	10.5	0.07	
A	66.00	66.50	38	3.61	6.30	17.80	0.08	0.08	3.92	25.5	10.5	0.07	
A	66.50	67.00	39	6.27	14.31	44.50	0.28	0.06	4.05	25.5	10.5	0.07	
A	67.00	67.50	40	1.72	5.47	31.20	0.23	0.14	3.11	15.0	6.0	0.02	
A	67.50	68.00	41	0.56	0.26	8.60	0.15	0.09	2.43	15.0	6.0	0.02	
A	68.00	68.50	42	0.85	1.76	10.30	0.03	0.10	2.06	15.0	6.0	0.02	
A	68.50	69.00	43	3.88	2.15	28.50	0.04	0.05	3.79	15.0	6.0	0.02	
A	69.00	69.50	44	1.83	5.32	21.00	0.05	0.04	4.01	35.7	1.8	0.02	
A	69.50	70.00	45	3.15	4.34	14.40	0.02	0.01	5.08	35.7	1.8	0.02	
A	70.00	70.50	46	4.09	8.42	19.30	0.05	0.02	4.50	35.7	1.8	0.02	
A	70.50	71.00	47	3.51	3.07	16.40	0.02	0.01	5.20	35.7	1.8	0.02	
A	71.00	71.50	48	3.51	4.42	15.80	0.02	0.01	3.44	30.8	2.3	0.02	
A	71.50	72.00	49	2.72	5.19	14.18	0.03	0.02	3.65	30.8	2.3	0.02	
A	72.00	72.50	50	2.62	6.88	19.18	0.10	0.11	3.59	30.8	2.3	0.02	

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66-47

Fabric Orientation Diagram:

Project: _____

Location: ZONE 3

Claim: _____

Terr. Plane Co-ords.: _____ N

E

Grid Co-ords.: 9599.8 ✓ N

15199.8 ✓ E

All symmetrical terminations looking

_____ with _____ dipping

_____ with dip azimuth _____.

Elevation: 4217.1 ✓

Total Depth: 700 ✓

Purpose: _____

Logged by: _____ Date(s) Logged: _____

Drilling Contractor:	Core:	Size	From	To	Collar Cased and Capped:
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Started: _____ Completed: _____

RL6647.FD + 6647.KA
→ 6647.OK

KP

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66-49

Fabric Orientation Diagram:

Project: _____

Location: ZONE 3

Claim: _____

Terr. Plane Co-ords.: _____ N

_____ E

Grid Co-ords.: 8,799.3 ✓ N

14,399.5 ✓ E

Elevation: 4059.5 ✓

Total Depth: 750' ✓

Purpose: _____

Logged by: _____

Date(s) Logged: _____

Drilling Contractor: _____

Core:	Size	From	To	Collar Cased and Capped:
_____	_____	_____	_____	_____
_____	_____	_____	_____	_____
_____	_____	_____	_____	_____

All symmetrical terminations looking _____ with _____ dipping _____ with dip azimuth _____.

merged with RL6649.FD

RL6649.FD + 6649.KP

→ 6649.OK

Started: _____ Completed: _____

66-49

GEOCHEMICAL LOG

FROM	TO	UNIT	Pb %	Zn %	Ag G/MT	Cu %	BaO %	S.G.	Py %	Po %	Mn %	
						0.00					0.00	
						0.00					0.00	
A	00	5550	1	0.00	9.00	0.00	0.00	2.75	19.0	10.9	0.00	
A	5550	5600	2	2.56	3.21	41.0	0.16	10.19	3.22	13.9	15.6	0.25
A	5600	5650	3	6.00	7.66	78.4	0.23	0.17	4.87	13.9	15.6	0.25
A	5650	5700	4	8.79	9.53	117.7	0.29	0.10	4.47	13.9	15.6	0.25
A	5700	5750	5	7.48	8.09	98.8	0.42	1.14	4.71	14.3	12.5	0.36
A	5750	5800	6	3.84	4.04	59.1	0.18	1.84	3.73	14.3	12.5	0.36
A	5800	5850	7	2.73	2.83	42.2	0.14	3.09	3.05	14.3	12.5	0.36
A	5850	5900	8	7.08	9.26	100.3	0.27	0.62	4.53	14.3	12.5	0.36
A	5900	5950	9	4.57	6.88	41.8	0.20	7.31	4.68	20.0	5.3	0.13
A	5950	6000	10	1.31	1.94	17.3	0.17	0.34	5.07	20.0	5.3	0.13
A	6000	6050	11	2.07	3.58	46.7	0.22	0.26	2.76	20.0	5.3	0.13
A	6050	6100	12	3.69	2.01	67.6	0.23	0.31	2.99	20.0	5.3	0.13
A	6100	6150	13	0.72	1.97	15.1	0.09	0.41	2.76	20.5	9.5	0.10
A	6150	6200	14	2.14	3.50	37.9	0.30	0.38	3.40	20.5	9.5	0.10
A	6200	6250	15	1.40	1.31	21.9	0.47	0.02	4.84	20.5	9.5	0.10
A	6250	6300	16	2.82	1.16	21.6	0.42	0.02	5.15	20.5	9.5	0.10
A	6300	6350	17	3.93	3.77	26.5	0.42	0.02	4.77	34.7	5.5	0.17
A	6350	6400	18	2.64	5.06	20.6	0.24	0.03	4.46	34.7	5.5	0.17
A	6400	6450	19	5.28	4.63	35.9	0.46	0.02	4.71	34.7	5.5	0.17
A	6450	6500	20	4.30	7.12	24.6	0.12	0.02	4.93	34.7	5.5	0.17
A	6500	6550	21	2.24	4.61	21.1	0.24	0.18	3.54	10.3	5.7	0.05
A	6550	6600	22	1.09	3.23	23.7	0.05	0.32	2.72	10.3	5.7	0.05
A	6600	6650	23	1.25	3.13	34.8	0.08	0.23	2.92	10.3	5.7	0.05
A	6650	6700	24	2.03	4.72	51.1	0.28	0.17	3.49	10.3	5.7	0.05

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66-52

Fabric Orientation Diagram:

Project: _____

Location: ZONE 3

Claim: _____

Terr. Plane Co-ords.: _____ N

_____ E

Grid Co-ords.: 8,996.9 ✓ N

14,199.1 ✓ E

Elevation: 4038.8 ✓

All symmetrical terminations looking
_____ with _____ dipping
_____ with dip azimuth _____.

Total Depth: 725

Purpose: _____

Logged by: _____ Date(s) Logged: _____

Drilling Contractor:	Core:	Size	From	To	Collar Cased and Capped:
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

ASSAYS
RL6652.FD + 6652.KP
→ 6652.OK

Started: _____ Completed: _____

CYPRUS ANVIL MINING CORP.
GEOCHEMICAL LOG

FROM	TO	UNIT	Pb %	Zn %	Ag G/MT	Cu %	BaO %	S.G.	Py %	Po %	Mn %	
						0.					0.	
						0.					0.	
						0.					0.	
A	5100	5150	1	0.00	0.00	0.00	0.00	2.75	0.0	0.0	0.00	
A	5150	5200	2	5.17	7.34	5.80	0.38	0.19	4.48	6.2	29.8	0.11
A	5200	5250	3	6.34	9.32	69.80	0.38	0.17	4.05	6.2	20.8	0.11
A	5250	5300	4	2.27	6.05	31.10	0.09	0.15	2.59	6.2	20.8	0.11
A	5300	5350	5	5.31	8.11	71.60	0.21	0.17	3.93	25.0	8.5	0.11
A	5350	5400	6	5.68	7.85	56.00	0.20	0.10	4.67	25.0	8.5	0.11
A	5400	5450	7	6.42	8.14	64.80	0.17	1.67	2.60	25.0	8.5	0.11
A	5450	5500	8	6.71	9.67	62.30	0.07	0.07	2.87	25.0	8.5	0.11
A	5500	5550	9	7.62	7.49	71.20	0.16	0.09	5.14	30.8	2.9	0.08
A	5550	5600	10	7.68	9.39	55.70	0.07	0.05	2.77	30.8	2.9	0.08
A	5600	5650	11	7.25	9.12	53.50	0.10	0.08	2.73	30.8	2.9	0.08
A	5650	5700	12	6.60	7.80	52.60	0.26	12.13	3.46	30.8	2.9	0.08
A	5700	5750	13	6.84	9.79	54.10	0.06	0.16	2.81	24.8	4.0	0.11
A	5750	5800	14	7.85	8.81	72.10	0.10	6.34	3.27	24.8	4.0	0.11
A	5800	5850	15	10.28	12.02	114.00	0.16	4.67	2.71	24.8	4.0	0.11
A	5850	5900	16	8.26	9.06	95.40	0.09	19.48	2.91	24.8	4.0	0.11
A	5900	5950	17	4.87	4.74	53.70	0.29	14.28	4.57	30.8	4.2	0.09
A	5950	6000	18	3.72	5.23	39.30	0.17	0.25	5.25	30.8	4.2	0.09
A	6000	6050	19	3.95	7.13	38.00	0.08	0.13	4.79	30.8	4.2	0.09
A	6050	6100	20	5.15	7.43	45.80	0.08	0.07	4.63	30.8	4.2	0.09
A	6100	6150	21	10.94	2.31	17.20	0.04	0.50	2.91	2.9	3.3	0.04
A	6150	6200	22	1.72	3.32	34.40	0.11	0.35	3.11	2.9	3.3	0.04
A	6200	6250	23	1.18	2.80	24.90	0.08	0.33	3.04	2.9	3.3	0.04

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66-55

Fabric Orientation Diagram:

Project: _____

Location: ZONE 1

Claim: _____

Terr. Plane Co-ords.: _____ N

_____ E

Grid Co-ords.: 9028.0 ✓

13,757.0 ✓

Elevation: 4047.0 ✓

All symmetrical determinations looking

_____ with _____ dipping

_____ with dip azimuth _____.

Total Depth: 602'

Purpose: _____

Logged by: _____ Date(s) Logged: _____

Drilling Contractor: _____ Core: _____ Size _____ From _____ To _____ Collar Cased and Capped: _____

Started: _____ Completed: _____

RL66TS.KP + 6655.KP
→ 6655-UK

KP

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66-57

Fabric Orientation Diagram: _____

Project: _____

Location: ZONE 1

Claim: _____

Terr. Plane Co-ords.: _____ N

_____ E

Grid Co-ords.: 9119.0 N

14,690.0 E

All symmetrical terminations looking

_____ with _____ dipping

_____ with dip azimuth _____

Elevation: 4207.8 ✓

Total Depth: 613'

Purpose: _____

Logged by: _____ Date(s) Logged: _____

Drilling Contractor:	Core:	Size	From	To	Collar Cased and Capped:
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

MS 6657.FD + 6657.KP ASSATS

→ 6657.OK

Started: _____ Completed: _____

GEOCHEMICAL LOG

FROM	TO	UNIT	Pb %	Zn %	Ag G/MT	Cu %	BaO %	S.G.	Py %	Po %	Mn %	
						0.					0.	
						0.					0.	
						0.					0.	
A	00	2950	1	0.00	0.00	0.0	0.00	0.00	2.75	0.0	0.0	0.00
A	2950	3000	2	0.91	3.49	21.9	0.03	0.10	3.81	11.8	7.5	0.06
A	3000	3050	3	1.50	4.23	16.3	0.08	0.10	3.81	11.8	7.5	0.06
A	3050	3100	4	3.06	4.02	40.1	0.32	0.08	3.32	11.8	7.5	0.06
A	3100	3600	5	0.00	0.00	0.0	0.00	0.00	2.75	0.0	0.0	0.00
						0.					0.	
						0.					0.	
A	3600	3650	6	1.30	0.16	34.0	0.18	0.13	2.77	18.2	3.2	0.04
A	3650	3700	7	2.21	0.62	40.4	0.33	0.09	3.45	18.2	3.2	0.04
A	3700	3750	8	0.76	0.50	9.0	0.06	0.04	3.04	18.2	3.2	0.04
A	3750	3800	9	0.50	1.68	20.0	0.03	0.15	3.20	18.2	3.2	0.04
A	3800	3850	10	1.54	3.45	16.2	0.11	0.15	3.23	7.4	4.3	0.05
A	3850	3900	11	1.68	4.37	22.2	0.10	0.17	3.12	7.4	4.3	0.05
A	3900	3950	12	1.06	0.36	24.0	0.14	0.10	2.66	7.4	4.3	0.05
A	3950	4000	13	1.14	2.48	19.3	0.25	0.11	3.19	7.4	4.3	0.05
A	4000	4050	14	1.88	4.62	24.3	0.23	0.06	3.26	11.4	5.4	0.05
A	4050	4100	15	3.62	11.03	27.0	0.06	0.14	3.47	12.6	3.9	0.04
A	4100	4150	16	0.66	2.96	12.2	0.16	0.14	3.35	12.6	3.9	0.04
A	4150	4200	17	2.96	7.80	25.7	0.08	0.11	3.57	12.6	3.9	0.04
A	4200	4250	18	5.10	14.30	34.0	0.04	0.12	3.64	9.6	4.1	0.04
A	4250	4300	19	1.98	3.54	19.7	0.23	0.13	2.89	9.6	4.1	0.04
A	4300	4350	20	5.79	9.02	43.2	0.12	0.12	3.48	9.6	4.1	0.04
A	4350	4400	21	3.52	7.93	23.3	0.16	0.11	3.19	9.6	4.1	0.04

