

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66E01

Fabric Orientation Diagram:

Project:

Location: ZONE 3

Claim:

Terr. Plane Co-ords.: N

E

Grid Co-ords.: 7541.5

15,604.0

Elevation: 4012.0

Total Depth: 450'

Purpose:

Logged by: Date(s) Logged:

Drilling Contractor: Core: Size From To Collar Cased and Capped:

converted silver
66E01.KP -> 66E01.AC

RL66E2.FD + 66E01.AC
↓
66E01.OK

All symmetry Determinations looking
with dipping
with dip azimuth

Started: Completed:

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66 E04

Fabric Orientation Diagram:

Project: _____

Location: ZONE 3

Claim: _____

Terr. Plane Co-ords.: _____ N

_____ E

Grid Co-ords.: 7,352.0 ' V N

15,416.0 V E

Elevation: 4023.0 V

All symmetry determinations looking

_____ with _____ dipping

_____ with dip azimuth _____.

Total Depth: 450'

Purpose: _____

Logged by: _____ Date(s) Logged: _____

Drilling Contractor: _____ Core: _____ Size _____ From _____ To _____ Collar Cased and Capped: _____

*Converted silver
66E04.KP → 66E04.A6*

*(RL66E04.FD + 66E04.A6
→ 66E04.OK*

Started: _____ Completed: _____

6.65.0.4

FROM	TO	UNIT	Pb %	Zn %	Ag G/MT	Cu %	BaO %	S.G.	Py %	Po %	Mn %	
						0					0	
A 11.00	13.00	1	10.00	10.00	10.00	0.00	0.00	2.75	10.0	0.0	0.0	
A 13.00	13.50	2	7.49	5.17	137.5	0.18	0.77	3.28	16.4	6.6	0.2	
A 13.50	14.00	3	10.36	10.12	17.0	0.11	0.38	3.06	16.4	6.6	0.2	
A 14.00	14.50	4	7.88	6.40	115.6	0.14	0.95	4.04	16.4	6.6	0.2	
A 14.50	15.00	5	5.49	3.95	71.3	0.14	0.32	3.37	16.4	6.6	0.2	
A 15.00	15.50	6	4.23	6.10	32.2	0.12	0.02	5.34	16.4	6.6	0.2	
A 15.50	16.00	7	4.87	9.96	50.2	0.04	0.02	4.84	26.6	7.1	0.07	
A 16.00	16.50	8	6.30	11.33	76.9	0.05	0.02	4.85	26.6	7.1	0.07	
A 16.50	17.00	9	4.41	7.63	55.7	0.21	0.23	4.96	26.6	7.1	0.07	
A 17.00	17.50	10	2.96	5.06	43.8	0.21	0.52	3.57	26.6	7.1	0.07	
A 17.50	18.00	11	1.95	3.42	31.3	0.14	0.04	3.43	10.6	11.4	0.06	
A 18.00	18.50	12	1.28	2.51	20.5	0.23	0.44	3.37	10.6	11.4	0.06	
A 18.50	19.00	13	4.18	8.17	73.4	0.25	1.63	3.87	10.6	11.4	0.06	
A 19.00	19.50	14	2.21	3.62	42.7	0.10	0.55	3.11	10.6	11.4	0.06	
A 19.50	20.00	15	1.76	2.88	32.2	0.09	0.52	3.22	12.2	3.7	0.06	
A 20.00	20.50	16	0.37	0.69	10.1	0.06	0.81	3.10	12.2	3.7	0.06	
A 20.50	21.00	17	0.19	1.64	8.2	0.10	0.54	3.08	12.2	3.7	0.06	
A 21.00	21.50	18	1.73	4.08	42.4	0.10	0.67	3.25	12.2	3.7	0.06	
A 21.50	22.00	19	3.77	4.67	68.0	0.09	0.68	3.26	5.6	4.4	0.04	
A 22.00	22.50	20	0.98	1.90	31.3	0.11	0.68	3.21	5.6	4.4	0.04	
A 22.50	23.00	21	0.83	1.32	17.4	0.00	0.95	2.61	5.6	4.4	0.04	
A 23.00	23.50	22	0.46	0.55	6.5	0.00	0.86	2.56	5.6	4.4	0.04	
A 23.50	24.00	23	0.50	1.30	8.2	0.00	0.54	2.69	3.7	5.3	0.04	
A 24.00	24.50	24	0.52	1.59	9.7	0.05	0.37	2.61	3.7	5.3	0.04	
A 24.50	25.00	25	0.00	0.32	14.7	0.31	0.25	2.93	3.7	5.3	0.04	

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66E05

Fabric Orientation Diagram:

Project: _____

Location: ZONE 3

Claim: _____

Terr. Plane Co-ords.: _____ N

_____ E

Grid Co-ords.: 7536.0 L N

15206.0 / E

Elevation: 4014.0 ✓

All symmetry determinations looking
_____ with _____ dipping
_____ with dip azimuth _____.

Total Depth: 345' ✓

Purpose: _____

Logged by: _____ Date(s) Logged: _____

Drilling Contractor: _____ Core: _____ Size _____ From _____ To _____ Collar Cased and Capped: _____

Converted AG. 's
66E05.KP - 66E05.AG

Started: _____ Completed: _____

RL66E05.FD + 66E05.AG
→ 66E05-OK

RP

CYPRUS ANVIL MINING CORP.
GEOCHEMICAL LOG

FROM	TO	UNIT	Pb %	Zn %	Ag G/MT	Cu %	BaO %	S.G.	Py %	Po %	Mn %	
						0					0	
A	100	2400	1	10.00	0.00	0.00	0.00	2.75	10.0	10.9	0.00	
A	2400	2450	2	10.00	10.01	15.7	0.16	2.69	18.4	5.4	0.09	
A	2450	2500	3	10.88	11.91	15.7	0.10	3.15	18.4	5.4	0.09	
A	2500	2550	4	10.81	11.20	14.0	0.00	2.57	18.4	5.4	0.09	
A	2550	2600	5	12.25	14.18	33.1	0.24	3.38	18.4	5.4	0.09	
A	2600	2650	6	11.30	11.92	23.8	0.61	3.59	18.4	5.4	0.09	
A	2650	2700	7	12.01	11.36	26.0	0.20	4.72	36.0	5.5	0.15	
A	2700	2750	8	11.72	13.03	21.3	0.07	4.76	36.0	5.5	0.15	
A	2750	2800	9	12.25	13.60	21.8	0.05	4.67	36.0	5.5	0.15	
A	2800	2850	10	12.77	15.18	26.0	0.00	4.78	36.0	5.5	0.15	
A	2850	2900	11	12.27	14.73	32.4	0.39	4.10	14.0	3.05	0.05	
A	2900	2950	12	12.01	13.62	38.6	0.73	4.08	14.0	3.05	0.05	
A	2950	3000	13	10.97	12.41	35.0	0.57	3.90	14.0	3.05	0.05	
A	3000	3050	14	11.43	12.55	48.6	0.49	3.92	14.0	3.05	0.05	
A	3050	3100	15	10.41	12.35	13.4	0.16	2.90	7.9	7.7	0.11	
A	3100	3150	16	11.82	14.48	31.4	0.13	2.88	7.9	7.7	0.11	
A	3150	3200	17	7.86	12.25	120.0	0.24	3.34	7.9	7.7	0.11	
A	3200	3250	18	12.14	14.27	72.0	0.07	3.05	7.9	7.7	0.11	
A	3250	3300	19	10.83	11.50	18.0	0.02	2.61	11.3	2.6	0.03	
A	3300	3350	20	10.87	11.23	19.0	0.03	2.69	11.3	2.6	0.03	
A	3350	3400	21	10.54	11.54	11.7	0.01	2.54	11.3	2.6	0.03	
A	3400	3450	22	10.78	11.82	22.8	0.03	2.69	11.3	2.6	0.03	
						0					0	
						0					0	
						0					0	
						0					0	

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66E06

Fabric Orientation Diagram:

Project: _____

Location: ZONE 3

Claim: _____

Terr. Plane Co-ords.: _____ N

_____ E

Grid Co-ords.: 7736.4 ✓ N

15399.4 ✓ E

Elevation: 4008.8 ✓

Total Depth: 500 ✓

Purpose: _____

Logged by: _____ Date(s) Logged: _____

Drilling Contractor:	Core:	Size	From	To	Collar Cased and Capped:
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

*Converted silver
66E06.KP → 66E06.AG*

*RL 66E06.FD + 66E06.AG
↓
66E06.OK*

Started: _____ Completed: _____

All symmetry determinations including _____ with _____ dipping _____ with dip azimuth _____.

CYPRUS ANVIL MINING CORP. GEOCHEMICAL LOG

FROM	TO	UNIT	Pb %	Zn %	Ag G/MT	Cu %	BaO %	S.G.	Py %	Po %	Mn %	
						0.					0.	
A	1100	2050	1	9.00	10.00	10.0	0.00	2.75	10.0	0.0	0.00	
A	2050	2100	2	11.93	3.38	18.2	0.09	3.52	21.4	2.6	0.04	
A	2100	2150	3	10.47	2.86	14.6	0.07	3.45	21.4	2.6	0.04	
A	2150	2200	4	11.76	5.85	15.0	0.03	3.59	21.4	2.6	0.04	
A	2200	2250	5	4.07	4.44	58.3	0.09	7.01	9.5	8.5	0.40	
A	2250	2300	6	10.35	8.13	120.0	0.13	1.64	3.99	9.5	8.5	0.40
A	2300	2350	7	2.44	2.26	32.4	0.04	2.45	2.98	9.5	8.5	0.40
A	2350	2400	8	3.76	2.22	53.4	0.07	5.59	3.37	9.5	8.5	0.40
A	2400	2450	9	1.25	1.22	22.3	0.06	4.48	2.99	15.5	8.9	0.13
A	2450	2500	10	0.66	0.95	18.1	0.04	2.34	2.75	15.5	8.9	0.13
A	2500	2550	11	2.94	5.90	39.4	0.31	0.50	4.31	15.5	8.9	0.13
A	2550	2600	12	2.41	5.05	34.5	0.24	0.04	4.31	15.5	8.9	0.13
A	2600	2650	13	2.58	4.35	32.8	0.36	0.04	4.33	25.8	6.6	0.07
A	2650	2750	14	2.97	6.01	19.0	0.12	0.02	4.82	25.8	6.6	0.07
A	2750	2800	15	2.10	4.03	20.9	0.04	0.54	2.95	25.8	6.6	0.07
A	2800	2850	16	2.48	5.33	28.5	0.02	0.59	2.86	9.5	5.5	0.04
A	2850	2900	17	3.90	5.04	52.4	0.21	0.13	3.53	9.5	5.5	0.04
A	2900	2950	18	1.07	4.46	22.7	0.02	0.43	2.95	9.5	5.5	0.04
A	2950	3000	19	1.42	4.64	27.2	0.03	0.31	2.94	9.5	5.5	0.04
A	3000	3050	20	1.30	2.77	26.6	0.02	0.21	2.78	2.9	3.8	0.02
A	3050	3110	21	1.92	3.72	35.7	0.07	0.13	3.05	2.0	3.4	0.01
A	3110	5000	22	0.00	0.00	0.0	0.00	0.00	2.75	0.0	0.0	0.00
							0.				0.	
							0.				0.	
							0.				0.	
							0.				0.	

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66E07

Fabric Orientation Diagram:

Project: _____

Location: ZONE 3

Claim: _____

Terr. Plane Co-ords.: _____ N

_____ E

Grid Co-ords.: 7131.0 N

15,217.0 E

Elevation: 4018.0

All symmetry determinations looking _____ with _____ dipping _____ with dip azimuth _____.

Total Depth: 504'

Purpose: _____

Logged by: _____ Date(s) Logged: _____

Drilling Contractor:	Core:	Size	From	To	Collar Cased and Capped:
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

*Converted AC
66E07.KP - 66E07.M
RL66E07.FD + 66E07.AK
= 66E07.OK*

Started: _____ Completed: _____

150

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66E08

Fabric Orientation Diagram:

Project: _____

Location: ZONE 3

Claim: _____

Terr. Plane Co-ords.: _____ N

_____ E

Grid Co-ords.: 7141.0 ✓ N

15,619.0 ✓ E

All ~~strata~~ ^{strata} laminations looking
_____ with _____ dipping
_____ with dip azimuth _____.

Elevation: 4012.0 ✓

Total Depth: 370.5'

Purpose: _____

Logged by: _____ Date(s) Logged: _____

Drilling Contractor:	Core:	Size	From	To	Collar Cased and Capped:
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Started: _____ Completed: _____

RL66E8.FD + 66E08.OK
→ 66E08.OK

EP

CYPRUS ANVIL MINING CORPORATION

DIAMOND DRILL CORE LOG

Hole Number: 66E09

Fabric Orientation Diagram:

Project: _____

Location: ZONE 3

Claim: _____

Terr. Plane Co-ords.: _____ N

_____ E

Grid Co-ords.: 7,943.0 6 N

15,592.0 ✓ E

Elevation: 4037.0 ✓

Total Depth: 546.5' ✓

All symmetrical terminations looking
_____ with _____ dipping
_____ with dip azimuth _____.

Purpose: _____

Logged by: _____ Date(s) Logged: _____

Drilling Contractor: _____ Core: _____ Size _____ From _____ To _____ Collar Cased and Capped: _____

*converted silver values
66E09.KP → 66E09.AG*

RL 66E09.FD + 66E09.AG

→ 66E09.OK

Started: _____ Completed: _____

GEOCHEMICAL LOG

FROM	TO	UNIT	Pb %	Zn %	Ag G/MT	Cu %	BaO %	S.G.	Py %	Po %	Mn %	
						0.					0.	
A 100	2300	1	0.00	0.00	0.0	0.00	0.00	2.75	0.0	0.0	0.00	
A 2300	2340	2	0.00	0.27	6.5	0.28	0.17	3.13	17.0	3.6	0.05	
A 2340	2400	3	5.73	11.14	34.5	0.03	0.11	3.97	17.0	3.6	0.05	
A 2400	2850	4	0.00	0.00	0.0	0.00	0.00	2.75	0.0	0.0	0.00	
						0.					0.	
A 2850	2900	5	0.87	0.21	23.7	0.25	0.30	3.08	25.1	10.9	0.18	
A 2900	2950	6	0.00	0.00	5.1	0.25	0.03	4.04	25.1	10.9	0.18	
A 2950	3000	7	0.87	0.65	40.1	0.75	0.06	3.46	25.1	10.9	0.18	
A 3000	3100	8	3.97	2.11	89.4	0.42	3.09	3.76	25.1	10.9	0.18	
A 3100	3150	9	2.39	1.95	36.8	0.20	0.05	3.57	32.8	7.2	0.33	
A 3150	3200	10	2.48	2.37	28.1	0.24	0.03	4.63	32.8	7.2	0.33	
A 3200	3250	11	3.46	2.22	39.4	0.27	0.02	4.95	32.8	7.2	0.33	
A 3250	3300	12	1.15	1.69	13.8	0.27	0.08	3.41	32.8	7.2	0.33	
A 3300	3350	13	0.45	0.00	8.3	0.23	0.06	4.80	39.5	2.0	0.06	
A 3350	3400	14	2.52	2.65	23.5	0.19	0.04	4.81	39.5	2.0	0.06	
A 3400	3450	15	1.18	0.78	23.4	0.26	0.04	4.76	39.5	2.0	0.06	
A 3450	3500	16	3.08	4.28	29.5	0.15	0.03	4.83	39.5	2.0	0.06	
A 3500	3550	17	2.95	5.39	29.9	0.18	0.03	4.32	32.2	1.9	0.06	
A 3550	3600	18	1.91	0.39	28.2	0.08	0.02	3.80	32.2	1.9	0.06	
A 3600	3650	19	1.08	0.71	12.8	0.10	0.02	4.39	32.2	1.9	0.06	
A 3650	3700	20	0.52	0.50	11.5	0.14	0.02	3.91	32.2	1.9	0.06	
A 3700	3750	21	0.78	2.42	10.2	0.08	0.15	3.17	26.1	1.5	0.02	
A 3750	3800	22	5.41	8.10	39.2	0.05	0.08	4.09	26.1	1.5	0.02	
A 3800	3850	23	1.54	2.11	18.1	0.21	0.08	3.91	26.1	1.5	0.02	
						0.					0.	
CONTINUED						0.					0.	

 * DDH: 66-E9 * SUMMARY DRILL LOG -- CORRECTED TO TRUE DEPTH AND

COLLAR COORDINATES -- EAST: 7943.0 NORTH: 15592.0 ELEV: 4037.0

----- STRUCTURAL LOG -----

DDH-FT =====	CODE =====	LITH =====	GEOCHM LOG		FEAT =====	SYM =====	S1		S2
			NO	INT			CA	DIPD	CA
447.0	L	27 2E1							
451.3	L	28 1C4							
454.5	L	29 2A0							
467.0	L	30 1C4							
471.5	L	31 1C0							
475.0	L	32 1C4							
482.0	L	33 1E1							
503.5	L	34 1C4							
546.5	L	35 1C1							
546.5	R								

FINISHED -- LENGTH = 546.50 ENTRIES = 56