



**STRIPPING PROGRAM**  
 Giants 1 to 21 inclusive will be set first, and will be reset, according to plan, as the stripping proceeds downstream.

The area from outlet "E" to outlet "J" will first be stripped on the right, and then the tailings will be blown over onto completed areas by giants 36 to 41 inclusive, advancing from a line along the left limit, and taking water from outlet "E".

Giants 16, 18, 20, 22, and 24 will then be set in their second positions, along the left limit, to strip the muck to grade. Where deep muck is encountered along the extreme right limit the stripping need not necessarily be completed before the tailings are blown over from the left limit, as long as sufficient ground is completed to provide room for the tailings. The area between outlets "J" and "O" will be handled in the same manner as that used on the area between outlets "E" and "J".

Giants 48 to 54 inclusive will be used to open up new ground for 1943 stripping operations.

- LEGEND**
- No. ● Drill Hole
  - Original Depth of Muck
  - Pipe Line 1st Position
  - Pipe Line 2nd Position
  - Advancing or Retreating Pipe Line
  - Giant Standard Setup
  - Giant Cowboy Setup
  - Dredge Limit and Required Top of Bank
  - Limit of Shallow Stripping
  - Limit of Completed Stripping
  - Creeks and Drains
  - Drift Tailings

YUKON CONS. GOLD CORP. LTD.  
 DAWSON, Y.T.  
 No. 10 STRIPPING LAYOUT  
 1942 SEASON  
 DRAWN BY: H.V.G.W. SCALE 1"=100'  
 TRACED BY: H.V.G.W.  
 DATE: Jan. 13, 1942. No. 3541  
 REVISED:

2224  
 FJSS-244  
 280 mofI 1102211003 9

1535  
 15922  
 15334