



UNIT No.	AREA Sq Yds.	No. of POINTS	AVERAGE DEPTHS			TOTAL FOOTAGE	VOLUME CU. Yds.
			MUCK	GR.	B'n		
51	18932	773	2	17	2	14687	132524
52	16887	688	2	20	2	15136	135096
53	17359	708	2	21	2	16284	144658
54	17359	708	2	23	2	17700	156231
55	17359	708	1	25	2	18408	162017
56	18815	768	2	26	2	21504	188150
57	18848	769	2	26	2	21532	188480
58	17469	713	2	26	2	19964	174690
TOTAL	143028	5835				145215	1281846

Probable driving rate per 9 hr. shift 100 ft.
 Probable driving season May 10 to Aug. 15 98 days
 Driving crew required Feet ÷ (Days x Rate) 15 men
 Order in which units will be driven 51-52-56
 53-54-55-57-58
 Point spacing in all units 16' centers

- LEGEND**
- 19-20 Drill Hole Thawed Frozen Part Thawed
 - No. Depth of Gravel
 - Depth of Remaining Muck
 - Pipe Line 1st Position
 - Pipe Line 2nd Position
 - Unit Boundary
 - Dredge Limit and
 - Top of Stripping Bank (Theor.)
 - Top of Stripping Bank (Actual)
 - Creeks and Drains
 - Power Lines

YUKON CONS. GOLD CORP. LTD.
 DAWSON, Y.T.
No. 5 THAWING LAYOUT
1941 SEASON
 DRAWN BY H. V. W. & AMN. SCALE 1"=100'
 TRACED BY: A. M. N.
 DATE: NOV. 27, 1940
 REVISED: **No 4058**

e011156397