



LEGEND

- No. Drill Hole
- Original Depth of Muck
- Pipe Line 1st Position
- Pipe Line End Position
- Advancing or Retreating Pipe Line
- Giant Standard Setup
- Giant Cowboy Setup
- Dredge Limit and Required
- Top of Stripping Bank
- Limit of Shallow Stripping
- Limit of Completed Stripping
- Creeks and Drains
- Drift Tailings

STRIPPING PROGRAM

A drain through the center of the area to be stripped will be cut with retreating giants taking off successively from outlets O, L, I, & E.

When the drain has been completed, giants 1 to 18 will strip their respective areas to grade, giants 3, 12, 13, 15, 16 & 18 first blowing the drift tailings onto the old dredge cut. As the giants complete their respective areas they will be reset in positions 19 to 41 inclusive. When the stripping has been completed as far downstream as outlet O, the pumps will be moved to a new location opposite that outlet.

Giants 42 to 65 inclusive will then be used to complete the area along the right limit which was opened up last year and to open up new ground. Giants 66 to 72 inclusive will be set to open up an area along the left limit.

YUKON CONS. GOLD CORP. LTD.
 DAWSON, Y.T.
 No. 11 STRIPPING LAYOUT
 1941 SEASON
 DRAWN BY: AMN & RWB SCALE: 1"=100'
 TRACED BY: A.M.N.
 DATE: Dec. 3, 1940
 REVISED: No. 3533