



UNIT No.	AREA Sq. Yds.	NO. OF POINTS	AVERAGE DEPTHS MUCK GR. B'K	TOTAL FOOTAGE	VOLUME CU. YDS.
19	16850	694	0 23 4	17350	151650
20	15444	636	16 7 3	15264	133848
21	4709	194	0 23 4	4850	42381
22	3936	162	0 23 4	4050	35424
23	2934	121	0 23 4	3025	26406
24	6150	253	0 23 4	6325	55350
25	14320	590	13 20 4	20650	176613
26	14113	581	11 18 5	18592	159947
27	9611	396	3 19 4	9504	83295
TOTAL	87767	3627		99610	864914

Probable driving rate per 9 hr. shift 120 ft.
Probable driving season May 10 to Aug. 15 98 days
Driving crew required Feet ÷ (Days x Rate) 9 men
Order in which units will be driven 19-21-25-20-22-23-26-24-27
Point spacing 16' centres throughout

LEGEND

- Drill Hole
- Thawed
- Frozen
- Part Thawed
- Depth of Gravel
- Depth of Remaining Muck
- Pipe Line 1st Position
- Pipe Line 2nd Position
- Unit Boundary
- Dredge Limit and Required Top of Bank
- Actual Top of Bank
- Creeks and Drains
- Power Lines

YUKON CONS. GOLD CORP. LTD.
DAWSON, Y.T.
No. 11 THAWING LAYOUT
1942 SEASON
DRAWN BY: H.V.G.W.
TRACED BY: H.V.G.W.
DATE: Jan 21, 1942
REVISED:
SCALE 1"=100'
No. 4089