



UNIT No.	AREA Sq. Yds.	No. of POINTS	AVERAGE DEPTHS			TOTAL FOOTAGE	VOLUME CU. Yds.
			MUCK	GR.	B'k		
39	6993	288	5	6	3	3456	32634
41	5271	217	5	6	3	2604	24598
43	2741	113	5	6	3	1356	12791
45	3479	143	5	6	3	1716	16235
47	5745	236	7	9	3	4012	36385
TOTAL	24229	997				13144	122643

Probable driving rate per 9hr. shift 85ft.
 Probable driving season May 10 to July 20 72 days
 Driving crew required Feet ÷ (Days x Rate) 3 men
 Order in which units will be driven 39-41-43-45-47
 Point spacing 16' centres throughout

- LEGEND**
- Drill Hole
 - Thawed
 - Frozen
 - Part Thawed
 - Depth of Gravel
 - Depth of Remaining Muck
 - Pipe Line 1st Position
 - Pipe Line 2nd Position
 - Unit Boundary
 - Dredge Limit and Required Top of Bank
 - Actual Foot of Bank
 - Creeks and Drains
 - Power Lines

YUKON CONS. GOLD CORP. LTD.
DAWSON Y.T.
No. 7 THAWING LAYOUT
1942 SEASON
 DRAWN BY: H.V.G.W. SCALE 1"=100'
 TRACED BY: H.V.G.W.
 DATE: Nov. 13, 1941
 REVISED: **No. 4085**