

16' from back of dump



UNIT No.	AREA Sq.Yds.	No. OF POINTS	AVERAGE DEPTHS			TOTAL FOOTAGE	VOLUME Cu. Yds.
			MUCK	GR.	B'K		
24	13200	544	4	16	2	10880	96800
25	11330	467	4	14	2	8406	75533
26	12452	513	5	17	2	11286	99616
27	13980	575	3	21	2	13800	121160
28	14270	587	2	21	2	13501	118917
29	14942	615	2	22	2	14760	129497
30	17418	718	1	18	2	13642	121926
31	12308	507	6	14	2	10140	90259
32	11690	490	4	17	2	10290	91157
33	10003	412	3	16	2	7828	70021
34	13976	576	1	11	2	6912	65221
TOTAL	145769	6004				121445	1080107

Probable driving rate per 9 hr. shift 100 ft.
 Probable driving season May 10 to Aug 15 98 days
 Driving crew required Feet ÷ (days x rate) 12 men
 Order in which units will be driven 24-25-26-27-28-29-30-31-32-33-34
 Point spacing 16' centres throughout

- LEGEND**
- Drill Hole
 - Thawed
 - Frozen
 - Part Thawed
 - Pipe Line 1st Position
 - Pipe Line 2nd Position
 - - - Unit Boundary
 - Dredge Limit and Required Top of Bank
 - Actual Top of Bank
 - Creeks and Drains
 - Power Lines

YUKON CONS. GOLD CORP. LTD.
DAWSON, Y.T.

No. 6 THAWING LAYOUT
1942 SEASON

Drawn by: AMN & H.V.G.W. SCALE 1"=100'
 Traced by: H.V.G.W.
 DATE: Oct. 29, 1941. **No 4084**
 Revised: