



DRIVING DATA

UNIT	AREA Sq.Yds.	No. of POINTS	AVERAGE DEPTHS			TOTAL FOOTAGE	VOLUME Cu.Yds.
			Muck	Gr.	B'k		
12	8679	1058	12	9	2	22218	66539
13	9011	1098	12	8	2	21960	66081
14	8085	986	6	8	1	13804	43120
15	8711	1062	14	7	1	22302	66784
16	8974	1094	5	7	3	14222	44870
17	9011	1098	15	7	3	25254	75092
18	8679	1058	3	8	2	11638	37609
19	9011	1098	15	10	2	27450	81099
20	8679	1058	3	8	2	11638	37609
21	9011	1098	6	11	2	18666	57070
22	8679	1058	11	7	3	19044	60753
23	10040	1228	12	6	3	23332	70280
	106570	12994				231528	706906

Probable driving rate per 9 hr shift 225 ft.
 Probable driving season May 10 to Aug. 20 102 days
 Driving Crew required Feet ÷ (Days x Rate) 11 men
 Order in which units will be driven 14-15-16-17-12-13-19-18-23-22-21-20

NOTE: All points on 9' spacing.

- LEGEND**
- 3-6 Frozen Drill Hole
 - 3-6 Depth of Gravel
 - 3-6 Depth of Remaining Muck
 - Pipe Line 1st Position
 - Pipe Line 2nd Position
 - - - Unit Boundary
 - - - Dredge Limit and Top of Stripping Bank
 - - - Edge of High Ridge
 - Creeks and Drains
 - Power Line

YUKON CONS. GOLD CORP. LTD.
 DAWSON, Y.T.
 No. 8 THAWING LAYOUT
 1939 SEASON
 DRAWN BY: A.M.N. & H.V.G.W. Scale 1"=100 FT.
 TRACED BY: A.M.N.
 DATE: Jan. 1939
 REVISED: **No 4028**