



UNIT No.	AREA Sq. Yds.	No. of POINTS	AVERAGE DEPTHS			TOTAL FOOTAGE	VOLUME CU. YDS.
			MUCK	Gr.	B'k		
57	16682	686	2	26	2	19208	166820
58	17469	720	2	26	2	20160	174690
59	17469	720	2	27	2	20880	180513
60	17469	720	3	27	2	21600	186336
61	7242	298	3	27	2	8940	77248
62	17172	706	3	26	2	20474	177444
TOTAL	93503	3850				111262	963051

Probable driving rate per 9 hr. shift 100 ft.
 Probable driving season May 10 to Aug. 15 98 days
 Driving crew required Feet ÷ (Days x Rate) 12 men
 Order in which units will be driven 57-58-59-60-61-62
 Point spacing 16' centres throughout.

- LEGEND**
- Drill Hole
 - Thawed
 - Frozen
 - Part Thawed
 - Depth of Gravel
 - Depth of Remaining Muck
 - Pipe Line 1st Position
 - Pipe Line 2nd Position
 - Unit Boundary
 - Dredge Limit and
 - Required Top of Bank
 - Actual Top of Bank
 - Creeks and Drains
 - Power Lines

YUKON CONS. GOLD CORP. LTD.
 Dawson, Y.T.
No. 5 THAWING LAYOUT
1942 SEASON
 Drawn by: H.V.G.W.
 Traced by: H.V.G.W.
 Date: Nov. 7, 1941.
 Revised:
 SCALE 1"=100'
No 4083