



DRIVING DATA

UNIT No	AREA Sq. Yds.	No of POINTS	AVERAGE DEPTHS			TOTAL FOOTAGE	VOLUME Cu. Yds.
			MUCK	GRAVEL	B'K		
41		220	5	25	2		21846
42		674	4	25.5	2		43863
43	15891	648	6	19	2	16200	143019
44	17359	708	3	22	2	17700	156231
45	17359	708	2	24	3	19116	167804
46	18800	758	2	23	2	19200	169200
47	17726	723	3	26	2	20967	183167
48	17359	708	2	28	2	21240	185163
	104494	5157				114423	1070293

Probable driving rate per 9 hr shift 100 ft.  
 Probable driving season May 10 to Aug 15 98 days  
 Order in which units will be driven 43-44  
 45-46-47-48  
 Driving Crew required Feet ÷ (Days x Rate) 12 men  
 Point spacing 16' centers throughout

- LEGEND**
- 12" 2-17 Drill Hole
  - Depth of Gravel
  - Depth of Remaining Muck
  - Pipe Line 1st Position
  - Pipe Line 2nd Position
  - Unit Boundary
  - Dredge Limit and Top of Stripping Bank (Theor)
  - Top of Stripping Bank (Actual)
  - Creeks and Drains
  - Power Lines
  - Outline of Dredge Cut

YUKON CONS. GOLD CORP LTD.  
 Dawson, Y.T.  
 No. 5 THAWING LAYOUT  
 1940 SEASON  
 DRAWN BY: H.V.G.W. SCALE 1"=100 FT.  
 TRACED BY: H.V.G.W.  
 DATE: Oct. 25, 1939  
 REVISED: **No 4037**